Q1: Borders and Padding Demonstration Page

index.html

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Borders and Padding - Q1</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <main class="container">
    <!-- Solid Border Box -->
    <div class="box solid-box">
      <h3>Solid Border</h3>
      <p>This box demonstrates a solid border with standard padding.</p>
    </div>

    <!-- Dashed Border Box -->
    <div class="box dashed-box">
      <h3>Dashed Border</h3>
      <p>This box demonstrates a dashed border with customized padding.</p>
    </div>

    <!-- Double Border Box -->
    <div class="box double-box">
```

```
        <h3>Double Border</h3>
        <p>This box demonstrates a double border with heavy padding.</p>
      </div>

      <!-- Groove Border Box -->
      <div class="box groove-box">
        <h3>Groove Border</h3>
        <p>This box demonstrates a groove border style and rounded corners.</p>
      </div>
    </main>
</body>
</html>
```

style.css

CSS

```
/* General page reset and background styling */
body {
    margin: 0;
    font-family: Arial, sans-serif;
    background-color: #f4f6f8;
    display: flex;
    justify-content: center;
    align-items: center;
    min-height: 100vh;
}

/* Flexbox container to align boxes horizontally */
```

```
.container {
    display: flex;
    gap: 20px;
    flex-wrap: wrap;
    justify-content: center;
    padding: 20px;
}

/* Common box styles */
.box {
    width: 220px;
    background-color: #ffffff;
    padding: 20px; /* Internal spacing demonstration */
    border-radius: 12px; /* Rounded corners */
    transition: border-color 0.4s ease, transform 0.3s ease;
    box-shadow: 0 4px 6px rgba(0, 0, 0, 0.05);
}

/* Specific border styles */
.solid-box {
    border: 3px solid #3498db;
}

.dashed-box {
    border: 3px dashed #e74c3c;
}
```

```
.double-box {
    border: 6px double #2ecc71;
}

.groove-box {
    border: 6px groove #9b59b6;
}

/* Hover effects changing border color and lifting slightly */
.solid-box:hover {
    border-color: #2980b9;
    transform: translateY(-5px);
}

.dashed-box:hover {
    border-color: #c0392b;
    transform: translateY(-5px);
}

.double-box:hover {
    border-color: #27ae60;
    transform: translateY(-5px);
}

.groove-box:hover {
```

```
    border-color: #8e44ad;
    transform: translateY(-5px);
}
```

Q2: Height and Width Practice Layout

index.html

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Height and Width Practice - Q2</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
    <main class="layout-container">
        <!-- Box 1: Fixed px dimensions -->
        <div class="box box-px">
            <h3>Box (Pixels)</h3>
            <p>Fixed width (250px) and height (200px).</p>
        </div>

        <!-- Box 2: Relative units & min-height/max-width -->
        <div class="box box-relative">
            <h3>Box (Relative/Min)</h3>
            <p>Uses max-width, min-height (18vh), and em units. This extra content tests overflow behavior when text exceeds standard vertical parameters.</p>
```

```
    </div>

    <!-- Box 3: Percentage and Overflow -->
    <div class="box box-percent">
      <h3>Box (Percentage)</h3>
      <p>Width defined using percentage. Overflow is set to scroll so content remains accessible without breaking boundaries.</p>
    </div>
  </main>
</body>
</html>
```

style.css

CSS

```
/* Center all boxes vertically and horizontally using Flexbox */
body {
  margin: 0;
  min-height: 100vh;
  background-color: #eef2f5;
  font-family: Arial, sans-serif;
  display: flex;
  justify-content: center;
  align-items: center;
}

.layout-container {
  display: flex;
```

```
    gap: 25px;
    flex-wrap: wrap;
    justify-content: center;
    align-items: center;
    width: 90%;
    max-width: 1000px;
}

/* Base styles for boxes */
.box {
    padding: 20px;
    border-radius: 8px;
    color: white;
    box-shadow: 0 4px 10px rgba(0,0,0,0.1);
}

/* Box 1: Pixels */
.box-px {
    width: 250px;
    height: 200px;
    background-color: #2c3e50;
}

/* Box 2: Min-height, max-width, em units */
.box-relative {
    max-width: 300px;
```

```
    min-height: 18vh;
    font-size: 1em;
    background-color: #16a085;
    overflow: hidden; /* Clips extra overflowing data safely */
}

/* Box 3: Percentage sizing and overflow handling */
.box-percent {
    width: 280px;
    height: 200px;
    background-color: #d35400;
    overflow: auto; /* Adds scrollbars if text overflows content bounds */
}
```

Q3: Gradient Background Webpage

index.html

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Gradient Webpage - Q3</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
    <!-- Fixed Header -->
    <header class="fixed-header">
```

```
    <h1>CSS Gradients Showcase</h1>
  </header>

  <!-- Main Content Area -->
  <main class="content-wrapper">
    <section class="gradient-section linear-section">
      <h2>Linear Gradient Section</h2>
      <p>This section demonstrates a straight-line color transition from top-left to bottom-right using standard linear-gradient syntax[cite: 34].</p>
    </section>

    <section class="gradient-section radial-section">
      <h2>Radial Gradient Section (Parallax-like Effect)</h2>
      <p>This section uses a radial gradient spreading outward from the center[cite: 37] with <code>background-attachment: fixed;</code>.</p>
    </section>
  </main>

  <!-- Fixed Footer -->
  <footer class="fixed-footer">
    <p>&copy; 2026 Gradient Design Layout</p>
  </footer>
</body>
</html>
```

style.css

CSS

```
body {
```

```
    margin: 0;
    font-family: Arial, sans-serif;
    color: #fff;
    text-align: center;
}

/* Fixed Header */
.fixed-header {
    position: fixed;
    top: 0;
    left: 0;
    width: 100%;
    height: 60px;
    background-color: rgba(0, 0, 0, 0.7);
    display: flex;
    justify-content: center;
    align-items: center;
    z-index: 1000;
}

.fixed-header h1 {
    font-size: 20px;
    margin: 0;
}

/* Content Sections */
```

```
.content-wrapper {
    margin-top: 60px;
    margin-bottom: 50px;
}

.gradient-section {
    height: 100vh;
    display: flex;
    flex-direction: column;
    justify-content: center;
    align-items: center;
    padding: 0 20px;
    box-sizing: border-box;
}

/* Linear Gradient background */
.linear-section {
    background-image: linear-gradient(135deg, #3498db, #8e44ad);
}

/* Radial Gradient background with fixed attachment */
.radial-section {
    background-image: radial-gradient(circle, #e74c3c, #2c3e50);
    background-attachment: fixed; /* Creates a parallax-like visual depth */
}
```

```
.gradient-section h2 {
    font-size: 36px;
    text-shadow: 2px 2px 6px rgba(0,0,0,0.5);
    margin-bottom: 15px;
}

.gradient-section p {
    font-size: 18px;
    max-width: 600px;
    line-height: 1.6;
    text-shadow: 1px 1px 4px rgba(0,0,0,0.5);
}

/* Fixed Footer */
.fixed-footer {
    position: fixed;
    bottom: 0;
    left: 0;
    width: 100%;
    height: 50px;
    background-color: rgba(0, 0, 0, 0.8);
    display: flex;
    justify-content: center;
    align-items: center;
    z-index: 1000;
}
```

```
.fixed-footer p {
    margin: 0;
    font-size: 14px;
}
```

Q4: Shadows and Depth Effect Layout

index.html

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Shadows and Depth - Q4</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
    <main class="card-container">
        <!-- Card 1 -->
        <div class="card card-one">
            <h2>Card Alpha</h2>
            <p>Utilizes a standard smooth drop shadow with layered depth effects.</p>
        </div>

        <!-- Card 2 -->
        <div class="card card-two">
            <h2>Card Beta</h2>
```

```
        <p>Utilizes a soft, multi-layered blur shadow configuration.</p>
      </div>

      <!-- Card 3 -->
      <div class="card card-three">
        <h2>Card Gamma</h2>
        <p>Utilizes an inset border/shadow blend style for inner depth.</p>
      </div>
    </main>
</body>
</html>
```

style.css

CSS

```
body {
    margin: 0;
    min-height: 100vh;
    background-color: #f7f9fa;
    font-family: Arial, sans-serif;
    display: flex;
    justify-content: center;
    align-items: center;
}

/* Single row layout using Flexbox */
.card-container {
    display: flex;
```

```
    gap: 30px;
    justify-content: center;
    flex-wrap: wrap;
    padding: 20px;
}

/* Card layout and base transition rules */
.card {
    background: #ffffff;
    width: 260px;
    padding: 30px 20px;
    border-radius: 12px;
    text-align: center;
    /* Smooth transition animation property */
    transition: transform 0.4s ease, box-shadow 0.4s ease;
}

/* Text-shadow for headings providing depth */
.card h2 {
    font-size: 22px;
    color: #333;
    text-shadow: 1px 2px 3px rgba(0, 0, 0, 0.15);
    margin-top: 0;
}

.card p {
```

```
    color: #666;
    font-size: 14px;
    line-height: 1.5;
}

/* Unique box-shadow styles for each card */
.card-one {
    box-shadow: 0 4px 10px rgba(0, 0, 0, 0.1);
}

.card-two {
    box-shadow: 0 8px 25px rgba(52, 152, 219, 0.25);
}

.card-three {
    box-shadow: inset 0 0 10px rgba(0,0,0,0.08), 0 5px 15px rgba(0, 0, 0, 0.08);
}

/* Hover effect: lift up using larger shadows */
.card:hover {
    transform: translateY(-10px);
}

.card-one:hover {
    box-shadow: 0 15px 30px rgba(0, 0, 0, 0.2);
}
```

```
.card-two:hover {
    box-shadow: 0 18px 35px rgba(52, 152, 219, 0.4);
}

.card-three:hover {
    box-shadow: inset 0 0 12px rgba(0,0,0,0.12), 0 15px 30px rgba(0, 0, 0, 0.2);
}
```

Q5: Webpage Demonstrating Advanced CSS Selectors

index.html

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Advanced Selectors - Q5</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
    <header class="page-header">
        <h1>Advanced CSS Selectors Demo</h1>
    </header>

    <main class="content-box">
        <!-- Attribute Selector Examples -->
        <section class="form-section">
```

```
    <h2>1. Attribute Selectors</h2>
    <input type="text" placeholder="Text input type..." />
    <br><br>
    <a href="https://example.com" target="_blank">Secure External Link (HTTPS)</a>
</section>

<!-- Pseudo-classes & Elements -->
<section class="list-section">
    <h2>2. Pseudo-classes & Pseudo-elements</h2>
    <ul class="styled-list">
        <li>List Item One</li>
        <li>List Item Two</li>
        <li>List Item Three</li>
        <li>List Item Four</li>
    </ul>
</section>

<!-- Combinators -->
<section class="combinator-section">
    <h2>3. Combinators Showcase</h2>
    <div class="parent-container">
        <p>Direct child paragraph (>) inside container.</p>
        <div>
            <p>Descendant paragraph inside inner wrapper.</p>
        </div>
    </div>
```

```
        <div class="sibling-group">
          <h3>Heading Element</h3>
          <p>Adjacent sibling paragraph (+).</p>
          <p>General sibling paragraph (~).</p>
        </div>
      </section>
    </main>
</body>
</html>
```

style.css

```
body { margin: 0; font-family: Arial, sans-serif; background-color: #f2f4f7; padding: 20px; }

.page-header { text-align: center; margin-bottom: 20px; }

.content-box { max-width: 700px; margin: 0 auto; background: #ffffff; padding: 30px; border-radius: 8px; box-shadow: 0 2px 8px rgba(0,0,0,0.05); }

section { margin-bottom: 25px; border-bottom: 1px solid #e1e4e8; padding-bottom: 20px; }

/* ========================================
```

1. ATTRIBUTE SELECTORS ================================ // Targets elements with specific attribute and value */ input[type="text"] { padding: 10px; width: 80%; border: 1px solid #ccc; border-radius: 4px; }

```
/* Targets attribute values beginning with specific string */ a[href^="https"] { color: #27ae60; font-weight: bold; text-decoration: none; }

/* ======================================== 2. PSEUDO-CLASSES & PSEUDO-ELEMENTS ======================================== // Pseudo-class: targets text input on focus */ input[type="text"]:focus { outline: none; border-color: #3498db; box-shadow: 0 0 5px rgba(52, 152, 219, 0.4); }

/* Pseudo-class: targets alternate child list items */ .styled-list li:nth-child(odd) { background-color: #f8f9fa; }

.styled-list li:hover { background-color: #e2e8f0; color: #1d4ed8; cursor: pointer; }
```

/* Pseudo-element: adds custom marker content before items */ .styled-list li::before { content: "▪ "; color: #3498db; }

/* ========== 3. COMBINATORS ========== // Child combinator (>): direct children only */ .parent-container > p { color: #c0392b; font-weight: bold; }

/* Descendant combinator (space): all nested descendants */ .parent-container div p { color: #7f8c8d; font-style: italic; }

/* Adjacent sibling combinator (+): matches paragraph immediately following h3 */ .sibling-group h3 + p { color: #2980b9; font-weight: bold; }

/* General sibling combinator (~): matches all paragraphs following h3 */ .sibling-group h3 ~ p { background-color: #fffbeb; padding: 5px; }

Q6: Design a CSS Transformations Showcase

`index.html`

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Transformations Showcase - Q6</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
    <main class="transform-container">
        <!-- Box 1: Rotate -->
```

```
      <div class="transform-item">
        <div class="box rotate-box"></div>
        <p class="label">rotate(45deg)</p>
      </div>

      <!-- Box 2: Scale -->
      <div class="transform-item">
        <div class="box scale-box"></div>
        <p class="label">scale(1.2)</p>
      </div>

      <!-- Box 3: Translate -->
      <div class="transform-item">
        <div class="box translate-box"></div>
        <p class="label">translateY(-15px)</p>
      </div>

      <!-- Box 4: Skew -->
      <div class="transform-item">
        <div class="box skew-box"></div>
        <p class="label">skew(15deg, 10deg)</p>
      </div>
    </main>
</body>
</html>
```

style.css

CSS

```
body {
    margin: 0;
    min-height: 100vh;
    background-color: #f1f5f9;
    font-family: Arial, sans-serif;
    display: flex;
    justify-content: center;
    align-items: center;
}

/* Arrange boxes horizontally using Flexbox */
.transform-container {
    display: flex;
    gap: 40px;
    flex-wrap: wrap;
    justify-content: center;
}

.transform-item {
    text-align: center;
}

/* Base box styles */
.box {
    width: 120px;
```

```
    height: 120px;
    background-color: #3b82f6;
    border-radius: 8px;
    box-shadow: 0 4px 6px rgba(0,0,0,0.1);
    /* Smooth transition configuration */
    transition: all 0.4s ease;
}

.label {
    margin-top: 15px;
    font-size: 14px;
    color: #333;
    font-weight: bold;
}

/* Hover transformations */
.rotate-box:hover {
    transform: rotate(45deg);
    background-color: #2563eb;
}

.scale-box:hover {
    transform: scale(1.2);
    background-color: #10b981;
}
```

```
.translate-box:hover {
    transform: translateY(-15px);
    background-color: #f59e0b;
}

.skew-box:hover {
    transform: skew(15deg, 10deg);
    background-color: #ef4444;
}
```

Q7: Typography and Text Styling Page

index.html

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Typography and Text Styling - Q7</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
    <main class="article-container">
        <article class="styled-article">
            <h1>Mastering Modern CSS Typography</h1>
            <p class="lead-paragraph">
                Typography in CSS refers to using different properties to style and arrange text on a webpage. It helps improve readability, aesthetics, and user experience[cite: 43].
```

```
        </p>
        <p>
            When formatting web content, developers use <mark>custom font families</mark>, weights, and sizes to establish hierarchy. Proper spacing using <strong>line-height</strong> and <em>letter-spacing</em> ensures visitors enjoy an optimal reading flow across devices.
        </p>
      </article>
  </main>
</body>
</html>
```

style.css

CSS

```
body {
  margin: 0;
  min-height: 100vh;
  background-color: #f8fafc;
  display: flex;
  justify-content: center;
  align-items: center;
  font-family: "Segoe UI", Arial, sans-serif;
  color: #334155;
}

.article-container {
  max-width: 680px;
  width: 90%;
  background: #ffffff;
```

```
    padding: 40px;
    border-radius: 12px;
    box-shadow: 0 4px 15px rgba(0, 0, 0, 0.05);
}

/* Heading Typography */
.styled-article h1 {
    font-family: "Georgia", serif;
    font-size: 32px;
    font-weight: 700;
    text-transform: capitalize;
    color: #1e293b;
    margin-bottom: 20px;
    border-bottom: 2px solid #e2e8f0;
    padding-bottom: 10px;
}

/* Article Body Typography & Spacing */
.styled-article p {
    font-size: 16px;
    line-height: 1.8; /* Vertical line spacing for legibility */
    letter-spacing: 0.5px; /* Spacing between characters */
    text-align: justify;
    margin-bottom: 20px;
}
```

```
/* Pseudo-elements for emphasis */
.lead-paragraph::first-letter {
    font-size: 3.5em;
    font-weight: bold;
    float: left;
    line-height: 1;
    margin-right: 8px;
    color: #2563eb;
}

.lead-paragraph::first-line {
    font-weight: 600;
    color: #0f172a;
}

/* Custom styling for semantic text elements */
mark {
    background-color: #fef08a;
    color: #854d0e;
    padding: 2px 4px;
    border-radius: 3px;
}

strong {
    color: #0284c7;
    font-weight: 700;
```

```
}

em {
   color: #db2777;
   font-style: italic;
}
```

Q8: Build a Box Model Exploration Page

index.html

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
   <meta charset="UTF-8">
   <title>Box Model Exploration - Q8</title>
   <link rel="stylesheet" href="style.css">
</head>
<body>
   <main class="exploration-container">
      <!-- Default Box Model Example -->
      <div class="box default-model">
         <span class="layer-label">Default Box Model</span>
         <div class="inner-content">Content Layer</div>
      </div>

      <!-- Border-Box Example -->
      <div class="box border-box-model">
```

```
            <span class="layer-label">Box-Sizing: Border-Box</span>
            <div class="inner-content">Content Layer</div>
        </div>
    </main>
</body>
</html>
```

style.css

CSS

```
body {
    margin: 0;
    min-height: 100vh;
    background-color: #e2e8f0;
    font-family: Arial, sans-serif;
    display: flex;
    justify-content: center;
    align-items: center;
}

.exploration-container {
    display: flex;
    gap: 40px;
    flex-wrap: wrap;
    justify-content: center;
}

/* Common box visual representation layers */
```

```
.box {
    width: 260px;
    height: 160px;
    /* Margin Layer (Outermost) */
    margin: 20px;
    /* Border Layer */
    border: 8px solid #3b82f6;
    /* Padding Layer */
    padding: 25px;
    background-color: #93c5fd; /* Padding area background */
    position: relative;
    box-shadow: 0 4px 6px rgba(0,0,0,0.1);
    outline: 4px dashed #ef4444; /* Represents Margin boundary outline */
    outline-offset: 12px;
}

/* Default Box Model behavior (content-box) */
.default-model {
    box-sizing: content-box;
}

/* Border-box behavior */
.border-box-model {
    box-sizing: border-box;
    background-color: #fde047;
    border-color: #ca8a04;
```

```
}

/* Content Area Layer (Innermost) */
.inner-content {
    background-color: #ffffff;
    height: 100%;
    display: flex;
    justify-content: center;
    align-items: center;
    font-weight: bold;
    color: #1e293b;
    font-size: 14px;
}

.layer-label {
    position: absolute;
    top: -35px;
    left: 0;
    font-size: 13px;
    font-weight: bold;
    color: #0f172a;
    background: #fff;
    padding: 3px 6px;
    border-radius: 3px;
}
```

Q9: Design an Outline and Focus Styling Form

index.html

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
   <meta charset="UTF-8">
   <title>Outline and Focus Form - Q9</title>
   <link rel="stylesheet" href="style.css">
</head>
<body>
   <main class="form-wrapper">
      <form class="contact-form">
         <h2>Contact Form</h2>

         <div class="form-group">
            <label for="name">Full Name</label>
            <input type="text" id="name" placeholder="Enter your name...">
         </div>

         <div class="form-group">
            <label for="message">Message</label>
            <textarea id="message" rows="4" placeholder="Type your message
here..."></textarea>
         </div>

         <button type="submit" class="submit-btn">Send Message</button>
```

```
      </form>
   </main>
</body>
</html>
```

style.css

CSS

```
body {
   margin: 0;
   min-height: 100vh;
   background-color: #f1f5f9;
   font-family: Arial, sans-serif;
   display: flex;
   justify-content: center;
   align-items: center;
}

.form-wrapper {
   width: 100%;
   max-width: 420px;
   padding: 20px;
}

.contact-form {
   background: #ffffff;
   padding: 30px;
   border-radius: 10px;
```

```
    box-shadow: 0 4px 12px rgba(0, 0, 0, 0.08);
}

.contact-form h2 {
    margin-top: 0;
    margin-bottom: 20px;
    color: #1e293b;
    text-align: center;
}

/* Uniform spacing between form elements */
.form-group {
    margin-bottom: 20px;
    display: flex;
    flex-direction: column;
}

label {
    font-size: 14px;
    font-weight: bold;
    color: #475569;
    margin-bottom: 6px;
}

/* Input and textarea common styling */
input, textarea {
```

```
    padding: 12px;
    border: 1px solid #cbd5e1;
    border-radius: 6px;
    font-size: 15px;
    font-family: inherit;
    background-color: #f8fafc;
    transition: all 0.3s ease;
    /* Default reset or basic outline */
    outline: 2px solid transparent;
}

/* Outline style and offset configuration on focus */
input:focus, textarea:focus {
    outline: 3px solid #3b82f6; /* Custom outline color and style */
    outline-offset: 3px;        /* Distance between element border and outline[cite: 52] */
    border-color: #2563eb;
    background-color: #ffffff;
    box-shadow: 0 2px 5px rgba(59, 130, 246, 0.2);
}

.submit-btn {
    width: 100%;
    padding: 12px;
    background-color: #3b82f6;
    color: white;
    border: none;
```

```
    border-radius: 6px;
    font-size: 16px;
    font-weight: bold;
    cursor: pointer;
    transition: background-color 0.3s ease;
}

.submit-btn:hover {
    background-color: #2563eb;
}
```

Q10: Create a Navigation Bar with Transitions and Hover Effects

index.html

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Navigation Bar - Q10</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
    <!-- Horizontal Navigation Bar using Flexbox -->
    <nav class="navbar">
        <ul>
            <li><a href="#" class="active">Home</a></li>
            <li><a href="#">Services</a></li>
```

```
            <li><a href="#">Portfolio</a></li>
            <li><a href="#">About</a></li>
            <li><a href="#">Contact</a></li>
        </ul>
    </nav>

    <!-- Main Content Placeholder -->
    <main class="main-content">
        <h2>Responsive Navbar Layout</h2>
        <p>Resize the screen below 700px to see the navigation links stack vertically.</p>
    </main>

    <!-- Footer Section with Centered Text -->
    <footer class="footer">
        <p>&copy; 2026 Navigation Bar Layout. All rights reserved.</p>
    </footer>
</body>
</html>
```

style.css

CSS

```
body {
    margin: 0;
    font-family: Arial, sans-serif;
    background-color: #f4f6f9;
    display: flex;
    flex-direction: column;
```

```
    min-height: 100vh;
}

/* Navigation Bar Container using Flexbox */
.navbar {
    background-color: #1e293b;
    width: 100%;
    box-shadow: 0 2px 4px rgba(0,0,0,0.1);
}

.navbar ul {
    list-style-type: none;
    margin: 0;
    padding: 0;
    display: flex;
    justify-content: center;
}

.navbar li a {
    display: block;
    color: #cbd5e1;
    padding: 18px 24px;
    text-decoration: none;
    font-size: 16px;
    border-bottom: 3px solid transparent;
    /* Smooth hover transition */
```

```
    transition: all 0.3s ease;
}

/* Hover effects */
.navbar li a:hover {
    background-color: #334155;
    color: #ffffff;
}

/* Active link highlight with distinct background or underline */
.navbar li a.active {
    color: #ffffff;
    border-bottom: 3px solid #3b82f6;
    background-color: #1e293b;
}

/* Main Content Area */
.main-content {
    flex: 1;
    display: flex;
    flex-direction: column;
    justify-content: center;
    align-items: center;
    text-align: center;
    padding: 20px;
}
```

```
/* Footer Section */
.footer {
    background-color: #0f172a;
    color: #94a3b8;
    text-align: center;
    padding: 20px;
    font-size: 14px;
}

/* Responsive breakpoint: stack vertically below 700px */
@media (max-width: 700px) {
    .navbar ul {
        flex-direction: column;
        align-items: stretch;
    }

    .navbar li a {
        text-align: center;
        border-bottom: 1px solid #334155;
    }

    .navbar li a.active {
        border-left: 5px solid #3b82f6;
        border-bottom: 1px solid #334155;
    }
```

```
}
```