Pave-Tech Tornado Crackfiller

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/28/2015 Version: 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Pave-Tech Tornado Crackfiller

Product code : 13050

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cold Pour Crack Filler

1.3. Details of the supplier of the safety data sheet

Pave-Tech
1283 Tri-County Hwy
Williamsburg, OH 45176
513.528.0777
www.tornadocrackfiller.com

1.4. Emergency telephone number

Emergency number : 800-424-9300 CHEMTREC 24 HOURS

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Carc. 1A H350
STOT RE 1 H372

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H350 - May cause cancer
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P260 - Do not breathe spray, vapours
P264 - Wash hands, forearms and face thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P280 - Wear eye protection, protective clothing, protective gloves
P308+P313 - If exposed or concerned: Get medical advice/attention
P314 - Get medical advice/attention if you feel unwell
P405 - Store locked up
P501 - Dispose of contents/container to in accordance with local, regional, and national regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
asphaltic bitumen, not cut back	(CAS No) 8052-42-4	41 - 48	Carc. 2, H351
silica	(CAS No) 14808-60-7	0.7 - 3.3	Carc. 1A, H350 STOT RE 1, H372
titanium(IV) oxide	(CAS No) 13463-67-7	< 0.286	Carc. 2, H351
Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]	(CAS No) 64742-65-0	> 0.1	Carc. 1B, H350

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse eyes with water as a precaution. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Foam. Water. Dry Chemical. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable in liquid state.

Explosion hazard : Product is not explosive.

Reactivity : Product is stable.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing vapours. Ensure good ventalation. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Obtain special instructions before use. Do not breathe vapours.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Avoid contact with strong oxidizers. Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Pave-Tech Tornado Crackfiller Cold Pour	
ACGIH	Not applicable
OSHA	Not applicable

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
ACGIH	Not applicable
OSHA	Not applicable

silica (14808-60-7)		
ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³
OSHA	Remark (OSHA)	(3) See Table Z-3.

titanium(IV) oxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m³)	1 mg/m³
ACGIH	Remark (ACGIH)	LRT irr; A3
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³

asphaltic bitumen, not cut back (8052-42-4)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventalation.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : protective gloves. Wear protective gloves.

Eye protection : Safety glasses. Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear respiratory protection. Wear appropriate mask.

Environmental exposure controls : Avoid release to the environment.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: a black thick liquid/mastic like consistency with a mild hydrocarbon odor.
Colour	: Black
Odour	: Very mild hydrocarbon odor.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: ≈ 212 °F
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 1.05 g/cm³
Solubility	: Water: Solubility in water of component(s) of the mixture : • lithium hydroxide, monohydrate: 22.3 g/100ml • xanthan gum: Complete • tall oil: 0.003 g/100ml • tetra-sodium pyrophosphate: 6 g/100ml • silica: insoluble • titanium(IV) oxide: 0.15 g/100ml • methyl benzimidazol-2-ylcarbamate: 0.0008 g/100ml • kaolin: < 0.1 g/100ml • 3-iodo-2-propynyl butylcarbamate: 0.02 g/100ml
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Product is stable.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity. Not established.

10.4. Conditions to avoid

Refer to Section 10 on Incompatible Materials. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

hydrogen sulfide, sulfides. Carbon dioxide. Carbon monoxide. fume.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

titanium(IV) oxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value; > 5000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 6.8 mg/l/4h (Rat; Experimental value)

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : May cause cancer.

silica (14808-60-7)	
IARC group	1 - Carcinogenic to humans

titanium(IV) oxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

asphaltic bitumen, not cut back (8052-42-4)	
IARC group	2A - Probably carcinogenic to humans, 2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : This product may cause adverse enviromental effcts if used improperly or released to the environment through a spill. Employ best managment practices to prevent this material rom entering storm sewers systems, waterways or otherwise impacting plant adn animal species.

12.2. Persistence and degradability

Pave-Tech Tornado Crackfiller Cold Pour	
	Not established.

Persistence and degradability

12.3. Bioaccumulative potential

Pave-Tech Tornado Crackfiller Cold Pour Crack Filler	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer :

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : This product, when discarded or disposed of, is not specifically listed as a hazardous waste in federal regulations. It could be designated as hazardous waste according to state regulations. This product could also become a hazardous waste if it is mixed with or comes in contact with a hazardous waste. If such contact occurs, consult 40 CFR, to determine whether it is a hazardous waste.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with all local, state, and national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Not regulated for transport

Additional information

Other information : Not classified as a hazardous material under HM-181.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Pave-Tech Tornado Crackfiller Cold Pour Crack Filler
Not listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

lithium hydroxide, monohydrate	CAS No 1310-66-3	0.0117%
Asphalt Emulsifier	CAS No	0.43%
silica	CAS No 14808-60-7	C>0.70% ; C<3.30%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations
No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

titanium(IV) oxide (13463-67-7)
Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

titanium(IV) oxide (13463-67-7)
U.S. - New Jersey - Right to Know Hazardous Substance List

asphaltic bitumen, not cut back (8052-42-4)
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information : None.


Full text of H-phrases:

Carc. 1A	Carcinogenicity, Category 1A
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 0 Minimal Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

TBC SDS US (GHS Hazcom 2012)

The information and recommendations contained herein are to the best of Pave-Tech's knowledge and belief, accurate and reliable as of the date issued. Pave-Tech does not warrant or guarantee their accuracy or reliability, and Pave-Tech shall not be liable for any loss or damage arising out of the use thereof.

The information and recommendations are offered for the users consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. It is also the users responsibility to make certain that it is relying upon the most recent, updated, information and recommendations available from Pave-Tech.

The Environmental Information included, as well as the Hazardous Material Identification System (HMIS) and National Fire Protection Association (NFPA) ratings, have been included by THE BREWER COMPANY in order to provide additional health and hazard classification information. The ratings recommended are based upon the criteria supplied by the developers of these rating systems, together with Pave-Tech'S interpretation of the available data.