

```
1: // $Id: vecsort.cpp,v 1.28 2015-03-31 18:29:40-07 - - $
2:
3: //
4: // NAME
5: //     vecsort - sort argv lexicographically
6: //
7: // SYNOPSIS
8: //     vecsort [argv...]
9: //
10: // DESCRIPTION
11: //     Takes each element of argv and inserts it into a vector,
12: //     paired with its index. Sorts the vector lexicographically,
13: //     then prints it out. Includes argv[0] in the sort.
14: //
15:
16: #include <algorithm>
17: #include <cstdlib>
18: #include <iostream>
19: #include <utility>
20: #include <vector>
21: using namespace std;
22:
23: using stringint = pair<string,int>;
24: using vecstring = vector<stringint>;
25:
26: template <typename pair_collection>
27: void printvec (const string &label, const pair_collection &vec) {
28:     for (const auto& item: vec) {
29:         cout << label << ": {" << item.first << ", " << item.second
30:             << "}" << endl;
31:     }
32:     cout << endl;
33: }
34:
35: // Sort by string then by int.
36: // On second test, after "or":
37: // not (2.f < 1.f) means 2.f >= 1.f means 1.f <= 2.f
38: // But 1.f < 2.f is false, so this means 1.f == 1.f
39: bool by_string (const stringint &si1, const stringint &si2) {
40:     return si1.first < si2.first
41:         or (not (si2.first < si1.first) and si1.second < si2.second);
42: }
43:
44: // Sort by int then by string.
45: bool by_int (const stringint &si1, const stringint &si2) {
46:     return si1.second < si2.second
47:         or (not (si2.second < si1.second) and si1.first < si2.first);
48: }
49:
```

```
50:
51: int main (int argc, char **argv) {
52:     vecstrint vec {"foo", 3}, {"bar", 14}, {"baz", 1},
53:                  {"qux", 77}, {"qux", 7}, {"qux", 14},
54:                  {"foo", 14}, {"bar", 1}, {"baz", 3}};
55:     for_each (&argv[1], &argv[argc],
56:              [&](char* arg) {vec.push_back ({arg, arg - argv[0]}); });
57:     printvec ("Unsorted", vec);
58:     sort (vec.begin(), vec.end());
59:     printvec ("Default", vec);
60:     sort (vec.begin(), vec.end(), by_string);
61:     printvec ("By string", vec);
62:     sort (vec.begin(), vec.end(), by_int);
63:     printvec ("By int", vec);
64:     return EXIT_SUCCESS;
65: }
66:
67: //TEST// ./vecsort >vecsort.lis 2>&1
68: //TEST// mkpspdf vecsort.ps vecsort.cpp* vecsort.lis
69:
```



```
1: Unsorted: {foo, 3}
2: Unsorted: {bar, 14}
3: Unsorted: {baz, 1}
4: Unsorted: {qux, 77}
5: Unsorted: {qux, 7}
6: Unsorted: {qux, 14}
7: Unsorted: {foo, 14}
8: Unsorted: {bar, 1}
9: Unsorted: {baz, 3}
10:
11: Default: {bar, 1}
12: Default: {bar, 14}
13: Default: {baz, 1}
14: Default: {baz, 3}
15: Default: {foo, 3}
16: Default: {foo, 14}
17: Default: {qux, 7}
18: Default: {qux, 14}
19: Default: {qux, 77}
20:
21: By string: {bar, 1}
22: By string: {bar, 14}
23: By string: {baz, 1}
24: By string: {baz, 3}
25: By string: {foo, 3}
26: By string: {foo, 14}
27: By string: {qux, 7}
28: By string: {qux, 14}
29: By string: {qux, 77}
30:
31: By int: {bar, 1}
32: By int: {baz, 1}
33: By int: {baz, 3}
34: By int: {foo, 3}
35: By int: {qux, 7}
36: By int: {bar, 14}
37: By int: {foo, 14}
38: By int: {qux, 14}
39: By int: {qux, 77}
40:
```