

# Email Transport Security in Practice

## Email Client Selftest Service

Jhannes Ernesto Reimann, Sofya Generalova

**Design IT.  
Create Knowledge.**

[www.hpi.de](http://www.hpi.de)



# Imagine writing an email in 2025



Your email  
credentials  
are stolen!



## How Is That Possible?

# Table of contents



1. Vulnerability
2. Vulnerable servers
3. Vulnerable clients
4. Original paper's methodology of testing clients
5. Selftest Service
6. Demo
7. Future Directions

# Protocols: Historical context



1. Email protocols  
in plaintext

SMTP:587/25

POP3:110

IMAP:143

2. Let's support TLS: two approaches

Implicit TLS

SMTP:465

POP3:995

IMAP:993

"Opportunistic" TLS

SMTP:587/25


POP3:110

IMAP:143

+ StartTLS

**Insecure!**

# Opportunistic TLS



An active attacker on the network can strip StartTLS and force no-TLS

***if email server and client don't explicitly disallow it***

## SMTP protocol with StartTLS

<https://www.twilio.com/en-us/blog/insights/what-is-starttls>

if **email server** and client  
don't explicitly disallow it

# How many email servers would accept plaintext?

# Passive Measurement with Shodan

Idea: scan Internet for email servers that advertise plain auth

SMTP example:

1. Client requests capabilities from server

EHLO test.com

2. Server lists capabilities

250-mail.nsipmail.de

250-PIPELINING

250-SIZE 10240000

250-VRFY

250-ETRN

250-STARTTLS

potentially effective before TLS → **250-AUTH PLAIN LOGIN**

...

**This does not guarantee server's vulnerability:**

Client tries to login

C: AUTH PLAIN AGFsaWNIAHNIY3JldA==


Server rejects

S: 530 5.7.0 Must issue a STARTTLS command first

# Passive Measurement with Shodan: results



NSIP 2025 – Mail services observed by Shodan (totals) (profile=product)



Totals are counts of Shodan-observed services (not unique organizations).


if email server and **client**  
don't explicitly disallow it

# How many email clients would authenticate in plaintext?

# A Multifaceted Study on the Use of TLS and Auto-detect in Email Ecosystems (2025)

## Email client behavior\*:

\*can differ depending on email protocol and TLS downgrade test case




**19 out of 49 tested clients may silently downgrade to no-TLS**

# A Multifaceted Study on the Use of TLS and Auto-detect in Email Ecosystems (2025)

Testing email client behavior: 4 variations of disruptions


T1:  
"classic" strip  
StartTLS test



# A Multifaceted Study on the Use of TLS and Auto-detect in Email Ecosystems (2025)

Testing email client behavior: 4 variations of disruptions


T3:  
disrupt after  
client selects  
StartTLS



# A Multifaceted Study on the Use of TLS and Auto-detect in Email Ecosystems (2025)

Testing email client behavior: 4 variations of disruptions


T2:  
disrupt during  
TLS handshake



# A Multifaceted Study on the Use of TLS and Auto-detect in Email Ecosystems (2025)

Testing email client behavior: 4 variations of disruptions

T4:  
disrupt  
ongoing TLS  
session




# Is your email client vulnerable?

# Selftest Service

A way to test your email client in use.

**Design IT.  
Create Knowledge.**

[www.hpi.de](http://www.hpi.de)



# What did we build?



- Public, server-side **mail client self-test** for **SMTP + IMAP**
- Tests whether a client can be coerced into **plaintext authentication** when TLS protection is disrupted
- Implements **baseline + T1–T4** behaviors (paper-inspired)

# Why did we build it?




- Paper setup assumes a **MITM/lab environment** (hard to reproduce for normal users)
- We want a “**click** → **configure account** → **observe result**” workflow
- No local proxy, no custom CA, no special network setup required

# Demo

**Design IT.  
Create Knowledge.**

[www.hpi.de](http://www.hpi.de)



# Result example



### Guided Self-Test

Progress

100%

Last progress: Completed

#### COMPLETED

#	Scenario	Testcase	Verdict	Findings	Details
1	immediate	baseline	PASS	tls_auth	Show
2	immediate	t1	FAIL	plaintext_auth	Show
3	immediate	t2	NOT_APPLICABLE	retry_like starttls_disrupted user_cannot_connect	Show
4	immediate	t3	NOT_APPLICABLE	retry_like starttls_disrupted user_cannot_connect	Show
5	immediate	t4	NOT_APPLICABLE	retry_like user_cannot_connect	Show
6	two_phase	t1	WARN	tls_auth starttls_disrupted user_prompt	Show
7	two_phase	t2	PASS	tls_auth starttls_disrupted	Show
8	two_phase	t3	PASS	tls_auth starttls_disrupted	Show
9	two_phase	t4	PASS	tls_auth	Show

# Possible Verdicts



- **PASS:** Auth/login happened only with TLS (no plaintext credentials seen).
- **FAIL:** Auth/login happened without TLS (plaintext credentials exposure).
- **INCONCLUSIVE:** No auth/login observed (client aborted / got stuck / never reached auth).
- **WARN:** Client showed a security prompt/downgrade warning (user-reported; no plaintext proven).
- **NOT\_APPLICABLE:** Test step couldn't be executed (cannot connect; user-reported).
- **SKIPPED:** Step was skipped in Guided mode

# Possible Automatic Findings

- **plaintext\_auth**: We observed an auth/login attempt without TLS (tls=false).
- **tls\_auth**: We observed an auth/login attempt with TLS (tls=true).
- **retry\_like**: Many reconnects / retries but no auth seen (client appears stuck).
- **starttls\_disrupted**: STARTTLS was refused / failed / dropped (e.g., "TLS not available", handshake wrap failed).

# Why we simulate (and why we don't run a proxy/MITM)



## Why no proxy on the client:

- as little setup as possible


## Why no proxy on the server (we simulate instead)

- For our research question, what matters is the **client's view / decision point**  
A test server can create the **same observable conditions** by responding "as if a MITM was present"  
Result: we can still measure whether the client ever sends **AUTH/LOGIN without TLS**


## Could we still do it with a server-side proxy?

- Build a **relay proxy**: client → proxy → real upstream mail server


# "Simulation" Diagram of T1



# "Simulation" Diagram of T1



# Selftest-Service architecture



# Why no POP3?



- User friction & configuration effort
- Result: adding POP3 would likely reduce completion rate for a public self-test
- For the initial service, IMAP + SMTP submission covers the most common real-world configurations

# Future directions



## **Selftest-Service:**

- POP3 extension
- Stronger session isolation + user accounts
- Lab-grade “real MITM” + real mailbox

## **Admin/server-side test tool**

- CLI/script for mail admins to test their own SMTP/IMAP/POP3 configuration against T1–T4 downgrade conditions

## **Manual vs autodetect behavior**

- Systematically investigate differences between manual configuration and autodiscovery-driven configuration paths.