

```
In [1]: %matplotlib inline
import matplotlib.pyplot as plt
import numpy as np
import os
import pandas as pd
```

```
In [2]: df = pd.read_csv('HW1.csv')
df.head() # To get first n rows from the dataset default value of n is 5
M=len(df)
M
```

Out[2]: 100

```
In [3]: df.describe()
```

```
Out[3]:
```

	X1	X2	X3	Y
count	100.000000	100.000000	100.000000	100.000000
mean	2.000000	2.000000	1.960000	1.851276
std	1.172181	1.172154	1.163005	2.774643
min	0.000000	0.070303	0.027879	-5.332455
25%	1.000000	0.979394	0.952121	0.527533
50%	2.000000	2.009697	1.949091	2.879003
75%	3.000000	3.040000	2.946061	3.925389
max	4.000000	3.949091	3.943030	5.545892

```
In [4]: # Separate features and labels
X = df.values[:, 0] # get input values from first column -- X is a list here
y = df.values[:, 3] # get output values from forth column -- Y is the list here
m = len(y) # Number of training examples
n = len(X) # Number of training examples


# Display first 5 records and the total number of training examples
print('X = ', X[: 5])
print('y = ', y[: 5])
print('m = ', m)
print('n = ', n)

X = [0.04040404 0.08080808 0.12121212 0.16161616]
y = [4.38754501 2.6796499 2.96848981 3.25406475 3.53637472]
m = 100
n = 100
```

```
In [5]: # Scatter plot
plt.scatter(X, y, color='red', marker='+')

# Grid, labels, and title
# plt.grid(True)
plt.rcParams["figure.figsize"] = (10, 10)
plt.xlabel('X')
plt.ylabel('Y')
plt.title('Scatter plot of training data')


# Show the plot
plt.show()
```



```
In [6]: import matplotlib.pyplot as plt
plt.style.use('fivethirtyeight')

plt.scatter(X, y, color='black')
plt.xlabel('X')
plt.ylabel('Y')
plt.gca().set_title("Scatter Plotr")
```

```
Out[6]: Text(0.5, 1.0, 'Scatter Plotr')
```



```
In [7]: m = len(y) # Number of training examples
        n = len(X) # Number of training examples
```

```
In [8]: X_0 = np.ones((m, 1))
        X_0[:5]
```

```
Out[8]: array([[1.],
               [1.],
               [1.],
               [1.],
               [1.]])
```

```
In [9]: X_1 = X.reshape(m, 1)
        X_1[:10]
```

```
Out[9]: array([[0.        ],
               [0.04040404],
               [0.08080808],
               [0.12121212],
               [0.16161616],
               [0.2020202 ],
               [0.24242424],
               [0.28282828],
               [0.32323232],
               [0.36363636]])
```

```
In [10]: # Lets use hstack() function from numpy to stack X_0 and X_1 horizontally (i.e. column
          # This will be our final X matrix (feature matrix)
          X = np.hstack((X_0, X_1))
          X[:5]
```

```
Out[10]: array([[1.      , 0.      ],
               [1.      , 0.04040404],
               [1.      , 0.08080808],
               [1.      , 0.12121212],
               [1.      , 0.16161616]])
```

```
In [11]: theta = np.zeros(2)
theta
```

```
Out[11]: array([0., 0.])
```

```
In [12]: def compute_cost(X, y, theta):
        """
        Compute cost for linear regression.
        Input Parameters
        -----
        X : 2D array where each row represent the training example and each column represent
        m= number of training examples
        n= number of features (including X_0 column of ones)
        y : 1D array of labels/target value for each traing example. dimension(1 x m)
        theta : 1D array of fitting parameters or weights. Dimension (1 x n)
        Output Parameters
        -----
        J : Scalar value.
        """
        predictions = X.dot(theta)
        errors = np.subtract(predictions, y)
        sqrErrors = np.square(errors)
        J = 1 / (2 * m) * np.sum(sqrErrors)
        return J

def gradient_descent(X, y, theta, alpha, iterations):
    """
    Compute cost for linear regression.
    Input Parameters
    -----
    X : 2D array where each row represent the training example and each column represent
    m= number of training examples
    n= number of features (including X_0 column of ones)
    y : 1D array of labels/target value for each traing example. dimension(m x 1)
    theta : 1D array of fitting parameters or weights. Dimension (1 x n)
    alpha : Learning rate. Scalar value
    iterations: No of iterations. Scalar value.
    Output Parameters
    -----
    theta : Final Value. 1D array of fitting parameters or weights. Dimension (1 x n)
    cost_history: Conatins value of cost for each iteration. 1D array. Dimansion(m x 1)
    """
    cost_history = np.zeros(iterations)
    for i in range(iterations):
        predictions = X.dot(theta)
        errors = np.subtract(predictions, y)
        sum_delta = (alpha / m) * X.transpose().dot(errors);
        theta = theta - sum_delta;
        cost_history[i] = compute_cost(X, y, theta)
    return theta, cost_history
```

```
In [13]: # Lets compute the cost for theta values
cost = compute_cost(X, y, theta)
print('The cost for given values of theta_0 and theta_1 =', cost)
```

The cost for given values of theta_0 and theta_1 = 5.524438459196242

```
In [14]: theta = [0., 0.]
iterations = 1500;
alpha = 0.1;

theta, cost_history = gradient_descent(X, y, theta, alpha, iterations)
print('Final value of theta =', theta)
print('cost_history =', cost_history)
```

Final value of theta = [5.92794892 -2.03833663]
cost_history = [5.16999006 4.96338989 4.7855721 ... 0.98499308 0.98499308 0.98499308]

```
In [15]: # Since X is list of list (feature matrix) lets take values of column of index 1 only
plt.scatter(X[:,1], y, color='b', marker='+', label= 'Training Data')
plt.plot(X[:,1],X.dot(theta), color='r', label='Linear Regression')
plt.rcParams["figure.figsize"] = (10,6)

plt.xlabel('Input Variable')
plt.ylabel('Output Variable')
```


```
plt.title('Linear Regression using 2 variables')
plt.legend()
```

Out[15]: <matplotlib.legend.Legend at 0x2c43ba24650>



```
In [16]: plt.plot(range(1, iterations + 1), cost_history, color='blue')
plt.rcParams["figure.figsize"] = (10,6)
# plt.grid()
plt.xlabel('Number of iterations')
plt.ylabel('Cost (J)')
plt.title('Convergence of gradient descent')
```

Out[16]: Text(0.5, 1.0, 'Convergence of gradient descent')



In [35]:

'export' is not recognized as an internal or external command,
operable program or batch file.

In []:

Loading [MathJax]/jax/output/CommonHTML/fonts/TeX/fontdata.js