Fall 2007 CS186 Discussion Section: Week 6, 10/01 - 10/05

Your Friendly TAs

October 2, 2007

1 Relational Algebra and Relational Calculus

Consider the following schema on figure ??:

```
Suppliers(sid:integer, sname:string, address:string)
Parts(pid:integer, pname:string, color:string)
Catalog(sid:integer, pid:integer, cost:real)
```

Table 1: Schema for the supply chain database.

The key fields are underlined, and the domain of each field is listed after the field name. The Catalog relation lists the prices charged for parts by Suppliers. Write the following queries in relational algebra:

1. Find the *names* of suppliers who supply some red part.

```
\pi_{name}(\pi_{sid}((\pi_{pid}\sigma_{color='red'}Parts) \bowtie Catalog) \bowtie Suppliers) \{R|\exists S \in Suppliers \land R.name = S.name \land (\exists C \in Catalog \land (\exists P \in Parts(P.color =' red' \land P.pid = C.pid \land S.sid = C.sid)))\}
```

2. Find the sids of suppliers who supply some red or green part.

```
\pi_{sid}(\pi_{pid}(\sigma_{color='red' \lor color='green'}Parts) \bowtie Catalog)
\{R|\exists C \in Catalog \land R.sid = C.sid \land (\exists P \in Parts((P.color='red' \lor P.color='green') \land P.pid = C.pid))\}
```

3. Find the sids of suppliers who supply some red part or are at 221 Packer Street.

```
\rho(R_1, \pi_{sid}((\pi_{pid}\sigma_{color='red'}Parts) \bowtie Catalog))
\rho(R_2, \pi_{sid}\sigma_{address='221PackerStreet'}Suppliers)
R_1 \cup R_2
\{R|\exists S \in Suppliers \land R.sid = S.sid \land (\exists C \in Catalog \land (\exists P \in Parts(P.pid = C.pid \land S.sid = C.sid \land (P.color =' red' \lor S.address =' 221 Parker St.'))))\}
```

4. Find the sids of suppliers who supply some red part and some green part.

```
\rho(R_1, \pi_{sid}((\pi_{pid}\sigma_{color='red'}Parts) \bowtie Catalog))
\rho(R_2, \pi_{sid}((\pi_{pid}\sigma_{color='green'}Parts) \bowtie Catalog))
R_1 \cap R_2
\{R|\exists C_1 \in Catalog \land R.sid = C_1.sid \land \exists C_2 \in Catalog(C_1.sid = C_2.sid \land C_1.pid \neq C_2.pid \land (\exists P_1 \in Parts(P_1.pid = C_1.pid \land P_1.color = 'red')) \land (\exists P_2 \in Parts(P_2.pid = C_2.pid \land P_2.color = 'green')))\}
```

5. Find the *sids* of suppliers who supply every part.

```
(\pi_{sid,pid}Catalog)/(\pi_{pid}Parts)
\{R|\forall P \in Parts \Rightarrow \exists C \in Catalog(C.sid = R.sid \land P.pid = C.pid)\}
```

6. Find the sids of suppliers who supply every red part.

```
(\pi_{sid,pid}Catalog)/(\pi_{pid}\sigma_{color='red'}Parts)
\{R|\forall P \in Parts(P.color='red') \Rightarrow \exists C \in Catalog(C.sid=R.sid \land P.pid=C.pid)\}
```

7. Find the sids of suppliers who supply every red or green part.

```
(\pi_{sid,pid}Catalog)/(\pi_{pid}\sigma_{color='red'\vee color='green'}Parts)
\{R|\forall P \in Parts(P.color='red'\vee P.color='green') \Rightarrow \exists C \in Catalog(C.sid=R.sid \land P.pid=C.pid)\}
```

8. Find the sids of suppliers who supply every red part or supply every green part.

```
\rho(R_1, ((\pi_{sid,pid}Catalog)/(\pi_{pid}\sigma_{color='red'}Parts)))
\rho(R_2, ((\pi_{sid,pid}Catalog)/(\pi_{pid}\sigma_{color='green'}Parts)))
R_1 \vee R_2 \ (\pi_{sid,pid}Catalog)/(\pi_{pid}\sigma_{color='red'\vee color='green'}Parts)
\{R|(\forall P \in Parts(P.color = 'red') \Rightarrow \exists C \in Catalog(C.sid = R.sid \land P.pid = C.pid)) \lor (\forall P \in Parts(P.color = 'green') \Rightarrow \exists C \in Catalog(C.sid = R.sid \land P.pid = C.pid))\}
```

9. Find pairs of sids such that the supplier with the first sid charges more for some part than the supplier with the second sid.

```
\rho(R_1, Catalog)
\rho(R_2, Catalog)
\pi_{R_1.sid, R_2.sid}\sigma_{R_1.pid=R_2.pid \land R_1.sid \neq R_2.sid \land R_1.cost > R_2.cost}(R_1 \times R_2)
\{R|\exists C_1 \in Catalog(R.sid_1 = C_1.sid \land \exists C_2 \in Catalog(R.sid_2 = C_2.sid \land C_1.sid \neq C_2.sid \land C_1.pid = C_2.pid \land C_1.cost > C_2.cost)\}
```

10. Find the pids of parts supplied by at least two different suppliers.

```
\rho(R_1, Catalog)
\rho(R_2, Catalog)
\pi_{R_1.pid}\sigma_{R_1.pid=R_2.pid \land R_1.sid \neq R_2.sid}(R_1 \times R_2)
\{R | \exists C_1 \in Catalog(R.pid = C_1.pid \land \exists C_2 \in Catalog(C_1.sid \neq C_2.sid \land C_1.pid = C_2.pid))\}
```

11. Find the pids of the most expensive parts, supplied by suppliers named ACME.

```
\begin{split} &\rho(R_1, \pi_{sid}\sigma_{name='\text{ACME'}}Suppliers) \\ &\rho(R_2, R_1 \bowtie Catalog) \\ &\rho(R_3, R_2) \\ &\rho(R_4(sid, pid, cost), \sigma_{R_3.cost < R_2.cost}(R_3 \times R_2)) \\ &\pi_{pid}(R_2 - \pi_{sid, pid, cost}R_4) \\ &\{R|\exists C_1 \in Catalog(R.pid = C_1.pid \land \exists S \in Suppliers(S.name =' \text{ACME'} \land C_1.sid = S.sid \land \forall C_2 \in Catalog(C_2.pid \neq C_1.pid \land C_2.sid = C_1.sid \land C_1.cost \neq C_2.cost))\} \end{split}
```