CALIGA Setup Checklist

Before you Start

James sends you three files. Save all three to your Downloads folder:

- **settings_default.ini**
- **customer_profiles.json**
- **caliga.env**

Clone the Repo

Mac

```
cd ~/Desktop
git clone https://github.com/jhepburn-hue/Internal-Tool-CALIGA.git
cd Internal-Tool-CALIGA
```

Windows

```
cd $HOME\Desktop
git clone https://github.com/jhepburn-hue/Internal-Tool-CALIGA.git
cd Internal-Tool-CALIGA
```

Sign in to GitHub if asked.

Install the Packages in a Virtual Environment

Mac

```
python3 -m venv .venv
.venv/bin/pip install -r requirements.txt
```

Windows

```
py -m venv .venv
.venv\Scripts\pip install -r requirements.txt
```

It's done when it says **Successfully installed**. You can ignore a notice about a new release of pip.

Place the Files

The .env file goes in the CALIGA folder. The two private files go in their own folder outside it.

Mac

```
mkdir -p ~/Documents/caliga-private
mv ~/Downloads/settings_default.ini ~/Downloads/customer_profiles.json
~/Documents/caliga-private/
mv ~/Downloads/caliga.env .env
```

Windows

```
mkdir $HOME\Documents\caliga-private
Move-Item $HOME\Downloads\settings_default.ini,
$HOME\Downloads\customer_profiles.json $HOME\Documents\caliga-private\
Move-Item $HOME\Downloads\caliga.env .env
```

Edit .env

First, generate a secret key and copy what it prints.

Mac

```
.venv/bin/python -c "import secrets; print(secrets.token_hex(32))"
```

Windows

```
.venv\Scripts\python -c "import secrets; print(secrets.token_hex(32))"
```

Next, find your username, which you need for the folder path.

Mac: whoami

Windows: echo $env:USERNAME

Then open the file.

Mac: open -e .env

Windows: notepad .env

Change these lines, then save:

Line	Mac	Windows
SECRET_KEY=	The key you generated	The key you generated
INI_PRIVATE_DIR=	/Users/<your username>/Documents/caliga-private	C:/Users/<your username>/Documents/caliga-private
ACTIVE_IAP_COOKIE=	Filled in when you copy the Forge cookie	Filled in when you copy the Forge cookie
ACTIVE_IAP_UID=	Filled in when you copy the Forge cookie	Filled in when you copy the Forge cookie

Line	Mac	Windows
PB_ADMIN_TOKEN=	Filled in when you copy the PocketBase value	Filled in when you copy the PocketBase value

Also check that the line **AUTH_MODE=dev** is in the file and doesn't start with #.

Sign in to Google Cloud

The same on Mac and Windows:

```
gcloud auth application-default login
```

A browser window opens. Sign in with your Wavelynx Google account.

Copy the Forge Cookie

1. Open Forge in Chrome and sign in.
2. Press F12 (Mac: Cmd+Option+I), then go to Application, then Cookies, then the Forge site.
3. Copy the value of the cookie whose name starts with **__Host-GCP_IAP_AUTH_TOKEN** and paste it after **ACTIVE_IAP_COOKIE=** in .env.
4. Copy the value of the **GCP_IAP_UID** cookie and paste it after **ACTIVE_IAP_UID=**.
5. Save .env.

The cookie expires. Repeat these steps whenever Forge builds start failing, then restart CALIGA.

Copy the PocketBase Value

6. Open PocketBase in Chrome and sign in.
7. Press F12 (Mac: Cmd+Option+I), then go to Application, then Local storage, then the Wavelynx site.
8. Copy the value of the key whose name is **pb_admin_auth** and paste it after **PB_ADMIN_TOKEN=** in .env.
9. Save .env.

The value expires. Repeat these steps whenever PocketBase tokens start failing, then restart CALIGA.

Run CALIGA

Mac

```
.venv/bin/python app.py
```

Windows

```
.venv\Scripts\python app.py
```

When it shows **Running on http://127.0.0.1:5000**, open that address in Chrome or Edge. Keep the terminal window open while you use CALIGA. Press Ctrl+C in it to stop CALIGA.