ⓘ This quiz has been re-graded; your score was affected.

Multiple Choice - Python - Spring 2025

- Due No due date
- Points 15
- Questions 15
- Time limit 75 Minutes

This quiz is no longer available as the course has been concluded.

Attempt history

	Attempt	Time	Score	Re-graded
LATEST	Attempt 1	48 minutes	11.17 out of 15	13 out of 15

ⓘ Correct answers are hidden.

Score for this quiz: 13 out of 15
Submitted 22 Oct 2025 at 19:07
This attempt took 48 minutes.

Partial

Question 1
0.67 / 1 pts

In Python,

- [ ] expression 'abc' - 'bc' evaluates to string 'a'
- [x] if variable lis is a list with a sufficient number of elements, lis[0:3] is the list of its first three elements
- [ ] expression 'c' + 'ab' evaluates to string 'abc'
- [x] expression "Sydney"[1:3] will evaluate to string "yd"
- [ ] expression re.split(":\s", "here: 235") calls method split of module re with string ":\s" as the first argument and string "here: 235" as the second

Partial

Question 2
0.5 / 1 pts

After the following Python code is executed:

```
a = 123
b = a
a = 'I was a number'
d = str(123)
```

Which of the following expressions will evaluate to True?

- [x] d == '123'
- [x] a == "I was a number"
- [ ] b == "123"
- [x] a is b

Question 3

Original score: 0 / 1 pts Re-graded score: 1 / 1 pts

This question has been re-graded.

Python has a module for regular expressions, **re**, which contains a method called **split**. Assuming that you have imported re, consider each of the following statements about method re.split and select it if it is true:

- [ ] calling re.split('-', '14/05/2024') returns list ['14', '05', '2024']
- [x] calling re.split('\d', 'alpha1beta2gamma') returns list ['alpha', 'beta', 'gamma']
- [ ] calling re.split(':', 'a:b:c') returns string 'abc'
- [x] calling print(re.split('\s+', 'Gen AI')) prints ['Gen', 'AI] to the standard output

Question 4

1 / 1 pts

In Python,

- [ ] len(sys.argv[0]) is the number of command line arguments
- [x] sys.argv is the list of the command line arguments passed to the script (sys.argv[0] is the script name)
- [x] sys.argv[1:3] is a list with the first and second arguments passed to the script from the command line, if provided
- [ ] sys.argv[1+2] are the first and second arguments passed to the script

Question 5

1 / 1 pts

In Python, which of these instructions will create a list called **lis** with content **['mars', 'earth', 'venus']**?

- [ ] lis[0:3] = ['mars', 'earth', 'venus']

  lis = ['mars']

  lis.append('earth')
- [x] lis.append('venus')
- [ ] lis = ['mercury', 'mars', 'earth', 'venus'] - ['mercury']

  lis = ['earth', 'venus']
- [x] lis.insert(0, 'mars')

lis = ['mars', 'earth']

- [ ] lis[2] = 'venus'

Question 6

1 / 1 pts

If my_list = [1, -1, 1, -1, 1], which of the following statements has the effect, possibly amongst others, of setting the value of the list's last element to 0?

- [x] my_list[-1] = 0
- [ ] my_list[4] += 1
- [x] my_list[3:5] = [0, 0]
- [x] my_list[my_list[1]] = 0 # tricky! pay attention!
- [x] my_list[4] = my_list[0] + my_list[1]

Question 7

1 / 1 pts

If y = [1,2,3,4,5,6,7,8,9,10], which of the following expressions evaluate to 10?

- [x] y[-1]
- [x] len(y[2:]) + len(y[0:2])
- [ ] 2 * y[5]
- [x] len(y)
- [ ] y[2] + y[8]

Question 8

1 / 1 pts

If my_dict = {"AAA": 10, "AAB": 7, "ABB": 4, "BBB": 1}, which of the following evaluate to True?

- [ ] my_dict[10] == "AAA"
- [x] my_dict["ABB"] == 4 * my_dict["BBB"]
- [x] "ABB" in my_dict
- [ ] len(my_dict) == 8
- [x] my_dict["BBB"] == 1

Question 9

1 / 1 pts

After executing the following statements:

```
scores_dict = {"mark": 150, "anika": 250}
scores_list = [150, 250]
scores_dict["dacheng"] = 200
scores_list.append(200)
```

- [ ] Expression scores_dict[0] returns an integer
- [ ] The value of scores_list[1] is 200
- [x] Expression scores_dict["dacheng"] == scores_list[2] evaluates to True
- [x] The value of scores_dict["mark"] is 150
- [ ] String '150' is a key in dictionary scores_dict

Partial

Question 10

0.67 / 1 pts

Using re.search() with the regular expression **\D{2}** in Python, in which of the following **strings** a match will be found? (NB: pay attention to the meaning of \D)

- [x] (0410) 676767
- [x] ******
- [x] my number is not 0410 676767
- [ ] 0410 676767
- [x] 8s20s20s

Question 11

1 / 1 pts

Consider this function:

```
def fun(w = 10, x = 10, b = 0):
    print(w * x + b)
```

If we call:

```
fun(9, 10, 10)
```

this function will print 100. Which of the following calls to the function will print the same value?

- [x] fun()
- [x] fun(0, -1, 100)
- [x] fun(b = 20, x = 8, w = 10)
- [ ] fun(100)
- [x] fun(6, 6, 64)

Partial

Question 12

0.67 / 1 pts

Given this Python function:

```
def maximum(*args):
    m = args[0]
    for item in args:
```

```
        if item > m:
            m = item
    print(m)
```

which of the following calls will print 4 as its output?

- [x] maximum(1, 2, 3, 4)
- [x] maximum(*[1, 2, 3, 4])
- [ ] maximum([1, 2, 3, 4])
- [ ] maximum(2 * 2)

Incorrect

Question 13

0 / 1 pts

After this Python code is executed:

```
def rotate(lis):
    lis.append(lis[0])
    del(lis[0])
my_list = ['a','b','c','d']
rotate(my_list)
```

which of the following statements are true?

- [x] The length of list my_list is 4
- [ ] my_list[-3] is equal to 'c'
- [ ] my_list is equal to ['b', 'c', 'd, 'a']
- [x] Function call rotate(my_list) cannot modify list my_list
- [ ] my_list is equal to ['b', 'c', 'd']

Question 14

1 / 1 pts

In Python, which of the following statements are true?

- [ ] A call to function bytes() returns an object of type string
- [x] Function struct.pack returns a value that can be written to a binary file
- [x] The first argument of function struct.pack is a format string
- [x] The bytes and bytearray types can be used to store binary data
- [ ] You can write strings or lists to a file opened for writing in binary mode without any conversion

Partial

Question 15

0.67 / 1 pts

In Python, which of the following statements about files are true?

Instruction **open('marks.csv')** opens file marks.csv for reading in text mode, assuming that the file exists in the current directory and the program's user has permission to read it.

If fin is a file object opened for reading in text mode, a call to method **fin.read()** will return exactly one line of text from the file, even if more are available.

The following code:

```
try:
    fin = open("marks.csv")
except:
    print(sys.exc_info()[0])
```

tries to open file marks.csv in the current directory and assigns the returned file object to variable fin. If this fails, it prints an error message from the system.

Instruction **open('marks.csv', 'ab')** opens file marks.csv for appending in binary mode, assuming that the program's user has the required permissions.

Quiz score: 13 out of 15

This quiz score has been manually adjusted by +0.8333333333333393 points.