



www.safeworkplace.org

(262) 652-8660

joe@industrialsafetycontrols.com | safetysensing@earthlink.net

Contact Information

Name: _____ Company: _____

Address: _____ City: _____ State: _____ Zip: _____

Phone: _____ Cell: _____ Fax: _____

Email: _____ Company Website: _____

DRIVE TECHNOLOGY AND MOTORSTARTERS

Product Type:

- ☐ Softstarter
- ☐ Motor Brake Relay
- ☐ Motorstarter
- ☐ Solid State Relay / Solid State Contactor
- ☐ Reversing Contactor
- ☐ Speed Controller / Phase Controller

Softstarters

230 V up to (For Single Phase Motors) :

- ☐ 1,5 kW
- ☐ 5 kW
- ☐ 3 kW
- ☐ 5,5 kW

400 V up to (For Three Phase Motors) :

- ☐ 0,75 kW
- ☐ 4 kW
- ☐ 5,5 kW
- ☐ 7,5 kW
- ☐ 11 kW
- ☐ 15 kW

- ☐ 18,5 kW
- ☐ 22 kW
- ☐ 30 kW

Load Voltage Up To:

- ☐ AC 230 V
- ☐ AC 480 V
- ☐ 3AC 230 / 400 V
- ☐ 3AC 400 V
- ☐ 3AC 460 V
- ☐ 3AC 480 V
- ☐ 3AC 475 V

Extra Functions:

- ☐ Temperature Monitoring
- ☐ Mains Monitoring

Approvals and Markings

- ☐ TUV
- ☐ UKCA
- ☐ UL-listed C/US, UKCA

Widths:

- ☐ 22,5 mm
- ☐ 35 mm
- ☐ 45 mm
- ☐ 52,5 mm
- ☐ 67,5 mm
- ☐ 72 mm
- ☐ 90 mm
- ☐ 100 mm
- ☐ 103 mm
- ☐ 105 mm
- ☐ 112,5 mm
- ☐ 205 mm

Contacts:

- ☐ 1 Changeover
- ☐ 2x1 NO Contact
- ☐ 2x1 Changeover
- ☐ 3x1 NO Contact

Quantity:**Target Delivery Date:**

Cross Reference Part Number:

Motor Brake Relays

Width (45mm - 110mm):

Braking Time Adjustable Up To Max:

- ☐ 15s
- ☐ 20s
- ☐ 31s
- ☐ 320s

Braking Current Adjustable Up To Max:

- ☐ 25 A
- ☐ 32 A
- ☐ 60 A
- ☐ 80 A
- ☐ 600 A

Contacts:

- ☐ 1 Changeover
- ☐ 2 NO Contacts
- ☐ 4 NO Contacts

Quantity:

Target Delivery Date:

Cross Reference Part Number:

Motorstarters

Load Current Up To:

- ☐ 5 A
- ☐ 7 A
- ☐ 9 A

Phase:

- ☐ 1 Phase
- ☐ 3 Phase

Approvals and Markings

- ☐ UL-listed C/US
- ☐ UKCA
- ☐ UL-listed C/US, UKCA

Aux Voltage:☐ DC 24 V**Bus Interface:**☐ Modbus RTV**Contacts:**☐ 1 Changeover**Load Voltage Up To:**☐ AC 230 V☐ 3AC 200 - 480 V**Width (22mm Only)**☐ Yes**Quantity:****Target Delivery Date:****Cross Reference Part Number:****Solid State Relays / Contactors****Load Current Up To:**☐ 40 A☐ 45 A☐ 2 x 48 A☐ 50 A☐ 60 A☐ 88 A☐ 125 A**Widths:**☐ 22,5mm☐ 45mm☐ 67,5mm☐ 90mm☐ 112,5mm**Number of Poles:**☐ 1☐ 2☐ 3

On/Off Input Control:

- ☐ DC
- ☐ AC
- ☐ AC/DC

Load Voltage Up To:

- ☐ AC 400 V
- ☐ AC 480 V
- ☐ AC 600 V

Approvals and Markings

- ☐ -
- ☐ UL-rec. C/US
- ☐ UL-listed C/US

Aux Voltage:

- ☐ DC 24 V

Analog Input Control:

- ☐ 4 - 20mA

Contacts:

- ☐ 1 Changeover
- ☐ with Signal Contact
- ☐ without Signal Contact

Quantity:**Target Delivery Date:****Cross Reference Part Number:****Reversing Contactors****Load Current Up To:**

- ☐ 12 A
- ☐ 20 A

Widths:

- ☐ 45mm
- ☐ 67,5mm
- ☐ 90mm
- ☐ 112,5mm

Number of Poles:

☐ 3**On/Off Input Control:**

- ☐ DC
- ☐ AC
- ☐ AC/DC

Load Voltage Up To:

- ☐ 3AC 24 - 480 V
- ☐ 3AC 400 V

Approvals and Markings

- ☐ -
- ☐ UL-listed C/US

Contacts:

- ☐ 1 Changeover
- ☐ 2 x 1 Changeover

Quantity:**Target Delivery Date:****Cross Reference Part Number:****Speed / Phase Controller****Nominal Load Up To:**

- ☐ 0,3 kW
- ☐ 2,2 kW

Width (53mm - 68mm):

- ☐ 45mm
- ☐ 67,5mm
- ☐ 90mm
- ☐ 112,5mm

Phases:

- ☐ 1 Phase
- ☐ 3 Phase

Contacts:

- ☐ For 1 Phase Operation
- ☐ For 3 Phase Operation

Enclosure Design:

- ☐ Switch Cabinet
- ☐ Distribution Board

Quantity:

Target Delivery Date:

Cross Reference Part Number:

