

In [1]:

```
# This mounts your Google Drive to the Colab VM.
from google.colab import drive
drive.mount('/content/drive', force_remount=True)

# Enter the foldername in your Drive where you have saved the unzipped
# assignment folder, e.g. 'cs231n/assignments/assignment1/'
FOLDERNAME = "Colab Notebooks/assignment1"
assert FOLDERNAME is not None, "[!] Enter the foldername."

# Now that we've mounted your Drive, this ensures that
# the Python interpreter of the Colab VM can load
# python files from within it.
import sys
sys.path.append('/content/drive/My Drive/{}'.format(FOLDERNAME))

# This downloads the CIFAR-10 dataset to your Drive
# if it doesn't already exist.
%cd drive/My Drive/$FOLDERNAME/cs231n/datasets/
!bash get_datasets.sh
%cd /content/drive/My Drive/$FOLDERNAME
```

```
Mounted at /content/drive
/content/drive/My Drive/Colab Notebooks/assignment1/cs231n/datasets
/content/drive/My Drive/Colab Notebooks/assignment1
```

Multiclass Support Vector Machine exercise

Complete and hand in this completed worksheet (including its outputs and any supporting code outside of the worksheet) with your assignment submission. For more details see the [assignments page](#) on the course website.

In this exercise you will:

- implement a fully-vectorized **loss function** for the SVM
- implement the fully-vectorized expression for its **analytic gradient**
- **check your implementation** using numerical gradient
- use a validation set to **tune the learning rate and regularization** strength
- **optimize** the loss function with **SGD**
- **visualize** the final learned weights

In [2]:

```
# Run some setup code for this notebook.
import random
import numpy as np
from cs231n.data_utils import load_CIFAR10
import matplotlib.pyplot as plt

# This is a bit of magic to make matplotlib figures appear inline in the
# notebook rather than in a new window.
%matplotlib inline
plt.rcParams['figure.figsize'] = (10.0, 8.0) # set default size of plots
plt.rcParams['image.interpolation'] = 'nearest'
plt.rcParams['image.cmap'] = 'gray'

# Some more magic so that the notebook will reload external python modules;
# see http://stackoverflow.com/questions/1907993/autoreload-of-modules-in-ipython
%load_ext autoreload
%autoreload 2
```

CIFAR-10 Data Loading and Preprocessing

In [3]:

```
# Load the raw CIFAR-10 data.
cifar10_dir = 'cs231n/datasets/cifar-10-batches-py'

# Cleaning up variables to prevent loading data multiple times (which may cause memory
try:
    del X_train, y_train
    del X_test, y_test
    print('Clear previously loaded data.')
except:
    pass


X_train, y_train, X_test, y_test = load_CIFAR10(cifar10_dir)

# As a sanity check, we print out the size of the training and test data.
print('Training data shape: ', X_train.shape)
print('Training labels shape: ', y_train.shape)
print('Test data shape: ', X_test.shape)
print('Test labels shape: ', y_test.shape)
```

```
Training data shape: (50000, 32, 32, 3)
Training labels shape: (50000,)
Test data shape: (10000, 32, 32, 3)
Test labels shape: (10000,)
```

In [4]:

```
# Visualize some examples from the dataset.
# We show a few examples of training images from each class.
classes = ['plane', 'car', 'bird', 'cat', 'deer', 'dog', 'frog', 'horse', 'ship', 'truck']
num_classes = len(classes)
samples_per_class = 7
for y, cls in enumerate(classes):
    idxs = np.flatnonzero(y_train == y)
    idxs = np.random.choice(idxs, samples_per_class, replace=False)
    for i, idx in enumerate(idxs):
        plt_idx = i * num_classes + y + 1
        plt.subplot(samples_per_class, num_classes, plt_idx)
        plt.imshow(X_train[idx].astype('uint8'))
        plt.axis('off')
        if i == 0:
            plt.title(cls)
plt.show()
```



In [5]:

```
# Split the data into train, val, and test sets. In addition we will
# create a small development set as a subset of the training data;
# we can use this for development so our code runs faster.
num_training = 49000
num_validation = 1000
num_test = 1000
num_dev = 500

# Our validation set will be num_validation points from the original
# training set.
mask = range(num_training, num_training + num_validation)
X_val = X_train[mask]
y_val = y_train[mask]

# Our training set will be the first num_train points from the original
# training set.
mask = range(num_training)
X_train = X_train[mask]
y_train = y_train[mask]

# We will also make a development set, which is a small subset of
# the training set.
mask = np.random.choice(num_training, num_dev, replace=False)
X_dev = X_train[mask]
y_dev = y_train[mask]

# We use the first num_test points of the original test set as our
# test set.
mask = range(num_test)
X_test = X_test[mask]
y_test = y_test[mask]

print('Train data shape: ', X_train.shape)
print('Train labels shape: ', y_train.shape)
```

```
print('Validation data shape: ', X_val.shape)
print('Validation labels shape: ', y_val.shape)
print('Test data shape: ', X_test.shape)
print('Test labels shape: ', y_test.shape)
```

```
Train data shape: (49000, 32, 32, 3)
Train labels shape: (49000,)
Validation data shape: (1000, 32, 32, 3)
Validation labels shape: (1000,)
Test data shape: (1000, 32, 32, 3)
Test labels shape: (1000,)
```

In [6]:

```
# Preprocessing: reshape the image data into rows
X_train = np.reshape(X_train, (X_train.shape[0], -1))
X_val = np.reshape(X_val, (X_val.shape[0], -1))
X_test = np.reshape(X_test, (X_test.shape[0], -1))
X_dev = np.reshape(X_dev, (X_dev.shape[0], -1))

# As a sanity check, print out the shapes of the data
print('Training data shape: ', X_train.shape)
print('Validation data shape: ', X_val.shape)
print('Test data shape: ', X_test.shape)
print('dev data shape: ', X_dev.shape)
```

```
Training data shape: (49000, 3072)
Validation data shape: (1000, 3072)
Test data shape: (1000, 3072)
dev data shape: (500, 3072)
```

In [7]:


```
# Preprocessing: subtract the mean image
# first: compute the image mean based on the training data
mean_image = np.mean(X_train, axis=0)
print(mean_image[:10]) # print a few of the elements
plt.figure(figsize=(4,4))
plt.imshow(mean_image.reshape((32,32,3)).astype('uint8')) # visualize the mean image
plt.show()

# second: subtract the mean image from train and test data
X_train -= mean_image
X_val -= mean_image
X_test -= mean_image
X_dev -= mean_image

# third: append the bias dimension of ones (i.e. bias trick) so that our SVM
# only has to worry about optimizing a single weight matrix W.
X_train = np.hstack([X_train, np.ones((X_train.shape[0], 1))])
X_val = np.hstack([X_val, np.ones((X_val.shape[0], 1))])
X_test = np.hstack([X_test, np.ones((X_test.shape[0], 1))])
X_dev = np.hstack([X_dev, np.ones((X_dev.shape[0], 1))])

print(X_train.shape, X_val.shape, X_test.shape, X_dev.shape)
```

```
[130.64189796 135.98173469 132.47391837 130.05569388 135.34804082
 131.75402041 130.96055102 136.14328571 132.47636735 131.48467347]
```



(49000, 3073) (1000, 3073) (1000, 3073) (500, 3073)

SVM Classifier

Your code for this section will all be written inside `cs231n/classifiers/linear_svm.py`.

As you can see, we have prefilled the function `svm_loss_naive` which uses for loops to evaluate the multiclass SVM loss function.

```
In [8]: # Evaluate the naive implementation of the loss we provided for you:
from cs231n.classifiers.linear_svm import svm_loss_naive
import time

# generate a random SVM weight matrix of small numbers
W = np.random.randn(3073, 10) * 0.0001

loss, grad = svm_loss_naive(W, X_dev, y_dev, 0.000005)
print('loss: %f' % (loss, ))
```

loss: 8.844316

The `grad` returned from the function above is right now all zero. Derive and implement the gradient for the SVM cost function and implement it inline inside the function `svm_loss_naive`. You will find it helpful to interleave your new code inside the existing function.

To check that you have correctly implemented the gradient correctly, you can numerically estimate the gradient of the loss function and compare the numeric estimate to the gradient that you computed. We have provided code that does this for you:

```
In [9]: # Once you've implemented the gradient, recompute it with the code below
# and gradient check it with the function we provided for you

# Compute the loss and its gradient at W.
loss, grad = svm_loss_naive(W, X_dev, y_dev, 0.0)

# Numerically compute the gradient along several randomly chosen dimensions, and
# compare them with your analytically computed gradient. The numbers should match
# almost exactly along all dimensions.
from cs231n.gradient_check import grad_check_sparse
f = lambda w: svm_loss_naive(w, X_dev, y_dev, 0.0)[0]
grad_numerical = grad_check_sparse(f, W, grad)

# do the gradient check once again with regularization turned on
```

```
# you didn't forget the regularization gradient did you?
loss, grad = svm_loss_naive(W, X_dev, y_dev, 5e1)
f = lambda w: svm_loss_naive(w, X_dev, y_dev, 5e1)[0]
grad_numerical = grad_check_sparse(f, W, grad)
```

```
numerical: 21.893952 analytic: 21.893952, relative error: 5.742220e-12
numerical: 33.024299 analytic: 33.024299, relative error: 1.251668e-11
numerical: 17.595546 analytic: 17.595546, relative error: 1.138822e-11
numerical: -15.438155 analytic: -15.438155, relative error: 2.731251e-11
numerical: 1.480697 analytic: 1.480697, relative error: 1.184671e-10
numerical: 18.358206 analytic: 18.358206, relative error: 8.535861e-12
numerical: 8.041961 analytic: 8.041961, relative error: 7.552094e-13
numerical: -36.227913 analytic: -36.227913, relative error: 2.159209e-12
numerical: -10.501263 analytic: -10.501263, relative error: 7.305446e-12
numerical: -6.915485 analytic: -6.915485, relative error: 4.402828e-11
numerical: 10.513555 analytic: 10.513555, relative error: 8.990463e-12
numerical: -1.345045 analytic: -1.345045, relative error: 1.882887e-10
numerical: 18.631909 analytic: 18.631909, relative error: 1.609035e-11
numerical: -2.529879 analytic: -2.529879, relative error: 1.597297e-11
numerical: 1.197091 analytic: 1.197091, relative error: 2.266631e-10
numerical: -1.901762 analytic: -1.901762, relative error: 1.111588e-12
numerical: 19.852910 analytic: 19.852910, relative error: 7.135166e-12
numerical: 19.749124 analytic: 19.749124, relative error: 1.669670e-12
numerical: 7.759538 analytic: 7.759538, relative error: 3.120427e-11
numerical: -38.785211 analytic: -38.785211, relative error: 2.100198e-12
```

Inline Question 1

It is possible that once in a while a dimension in the gradcheck will not match exactly. What could such a discrepancy be caused by? Is it a reason for concern? What is a simple example in one dimension where a gradient check could fail? How would change the margin affect of the frequency of this happening? *Hint: the SVM loss function is not strictly speaking differentiable*

Your Answer : 매우 간단한 예로, *loss function*에서 미분 불가능한 점이 있을 때 *discrepancy*가 발생하게 된다. 즉, $f(x) = \max(0, x)$ 이라는 함수는 $x = 0$ 에서 첨점을 가지게 되어 미분불가능하다는 것을 쉽게 알 수 있는데, 이러한 점에서 *discrepancy*가 발생하게 되는 것이다.

```
In [10]: # Next implement the function svm_loss_vectorized; for now only compute the loss;
# we will implement the gradient in a moment.
tic = time.time()
loss_naive, grad_naive = svm_loss_naive(W, X_dev, y_dev, 0.000005)
toc = time.time()
print('Naive loss: %e computed in %fs' % (loss_naive, toc - tic))

from cs231n.classifiers.linear_svm import svm_loss_vectorized
tic = time.time()
loss_vectorized, _ = svm_loss_vectorized(W, X_dev, y_dev, 0.000005)
toc = time.time()
print('Vectorized loss: %e computed in %fs' % (loss_vectorized, toc - tic))

# The losses should match but your vectorized implementation should be much faster.
print('difference: %f' % (loss_naive - loss_vectorized))
```

```
Naive loss: 8.844316e+00 computed in 0.121450s
Vectorized loss: 8.844316e+00 computed in 0.013136s
difference: 0.000000
```

```
In [11]: # Complete the implementation of svm_loss_vectorized, and compute the gradient
# of the loss function in a vectorized way.

# The naive implementation and the vectorized implementation should match, but
# the vectorized version should still be much faster.
tic = time.time()
```

```
_, grad_naive = svm_loss_naive(W, X_dev, y_dev, 0.000005)
toc = time.time()
print('Naive loss and gradient: computed in %fs' % (toc - tic))

tic = time.time()
_, grad_vectorized = svm_loss_vectorized(W, X_dev, y_dev, 0.000005)
toc = time.time()
print('Vectorized loss and gradient: computed in %fs' % (toc - tic))

# The loss is a single number, so it is easy to compare the values computed
# by the two implementations. The gradient on the other hand is a matrix, so
# we use the Frobenius norm to compare them.
difference = np.linalg.norm(grad_naive - grad_vectorized, ord='fro')
print('difference: %f' % difference)
```

Naive loss and gradient: computed in 0.116507s
 Vectorized loss and gradient: computed in 0.017767s
 difference: 0.000000

Stochastic Gradient Descent

We now have vectorized and efficient expressions for the loss, the gradient and our gradient matches the numerical gradient. We are therefore ready to do SGD to minimize the loss. Your code for this part will be written inside `cs231n/classifiers/linear_classifier.py`.


In [12]:

```
# In the file linear_classifier.py, implement SGD in the function
# LinearClassifier.train() and then run it with the code below.
from cs231n.classifiers import LinearSVM
svm = LinearSVM()
tic = time.time()
loss_hist = svm.train(X_train, y_train, learning_rate=1e-7, reg=2.5e4,
                      num_iters=1500, verbose=True)
toc = time.time()
print('That took %fs' % (toc - tic))
```

```
iteration 0 / 1500: loss 400.852011
iteration 100 / 1500: loss 241.032289
iteration 200 / 1500: loss 146.400135
iteration 300 / 1500: loss 90.639671
iteration 400 / 1500: loss 56.286532
iteration 500 / 1500: loss 35.745908
iteration 600 / 1500: loss 23.158458
iteration 700 / 1500: loss 16.502893
iteration 800 / 1500: loss 11.707671
iteration 900 / 1500: loss 9.129173
iteration 1000 / 1500: loss 7.272025
iteration 1100 / 1500: loss 6.533916
iteration 1200 / 1500: loss 5.995013
iteration 1300 / 1500: loss 5.535277
iteration 1400 / 1500: loss 5.248094
That took 9.586134s
```

In [13]:

```
# A useful debugging strategy is to plot the loss as a function of
# iteration number:
plt.plot(loss_hist)
plt.xlabel('Iteration number')
plt.ylabel('Loss value')
plt.show()
```



```
In [14]: # Write the LinearSVM.predict function and evaluate the performance on both the
# training and validation set
y_train_pred = svm.predict(X_train)
print('training accuracy: %f' % (np.mean(y_train == y_train_pred), ))
y_val_pred = svm.predict(X_val)
print('validation accuracy: %f' % (np.mean(y_val == y_val_pred), ))
```

```
training accuracy: 0.377347
validation accuracy: 0.377000
```

```
In [28]: # Use the validation set to tune hyperparameters (regularization strength and
# learning rate). You should experiment with different ranges for the learning
# rates and regularization strengths; if you are careful you should be able to
# get a classification accuracy of about 0.39 on the validation set.

# Note: you may see runtime/overflow warnings during hyper-parameter search.
# This may be caused by extreme values, and is not a bug.

# results is dictionary mapping tuples of the form
# (learning_rate, regularization_strength) to tuples of the form
# (training_accuracy, validation_accuracy). The accuracy is simply the fraction
# of data points that are correctly classified.
results = {}
best_val = -1 # The highest validation accuracy that we have seen so far.
best_svm = None # The LinearSVM object that achieved the highest validation rate.

#####
# TODO:
# Write code that chooses the best hyperparameters by tuning on the validation #
# set. For each combination of hyperparameters, train a linear SVM on the #
# training set, compute its accuracy on the training and validation sets, and #
# store these numbers in the results dictionary. In addition, store the best #
# validation accuracy in best_val and the LinearSVM object that achieves this #
```



```

# accuracy in best_svm.
#
# Hint: You should use a small value for num_iters as you develop your
# validation code so that the SVMs don't take much time to train; once you are
# confident that your validation code works, you should rerun the validation
# code with a larger value for num_iters.
#####

# Provided as a reference. You may or may not want to change these hyperparameters
learning_rates = [1e-7, 5e-5]
regularization_strengths = [2.5e4, 5e4]

# *****START OF YOUR CODE (DO NOT DELETE/MODIFY THIS LINE)*****

from itertools import product
grid_search = list(product(*[learning_rates, regularization_strengths]))

for lr, rg in grid_search :
    svm = LinearSVM()

    svm.train(X_train, y_train, learning_rate = lr, reg = rg,
              num_iters = 2000)

    y_train_predict = svm.predict(X_train)
    learning_accuracy = np.mean(y_train_predict == y_train)

    y_validation_predict = svm.predict(X_val)
    validation_accuracy = np.mean(y_validation_predict == y_val)

    results[(lr,rg)] = (learning_accuracy, validation_accuracy)

    if best_val < validation_accuracy :
        best_val = validation_accuracy
        best_svm = svm
# *****END OF YOUR CODE (DO NOT DELETE/MODIFY THIS LINE)*****

# Print out results.
for lr, reg in sorted(results):
    train_accuracy, val_accuracy = results[(lr, reg)]
    print('lr %e reg %e train accuracy: %f val accuracy: %f' % (
        lr, reg, train_accuracy, val_accuracy))

print('best validation accuracy achieved during cross-validation: %f' % best_val)

```

```

/content/drive/My Drive/Colab Notebooks/assignment1/cs231n/classifiers/linear_svm.py:9
4: RuntimeWarning: overflow encountered in double_scalars
    loss = margins_sum/num_train + 0.5*reg*np.sum(W*W)
/usr/local/lib/python3.7/dist-packages/numpy/core/fromnumeric.py:87: RuntimeWarning: o
verflow encountered in reduce
    return ufunc.reduce(obj, axis, dtype, out, **passkwargs)
/content/drive/My Drive/Colab Notebooks/assignment1/cs231n/classifiers/linear_svm.py:9
4: RuntimeWarning: overflow encountered in multiply
    loss = margins_sum/num_train + 0.5*reg*np.sum(W*W)
/content/drive/My Drive/Colab Notebooks/assignment1/cs231n/classifiers/linear_svm.py:9
0: RuntimeWarning: overflow encountered in subtract
    margins = np.maximum(0, scores - correct_class_scores + 1) # SVM
/content/drive/My Drive/Colab Notebooks/assignment1/cs231n/classifiers/linear_svm.py:9
0: RuntimeWarning: invalid value encountered in subtract
    margins = np.maximum(0, scores - correct_class_scores + 1) # SVM
/content/drive/My Drive/Colab Notebooks/assignment1/cs231n/classifiers/linear_svm.py:1
16: RuntimeWarning: overflow encountered in multiply
    dW += reg*W
/content/drive/My Drive/Colab Notebooks/assignment1/cs231n/classifiers/linear_classifi
er.py:88: RuntimeWarning: invalid value encountered in add
    self.W += -learning_rate * grad # 수식참조
lr 1.000000e-07 reg 2.500000e+04 train accuracy: 0.378367 val accuracy: 0.387000

```

```
lr 1.000000e-07 reg 5.000000e+04 train accuracy: 0.371918 val accuracy: 0.380000
lr 5.000000e-05 reg 2.500000e+04 train accuracy: 0.149714 val accuracy: 0.157000
lr 5.000000e-05 reg 5.000000e+04 train accuracy: 0.100265 val accuracy: 0.087000
best validation accuracy achieved during cross-validation: 0.387000
```

In [29]:


```
# Visualize the cross-validation results
import math
import pdb

# pdb.set_trace()

x_scatter = [math.log10(x[0]) for x in results]
y_scatter = [math.log10(x[1]) for x in results]

# plot training accuracy
marker_size = 100
colors = [results[x][0] for x in results]
plt.subplot(2, 1, 1)
plt.tight_layout(pad=3)
plt.scatter(x_scatter, y_scatter, marker_size, c=colors, cmap=plt.cm.coolwarm)
plt.colorbar()
plt.xlabel('log learning rate')
plt.ylabel('log regularization strength')
plt.title('CIFAR-10 training accuracy')

# plot validation accuracy
colors = [results[x][1] for x in results] # default size of markers is 20
plt.subplot(2, 1, 2)
plt.scatter(x_scatter, y_scatter, marker_size, c=colors, cmap=plt.cm.coolwarm)
plt.colorbar()
plt.xlabel('log learning rate')
plt.ylabel('log regularization strength')
plt.title('CIFAR-10 validation accuracy')
plt.show()
```



```
In [30]: # Evaluate the best svm on test set
y_test_pred = best_svm.predict(X_test)
test_accuracy = np.mean(y_test == y_test_pred)
print('linear SVM on raw pixels final test set accuracy: %f' % test_accuracy)
```

linear SVM on raw pixels final test set accuracy: 0.367000

```
In [31]: # Visualize the learned weights for each class.
# Depending on your choice of learning rate and regularization strength, these may
# or may not be nice to look at.
w = best_svm.W[:-1,:] # strip out the bias
w = w.reshape(32, 32, 3, 10)
w_min, w_max = np.min(w), np.max(w)
classes = ['plane', 'car', 'bird', 'cat', 'deer', 'dog', 'frog', 'horse', 'ship', 'truck']
for i in range(10):
    plt.subplot(2, 5, i + 1)

    # Rescale the weights to be between 0 and 255
    wimg = 255.0 * (w[:, :, :, i].squeeze() - w_min) / (w_max - w_min)
    plt.imshow(wimg.astype('uint8'))
    plt.axis('off')
    plt.title(classes[i])
```



Inline question 2

Describe what your visualized SVM weights look like, and offer a brief explanation for why they look the way that they do.

Your Answer : SVM weights은 그 label class에 있는 데이터들의 평균적인 모양이다(즉, 평균적으로 보이는 모양을 나타낸다). 여기서 나의 visualized SVM weights는 매우 흐릿하게 형상화되어 있다. 그 이유는 predict를 위해 label의 score를 구할 때 X 값(Sample)과 가중치(Weights)의 내적을 통해서 구하는데, 여기서 prediction의 값이 전반적으로 낮게 나왔기 때문이다. 이를 높이기 위해서는 일반적으로 X 와 가중치가 평행에 가까워야 한다.