

SILKWAVE Web/Admin API — hand-authored spec, not auto-generated

spec source: [silkwave-web-api-openapi.yaml](#)

SILKWAVE Web/Admin API 1.0.0 OAS 3.1

[./silkwave-web-api-openapi.yaml](#)

OpenAPI description of the HTTP(S) servlet API exposed by `io.silkwave.web.WebServer` (embedded Jetty, plain `jakarta.servlet.http.HttpServlet` implementations — no Spring MVC, no JAX-RS). Hand-authored from source review of `WebServer.java` and the servlet classes listed under `EndpointsDocumented` below; it is not generated from annotations, since none exist in this codebase.

Server modes

The server runs in exactly one connector mode at a time: HTTP (default port 8501) or HTTPS (default port 8601), whichever is enabled — HTTPS wins if both flags are set. See the `servers` list below for both.

Authentication

All paths under `/` require Jetty Form authentication (roles `user` / `admin` / `moderator`) **except when the server is running in HTTPS-only mode**, where no security handler is attached at all — see the technical report for details. The following paths are explicitly whitelisted from authentication in HTTP mode: `/health`, `/resources-export/*` (note: NOT the bare `/resources-export` path), and static login assets. `/rest/v3/*` is unauthenticated in all modes because it lives on a separate, unsecured servlet context.

Coverage

This spec covers the servlet set reviewed in source, including the admin endpoints below: `HealthServlet`, `SilkwaveAdminServlet`, `NamingServiceAdminServlet`, `ResourcesExportServlet`, `DiscoveryServiceAdminServlet`, `NetworkStatusAdminServlet`, `RegistrationAdminServlet`, `RoutingAdminServlet`, `SecurityAdminServlet`, `NamingAdminServlet`, `StreamAdminServlet`, `FileAdminServlet`, and the optional `CasportV3SimServlet`. The shapes below are intentionally conservative and reflect only the request/response patterns visible in the Java sources.

Servers

`http://{host}:{port}` - HTTP connector (plaintext). Default port 8501.

Computed URL: `http://localhost:8501`

Server variables

host

localhost

port

8501

Authorize



health

Liveness probe

^

GET	/health	Liveness probe	✓
POST	/health	Liveness probe (POST alias)	✓

admin

Hub status / dashboard administration

^

GET	/SilkwaveAdminServlet	Hub dashboard / admin actions	 ✓
POST	/SilkwaveAdminServlet	Hub dashboard / admin actions (POST form, required for action=validate)	 ✓

discovery

Discovery service inventory and service dump

^

GET	/DiscoveryServiceAdminServlet	Discovery service inventory dump	 ✓
-----	-------------------------------	----------------------------------	---

network

Network ownership and subscription inspection

^

GET	/NetworkStatusAdminServlet	Network owner and subscription browser	 ✓
-----	----------------------------	--	---

registration

Local registry and connection registration inspection

^

GET

/RegistrationAdminServlet

Local registry and connection table browser

^

routing

Routing table inspection

^

GET

/RoutingAdminServlet

Routing table browser

^

security

Security registry and cache inspection

^

GET

/SecurityAdminServlet

Security registry and cache browser

^

naming

Name server route inspection

^

GET

/NamingServiceAdminServlet

Name server route browser

^

GET

/NamingAdminServlet

Naming cache browser and route drilldown

^

POST

/NamingAdminServlet

Naming cache browser and route drilldown (POST alias)

^

streams

Stream request and stream-state diagnostics

^

GET

/StreamAdminServlet

Stream diagnostics and request browser

^

files

File transfer and transfer-state diagnostics

^

GET

/FileAdminServlet

File-transfer diagnostics and file list

^

Supports cancel operations (**action=cancel**), a single file detail view (**action=file**), and the file list (**action=files**).

Parameters

Cancel

Name	Description
action * required string (query)	file
token string (query)	Required for cancel and file actions. token
rows integer (query)	10
page integer (query)	1

Servers

These operation-level options override the global server options.

Computed URL:

Server variables

host

port

Execute

Clear

Responses

```
Curl
curl -X 'GET' \
'http://localhost:8501/FileAdminServlet?action=file&rows=10&page=1' \
localhost:8501/docs/#/files/fileAdmin
```

-H 'accept: application/json'

Request URL

http://localhost:8501/FileAdminServlet?action=file&rows=10&page=1

Server response

Code	Details
200	Response body <pre><html> <head> <title>Silkwave Admin Service Login Page</title> <link rel="stylesheet" type="text/css" href="jquery-ui/css/redmond/jquery-ui-1.10.4.custom.min.css"> <link rel="stylesheet" type="text/css" href="css/login.css"> <script type="text/javascript" src="jquery/jquery-2.1.0.min.js"></script> <script type="text/javascript" src="jquery-ui/js/jquery-ui-1.10.4.custom.min.js"></script> <script type="text/javascript" src="js/login.js"></script> </head> <body> <div id="login"> <div> <form action="j_security_check" method=post> <label class="login-label">User:</label> <input id="userId" class="login-input" name="j_username"> <div style="clear: both"></div> <label class="login-label">Password:</label> <input id="password" type="password" class="login-input" name="j_password"> <div style="clear: both"></div> <div class="login-button-div"> <button type="submit" value="Login">Login <button type="button" value="Download" >Download </div> </form> </div> </div> </body> </html></pre> Response headers <pre>accept-ranges: bytes content-length: 1010 content-type: text/html date: Wed,09 Sep 2026 12:06:32 GMT last-modified: Mon,08 Jun 2026 13:49:04 GMT server: Jetty(11.0.24)</pre>

Responses

Code	Description	Links
200	File transfer data page or cancel acknowledgement Media type application/json Controls Accept header. Example Value Schema	No links

Code	Description	Links
	<pre>{ "total": "string", "page": "string", "records": "string", "rows": [{ "id": "string", "cell": ["string"] }]}</pre>	
400	Missing or invalid file token/state	No links
Media type text/plain Example Value Schema Error		

resources-export

Read-only export of NameServer resource maps

^

GET	/resources-export	List available domains and sub-endpoints	▼
GET	/resources-export/	List available domains and sub-endpoints (trailing-slash form)	▼
GET	/resources-export/routing	Read-only export of routing tables	^
Exposes the current primary, alternate, and neighboring route tables. This path is whitelisted from Jetty form authentication because it falls under the /resources-export/* prefix.			
Parameters			Cancel
No parameters			
Servers			
These operation-level options override the global server options.			

http://{host}:{port} - HTTP connector (plaintext). Default port 8501.

Computed URL: http://localhost:8501

Server variables

host

localhost

port

8501

Execute

Clear

Responses

Curl

```
curl -X 'GET' \
  'http://localhost:8501/resources-export/routing' \
  -H 'accept: application/json'
```

Request URL

http://localhost:8501/resources-export/routing

Server response

Code

Details

200

Response body

```
{
  "hubs": [
    "hub1.silkwave.local",
    "hub3.silkwave.local"
  ],
  "cost": 5
},
{
  "hubs": [
    "hub1.silkwave.local",
```

Code

```
        "hub4.silkwave.local"
      ],
      "cost": 10
    },
    {
      "hubs": [
        "hub1.silkwave.local",
        "hub2.silkwave.local",
        "hub4.silkwave.local"
      ]
    }
  ]
}
```

Download

Response headers

```
content-length: 852
content-type: application/json;charset=utf-8
date: Fri, 11 Sep 2026 12:01:21 GMT
server: Jetty(11.0.24)
```

Responses

Code	Description	Links
------	-------------	-------

200	Successfully retrieved the routing table export	No link
-----	---	---------

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "routes": {
    "additionalProp1": {}
  },
  "alternateRoutes": {
    "additionalProp1": {}
  },
  "neighbors": [
    "string"
  ],
  "timestamp": 9007199254740991
}
```

500	Unexpected server error (message included, no stack trace)	No links
-----	--	----------

Media type

application/json

Example Value Schema

```
{
  "error": "string",
  "status": 0,
  "timestamp": 9007199254740991
}
```

503	Routing service is unavailable	No links
-----	--------------------------------	----------

Media type

application/json

Code	Description	Links
	Example Value Schema <pre>{ "error": "string", "status": 0, "timestamp": 9007199254740991 }</pre>	

GET

/resources-export/resources

Export the `resources` map (ResourceRoute entries) for a domain

Parameters

Cancel

Name	Description
domain string (query)	Nameserver domain to export. If omitted, the first domain returned by <code>NameServerLocator.getNameServerDomains()</code> is used.
	domain

Servers

These operation-level options override the global server options.

http://{host}:{port} - HTTP connector (plaintext). Default port 8501.

Computed URL: http://localhost:8501

Server variables

host

localhost

port

8501

Execute

Clear

Responses

Curl

```
curl -X 'GET' \
  'http://localhost:8501/resources-export/resources' \
  -H 'accept: application/json'
```

Request URL

http://localhost:8501/resources-export/resources

Server response

Code	Details
200	Response body <pre>{ "resources": {}, "count": 0, "timestamp": 1789127993496 }</pre> Download Response headers <pre>content-length: 52 content-type: application/json;charset=utf-8 date: Fri,11 Sep 2026 11:59:53 GMT server: Jetty(11.0.24)</pre>

Responses

Code	Description	Links
200	Resource map for the domain Media type application/json Controls Accept header. Example Value Schema <pre>{ "resources": { "additionalProp1": {} }, "count": 0, "timestamp": 9007199254740991 }</pre>	No links
404	Domain not found, or no nameservers registered Media type application/json Example Value Schema	No links

Code	Description	Links
	<pre>{ "error": "string", "status": 0, "timestamp": 9007199254740991 }</pre>	
500	Unexpected server error (message included, no stack trace) Media type application/json Example Value Schema <pre>{ "error": "string", "status": 0, "timestamp": 9007199254740991 }</pre>	No links

GET	/resources-export/netResources	Export the `netToResources` map for a domain	▼
-----	--------------------------------	--	---

GET	/resources-export/nameServerResources	Export the `nameServersToResources` map for a domain	▼
-----	---------------------------------------	--	---

GET	/resources-export/all	Export all three resource maps for a domain in one response	^
-----	-----------------------	---	---

Parameters		Try it out
Name	Description	
domain string (query)	Nameserver domain to export. If omitted, the first domain returned by <code>NameServerLocator.getNameServerDomains()</code> is used. domain	
Responses		
Code	Description	Links
200	All resource maps for the domain Media type	No links

Code	Description	Links
	application/json Controls Accept header. Example Value Schema <pre>{ "resources": { "additionalProp1": {} }, "netToResources": { "additionalProp1": {} }, "nameServersToResources": { "additionalProp1": {} }, "exportTimestamp": 9007199254740991}</pre>	
404	Domain not found, or no nameservers registered Media type application/json Example Value Schema <pre>{ "error": "string", "status": 0, "timestamp": 9007199254740991}</pre>	No links
500	Unexpected server error (message included, no stack trace) Media type application/json Example Value Schema <pre>{ "error": "string", "status": 0, "timestamp": 9007199254740991}</pre>	No links

casport-sim

CASPORT v3 group-membership simulator (test/dev only)

^

GET	/rest/v3/groups/{group}/members/{member} CASPORT v3 group-membership check (simulator, dev/test only)	▼
POST	/rest/v3/groups/{group}/members/{member} CASPORT v3 group-membership check (POST alias)	▼

Schemas

**EmptyObject** ^ Collapse all **object**

Empty JSON object, returned by several **SilkwaveAdminServlet** actions.

Example `{}`

DomainResponse ^ Collapse all **object**

domain* **string**

Example `{"domain": "test.appgeo.hub1"}`

HubStatus ^ Collapse all **object**

Full hub dashboard payload returned by **GET /SilkwaveAdminServlet?action=load** (or the default action). Note the source builds this via manual **StringBuilder** concatenation rather than a typed model, so field presence/order is not guaranteed to be stable across versions — treat this as a best-effort shape.

loggedInName > Expand all **string**

currenttime **string**

starttime **string**

uptime > Expand all **string**

messages > Expand all **string**

incomingtotal **string**

incomingsize **string**

incomingmin **string**

incomingmax **string**

incomingavg **string**

heartbeattotal **string**

heartbeatsize **string**

heartbeatmin **string**

heartbeatmax **string**

heartbeatavg **string**

coretotal **string**

coresize **string**

coremin **string**

coremax **string**

coreavg **string**

authenticationtotal **string**

authenticationsize **string**

authenticationmin **string**

```

authenticationmax string
authenticationavg string
summaryqueued string
failedmessages string
badenvelopemessages string
invalidsourcemessages string
notdeliverablemessages string
notresolvablemessages string
notroutablemessages string
unknownfailedmessages string
invalidnetpayloadmessages string
notauthorizedmessages string
improperclassificationmessages string
connections string
privconnections string
neighbors string
totalhubs string
hubminsecurity string
hubmaxsecurity string

```

NameServerList [^] Collapse all **object**

```
nameservers* > Expand all array<string>
```

RouteGridPage [^] Collapse all **object**

jqGrid-format paginated route listing, returned by **action=query** .

```
total > Expand all string
```

```
page string
```

```
records > Expand all string
```

```
rows > Expand all array<object>
```

NetIdGridPage [^] Collapse all **object**

jqGrid-format paginated NetId listing for a single route, returned by **action=subquery** .

```
total string
```

```
page string
```

```
records string
```

```
rows > Expand all array<object>
```

NameCachesResponse ^ Collapse all object

List of available naming caches returned by **action=namecaches** .

namecaches* > Expand all **array<string>**

DomainListResponse ^ Collapse all object

domains* > Expand all **array<string>**

endpoints* > Expand all **array<string>**

RoutingExportResponse ^ Collapse all object

Current routing service state. The route table entry structures are owned by the routing subsystem and may vary with the configured route implementation.

routes* > Expand all **object**

alternateRoutes* > Expand all **object**

neighbors* > Expand all **array<string>**

timestamp* > Expand all **integer int64**

ResourceMapResponse ^ Collapse all object

resources* > Expand all **object**

count* **integer**

timestamp* > Expand all **integer int64**

NetResourcesMapResponse ^ Collapse all object

netToResources > Expand all **object**

nameServersToResources > Expand all **object**

count **integer**

timestamp **integer int64**

AllResourcesResponse ^ Collapse all object

resources* > Expand all **object**

netToResources* > Expand all **object**

nameServersToResources* > Expand all **object**

exportTimestamp* **integer int64**

ErrorResponse ^ Collapse all object

```
error* string
status* integer
timestamp* integer int64
```

DestinationInfoResponse ^ Collapse all object

Destination queue details returned by [GFT /RegistrationAdminServlet?action=connectioninfo&destination=...](#). All values are JSON strings; `{}` is returned when the destination is not found.

```
destinationname string
destinationsize string
destinationenqueued string
destinationdequeued string
Additional properties forbidden
```