

SILKWAVE Web/Admin API — hand-authored spec, not auto-generated

spec source: [silkwave-web-api-openapi.yaml](#)

SILKWAVE Web/Admin API 1.0.0 OAS 3.1

[./silkwave-web-api-openapi.yaml](#)

OpenAPI description of the HTTP(S) servlet API exposed by `io.silkwave.web.WebServer` (embedded Jetty, plain `jakarta.servlet.http.HttpServlet` implementations — no Spring MVC, no JAX-RS). Hand-authored from source review of `WebServer.java` and the servlet classes listed under `EndpointsDocumented` below; it is not generated from annotations, since none exist in this codebase.

Server modes

The server runs in exactly one connector mode at a time: HTTP (default port 8501) or HTTPS (default port 8601), whichever is enabled — HTTPS wins if both flags are set. See the `servers` list below for both.

Authentication

All paths under `/` require Jetty Form authentication (roles `user` / `admin` / `moderator`) **except when the server is running in HTTPS-only mode**, where no security handler is attached at all — see the technical report for details. The following paths are explicitly whitelisted from authentication in HTTP mode: `/health`, `/resources-export/*` (note: NOT the bare `/resources-export` path), and static login assets. `/rest/v3/*` is unauthenticated in all modes because it lives on a separate, unsecured servlet context.

Coverage

This spec covers only the servlets that were available for source review: `HealthServlet`, `SilkwaveAdminServlet`, `NamingServiceAdminServlet`, `ResourcesExportServlet`, and the optional `CasportV3Servlet`. Other servlets registered in `WebServer.java` (`DiscoveryServiceAdminServlet`, `NetworkStatusAdminServlet`, `RegistrationAdminServlet`, `RoutingAdminServlet`, `SecurityAdminServlet`, `NamingAdminServlet`, `StreamAdminServlet`, `FileAdminServlet`) are NOT included here because their implementations were not reviewed — add them once their source is available rather than guessing at their shape.

Servers

`http://{host}:{port}` - HTTP connector (plaintext). Default port 8501.

Computed URL: `http://localhost:8501`

Server variables

host

localhost

port

8501

Authorize



health

Liveness probe



GET

/health Liveness probe

POST

/health Liveness probe (POST alias)

admin

Hub status / dashboard administration



GET

/SilkwaveAdminServlet Hub dashboard / admin actions

POST

/SilkwaveAdminServlet
Hub dashboard / admin actions (POST form, required for action=validate)

naming

Name server route inspection



GET

/NamingServiceAdminServlet Name server route browser

resources-export

Read-only export of NameServer resource maps



GET

/resources-export List available domains and sub-endpoints

GET

/resources-export/ List available domains and sub-endpoints (trailing-slash form)

GET

/resources-export/resources
Export the `resources` map (ResourceRoute entries) for a domain

GET **/resources-export/netResources** Export the `netToResources` map for a domain

GET **/resources-export/nameServerResources**
Export the `nameServersToResources` map for a domain

GET **/resources-export/all** Export all three resource maps for a domain in one response

casport-sim CASPORT v3 group-membership simulator (test/dev only)

GET **/rest/v3/groups/{group}/members/{member}**
CASPORT v3 group-membership check (simulator, dev/test only)

POST **/rest/v3/groups/{group}/members/{member}**
CASPORT v3 group-membership check (POST alias)

Schemas

EmptyObject ^ Collapse all object

Empty JSON object, returned by several [SilkwaveAdminServlet](#) actions.

Example `{}`

DomainResponse ^ Collapse all object

domain* string

Example `{"domain": "test.appgeo.hub1"}`

HubStatus ^ Collapse all object

Full hub dashboard payload returned by [GET /SilkwaveAdminServlet?action=load](#) (or the default action). Note the source builds this via manual [StringBuilder](#) concatenation rather than a typed model, so field presence/order is not guaranteed to be stable across versions — treat this as a best-effort shape.

loggedName > Expand all string

currenttime string

starttime string

uptime > Expand all string

messages > Expand all string

incomingtotal string

incomingsize string

incomingmin string

```
incomingmax string
incomingavg string
heartbeattotal string
heartbeatsize string
heartbeatmin string
heartbeatmax string
heartbeatavg string
coretotal string
coresize string
coremin string
coremax string
coreavg string
authenticationtotal string
authenticationsize string
authenticationmin string
authenticationmax string
authenticationavg string
summaryqueued string
failedmessages string
badenvelopemessages string
invalidsourcemessages string
notdeliverablemessages string
notresolvablemessages string
notroutablemessages string
unknownfailedmessages string
invalidnetpayloadmessages string
notauthorizedmessages string
improperclassificationmessages string
connections string
privconnections string
neighbors string
totalhubs string
hubminsecurity string
hubmaxsecurity string
```

NameServerList ^ Collapse all **object**

nameservers* > Expand all **array<string>**

RouteGridPage ^ Collapse all **object**

jqGrid-format paginated route listing, returned by **action=query** .

total > Expand all **string**

page **string**

records > Expand all **string**

rows > Expand all **array<object>**

NetIdGridPage ^ Collapse all **object**

jqGrid-format paginated NetId listing for a single route, returned by **action=subquery** .

total **string**

page **string**

records **string**

rows > Expand all **array<object>**

DomainListResponse ^ Collapse all **object**

domains* > Expand all **array<string>**

endpoints* > Expand all **array<string>**

ResourceMapResponse ^ Collapse all **object**

resources* > Expand all **object**

count* **integer**

timestamp* > Expand all **integer** **int64**

NetResourcesMapResponse ^ Collapse all **object**

netToResources > Expand all **object**

nameServersToResources > Expand all **object**

count **integer**

timestamp **integer** **int64**

AllResourcesResponse ^ Collapse all **object**

resources* > Expand all **object**

netToResources* > Expand all **object**

nameServersToResources* > Expand all **object**

```
exportTimestamp* integer int64
```

ErrorResponse ^ Collapse all object

```
error* string
```

```
status* integer
```

```
timestamp* integer int64
```