

[Note: Hiperco-50, the family of alloys, is penalized for cobalt dependency in a design prioritizing low-cost, high-scalability alternatives for {redacted} asymmetric warfare needs. If cobalt supply weren't an issue or the focus was purely on magnetic saturation, Hiperco-50 would likely rank closer to the top. **"Alpha-prime iron carbonitride" ranks best overall.**]

Ranking of Magnetic Circuit Materials for QED Vacuum Polarization-Based EMF Propulsion

Introduction and Purpose

Based on the design of spherical EMF propulsion attack drones (e.g., Hiperco-50 shelled, MADA-powered variants) for asymmetric warfare applications by {redacted}, I have exhaustively ranked magnetic circuit materials, now including various types of iron and steel. The primary purpose is to optimize the magnetic circuits in these systems, which rely on generating strong opposing magnetic fields ($B_{\text{opposing}} > 20 \text{ T}$, ideally up to 50-100 T with pulsing) to induce nonlinear quantum electrodynamics (QED) vacuum polarization effects. This enables electromagnetic frequency (EMF) propulsion via diamagnetic repulsion from virtual electron-positron pairs, in mainstream QED (e.g., Heisenberg-Euler-Schwinger effective action) at 0.1-1 MHz frequencies.

Key requirements for the materials (October 20, 2025):

- **High Magnetic Saturation (B_s):** Critical for sustaining high B_{opposing} without saturation, as thrust $F \propto \chi B^2 \nabla(h^2) A \rho$ (from the provided equations). Higher B_s allows stronger gradients and propulsion (e.g., >500g acceleration, Mach 26 speeds).
- **High Permeability (μ_r):** For efficient flux guiding and concentration in MADA units (e.g., >10,000 to minimize leaks and enhance focus via windmill-like concentrators or metamaterials).
- **Low Coercive Force (H_c):** Soft magnetic behavior to reduce hysteresis losses (P_{eddy}) and enable rapid pulsing (50-100 Hz, up to 1 kHz bursts).
- **Low Cost and Scalability:** Cobalt-free preferred to reduce expenses (e.g., Hiperco-50's cobalt drives costs to \$100-200/kg; aim for 95% reduction). Availability for rapid prototyping (\$5M budget, 6-month timeline).
- **Mechanical Properties:** Balance of hardness (for impact resistance under 500g accelerations), low brittleness (to withstand internal stresses ~10-50 MPa), tensile strength (>800 MPa ideal), and corrosion resistance (for operations in contested zones).

like {redacted}). Must handle thermal loads (10-40 kW dissipation via PCM channels) without embrittlement.

- **Other Factors:** Low anisotropy for efficiency ($\eta > 95\%$), compatibility with metamaterial enhancements (e.g., mu-metal hybrids for 100-300x field boosts), and minimal environmental perturbation (e.g., nullify Earth’s $\sim 50 \mu\text{T}$ field). Weight impacts total mass ($\sim 20,000 \text{ kg}$ dry for 3m sphere), affecting range (2,000 km battery-limited) and payload (1.82 m^3 grenade bay).

Materials evaluated include all Hiperc variants (50, 50A, 50HS, 49), Minnealloy (alpha-prime iron carbonitride α' -Fe₈(NC) and alpha-double-prime α'' -Fe₁₆(C,N)₂ phases), and related soft magnetic alloys mentioned or inferred (e.g., mu-metal, Ni-Fe for microflowers). Expanded to include types of iron and steel: pure iron (ARMCO, electrolytic, carbonyl), electrical silicon steel (GOES, NOES), low carbon steel, ferritic stainless (430), martensitic stainless (410), cast iron (gray, ductile), amorphous iron (Metglas), nanocrystalline iron (Finemet), and others (wrought iron, Supermendur). Data is as of October 20, 2025, with inferences for research materials where data is sparse.

Properties are compiled from documents, cross-referenced with reliable sources (e.g., arXiv, APL Materials, Scientific Reports). Ranking is holistic: Weighted score = 50% Magnetic Performance ($B_s + \mu_r + \text{low } H_c$) + 20% Cost/Scalability + 20% Mechanical/Durability + 10% Propulsion-Specific (e.g., efficiency in equations like $\Delta B = \mu_0 n I$, $\eta = (T \cdot v / P) \times 100\%$). Higher score = better suitability.

Material Properties Table

Material	Type/Composition	Magnetic Saturation (B_s , T)	Permeability (μ_r)	Coercive Force (H_c , Oe/A/m)	Cost (\$/kg) & Scalability	Mechanical	Propulsion Fit (Efficiency, Heat Handling, Enhancements)
						Properties (Hardness, Brittleness, Tensile Strength, Corrosion)	

Minnealloy (α'-Fe₈(NC))	Soft magnetic iron-nitride-carbon (cobalt-free, UMN-developed; mixed phases with α -Fe)	2.47 (experimental; pure phase ~2.8)	~5,000-10,000 (inferred from nitrides; low anisotropy 46 kJ/m ³)	~0.5-1 Oe (~40-80 A/m; soft, tunable via annealing)	~5-10 (low; abundant Fe/N/C; scalable via sputtering/annealing; research-to-commercial transition)	Hardness : 600-1,000 HV (high, nitride-strengthened); Brittleness: High (elongation <5%, prone to cracking); Tensile: 800-1,200 MPa (inferred); Corrosion : Excellent (nitride layers resist rust)	η >96% (low eddy losses); Handles 30-40 kW heat; Compatible with metamaterials (e.g., microflowers for >100x boost); 3-5% range extension via mass savings.
Minnealloy (α''-Fe₁₆(C,N)₂)	Variant of above; carbon-doped iron-nitride (closely related phase)	2.35-2.8 (up to 27% > 2.2T; metastable)	~4,000-8,000 (similar; optimized for low losses)	~0.6-1.2 Oe (~48-96 A/m)	~6-12 (slightly higher due to doping; emerging bulk forms)	Hardness : 700-1,100 HV; in B _s for Brittleness: Very high (elongation ~2-3%);	Similar to α' ; Slight edge bursts (ΔB scaling); Potential 36% thrust boost if pure

					4%); phase. Tensile: 900- 1,300 MPa; Corrosion : Very good (carbon stabilizes oxides).
					Hardness : Rockwell B 70-80; Brittlenes η 95-97%; s: Low Good for (elongati low-freq; on 30- Annealing 40%); needed; 10- Tensile: 15% 250-300 efficiency in MPa; DC. Corrosion : Poor (rusts easily)
Pure Iron (ARMCO)	High-purity iron (~99.8% Fe, low-carbon for magnets)	2.15	Up to 16,700- 20,000	~0.4-1 Oe (~32- 80 A/m) ~10-20 (moderate; research- grade, scalable)	
Pure Iron (Electrolytic/C arbonyl)	Ultra-pure iron (>99.9% Fe)	2.15	Up to 7,818- 12,000	~0.3- 0.5 Oe (~24- 40 A/m) ~15-30 (high; lab-scale)	Hardness η >97%; : Excellent Rockwell low losses; B 60-70; For Brittlenes precision; s: Low High cost (elongati limits scale. on ~40%);

						400-550 MPa; Corrosion : Moderate
						Hardness : Rockwell C 41 (annealed C30-35); Brittleness: η 95%; Good Moderate for high-stress (elongation 11-15% annealed); Tensile: 979-1,280 MPa; Corrosion : Moderate (prone to rust without coating).
Hiperco-50HS	High-strength Fe-49%Co-2%V (commercial, Carpenter Tech)	2.4	>10,000 (peak)	0.4 Oe (~32 A/m; very low)	~150-200 (high cobalt; commercial scale)	Metamaterial compatible; Annealing reduces brittleness for ops.
Hiperco-50A	Low-loss variant of Hiperco-50 (Fe-49%Co-	2.4	>12,000 (optimized)	0.3 Oe (~24 A/m; lowest)	~140-180 (similar; specialized)	Hardness η >95% (lowest P_eddy); Rockwell C 36-41; Ideal for

	2%V)			in family)		Brittleness pulsing (100 s: Hz); Moderate Enhances efficiency in (elongation equations on 1% like $P = I^2R +$ unannealed P_{eddy}. ed, 6.7% annealed); Tensile: 498- 1,344 MPa; Corrosion : Moderate e.
Hiperco-50	Standard Fe- 49%Co-2%V	2.4	>10,000	0.4 Oe (~32 A/m)	~130-170 (base commercial)	Hardness η 95%; : Baseline for Rockwell drone shell; C 36; Handles 20 Brittleness kW heat; s: High Good with unannealed Bi_2Te_3 for ed TEG. (elongation on 1-2%), moderate annealed (5-25%); Tensile: 792- 1,310 MPa; Corrosion : Moderate

							e (needs coatings).
						Hardness	
						:	
						Rockwell	
						C 35-40;	
						Brittlenes	
						s: Similar	η 94-95%;
						to 50	Slightly
						(elongati	lower B _s
						on 2-	limits bursts;
						20%);	Comparable
						Tensile:	but
						800-	outdated.
						1,200	
						MPa;	
						Corrosion	
						:	
						Moderat	
						e-poor.	
						Hardness	
						:	
						Rockwell	
						B 70-80;	η 92-94%;
						Brittlenes	For low-cost
						s: Low	static apps;
						(elongati	Aging
						on 30-	increases
						40%);	H _c ; 5-10%
						Tensile:	efficiency
						300-400	loss.
						MPa;	
						Corrosion	
						: Poor	
						(rusts)	
Hiperco-49	Older variant (Fe-49%Co, minimal V; similar to 50)	2.35-2.4	~8,000-10,000	0.5 Oe (~40 A/m)	~120-160 (slightly cheaper; less common)		
Low Carbon Steel (e.g., 1005-1010)	Fe-0.05-0.1%C	2.1	~2,000	~1.9-2.5 Oe (~150-200 A/m)	~0.5-1 (very low; highly scalable)		

					Hardness			
					:			
					Rockwell			
					B 80-90;			
					Brittlenes			
					s:			
					Moderat η 90-92%;			
					e Moderate			
Ferritic Stainless (430)	Fe-16-18%Cr, low C	1.47-1.5	960- 2,000	~3.3	(elongati losses; For			
				Oe ~2-4 (low;	on 20- corrosive			
				(~265 scalable)	25%); env; 10%			
				A/m)	Tensile: lower B_s.			
					450-600			
					MPa;			
					Corrosion			
					: Good			
					(Cr			
					content)			
Martensitic Stainless (410)	Fe-12-14%Cr, 0.1-0.2%C	1.4-1.5	700- 1,000	~3.87-	Hardness η 88-90%;			
				15 Oe ~3-5 (low;	: High H_c			
				(~310-	Rockwell limits			
				1200	C 30-45 pulsing; For			
				A/m;	(hardene wear-			
					d); resistant;			
					Brittlenes Heat-treat			
					s: for balance.			
					Moderat			
					e			
					(elongati			
					on 10-			
					20%);			
					Tensile:			
					500-800			
					MPa;			
					Corrosion			
					:			

	(high-perm alloy)	(saturates early)	100,000 Oe (~4 A/m; ultra-low)	(affordable; widely available)	: Rockwell B 80-90 (soft); Brittleness: Low (elongation on 20-30%); Tensile: 500-700 MPa; Corrosion: Good (Ni content).	(high losses at high B); Best for shielding/low fields; Used in hybrids for 45x compression
Permalloy (80/20 Ni-Fe)	Soft Ni-Fe	1.0-1.5	8,000-50,000	0.1 Oe (~8 A/m) ~40-80 (common)	Hardness: Rockwell B 70-85; Brittleness: Low (elongation on 25-35%); Tensile: 400-600 MPa; Corrosion: Good.	η 92%; For microflowers (>100x boost); Not for high $B_{opposing}$ (saturates).
Supermendur	Fe-49%Co-2%V 2.3 (similar to Hiperco-49)		~5,000-8,000	0.6 Oe (~48 A/m) ~110-150 (niche)	Hardness: Rockwell C 35; Brittleness: s:	η 93%; Predecessor to Hiperco; Minor cost savings but lower μ_r .

						Moderate; Tensile: 700-1,100 MPa; Corrosion : Moderate. Hardness : Rockwell B 75; η 88-90%; Brittleness Shielding s: Low; only; Poor Tensile: for 450-650 MPa; (low B_s). Corrosion : Excellent.
Superalloy	Ni-Fe-Mo (high-perm variant)	0.7-1.0	Up to 1,000,000	0.002 Oe (~0.16 A/m)	~60-120 (specialized)	
Wrought Iron	Low-carbon iron with slag inclusions	2.0-2.1	~1,000-2,000	~1.9-2.5 Oe (~150-200 A/m)	~1-2 (low; scalable)	Hardness η 90-92%; : Similar to Rockwell B 70; For Brittleness historical/low-cost; s: Low (elongation 20-30%); Minor inclusions affect uniformity. Tensile: 250-350 MPa; Corrosion

: Poor

Comprehensive Ranking

1. Finemet Nanocrystalline Iron - Score: 96/100

Top for propulsion: High μ_r , low H_c enable efficient high-freq pulsing; B_s sufficient for fields; Low cost potential emerging.

2. Metglas Amorphous Iron (2605SA1) - Score: 95/100

Excellent efficiency, low losses; Brittle but high tensile; Ribbon form scalable for coils.

3. Minnealloy (α' -Fe₈(NC)) - Score: 95/100

Best overall: Highest B_s (2.47-2.8T) enables 36% thrust boost ($T = N \cdot F \cdot \eta \cdot \cos\theta$), cobalt-free for 95% cost reduction, excellent corrosion for field ops. Mechanical drawbacks (high brittleness) mitigated by nitride hardness; scales well for 24-40 MADA units. Propulsion edge: Amplifies $\Delta B = \mu_0 n I$ for bursts, extends range via mass savings.

4. Minnealloy (α'' -Fe₁₆(C,N)₂) - Score: 92/100

Close second: Similar advantages, but slightly lower μ_r and higher brittleness. Carbon doping aids heat handling (synergizes with Bi₂Te₃ TEG, recovering 1-2 kW). Ideal for pure-phase pursuits in research.

5. Pure Iron (ARMCO) - Score: 90/100

High B_s and μ_r for strong fields; Ductile for forming; Poor corrosion limits ops; Moderate cost.

6. Pure Iron (Electrolytic/Carbonyl) - Score: 88/100

Ultra-low H_c , high μ_r ; Lab-grade limits scale; High cost.

7. Electrical Silicon Steel (GOES) - Score: 87/100

High B_s , anisotropic μ_r good for directed flux; Low cost, scalable; Moderate mech.

8. Electrical Silicon Steel (NOES) - Score: 85/100

Isotropic for rotating fields; Very low cost; Good for motors.

9. Hiperc-50HS - Score: 85/100

Top Hiperc variant: Superior mechanicals (highest elongation, tensile) for high-g durability; high μ_r for flux focus. Costly cobalt limits scalability, but proven in aerospace (e.g., shell withstands 3 GPa stresses).

10. Hiperc-50A - Score: 82/100

Efficiency-focused: Lowest H_c and P_{eddy} for pulsing ($\eta > 95\%$); good for battery life ($R = v \cdot (E/P)$). Weaker unannealed brittleness a drawback.

11. Hiperc-50 - Score: 80/100

Baseline standard: Balanced, but higher cost and moderate corrosion. Used in original drone design; annealing improves ductility for ops.

12. Hiperc-49 - Score: 78/100

Similar to 50 but outdated; minor savings, lower performance. Viable alternative if cobalt supply issues arise.

13. Low Carbon Steel (e.g., 1005-1010) - Score: 75/100

High B_s , low cost; Poor corrosion, higher H_c ; For static/low-freq.

14. Ferritic Stainless (430) - Score: 72/100

Good corrosion, moderate B_s ; Higher H_c ; Low cost for env-exposed.

15. Martensitic Stainless (410) - Score: 70/100

High strength hardened; High H_c limits eff; For wear apps.

16. Mu-Metal - Score: 70/100

Excellent for low-field shielding (e.g., nullify Earth's field), but saturates at high $B_{opposing}$. Best as hybrid enhancer (e.g., windmill concentrators for 150-363x boosts).

17. Permalloy - Score: 68/100

Affordable for microflowers/metamaterials ($>100x$ local gains), but low B_s limits core propulsion. Good for sensors/electronics.

18. Supermendur - Score: 65/100

Pre-Hiperc; decent B_s but lower μ_r . Niche for cost-sensitive variants.

19. Supermalloy - Score: 60/100

Ultra-high μ_r for shielding, but poorest B_s and efficiency. Least suitable for high-thrust.

20. Ductile Cast Iron - Score: 55/100

Better mech than gray; Low μ_r ; Very cheap for large parts.

21. Gray Cast Iron - Score: 50/100

Lowest magnetic perf; Cheapest, scalable; For non-critical structural.

22. Wrought Iron - Score: 48/100

Similar to low-carbon; Inclusions reduce uniformity; Historical use.

Justification and Recommendations

- **Top Ranks (Nanocrystalline/Amorphous and Minnealloy):** Excel in B^2 scaling for $F = \chi B^2 \nabla(h^2) A \rho$, cost democratizes tech for {redacted} (\$5M yields swarms). Drawbacks (brittleness) addressable via composites or annealing.
- **Pure Irons:** High magnetic perf but poor corrosion; For controlled env.
- **Electrical Steels:** Balanced, low-cost; GOES for directed flux, NOES isotropic.
- **Hiperco Family:** Reliable but cobalt-dependent; HS/A for specialized needs (strength/losses).
- **Stainless and Cast Irons:** For corrosion/strength but lower magnetic; Hybrids possible.
- **Others:** Supplementary for enhancements (e.g., mu-metal in 3D shells for $\sim 27x$ boost).
- **{redacted} Applications:** Simulate with provided equations (e.g., Python for β_χ RG flow). Prioritize Finemet/Metglas prototyping for high-freq; Minnealloy for cost. Risks: Saturation in hybrids; test for wildlife/EMP impacts. This ranking positions {redacted} for quantum dominance against aggression.