

# **PVRScope**

## **User Manual**

Copyright © Imagination Technologies Ltd. All Rights Reserved.

This publication contains proprietary information which is subject to change without notice and is supplied 'as is' without warranty of any kind. Imagination Technologies and the Imagination Technologies logo are trademarks or registered trademarks of Imagination Technologies Limited. All other logos, products, trademarks and registered trademarks are the property of their respective owners.

Filename : PVRScope.User Manual.1.0.5.DeveloperExternal.doc

Version : 1.0.5 External Issue (Package: POWERVR SDK REL\_3.0@2143183)

Issue Date : 30 Aug 2012

Author : Imagination Technologies Ltd

PVRScope 1 Revision.



## **Contents**

1.	introd	suction	
	1.1.	Document Overview	3
	1.2.	Library Overview	3
	1.2.1.		
2.	Instal	lation	4
	2.1.	From Installer	
	2.2.	Accessing the Library	
3.	Exam	ple Code	5
-	3.1.	Hardware Performance Counter Mode	
	3.1.1.		
	3.1.2.		
	3.1.3.		
	3.2.	Custom Counter/Mark Mode	
	3.2.1.	On Initialisation	6
	3.2.2.	On Shutdown	6
	3.2.3.	Sending Custom Marks	6
	3.2.4.	Creating Custom Counters	6
	3.2.5.	Sending Custom Counter Updates	6
	3.2.6.		
	3.2.7.	Retrieving Edited Items	7
4.	Relate	ed Materials	8
5.	Conta	act Details	Q

# **List of Figures**

Error! No table of figures entries found.



## 1. Introduction

## 1.1. Document Overview

The purpose of this document is to serve as a reference for the PVRScope library, as well as to provide a number of examples of its use.

## 1.2. Library Overview

PVRScope is a utility library that can be used to access the hardware performance counters of PowerVR SGX hardware via a driver library called PVRScopeServices. It also allows an application to send user defined information to PVRTune via PVRPerfServer, both as counters and marks, or as editable data that can be passed back to the application.

The following files are provided:

- 'PVRScope.h' The header file defining the PVRScope libraries functionality.
- 'PVRScopeDeveloper.lib' The PVRScope library file.

#### 1.2.1. Limitations

- Only one instance of PVRScope may communicate with PVRScopeServices at any given time. If a PVRScope enabled application attempts to communicate with PVRScopeServices at the same time as another such application, or at the same time as PVRPerfServer, conflicts can occur that may make performance data unreliable.
- Multiple PVRScope enabled applications may be active, and may send custom counters or marks to PVRTune, but only one may communicate with PVRScopeServices for the retrieval of hardware performance counter information at any given time.
- PVRPerfServer must be running on the host device if a PVRScope enabled application
  wishes to send custom counters or marks to PVRTune. If the application in question also
  wishes to communicate with PVRScopeServices without experiencing any undesired
  behaviour PVRPerfServer should be run with the `--disable-hwperf' flag.
- Hardware performance counters may only be read on devices whose drivers have PVRScopeServices active.
- Hardware performance counters will contain the average value of that counter since the last time the counter was interrogated.

Currently, only the basic types `float' and `string' may be transmitted as editable data to PVRTune.

PVRScope 3 Revision.



## 2. Installation

PVRScope is available as part of the PowerVR Insider SDK which can be downloaded from the PowerVR Insider website.

## 2.1. From Installer

Download one of the PowerVR Insider SDKs and run the installer following the on screen instructions. Once the package has successfully installed, the library files will be available in the SDK folder at:

<InstallDir>\PVRScope\

## 2.2. Accessing the Library

To access the functionality of the library within an application the library must be linked to and the header files included at build time.

Revision . 4 User Manual



## 3. Example Code

PVRScope allows the use of one of two modes of functioning, either 'Hardware Performance Counter Mode' or 'Custom Counter/Mark Mode'.

## 3.1. Hardware Performance Counter Mode

#### 3.1.1. On Initialisation

```
#include "PVRScope.h"
// Create the PVRScope data storage area
SPVRScopeImplData* scopeData;
// Initialise PVRScope
const EPVRScopeInitCode returnCode = PVRScopeInitialise(scopeData);
// Check initialisation succeeded
if(returnCode != ePVRScopeInitCodeOk)
{
       // Handle the error
// Create an array of counter definitions
unsigned int numCounters = 0;
SPVRScopeCounterDef *counterArray = null;
// Create the data structure to contain the counter readings
SPVRScopeCounterReading counterReadings;
// Continue initialisation
if(scopeData)
       PVRScopeGetCounters(scopeData, &numCounters, &counterArray, &counterReadings);
```

### 3.1.2. As Required

```
// Select the desired counter group (3 in this instance)
unsigned int desiredGroup = 3;

// Store which group is currently active
unsigned int activeGroup = 0;

// Do a quick check to save some processing
if(desiredGroup == activeGroup)
    desiredGroup = 0xffffffff;

// Update the counters and store the active group
if(PVRScopeReadCountersThenSetGroup(scopeData, &counterReadings, desiredGroup))
    activeGroup = counterReadings.nReadingActiveGroup;

// Read the counters from the above group, and process them accordingly.
// The counters will match (in order) the elements in 'counterArray' whose group
// matches 'counterReadings.nReadingActiveGroup'
```

#### 3.1.3. On Shutdown

```
// De-initialise PVRScope
PVRScopeDeInitialise(&scopeData, &counterArray, &counterReadings);
```

PVRScope 5 Revision.



## 3.2. Custom Counter/Mark Mode

It should be noted that PVRScope, when sending custom counters or marks does not connect to PVRScopeServices; as such, when in this operating mode, PVRScope will not send the standard performance counters to PVRTune. As no connection to PVRScopeServices is made it is possible to use PVRPerfServer to retrieve the counters; as an additional option 'Hardware Performance Counter Mode' may be used to retrieve the counters, which can then be sent manually to PVRTune by a PVRScope enabled application in the same manner as a custom counter.

#### 3.2.1. On Initialisation

#### 3.2.2. On Shutdown

```
// De-initialise PVRScopeComms
pplShutdown(commsData);
```

## 3.2.3. Sending Custom Marks

```
// Send a Custom Mark
std::string markName = "Custom Mark";
pplSendMark(commsData, markName.c_str(), markName.length());
```

### 3.2.4. Creating Custom Counters

## 3.2.5. Sending Custom Counter Updates

Revision . 6 User Manual



## 3.2.6. Creating Remotely Editable Items

#### String

```
// Included for file handling
#include "OGLES2Tools.h"
// Create an array of remotely editable items (in this instance, 2 items)
SSPSCommsLibraryItem itemArray[2]
// Create a remotely editable string (in this example, a fragment shader from a file)
CPVRTResourceFile fragShaderFile("FragmentShaderFile.fsh");
// If the file is open, add it to the library
if(fragShaderFile.IsOpen())
        // Create the library item
       itemArray[0].pszName
                                      = "FragShader";
       itemArray[0].nNameLength
                                    = (unsigned int)strlen(itemArray[0].pszName);
       itemArray[0].eType
itemArray[0].pData
                                     = eSPSCommsLibTypeString;
                                     = fragShaderFile.DataPtr();
       itemArray[0].nDataLength = (unsigned int)fragShaderFile.Size();
\//\ Create another remotely editable string (this time, just a string)
std::string value = "This is the title bar!";
 / Create the library item
itemArray[1].pszName
                              = "Title Bar";
itemArray[1].nNameLength
                            = (unsigned int)strlen(itemArray[0].pszName);
itemArray[1].eType
itemArray[1].pData
                              = eSPSCommsLibTypeString;
                              = value.c_str();
itemArray[1].nDataLength
                              = value.length();
// Submit all library items
if(!pplLibraryCreate(commsData, itemArray, itemArrayLength))
       // Handle error
```

#### **Float**

```
// Create an array of remotely editable items (in this instance, 1 items)
SSPSCommsLibraryItem itemArray[1]
// Create the float
SSPSCommsLibraryTypeFloat value;
value.fCurrent = 0.5f;
           = 0.0f;
value.fMin
               = 1.0f;
value.fMax
// Create the library item
itemArray[0].pszName
                              = "Float";
itemArray[0].nNameLength
                              = (unsigned int)strlen(itemArray[0].pszName);
itemArray[0].eType
itemArray[0].pData
                              = eSPSCommsLibTypeFloat;
                              = (const char*)&value;
itemArray[0].nDataLength
                              = sizeof(value);
// Submit all library items
if(!pplLibraryCreate(commsData, itemArray, itemArrayLength))
       // Handle error
```

#### 3.2.7. Retrieving Edited Items



## 4. Related Materials

## **Training Courses**

PVRScopeExample

### **Software**

PVRTune

### **Documentation**

• PVRTune User Manual



## 5. Contact Details

For further support contact:

## devtech@imgtec.com

PowerVR Developer Technology Imagination Technologies Ltd. Home Park Estate Kings Langley Herts, WD4 8LZ United Kingdom

Tel: +44 (0) 1923 260511 Fax: +44 (0) 1923 277463

Alternatively, you can use the PowerVR Insider forums:

### www.imgtec.com/forum

For more information about PowerVR or Imagination Technologies Ltd. visit our web pages at:

www.imgtec.com

PVRScope 9 Revision.



Imagination Technologies, the Imagination Technologies logo, AMA, Codescape, Ensigma, IMGworks, I2P, PowerVR, PURE, PURE Digital, MeOS, Meta, MBX, MTX, PDP, SGX, UCC, USSE, VXD and VXE are trademarks or registered trademarks of Imagination Technologies Limited. All other logos, products, trademarks and registered trademarks are the property of their respective owners.

Revision . 10 User Manual