

Rellenolisto Exteriors

Rellenolisto Exteriors is a gray powder product, made up of high-purity minerals combined with state-of-the-art technology resulting in special characteristics for optimal cost-effective performance outdoors.

Advantages

Rellenolisto Exteriors can be used as a substitute for traditional plaster with the advantages of an easier, faster and cleaner application. It comes in two presentations: Coarse and Fine which offer the user the option of filling or finishing the surfaces, depending on their needs.

Its advanced formula provides high yield for the applicator and excellent mechanical characteristics of the finishes and great performance outdoors.

Applications

- Rellenolisto Exteriors is designed to be applied as a filler on facades, on different types of masonry such as common brick, latern brick, structural brick, concrete blocks, precast blocks and poured concrete slabs.

Technical Characteristics

*Consumption: 1.3 to 1.5 kg/m² per millimeter of thickness, depending on the type and level of the surface.

Setting time: Minimum 50 minutes under normal conditions.

*Color: Gray

**These properties are reported in the analysis certificate as requested by the client.*

Presentation: 25 kg laminated polypropylene packaging.

Durability: Three (3) months in its original packaging, sealed and protected from moisture

Preparation and Application

Remove dust and any loose particles from surfaces. When applied to precast and concrete slabs, completely remove any residues from the release agent or grease.

Moisten the substrate (surface) where you are going to apply Rellenolisto Exteriors, in order to avoid dehydration of the mixture to be applied and minimize cracks as the filler begins to set.

Do not mix Rellenolisto Exteriors with another substance or product. Use only potable water (free of oils, salts, organic matter or any other substance that may impair the quality, resistance and durability of the product).

Use gloves to mix thoroughly by hand, use a dust mask during the preparation; add the powder Rellenolisto Exteriors in the mixing water, until obtaining a paste with the appropriate consistency for its application. The first covering layers must be pasty.

For fillings, apply Rellenolisto Exteriors with a metal trowel, spreading it in alternating vertical and horizontal coats, allowing it to harden enough before applying the second coat.

Preparation and Application

Refine and settle the product with the trowel between coats, to obtain a better compaction and sealing of the surface.

To level the surface run the strut tightly horizontally and vertically to smooth over after each layer.

Remove the material collected on the strut and apply again into the marked depressions until they are filled up and go over the surface with the strut until the surface is completely leveled.

For thick fillings it is better to apply the material in layers. You can fill up to 3 cm.

Avoid exposure of Rellenolisto to environmental humidity or water. Do not leave the bags of product uncovered for a long time.

Recommendations

Only prepare sufficient amount of material to be applied within 20 minutes. This is the time required to begin to set. Avoid remixing After consuming the product, wash the container with impurity-free water.

Periodically clean the tools (trowel and strut).

The final quality of the finish depends on the skills of the stucco operator, the correct homogenization of the product in the water, the correct application of the product and the strict observance of these instructions.

If Rellenolisto Exteriors is applied directly on the concrete slabs, it is necessary to check that they are completely set.

Avoid applying Rellenolisto Exteriors over surfaces with leaks or permanent humidity, such as bathrooms, kitchen. Tiles or veneers are not to be bond over this product.

Once the surface is finished, let it dry and apply a special exterior paint.

Technical Assistance

IMPADOC's technical team works hand by hand to offer the best knowledge and optimal use of construction and industry products. If you have any concerns or suggestions, please contact us: asistenciatecnica@impadoc.com

The information provided in this document refers to the product data supplied by Impadoc S.A. and is not intended to guarantee its correct use by the client. When buying the product the client agrees with the characteristics of the product in meeting his requirements, regardless of the particular final use. In case of any failure to meet the conditions of the agreement, within 30 days after the delivery of the product the client will be able to make a claim, as long as the product has been stored in appropriate conditions.

OFFICE AND MANUFACTURING PLANT CALI Address: km 7 vía Jamundí - Cascajal PBX: (602) 555 2406
e-mail: ventas@impadoc.com - Cali – Colombia

OFFICE AND MANUFACTURING PLANT SIBATÉ km 0 + 750 m Vía Silvania, Parque Industrial Tequendama IV. PBX: (601) 3571800
e-mail: ventasbogota@impadoc.com - Sibaté - Colombia