

Fast Drying Putty Paneling Stucco Joint Compound

Fast-drying Multipurpose Putty Paneling Stucco is an acrylic-based product intended for interiors, that uses high-quality raw materials, making it a versatile putty that can be adjusted to the application, adhesion and quick-drying needs on drywall sheets used in light construction and as a stucco to give a final finish.

Advantages

- Multipurpose putty.
- Easy to apply, ready to use
- Good workability that allows for easy spreading.
- Excellent adhesion.
- White color.
- Minimum shrinkage on drying.
- Minimum pulling away.
- High yield
- High anti-cracking power

Applications

Uses of the Fast-drying Multipurpose Putty Paneling Stucco :

- Treatment and patching of joints in drywall, bonding of mesh tapes, paper tapes, corners, flanges, screws and ceilings.
- Finishing of plaster panel sheets
- As a finishing stucco on leveled surfaces of walls and ceilings (paste).

Technical Characteristics

Reference Standard ASTM C475

Presentation: Joint compound putty for finishing drywall sheets in interiors.

Wet density: 1.60 - 1.80 kg/L.

Finish: Smooth and homogeneous.

Color: White.

Drying time (hours): 4 to 5 hours Total System.

Appearance: Viscous paste.

Application: Trowel or spatula

Approximate theoretical yield: Depending on the quality of the surface of the drywall sheet and the quality of the work, the approximate yield is 0.75 to 1.2 kg/m².

Equipment cleaning: Water

Presentation: 28 kilo bucket, 5.6 kilo gallon, 14 kgbucket and 1/4 gallon (1,5 kg).

Durability: Shelf life of the product tightly closed in its original packaging, 6 months.

Preparation and Application

Surface Preparation

Make sure the surface of the drywall sheet is clean, dry and free of dust, grease and humidity before applying FAST DRYING MULTIPURPOSE PUTTY PANELING STUCCO.

Application as putty

- Before use, stir the SR Multipurpose putty paneling stucco until the product is homogeneous.
- Apply SR Multipurpose putty paneling stucco on the joints of the drywall and apply the tape by pressing with a spatula to fix it. Subsequently, apply a coat of SR putty paneling stucco sufficiently to cover the tape. Allow to dry for 3 to 4 hours.
- Once the SR multipurpose putty paneling stucco has dried, another layer of product is applied and spread to the sides of the tape about 20 cm until obtaining a more uniform finish. Use a spatula to remove any excess of material from the edges.
- When the material has dried, another layer of SR multipurpose putty paneling stucco is applied for a better finish or polish.
- Once the application of the ST multipurpose putty paneling stucco is completed, the surface can be slightly sanded before applying the finish (paint).
- The whole process takes within 4 to 5 hours depending on the weather and humidity conditions.

Application as a stucco

- Before use, stir the SR multipurpose putty paneling stucco until the product is homogenous; make a thin polished layer and let dry before applying the next layer. The application of three layers is recommended.

Paint Application

Depending on weather conditions, let the putty dry for at least 24 hours before painting.

IMPORTANT: Non-toxic product.

Recommendations

1. Store the product indoors in a cool place and keep it in its original tightly closed packaging, protected from extreme temperatures. Keep away from direct sunlight.
2. The FAST DRYING MULTIPURPOSE PUTTY PANELING STUCCO must not be repackaged, since being a water-based product, it is sensitive to contamination from fungi and bacteria.
3. The product MUST NOT be mixed with any other material to avoid altering its formulation and performance.
4. Make sure the container is properly closed between each application.
5. It is suggested to rotate stock every 90 days.

Technical Assistance

IMPADOC's technical team works hand by hand to offer the best knowledge and optimal use of construction and industry products. If you have any concerns or suggestions, please contact us: asistenciatecnica@impadoc.com

The information provided in this document refers to the product data supplied by Impadoc S.A. and is not intended to guarantee its correct use by the client. When buying the product the client agrees with the characteristics of the product in meeting his requirements, regardless of the particular final use. In case of any failure to meet the conditions of the agreement, within 30 days after the delivery of the product the client will be able to make a claim , as long as the product has been stored in appropriate conditions.

OFFICE AND MANUFACTURIN PLANT CALI Dirección km 7 vía Jamundí - Cascajal PBX: (572) 555 2406
e-mail: ventas@impadoc.com - Cali – Colombia

OFFICE AND MANUFACTURING PLANT SIBATÉ km 0 + 750 m Vía Silvania, Parque Industrial Tequendama IV. PBX: (571) 3571800
e-mail: ventasbogota@impadoc.com - Sibaté - Colombia.