STARLEGENDS

Starlegends HRIS

Functionality, Flows & UI Guide

A code-based product reference for the role-based HR and employee operations app.

Build 1.0.11+14 · com.starlegends.hris · Flutter · Material 3 · Supabase · Firebase FCM

Product reference · October 2026

ABOUT THIS GUIDE

Everything the app does, on one page at a time.

Starlegends HRIS is a role-based Human Resources and employee operations app. It brings together employee information, attendance, schedules, leave and HR requests, payroll, performance, company communications, documents, reporting and administration in a mobile-oriented Flutter UI. This guide describes the implementation found in the project source and is suitable as source material for a fuller product or user guide.

8	16	4	6+
account roles	feature modules	bottom-nav tabs	theme colors, plus custom

SCOPE NOTE

This guide does not prove that every Supabase migration, RPC, Storage bucket, Firebase setting or Edge Function has been deployed to a live environment. Some modules have local development fallbacks; others require an authenticated backend and do not work as a local-only feature.

CONTENTS

01 What the app is . . . 3
02 Main user journey . . . 3
03 Navigation & screens . . . 4
04 Roles & access model . . . 5
05 Feature inventory & workflows . . . 6
06 Settings & preferences . . . 9
07 Trash, restore & retention . . . 10
08 UI & visual design . . . 11
09 Data, backend & integrations . . . 12
10 Platform & production caveats . . . 12
11 Key source locations . . . 13

01 What the app is

Purpose, technology and building blocks

Starlegends HRIS is built with **Flutter** and **Material 3**. Its service layer can connect to Supabase for authentication and business data. Firebase Cloud Messaging (FCM) delivers configured remote push, and local device preferences hold selected settings and development fallbacks.

Flutter + Material 3

Mobile-oriented UI with shared light and dark themes. Android, iOS and web project support.

Supabase

Authentication, relational HR records, RLS policies, Storage and Realtime workflows.

Firebase FCM

Configured remote push delivery, dispatched by a Supabase function.

Local preferences

Selected settings, cached data and development fallbacks on the device.

02 Main user journey

How the app flows from launch to sign-out

1 App startup
Flutter initializes; Supabase starts only if URL and key are present; local notifications start separately.

→

2 Splash & routing
Branded splash checks session and biometric state, then routes by account state.

→

3 Authentication
Employee ID plus password; role loaded from the authenticated profile.

↓

4 Dashboard
Role-sensitive shortcuts, counts and summaries load with a startup timeout.

→

5 Feature work
Open a module, view, submit, review or approve based on permissions.

→

6 Sign-out
Session ends; push handling deactivates the device token when possible.

2.1 App startup and splash

- Flutter initializes, then backend bootstrap initializes Supabase **only** if the build has the required URL and publishable/anonymous key.
- Local notifications initialize separately from remote push, so local attendance reminders do not inherently need Firebase push setup.
- When Firebase/Supabase push configuration is complete, the push service starts its messaging listeners.
- The splash screen waits through the branded intro, then routes to sign in, a required temporary-password change, or the dashboard.

2.2 Authentication

- Sign in with the assigned numeric **Employee ID** in `YY-NN-NNN` format plus a password. The ID formats while typing and also accepts a pasted number without separators.
- With Supabase configured, an **Edge Function** maps the Employee ID to its linked Auth account, validates that the mapping is unique and eligible, and establishes the session. The role comes from the profile, not from a user choice.
- Password reset uses the linked work email. Accounts flagged for a temporary password must change it before proceeding.
- Inactive accounts are rejected during session restoration.
- **Biometric sign-in** is optional on supported native devices after setup; unavailable on web.

> **DEVELOPMENT VS PRODUCTION**
> Without Supabase, debug builds may use local or sample behavior. That is not production authentication; release builds must use the intended backend configuration.

2.3 Dashboard and feature work

- Initial loading gathers employee, attendance, announcement, notification, message and summary data. The blocking wait has a timeout so slow requests do not hold the screen.
- Dashboard cards, shortcuts, unread counts and the drawer lead to modules. Some announcements and messages update through Supabase Realtime, with refresh/polling fallbacks.
- In a module, the user loads allowed records, then views, submits, reviews, approves or updates. Successful changes refresh the screen; errors surface through dialogs, banners or snackbars.

03 Navigation & screens

Where things live



Element	What it does
Bottom navigation	Four persistent tabs: **Dashboard**, **Leave**, **Attendance** and **Profile**.
Dashboard drawer	Layout varies for employee versus non-employee audiences and provides additional feature navigation.
Feature launcher	Opens module screens and passes the current user and role context. Some secondary pages are pushed directly rather than registered as named routes.
Notifications	Selected items deep-link to related request, approval or payroll review work.
Settings	Personal preferences, profile actions, support and role-limited administration.
Fallback page	A generic feature-detail screen exists for launcher entries without a dedicated branch.

The role and permission helper lives in `permission_service.dart`. Individual screens and Supabase Row Level Security (RLS) policies can apply additional limits beyond the dashboard's visible feature list.

04 Roles & access model

Eight account roles, one authenticated profile

LEVEL 1
Employee
Attendance, leave, requests, schedule, WFH, own profile.

LEVEL 2
Team Leader
Leave approvals, itinerary workflow, first-stage WFH review.

LEVEL 3
Department Head
Leave approvals, itinerary workflow, first-stage WFH review.

LEVEL 4
HR Admin
Employee records, payroll preparation, leave and WFH final approval.

LEVEL 5
Finance
Second step of the payroll approval chain.

LEVEL 6
Management
Allowed through the admin-settings helper.

LEVEL 7
Top Management
Releases payroll. No attendance recording or Performance.

LEVEL 8
Super Admin
System accounts, employee deletion. No attendance or Performance.

4.1 Payroll approval chain

HR Admin prepares → **Finance advances** → **Top Mgmt releases**

4.2 Rule highlights

Area	Rule in the app
Employee management	HR Admin and Super Admin manage employee records; the directory **delete** action is Super Admin-only.
System accounts	Account access and management are explicitly Super Admin-only.
Attendance	Recording is allowed for roles other than Super Admin and Top Management. Backend policies may restrict further.
Leave approvals	Approval-feature access is explicit for HR Admin, Department Head and Team Leader; exact steps depend on workflow rules and request state.
Itinerary	Employee, Department Head, Team Leader and HR Admin are explicitly allowed to participate.
Announcements	Employees are excluded from management; other roles can be offered management actions, subject to screen and backend rules.
Performance	Super Admin and Top Management are excluded by the feature permission helper.
Admin settings	Super Admin, HR Admin and Management are allowed through the helper; individual settings may be stricter.

Reading access correctly: use the signed-in role, the screen's action permissions and backend policies together; a visible navigation item alone does not guarantee every action is permitted.

05 Feature inventory & workflows

Sixteen modules, what each one does

5.1 Dashboard and at-a-glance information

- Role-appropriate shortcuts plus attendance status/summary, recent announcements, notification state and message counts.
- The “Today's attendance” summary supports operational monitoring and refreshes periodically where enabled.
- Selecting a feature opens its dedicated workflow. Branded loading shows until the startup wait completes or times out, then available content appears.

5.2 Employee directory and profiles


- Browse employee records and open a profile with name, role, department, position, contact and employee details.
- HR Admin and Super Admin manage records; field editing has role-specific restrictions. Non-HR users cannot change department, since it is part of the data-access scope.
- Login uses the assigned numeric Employee ID; the ID is not allocated or renumbered during login.
- Profile images are stored locally without Supabase, and through Supabase Storage path handling when configured.

EMPLOYEE ID CARD

A linked employee can open their card from the profile or the dashboard menu. It shows **only** employee number, name, position and department, never contact details, pay or other private data. Preview front and back, save each side or both as PNG, or export a two-page portrait CR80-size PDF. The optional profile image loads through the configured profile-image flow.

5.3 Attendance and adjustments

- Employees and permitted roles view attendance history and the current day's status. Authorized users can see scoped live/team attendance.
- Time-out may show an early/under-time confirmation when recorded time is below the expected duration.
- Users submit an **attendance adjustment** request for a date/time correction. Schedule start/end values inform lateness and duration calculations.
- With Supabase configured, attendance writes use a server-validated clock workflow, and reads are limited by database policies.
- Completed personal history can go to Trash, be restored, or be permanently deleted. Permanent deletion removes the official record used by HR and payroll, and needs explicit confirmation.



5.4 Leave requests and approvals

- Employees create leave requests and track status and history.
- Reviewers see pending approval work and approve or reject through the configured multi-step workflow (Department Head, Team Leader, HR and other stages depend on the installed database workflow and request state).
- HR self-leave support has a dedicated migration and workflow.

- Active requests are never hidden as completed history; completed personal leave history may go to Trash without deleting official approval records.

5.5 General HR requests

- Submit from the Requests area; status and approval progress appear in the list and detail flows. Approvers act according to request type and role.
- Supabase-backed behavior uses HR request tables and workflow setup; local development behavior may be available without Supabase.
- Completed personal request history can be hidden and restored through Trash; active requests stay in workflow processing.

> **WORK FROM HOME (WFH)**
> Pick **one upcoming date** and give a required reason. The date must be an HR-assigned office duty day and cannot conflict with approved leave. Requires Supabase and the WFH workflow migration. Flow: Department Head or Team Leader reviews first, then HR Admin gives final approval or rejection. Employees cannot review their own request. Approval covers that date only, does not change the weekly schedule, and does **not** mark attendance present; the employee must still clock in and out.

5.6 Schedules and schedule changes

- View the assigned weekly schedule and approved changes. Authorized administrators assign and update work schedules.
- Request a schedule adjustment, day-off change or similar; requests move through role-configured review steps.
- Assignments carry effective dates, weekly day definitions, work/rest-day type, shift start/end and location.
- Completed personal schedule-request history may go to Trash without removing official approval or schedule records.

5.7 Payroll and payslips

- Payroll users prepare payroll for a selected period/cutoff, using attendance, schedules, leave and employee/pay inputs to calculate summaries, pay and deductions.
- HR can review and load attendance inputs and adjust supported fields before saving.
- Approval and release: HR to Finance, Finance to Top Management, then release by Top Management.
- Employees and authorized users view applicable payslip details. Payroll records are compliance/history data, not ordinary employee-facing Trash items.
- Correctness depends on the deployed payroll schema/workflow migrations and the production role/policy setup.

5.8 Performance

- Performance review and dashboard information with related records, served through the performance service and a performance-dashboard database setup.
- Visibility is role-sensitive; the permission helper excludes Super Admin and Top Management.

5.9 Reports and itinerary

- The Reports area provides reporting entry points. Employees and designated reviewers use the itinerary/report workflow to submit periodic or daily information and review its status.
- Reviewers process or return reports depending on workflow state.
- Setup covers report submissions, review history, policy settings, notifications and private file-storage policies when the Supabase migration is installed.

- Scheduled missed-submission detection depends on the database job/cron setup in the Supabase setup guide.

5.10 Documents

- View available employee documents, upload through a dedicated form, and assign required-document items through the requirement-management flow.
- Supabase-backed documents rely on the document-management schema and storage policies, with action-specific role gates.
- Documents are not a general employee-Trash category because they can be records required for HR/compliance.

5.11 Recruitment

- Lists open positions and applicants. Add a job opening with a title, department and status: **Open**, **Screening** or **Paused**.
- With Supabase, openings read from `job_openings` and read failures are reported rather than replaced with samples.
- The applicant list is development-only sample data and is empty online; a full applicant-tracking workflow is **not yet implemented**.

5.12 Announcements and company feed

- View the feed. Authorized users create, edit and delete announcements. Posts can carry attachments, reactions and comments, with replies and reactions where the engagement migration is installed.
- Supabase Realtime delivers cross-device updates, with a refresh fallback. In non-Supabase development mode, feed and engagement data can use local preferences.
- Deleted announcements can be recovered from Trash when the announcement Trash migration is installed.

5.13 Notifications

- View notifications and open related actions; mark one or all as read; clear supported entries into Trash rather than purging them immediately.
- Data uses Supabase or a local-preferences fallback depending on configuration.
- Remote device push is a **separate path** from the in-app list and needs Firebase plus Supabase push-dispatch configuration.

5.14 Direct messages and company group chat

- Direct-message and company-wide chat entry points with message history, read state/unread counts, attachments and live updates.
- Company chat supports staff mentions and **@Everyone** when the database migration is deployed. Direct-message directory visibility is role-scoped by backend rules.
- Requires an authenticated Supabase user and database setup; unlike other modules there is **no local-only chat fallback**.
- Sent direct messages can be moved to Trash for the sender's view; company chat recovery follows its room-wide Trash behavior and backend setup.

5.15 Accounts and access administration

- Super Admin manages system accounts through the Accounts screen and account form.
- Production provisioning is intended to use secured Supabase Edge Functions; the mobile client must never hold a service-role key.
- Account approval, password reset, management and provisioning each have separate Edge Function support files that need deployment and server-side secrets.

5.16 Team management

- Admin settings include team and membership configuration. Online sessions load and save Supabase `teams` and `team_members`; development mode uses local SharedPreferences.
- Online team scope reloads when the authenticated account changes and does not retain sample scope for empty results. Membership writes still use multiple database operations.

06 Settings & preferences

Personal controls, security, support and admin tools

6.1 Personal preferences

Setting	What it does	Needs / notes
Dark mode	Switches between light and dark appearance.	Stored on the device by the theme controller.
Theme color	Green, Blue, Red, Violet, Yellow or Orange, or a custom color via six-digit hex input and hue/saturation/brightness sliders.	Stored locally; applies to light and dark themes; independent of dark mode.
Notifications	Enables Firebase-backed remote push for the signed-in account: requests OS permission, gets a device token, registers it with Supabase.	Firebase setup plus Supabase push schema, Edge Function and secrets.
Attendance reminders	Local alerts two minutes before assigned shift start and end, in Asia/Manila time, scheduled for the next 14 days.	Separate from FCM. Skips rest days, past times and the alert after attendance is recorded. Device-local; needs notification permission. Android uses inexact alarms and may delay slightly. Unavailable on web.
Biometric login	Authenticates before enabling; persists enable/disable through the biometric service. Cancelled or unavailable authentication does not enable it.	State stored locally and cleared at logout. Not on web; needs OS/device configuration.



Theme accent options (swatches are illustrative).

6.2 Profile, security and support

- **Profile:** opens the employee profile/details page and edit actions, subject to role restrictions.
- **Change password:** updates the signed-in Supabase Auth password when Supabase is configured.
- **Help Center:** offers a direct HR chat; the HR recipient is resolved through a backend RPC, so messaging backend setup is required.
- **Log out:** asks for confirmation before returning to the login screen.

6.3 Administrative settings

- **Company Setup** links to Departments, Positions and Leave Types. **Departments** and **Roles** open their settings lists.
- **Team management** configures teams and members. The Teams shortcut shows for HR Admin and Super Admin.
- **Audit Logs** displays available history. The service can show sample fallback rows when Supabase is unavailable, a query is empty or a read fails.
- **Trash** restores or permanently removes only supported trashed items.
- Admin visibility is permission-controlled, and settings lists can show configured Supabase entries or built-in fallback values.

DO NOT TREAT FALLBACK ROWS AS PRODUCTION DATA
Sample audit rows must not be presented as verified live audit events. Verify the backend before treating settings contents as production configuration.

07 Trash, restore & retention

An organizational tool, not a universal eraser

Supported in Trash

- Announcements
- Notifications
- Sent direct messages
- Company group-chat messages
- Completed personal HR history: attendance, leave, requests, schedule requests, attendance adjustments, itinerary history

Not ordinary Trash items

- Payroll records (compliance/history data)
- Documents (may be HR/compliance records)
- Active workflow items, never treated as completed history

- Where applicable, users restore items or permanently delete supported Trash entries.
- Permanent deletion of completed personal HR history removes the underlying record plus linked workflow details and files, when present.
- Cloud Trash depends on the Trash SQL migration and its prerequisite tables. Online permanent attendance/history deletion also requires `supabase/permanent_trash_delete.sql`. The source repository does not establish whether production has applied these.

08 UI & visual design

Look, feel and feedback

Aspect	Implementation
Design system	Material 3 with shared light and dark themes.
Branding	Green-led accent palette, configurable theme accents, branded splash/login treatments, HRIS logo and icon assets.
Typography	Plus Jakarta Sans via Google Fonts configuration.
Components	Rounded cards and controls, clear section labels, icon-led rows and actions, status chips/cards, theme-adapted color.
Navigation	Role-sensitive dashboard drawer plus a persistent four-item bottom navigation.
Loading	Branded Lottie loading assets in loading widgets and startup, with progress-indicator fallbacks in places.
Feedback	Success/error animation dialogs and snackbars on important save and error events.
Motion	Lottie artwork and selected animated dashboard/screen elements.
Robustness	Standard Flutter Material controls and scrollable form/list layouts; exact behavior varies by module.

The UI includes Android, iOS and web project support, but not every feature is available on every platform. Native notifications and biometrics are platform-dependent.

09 Data, backend & integrations

What the app talks to

Layer	Role	Key points
Supabase	Configured auth, relational HR records, policies, storage and Realtime.	Values supplied at build/run time, not committed. RLS, RPCs, Edge Functions and migrations are part of the functional contract; URL and key alone do not enable every workflow.
Local persistence	SharedPreferences for preferences, cached/development data and fallback services.	Identify the source of a record per module; not every feature automatically syncs.
Firebase	Firebase Messaging for configured remote push.	Server-side push uses a Supabase dispatcher/Edge Function and secrets. No Firebase service-account secret belongs in the Flutter app or build-define file.
Storage	Profile images, documents, itinerary files.	Depends on Supabase Storage buckets, RPCs and storage policies.
Data migrations	Versioned SQL setup and remediation scripts under supabase/.	Apply the documented sequence to the intended project; do not infer deployment state from checked-in files. See `supabase_setup.md`.

10 Platform & production caveats

Read before relying on a feature

Area	Caveat
Android / iOS	Native notification and biometric capability depends on device permission and platform project configuration.
Web	Biometric login, FCM mobile push and scheduled local attendance reminders are unavailable.
Push notifications	Require configured Firebase plus Supabase **device_push_tokens**, a dispatcher function and server secrets.
Attendance reminders	Do not need FCM, but need local notification permission and access to the current schedule and attendance records at refresh.
Messaging	Needs authenticated Supabase access and the applicable migrations.
Trash	Restore and permanent-delete availability depends on installed SQL scripts and prerequisite tables.
Accounts	Production provisioning must run through a secured server/Edge Function, never a service-role key in the client.

FALLBACK DATA CAN LOOK REAL
Some services show local or sample records when backend configuration or data is missing, so the UI may look populated without representing live production records.

DEPLOYMENT NOT VERIFIED
This document has not verified production SQL, secrets, Firebase/APNs, permissions, accounts or live data.

11 Key source locations

Where to look in the code

Area	Files
Startup & composition	`lib/main.dart` `lib/app.dart`
Authentication	`lib/services/auth_service.dart` `lib/screens/auth/login_screen.dart`
Dashboard & navigation	`lib/screens/dashboard/dashboard_screen.dart` `lib/services/permission_service.dart`
Settings	`lib/screens/settings/settings_screen.dart` `lib/core/theme/theme_controller.dart`
Backend setup	`lib/core/config/backend_config.dart` `docs/supabase_setup.md`
Notifications & reminders	`lib/services/push_notification_service.dart` `lib/services/attendance_reminder_service.dart`
Design theme	`lib/core/theme/app_theme.dart`