

# **Safety Data Sheet**

# **Dust-Off Compressed Gas Duster**

# Section 1. Identification

Product Identifier Dust-Off Compressed Gas Duster

Synonyms Professional 12 oz.; Jumbo 17 oz.; Classic and Plus; Dust-Off" Compressed Gas

Duster

Manufacturer Stock

Numbers

N/A

Manufacturer Contact

Address

Falcon Safety Products, Inc. 25 ImClone Drive Branchburg, NJ, 08876

USA

Phone Emergency Phone Fax (908) 707-4900 (800) 498-7192 N/A

## Section 2. Hazards Identification

Classification FLAMMABLE GASES - Category 2

GASES UNDER PRESSURE - Compressed gas

Signal Word Warning

**Pictogram** 



Hazard Statements Contains gas under pressure; may explode if heated

Flammable gas

**Precautionary Statements** 

Response Eliminate all ignition sources if safe to do so.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Prevention Do not spray on an open flame or other ignition source.

Keep away from heat.

Pressurized container: Do not pierce or burn, even after use.

Storage Protect from sunlight. Store in a well-ventilated place.

Store at temperatures not exceeding 120 degrees F/49 degrees C

Disposal N/A

General Keep out of reach of children

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

N/A

No Data Available

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
75-37-6	Ethane, 1,1-difluoro-	100 %

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First-Aid Measures

General Advice Never give anything by mouth to an unconscious person. When symptoms persist

or in all cases of doubt, seek medical advice.

Inhalation Remove from exposure, lie down. Move to fresh air. Keep patient warm and at rest.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get

immediate medical attention.

Skin Take off all contaminated clothing immediately. Flush area with lukewarm water.

Do not use hot water. If frostbite has occurred, call a physician.

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get Eye

medical attention.

Ingestion Is not considered a potential route of exposure.

Most important

delayed

Anaesthetic effects: light-headedness, irregular heartbeat with a strange sensation symptoms/effects, acute and in the chest, heart thumping, apprehension, feeling of fainting, dizziness or

weakness.

Protection of First-aiders If potential for exposure exists refer to Section 8 for specific personal protective

equipment.

Because of possible disturbances of cardiac rhythm catecholamine drugs, such as Notes to Physician

epinephrine, which may be used in situations of emergency life support, should be

used with special caution.

# Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Water spray, water fog, dry chemical, alcohol resistant foam, carbon dioxide (CO2)

Unsuitable Extinguishing

Media

No applicable data available.

Specific Hazards

Flammable. This substance's fire decomposition by-products will include hydrofluoric acid and possibly carbonyl flouride. Avoid contact with these materials, which are toxic and irritating. Evacuate personnel immediately in the event of a fire involving this substance. Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Vapors or gases may travel

considerable distances to ignition source and flash back.

Special protective equipment for firefighters Further Information

Use personal protective equipment. Wear neoprene gloves during cleaning up work after a fire. Exposure to decompositon products may be a hazard to health. Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment. Cool containers/tanks with water spray.

#### Section 6. Accidental Release Measures

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections

before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE

EQUIPMENT during clean-up.

Safeguards (Personnel) Evacuate personnel to safe areas. Ventilate the area. Refer to protective measures

listed in sections 7 and 8.

Spill Clean-up If this product is spilled and not recovered, or is recovered as a waste for treatment

and disposal, the CERCLA Reportable Quantity is 100 lbs. (release of an Unlisted Hazardous Waste with the Characteristic of Ignitability). Evaporates. Ventilate area using forced ventilation, especially low or enclosed places where heavy vapors

might collect.

Accidental Release

Measures

Wear self-contained breathing apparatus (SCBA).

# Section 7. Handling and Storage

Handling (Personnel) Avoid breathing vapors or mist. Avoid contact with skin, eyes and clothing. Provide

sufficient air exchange and/or exhaust in work rooms. For personal protection see section 8. Handle in accordance with good industrial hygiene and safety practice.

Handling (Physical Aspects) Vapors are heavier than air and may spread along floors. Vapors may form

flammable mixture with air. The product should only be used in areas from which all

naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropirate standard. No sparking tools should be used. Take measures to prevent the build up of electrostatic charge. Keep away from open flames, hot surfaces and sources of ignition. When using DO NOT SMOKE. Do not use in areas where vapors may accumulate such as

paper shredders.

**Dust Explosion class** 

Not applicable

Storage

Keep container tightly closed and in a dry, well-ventilated location. Store in original

container. The product has an indefinite shelf life when stored properly.

Storage Period Recommended shelf life - 10 years provided product is stored in a dry location as

directed.

Storage Temperature Do not expose to temperatures above 120 degrees F (49 degrees C) as

overheating could cause can to burst. DO NOT leave in direct sunlight or enclosed

vehicle.

# Section 8. Exposure Controls/Personal Protection

**ACGIH TLV OSHA PEL STEL** Occupational Exposure Ingredient Name Limits N/A N/A N/A Ethane, 1,1-difluoro-Personal Protective Equipment **Engineering controls** Ensure adequate ventilation, especially in confined areas. Use respiratory protection if needed. **Eye/Face Protection** Wear safety glasses with side shields. Direct contact with liquid may cause frostbite. For rescue use self-contained breathing apparatus. Vapors are heavier than air **Respiratory Protection** and can cause suffication by reducing oxygen available for breathing. Skin and body protection As required by employer code. If there is risk of skin contact, wear protective clothing, gloves, etc. Direct contact with liquid can cause frostbite. General Hygiene Handle in accordance with good industrial hygiene and safety practices. When Considerations using do not eat or drink. Wash hands and face before breaks and immediately after handling the product.

# Section 9. Physical and Chemical Properties

Physical State	Gas
Color	Clear
Odor	slight, ether- like
Odor Threshold	No applicable data available
Solubility	Water - Slightly
Partition coefficient Water/n-octanol	N/A
VOC%	N/A
Viscosity	No applicable data available
Specific Gravity	0.91
Density lbs/Gal	0.9
Pounds per Cubic Foot	N/A
Flash Point	<-58°F (<-50° C)
FP Method	N/A
Ph	Neutral
Melting Point	No applicable data available
Boiling Point	-13 °F (-25 ° C)
Boiling Range	N/A
LEL	3.9
UEL	16.9
Evaporation Rate	No applicable data available
Flammability	Flammable
Decomposition Temperature	N/A
Auto-ignition Temperature	No applicable data available
Vapor Pressure	5,960 KPa at 77F (25C)
Vapor Density	2.4 at 77F (25C) (Air=1)

# Section 10. Stability and Reactivity

Reactivity Stable under recommended storage conditions.

Chemical Stability The product is chemically stable under recommended storage conditions.

Conditions to Avoid Aerosol containers are unstable at temperatures above 120 degrees F/49 degrees

С

Incompatible Materials Incompatible products include Alkali metals, Alkaline earth metals, powdered

metals, powdered metal salts.

Hazardous Decomposition

**Products** 

Decomposition products are hazardous. This material can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid

and possibly carbonyl fluoride.

# Section 11. Toxicological Information

Component Analysis - LC50 1,1-Difluoroethane - > 64000 ppm rat Component analysis - Oral 1,1-Difluoroethane - 1500 mg/kg rat

LD50

Effects of Acute Exposure - Contact with liquid may cause frostbite

Eye

Effects of Acute Exposure -

Skin

Effects of Acute Exposure -

Inhalation

Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effect (headaches, dizziness). Vapors may cause dizziness or

suffocation.

Effects of Acute Exposure -

Ingestion

Not a normal route of exposure

Contact with liquid may cause frostbite

Sensitization Non-hazardous by WHMIS/OSHA criteria.

Carcinogenicity Not classifiable as a human carcinogen. Animal testing did not show carcinogenic

effects. None of the components present in this material at concentrations equal to

or greater than 0.1% are listed by IARC, NTP, or OSHA as a carcinogen.

Mutagenicity Animal testing did not show any mutagenic effects. Did not cause genetic damage

in cultured bacterial cells. Tests on mammalian cell cultures showed mutagenic

effects.

Reproductive Toxicity

No toxcicity to reproduction. Animal testing showed no reproductive toxicity.

Teratogenicity
Further Information

Animal testing showed no developmental toxicity.

Cardiac sensitization threshold limit: 405000 mg/m3

#### Section 12. Ecological Information

Aquatic Toxicity 1,1-Difluoroethane 96 h LC50 : Fish 295.78 mg/l 96 h EC50 : Algae 47.76 mg/l 48

h EC50: Daphnia (water flea) 146.7 mg/l

# Section 13. Disposal

Waste Disposal Methods Comply with applicable Federal, State/Provincial and Local Regulations. May be a

RCRA Hazardous waste due to the ignitability characteristic. Do not puncture or

incinerate container.

Contaminated Packaging Not Available

# Section 14. Transport Information

**UN Number** 1030

**UN Proper Shipping Name** 1,1-Difluoroethane

**DOT Classification** 2.1 N/A **Packing Group** 

Packaging Exceptions Note: Falcon Safety Products has been granted a DOT special permit. A copy of

DOT Special Permit SP-11516 can be obtained by calling Falcon Safety Products,

Inc. at 908-707-4900.

Transportation of Dangerous Proper Shipping name: 1,1-Difluoroethane Hazard Class: 2.1 UN number: 1030

Goods (TDG - Canada)

IATA/ICAO (Air)

Packaging Exceptions: Limited quantity (containers up to 125mL)

Proper Shipping Name: 1,1-Difuoroethane. Hazard Class: 2.1. UN Number: 1030.

Maximum Net Quantity Packaging: Cargo Aircraft only - 150 kg maximum (forbidden on passenger aircraft). Maximum Net Quantity packaging cargo only:

150 kg.

Proper Shipping Name: 1,1-DIFLUOROETHANE. Hazard Class: 2.1. UN Number: IMDG (Marine Transport)

1030.

Additional Information TDG Canada: Falcon Safety Products has been granted Equivalency Certificate

SU 9211 (ren. 1) by the TCSS, TDGD to offer for transport by road, rail and marine.

#### Section 15. Regulatory Information

Canadian Federal This product has been classified in accordance with the hazard criteria of the Regulations

Controlled Products Regulations and the SDS contains all the information required

by the Controlled Products Regulations.

WHMIS Status Controlled

WHMIS Classification Class A - Compressed Gas, Class B - Division 1 - Flammable Gas

**TSCA** On the inventory, or in compliance with the inventory.

SARA 313 Regulated This material does not contain any chemical components with known CAS

Chemical(s)

numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

**US Federal Regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910,1200.

Chemical(s)

NJ Right to Know Regulated Substances on the New Jersey Workplace Hazardous Substance List present at a

concentration of 1% or more (0.1% for substances identified as carcinogens,

mutagens or teratogens): 1,1-Difluoroethane.

California Prop. 65 This product does not contain a chemical known to the State of California to cause

cancer, birth defects or other reproductive harm.

Canada Domestic

This product is listed on the DSL inventory list and complies with the inventory

requirements administered by the governing country. Substances List (DSL)

# Section 16. Other Information

Revision Date 4/28/2015

Disclaimer Information contained herein was obtained from sources considered technically

accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any

information contained in this document.

Prepared By Falcon Safety Products, Inc. 908-707-4900