

Case Study: Turbulence

2022-10-31

Introduction

Data (dont include)

```
data_train <- read.csv("/Users/juliarosner/Desktop/Stat 325/Case Study/Data/data-train.csv")
data_test <- read.csv("/Users/juliarosner/Desktop/Stat 325/Case Study/Data/data-test.csv")
data_train
```

##	St	Re	Fr	R_moment_1	R_moment_2	R_moment_3	R_moment_4
## 1	0.10	224	0.052	0.00215700	1.3035e-01	1.4374e+01	1.5865e+03
## 2	3.00	224	0.052	0.00379030	4.7042e-01	6.9940e+01	1.0404e+04
## 3	0.70	224	Inf	0.00290540	4.3499e-02	8.2200e-01	1.5551e+01
## 4	0.05	90	Inf	0.06352800	9.0653e-02	4.6746e-01	3.2696e+00
## 5	0.70	398	Inf	0.00036945	6.2242e-03	1.2649e-01	2.5714e+00
## 6	2.00	90	0.300	0.14780000	2.0068e+00	3.6249e+01	6.7167e+02
## 7	0.20	90	Inf	0.08127300	3.2450e-01	3.0363e+00	3.2976e+01
## 8	3.00	224	Inf	0.00574730	1.1966e-01	2.7480e+00	6.3159e+01
## 9	0.90	224	Inf	0.00302150	4.5244e-02	8.4530e-01	1.5809e+01
## 10	0.60	398	0.052	0.00031431	4.4672e-03	8.2060e-02	1.5077e+00
## 11	0.90	90	Inf	0.09102700	5.9539e-01	7.2454e+00	9.5166e+01
## 12	0.30	398	Inf	0.00036022	6.2830e-03	1.3546e-01	2.9211e+00
## 13	2.00	224	Inf	0.00447250	8.0804e-02	1.6668e+00	3.4408e+01
## 14	1.00	224	0.052	0.00312380	3.6478e-01	5.3322e+01	7.7958e+03
## 15	0.50	90	0.052	0.12670000	6.8596e+02	5.4300e+06	4.2900e+10
## 16	0.60	224	0.300	0.00257400	3.6621e-02	6.7102e-01	1.2309e+01
## 17	0.10	90	Inf	0.07722700	2.2120e-01	1.8833e+00	2.0190e+01
## 18	1.00	90	0.300	0.11236000	1.1261e+00	1.7335e+01	2.8261e+02
## 19	0.70	224	0.052	0.00285610	3.1273e-01	4.4529e+01	6.3423e+03
## 20	0.20	90	0.052	0.11760000	5.1774e+02	3.8100e+06	2.8000e+10
## 21	0.10	90	0.300	0.06125200	6.9867e-02	2.4338e-01	1.1379e+00
## 22	0.50	398	Inf	0.00036800	6.3559e-03	1.3341e-01	2.8013e+00
## 23	0.20	224	Inf	0.00269160	3.9016e-02	7.6384e-01	1.4978e+01
## 24	1.50	398	0.052	0.00038321	5.9338e-03	1.1156e-01	2.1004e+00
## 25	0.90	398	Inf	0.00038344	6.4432e-03	1.2925e-01	2.5935e+00
## 26	0.50	224	0.052	0.00274240	3.0355e-01	4.3911e+01	6.3530e+03
## 27	0.10	398	0.052	0.00027479	3.2549e-03	5.8006e-02	1.0344e+00
## 28	0.40	224	0.052	0.00268090	2.8897e-01	4.1585e+01	5.9861e+03
## 29	0.30	90	0.052	0.12261000	6.2727e+02	4.9100e+06	3.8500e+10
## 30	0.05	224	0.052	0.00173740	1.6633e-03	2.0228e-02	3.6438e-01
## 31	1.50	224	0.052	0.00341630	4.0300e-01	5.8417e+01	8.4710e+03
## 32	0.80	90	Inf	0.09107400	6.1825e-01	7.4973e+00	9.7048e+01
## 33	1.50	90	0.052	0.15181000	9.9690e+02	8.5500e+06	7.3300e+10

```

## 34 0.05 398   Inf 0.00022202 1.0055e-03 1.0857e-02 1.1782e-01
## 35 0.80 224   Inf 0.00298090 4.4580e-02 8.3764e-01 1.5759e+01
## 36 0.90 224 0.300 0.00280490 4.1143e-02 7.5132e-01 1.3729e+01
## 37 0.40 224   Inf 0.00292630 4.6261e-02 9.2914e-01 1.8681e+01
## 38 0.80 398 0.052 0.00033341 4.9036e-03 9.1143e-02 1.6948e+00
## 39 1.50 224 0.300 0.00341050 5.4101e-02 1.0222e+00 1.9340e+01
## 40 0.20 224 0.052 0.00257870 2.6830e-01 3.9080e+01 5.6959e+03
## 41 0.30 224   Inf 0.00283770 4.3589e-02 8.6962e-01 1.7373e+01
## 42 0.30 224 0.300 0.00250630 3.5881e-02 6.8596e-01 1.3132e+01
## 43 2.00 224 0.300 0.00381230 6.1927e-02 1.1844e+00 2.2705e+01
## 44 1.00 90    Inf 0.09691800 6.7696e-01 8.2384e+00 1.0602e+02
## 45 0.80 224 0.052 0.00295750 3.3361e-01 4.8161e+01 6.9539e+03
## 46 1.00 224 0.300 0.00289530 4.2300e-02 7.6755e-01 1.3941e+01
## 47 0.70 90 0.300 0.09471100 6.9751e-01 9.1793e+00 1.3187e+02
## 48 0.30 224 0.052 0.00256750 2.6547e-01 3.7665e+01 5.3451e+03
## 49 0.40 224 0.300 0.00262070 3.9502e-02 7.6851e-01 1.4966e+01
## 50 0.10 224 0.300 0.00221530 2.4475e-02 4.2167e-01 7.2842e+00
## 51 3.00 90    Inf 0.17234000 2.2386e+00 4.0454e+01 7.6198e+02
## 52 1.00 224   Inf 0.00309680 4.6454e-02 8.6381e-01 1.6077e+01
## 53 2.00 398   Inf 0.00053647 1.0022e-02 2.1023e-01 4.4109e+00
## 54 0.80 90 0.052 0.13793000 8.2524e+02 6.8000e+06 5.6100e+10
## 55 0.40 398 0.052 0.00029691 4.1375e-03 7.6124e-02 1.4014e+00
## 56 0.50 398 0.052 0.00030716 4.3494e-03 8.0143e-02 1.4770e+00
## 57 0.70 90    Inf 0.09217600 5.6482e-01 6.7191e+00 8.8723e+01
## 58 2.00 90 0.052 0.15433000 1.0269e+03 8.8700e+06 7.6700e+10
## 59 0.90 90 0.300 0.10962000 1.0319e+00 1.5797e+01 2.6136e+02
## 60 0.30 90    Inf 0.07694500 3.2652e-01 3.4052e+00 4.1042e+01
## 61 0.50 224 0.300 0.00250710 3.5152e-02 6.4378e-01 1.1801e+01
## 62 0.50 90 0.300 0.08477300 4.9728e-01 6.0317e+00 8.3287e+01
## 63 0.80 398   Inf 0.00037399 6.2457e-03 1.2542e-01 2.5193e+00
## 64 0.20 398   Inf 0.00033521 5.4505e-03 1.1408e-01 2.3884e+00
## 65 0.70 90 0.052 0.13173000 7.3694e+02 5.8700e+06 4.6700e+10
## 66 2.00 398 0.052 0.00039644 6.1040e-03 1.1209e-01 2.0593e+00
## 67 0.70 224 0.300 0.00260870 3.6438e-02 6.5445e-01 1.1765e+01
## 68 0.60 224 0.052 0.00279390 3.0594e-01 4.3745e+01 6.2554e+03
## 69 0.30 398 0.052 0.00030066 4.3488e-03 8.3446e-02 1.6023e+00
## 70 0.90 224 0.052 0.00305410 3.5419e-01 5.1795e+01 7.5758e+03
## 71 0.80 224 0.300 0.00268160 3.7714e-02 6.7549e-01 1.2112e+01
## 72 0.20 224 0.300 0.00246950 3.4818e-02 6.7088e-01 1.2939e+01
## 73 3.00 398 0.052 0.00040188 5.4492e-03 9.1871e-02 1.5565e+00
## 74 0.90 90 0.052 0.14184000 8.7019e+02 7.2500e+06 6.0400e+10
## 75 0.40 398   Inf 0.00036977 6.4986e-03 1.3933e-01 2.9880e+00
## 76 0.20 90 0.300 0.07798500 2.5598e-01 2.0965e+00 2.0849e+01
## 77 0.60 90 0.052 0.12946000 7.1816e+02 5.7200e+06 4.5600e+10
## 78 1.50 90 0.300 0.13678000 1.8254e+00 3.2833e+01 6.0903e+02
## 79 0.10 90 0.052 0.10464000 1.6015e+02 6.9900e+05 3.0700e+09
## 80 3.00 90 0.052 0.15538000 1.0443e+03 9.1400e+06 8.0000e+10
## 81 2.00 224 0.052 0.00363470 4.4512e-01 6.5387e+01 9.6105e+03
## 82 0.05 90 0.052 0.08786800 5.3449e-01 2.2205e+01 1.5679e+03
## 83 0.40 90 0.300 0.08095700 3.9996e-01 4.3303e+00 5.3618e+01
## 84 0.90 398 0.052 0.00034145 5.0555e-03 9.4083e-02 1.7522e+00
## 85 3.00 90 0.300 0.16433000 2.3317e+00 4.4516e+01 8.8779e+02
## 86 0.05 224   Inf 0.00153380 2.5653e-04 3.0407e-04 5.4466e-04
## 87 0.05 224 0.300 0.00135380 1.0303e-04 5.1400e-05 4.1600e-05

```

```
## 88 0.60 224    Inf 0.00291710 4.4317e-02 8.5282e-01 1.6431e+01
## 89 1.50 224    Inf 0.00370310 6.0910e-02 1.1829e+00 2.2990e+01
```

Goals (include in writeup)

- (1) Prediction: For a new parameter setting of (Re, Fr, St), predict its particle cluster volume distribution in terms of its four raw moments.
- (2) Inference: Investigate and interpret how each parameter affects the probability distribution for particle cluster volumes.

Exploratory Data Analysis (dont include in writeup, see methodology)

To begin, we will explore the data to ensure it is fit for modelling, determine initial transformations needed of the data, and determine which model we see would best fit the data.

```
names(data_train)
```

```
## [1] "St"          "Re"          "Fr"          "R_moment_1" "R_moment_2"
## [6] "R_moment_3" "R_moment_4"
```

```
summary(data_train)
```

```
##           St           Re           Fr           R_moment_1
##  Min.   :0.0500   Min.   : 90.0   Min.   :0.052   Min.   :0.000222
## 1st Qu.:0.3000   1st Qu.: 90.0   1st Qu.:0.052   1st Qu.:0.002157
##  Median:0.7000   Median :224.0   Median :0.300   Median :0.002958
##  Mean   :0.8596   Mean   :214.5   Mean   : Inf    Mean   :0.040394
## 3rd Qu.:1.0000   3rd Qu.:224.0   3rd Qu.: Inf    3rd Qu.:0.087868
##  Max.   :3.0000   Max.   :398.0   Max.   : Inf    Max.   :0.172340
##  R_moment_2   R_moment_3   R_moment_4
##  Min.   : 0.0001   Min.   : 0     Min.   :0.000e+00
## 1st Qu.: 0.0245   1st Qu.: 0     1st Qu.:3.000e+00
##  Median : 0.0808   Median : 1     Median :2.100e+01
##  Mean   : 92.4902   Mean   :753370   Mean   :6.194e+09
## 3rd Qu.: 0.5345   3rd Qu.: 40     3rd Qu.:5.345e+03
##  Max.   :1044.3000   Max.   :9140000   Max.   :8.000e+10
```


Histograms

```
hist(data_train$R_moment_1)
```




```
hist(data_train$R_moment_2)
```

Histogram of data_train\$R_moment_2




```
hist(data_train$R_moment_3)
```

Histogram of data_train\$R_moment_3




```
hist(data_train$R_moment_4)
```

Histogram of data_train\$R_moment_4




```
hist(data_train$Fr, breaks=20)
```

Histogram of data_train\$Fr




```
hist(data_train$St, breaks=20)
```


Histogram of data_train\$St




```
hist(data_train$Re, breaks=20)
```



These histograms indicate that each `R_moment` has distributions that are heavily skewed to the right, because the data has many rows of 0. In `R_moment_3` and `R_moment_4`, we notice that the maximum values are extremely high, while the medians are much smaller in comparison. This could pose a problem to our analysis, thus we believe it is best then to apply a transformation to these variables in order to obtain more accurate analysis.


```
hist(log(data_train$R_moment_1), breaks=20)
```

Histogram of $\log(\text{data_train}\$R_moment_1)$




```
hist(log(data_train$R_moment_2), breaks=20)
```

Histogram of $\log(\text{data_train}\$R_moment_2)$




```
hist(log(data_train$R_moment_3), breaks=20)
```

Histogram of $\log(\text{data_train}\$R_moment_3)$



```
hist(log(data_train$R_moment_4), breaks=20)
```


Histogram of $\log(\text{data_train}\$R_moment_4)$



Performing a log transformation on these variables created more normally distributed variables. While not perfectly normal, this is a big improvement to the non-transformed variables. We will use the log version of variables and will reflect these transformed variables as such in our interpretations and analysis.

Another transformation to consider is to turn Fr and Re into ordered, categorical variables, since they each only have 2 or 3 unique values.

```
pairs(data_train)
```



It appears that each R_moment variable has somewhat of a linear relationship with St . Thus, we may want to begin our search for a best model by fitting a linear model.

Modeling

We will fit a basic linear model onto each log-transformed response variable.

```
model1 <- lm(log(R_moment_1) ~ St + factor(Re) + factor(Fr), data=data_train)
summary(model1)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ St + factor(Re) + factor(Fr),
##     data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.47532 -0.07168  0.02101  0.10237  0.23554
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  -2.40825    0.04137  -58.218  <2e-16 ***
## St              0.24652    0.02165   11.386  <2e-16 ***
## factor(Re)224 -3.62590    0.03836  -94.517  <2e-16 ***
## factor(Re)398 -5.75678    0.04826 -119.287  <2e-16 ***
```

```
## factor(Fr)0.3 -0.10770    0.04422   -2.435    0.017 *
## factor(Fr)Inf -0.02584    0.03945   -0.655    0.514
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1593 on 83 degrees of freedom
## Multiple R-squared:  0.9952, Adjusted R-squared:  0.9949
## F-statistic: 3460 on 5 and 83 DF,  p-value: < 2.2e-16

model2 <- lm(log(R_moment_2) ~ St + factor(Re) + factor(Fr), data=data_train)
summary(model2)
```

```
##
## Call:
## lm(formula = log(R_moment_2) ~ St + factor(Re) + factor(Fr),
##     data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -5.0075 -1.2112 -0.1009  1.1631  3.0215
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    3.2049    0.4690   6.833 1.29e-09 ***
## St              0.7167    0.2455   2.920  0.00451 **
## factor(Re)224  -4.6321    0.4350 -10.650 < 2e-16 ***
## factor(Re)398  -7.7930    0.5472 -14.242 < 2e-16 ***
## factor(Fr)0.3  -3.4422    0.5014  -6.865 1.12e-09 ***
## factor(Fr)Inf  -2.7650    0.4473  -6.182 2.27e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.806 on 83 degrees of freedom
## Multiple R-squared:  0.7768, Adjusted R-squared:  0.7633
## F-statistic: 57.76 on 5 and 83 DF,  p-value: < 2.2e-16
```

```
model3 <- lm(log(R_moment_3) ~ St + factor(Re) + factor(Fr), data=data_train)
summary(model3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ St + factor(Re) + factor(Fr),
##     data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -7.7282 -2.3839 -0.4306  2.1123  5.4634
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    9.6598    0.8341  11.581 < 2e-16 ***
## St              0.9452    0.4366   2.165  0.0332 *
## factor(Re)224  -5.8796    0.7735  -7.601 4.03e-11 ***
```



```
## factor(Re)398 -10.2176      0.9731 -10.500 < 2e-16 ***
## factor(Fr)0.3  -6.8055      0.8917  -7.632 3.50e-11 ***
## factor(Fr)Inf  -5.4848      0.7955  -6.895 9.77e-10 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 3.211 on 83 degrees of freedom
## Multiple R-squared:  0.6983, Adjusted R-squared:  0.6802
## F-statistic: 38.43 on 5 and 83 DF,  p-value: < 2.2e-16
```

```
model4 <- lm(log(R_moment_4) ~ St + factor(Re) + factor(Fr), data=data_train)
summary(model4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ St + factor(Re) + factor(Fr),
##     data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -10.1076  -3.5768  -0.7964   3.0052   7.8067
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    16.2281     1.1836  13.711 < 2e-16 ***
## St              1.1304     0.6195   1.825  0.0716 .
## factor(Re)224   -7.1866     1.0977  -6.547 4.58e-09 ***
## factor(Re)398  -12.7305     1.3808  -9.219 2.38e-14 ***
## factor(Fr)0.3  -10.1437     1.2654  -8.016 6.04e-12 ***
## factor(Fr)Inf   -8.1791     1.1288  -7.246 2.02e-10 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.557 on 83 degrees of freedom
## Multiple R-squared:  0.6716, Adjusted R-squared:  0.6518
## F-statistic: 33.95 on 5 and 83 DF,  p-value: < 2.2e-16
```

Exploring collinearity:

```
vif(model1)
```

```
##              GVIF Df GVIF^(1/(2*Df))
## St              1.004871  1          1.002433
## factor(Re) 1.107716  2          1.025905
## factor(Fr) 1.109374  2          1.026289
```

```
vif(model2)
```

```
##              GVIF Df GVIF^(1/(2*Df))
## St              1.004871  1          1.002433
## factor(Re) 1.107716  2          1.025905
## factor(Fr) 1.109374  2          1.026289
```

```
vif(model3)
```

```
##              GVIF Df GVIF^(1/(2*Df))
## St              1.004871  1          1.002433
## factor(Re) 1.107716  2          1.025905
## factor(Fr) 1.109374  2          1.026289
```

```
vif(model4)
```

```
##              GVIF Df GVIF^(1/(2*Df))
## St              1.004871  1          1.002433
## factor(Re) 1.107716  2          1.025905
## factor(Fr) 1.109374  2          1.026289
```

Including all interaction terms:

```
glm.full <- lm(cbind(log(R_moment_1), log(R_moment_2), log(R_moment_3), log(R_moment_4)) ~ (St + factor(Re) + factor(Fr))^2, data = data_train)
summary(glm.full)
```

```
## Response log(R_moment_1) :
##
## Call:
## lm(formula = 'log(R_moment_1)' ~ (St + factor(Re) + factor(Fr))^2,
##     data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.41510 -0.01331  0.01761  0.05940  0.13973
##
## Coefficients: (1 not defined because of singularities)
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    -2.186457   0.044127  -49.549   < 2e-16 ***
## St              0.152307   0.032368   4.705 1.11e-05 ***
## factor(Re)224   -3.854073   0.055437 -69.522   < 2e-16 ***
## factor(Re)398   -5.970943   0.066863 -89.301   < 2e-16 ***
## factor(Fr)0.3   -0.419887   0.065701  -6.391 1.20e-08 ***
## factor(Fr)Inf   -0.454654   0.059741  -7.610 6.11e-11 ***
## St:factor(Re)224  0.041342   0.035969   1.149 0.254002
## St:factor(Re)398 -0.005585   0.046504  -0.120 0.904722
## St:factor(Fr)0.3  0.165845   0.044159   3.756 0.000337 ***
## St:factor(Fr)Inf  0.146870   0.037025   3.967 0.000164 ***
## factor(Re)224:factor(Fr)0.3 0.252705   0.067863   3.724 0.000375 ***
## factor(Re)398:factor(Fr)0.3      NA         NA      NA      NA
## factor(Re)224:factor(Fr)Inf 0.392182   0.068754   5.704 2.13e-07 ***
## factor(Re)398:factor(Fr)Inf 0.494113   0.075178   6.573 5.54e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.116 on 76 degrees of freedom
## Multiple R-squared:  0.9977, Adjusted R-squared:  0.9973
## F-statistic: 2723 on 12 and 76 DF, p-value: < 2.2e-16
##
```

```
##
## Response log(R_moment_2) :
##
## Call:
## lm(formula = 'log(R_moment_2)' ~ (St + factor(Re) + factor(Fr))^2,
##     data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -5.8344 -0.0069  0.2296  0.5224  1.0188
##
## Coefficients: (1 not defined because of singularities)
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      5.164989    0.470307  10.982 < 2e-16 ***
## St              0.858695    0.344985   2.489  0.015 *
## factor(Re)224    -7.434512    0.590851 -12.583 < 2e-16 ***
## factor(Re)398   -10.787379    0.712633 -15.137 < 2e-16 ***
## factor(Fr)0.3    -6.678147    0.700244  -9.537 1.26e-14 ***
## factor(Fr)Inf    -6.737794    0.636727 -10.582 < 2e-16 ***
## St:factor(Re)224 -0.004091    0.383357  -0.011  0.992
## St:factor(Re)398 -0.593466    0.495640  -1.197  0.235
## St:factor(Fr)0.3  0.250783    0.470653   0.533  0.596
## St:factor(Fr)Inf  0.112392    0.394615   0.285  0.777
## factor(Re)224:factor(Fr)0.3  4.477795    0.723295   6.191 2.81e-08 ***
## factor(Re)398:factor(Fr)0.3      NA         NA      NA      NA
## factor(Re)224:factor(Fr)Inf  4.694433    0.732788   6.406 1.13e-08 ***
## factor(Re)398:factor(Fr)Inf  6.883436    0.801251   8.591 8.12e-13 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.237 on 76 degrees of freedom
## Multiple R-squared:  0.9041, Adjusted R-squared:  0.889
## F-statistic: 59.73 on 12 and 76 DF, p-value: < 2.2e-16
##
##
## Response log(R_moment_3) :
##
## Call:
## lm(formula = 'log(R_moment_3)' ~ (St + factor(Re) + factor(Fr))^2,
##     data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -10.2415  0.0321  0.3599  0.8096  1.7370
##
## Coefficients: (1 not defined because of singularities)
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)     13.27626    0.76479  17.359 < 2e-16 ***
## St              1.31188    0.56100   2.338  0.022 *
## factor(Re)224   -11.09434    0.96082 -11.547 < 2e-16 ***
## factor(Re)398   -16.02257    1.15885 -13.826 < 2e-16 ***
## factor(Fr)0.3   -12.80536    1.13871 -11.246 < 2e-16 ***
## factor(Fr)Inf   -12.80794    1.03542 -12.370 < 2e-16 ***
## St:factor(Re)224 -0.07617    0.62340  -0.122  0.903
```

```

## St:factor(Re)398          -1.01438    0.80599   -1.259    0.212
## St:factor(Fr)0.3          0.29860    0.76536    0.390    0.698
## St:factor(Fr)Inf          0.06435    0.64171    0.100    0.920
## factor(Re)224:factor(Fr)0.3  8.49426    1.17619    7.222 3.35e-10 ***
## factor(Re)398:factor(Fr)0.3      NA          NA          NA          NA
## factor(Re)224:factor(Fr)Inf  8.74071    1.19163    7.335 2.04e-10 ***
## factor(Re)398:factor(Fr)Inf 13.04934    1.30296   10.015 1.55e-15 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.011 on 76 degrees of freedom
## Multiple R-squared:  0.8917, Adjusted R-squared:  0.8746
## F-statistic: 52.14 on 12 and 76 DF,  p-value: < 2.2e-16
##
##
## Response log(R_moment_4) :
##
## Call:
## lm(formula = 'log(R_moment_4)' ~ (St + factor(Re) + factor(Fr))^2,
##     data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -14.2051   0.0767   0.4981   1.0761   2.3826
##
## Coefficients: (1 not defined because of singularities)
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    21.476884    1.024275   20.968 < 2e-16 ***
## St              1.714788    0.751338    2.282  0.0253 *
## factor(Re)224   -14.780292    1.286808  -11.486 < 2e-16 ***
## factor(Re)398   -21.349343    1.552033  -13.756 < 2e-16 ***
## factor(Fr)0.3   -18.836080    1.525053  -12.351 < 2e-16 ***
## factor(Fr)Inf   -18.790108    1.386720  -13.550 < 2e-16 ***
## St:factor(Re)224  -0.138437    0.834909   -0.166  0.8687
## St:factor(Re)398  -1.381788    1.079449   -1.280  0.2044
## St:factor(Fr)0.3   0.320628    1.025029    0.313  0.7553
## St:factor(Fr)Inf   0.006509    0.859426    0.008  0.9940
## factor(Re)224:factor(Fr)0.3 12.435539    1.575254    7.894 1.75e-11 ***
## factor(Re)398:factor(Fr)0.3      NA          NA          NA          NA
## factor(Re)224:factor(Fr)Inf 12.719148    1.595930    7.970 1.26e-11 ***
## factor(Re)398:factor(Fr)Inf 19.134575    1.745034   10.965 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.693 on 76 degrees of freedom
## Multiple R-squared:  0.895, Adjusted R-squared:  0.8784
## F-statistic: 53.96 on 12 and 76 DF,  p-value: < 2.2e-16

```

Re and Fr seem to have significant interaction for all moments, while St and Re only have significant interaction for the first moment.

A model with the interaction term for Re and Fr:

```
glm.interaction <- lm(cbind(log(R_moment_1), log(R_moment_2), log(R_moment_3), log(R_moment_4)) ~ (St +
summary(glm.interaction)
```

```
## Response log(R_moment_1) :
##
## Call:
## lm(formula = 'log(R_moment_1)' ~ (St + factor(Re) + factor(Fr) +
##     factor(Re) * factor(Fr)), data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.48592 -0.00915  0.03880  0.07277  0.17182
##
## Coefficients: (1 not defined because of singularities)
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    -2.27306    0.04110  -55.299 < 2e-16 ***
## St              0.24989    0.01803   13.863 < 2e-16 ***
## factor(Re)224   -3.81588    0.05160  -73.948 < 2e-16 ***
## factor(Re)398   -5.98854    0.05621 -106.548 < 2e-16 ***
## factor(Fr)0.3   -0.26297    0.05622   -4.678 1.16e-05 ***
## factor(Fr)Inf   -0.32944    0.05787   -5.693 1.99e-07 ***
## factor(Re)224:factor(Fr)0.3  0.22050    0.07574    2.911 0.00466 **
## factor(Re)398:factor(Fr)0.3      NA         NA         NA      NA
## factor(Re)224:factor(Fr)Inf  0.40185    0.07759    5.179 1.63e-06 ***
## factor(Re)398:factor(Fr)Inf  0.50151    0.08366    5.995 5.58e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1312 on 80 degrees of freedom
## Multiple R-squared:  0.9969, Adjusted R-squared:  0.9966
## F-statistic: 3193 on 8 and 80 DF, p-value: < 2.2e-16
##
##
## Response log(R_moment_2) :
##
## Call:
## lm(formula = 'log(R_moment_2)' ~ (St + factor(Re) + factor(Fr) +
##     factor(Re) * factor(Fr)), data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -5.8551 -0.0206  0.3104  0.5102  1.0043
##
## Coefficients: (1 not defined because of singularities)
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      5.1869    0.3843  13.498 < 2e-16 ***
## St              0.8340    0.1685   4.949 4.06e-06 ***
## factor(Re)224    -7.4387    0.4824 -15.420 < 2e-16 ***
## factor(Re)398   -11.3837    0.5254 -21.665 < 2e-16 ***
## factor(Fr)0.3    -6.4163    0.5256 -12.208 < 2e-16 ***
## factor(Fr)Inf    -6.6523    0.5410 -12.297 < 2e-16 ***
## factor(Re)224:factor(Fr)0.3  4.3872    0.7081    6.196 2.37e-08 ***
## factor(Re)398:factor(Fr)0.3      NA         NA         NA      NA
```

```

## factor(Re)224:factor(Fr)Inf    4.7181    0.7254    6.504 6.25e-09 ***
## factor(Re)398:factor(Fr)Inf    7.0758    0.7821    9.047 7.09e-14 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.226 on 80 degrees of freedom
## Multiple R-squared:  0.9008, Adjusted R-squared:  0.8909
## F-statistic: 90.79 on 8 and 80 DF,  p-value: < 2.2e-16
##
##
## Response log(R_moment_3) :
##
## Call:
## lm(formula = 'log(R_moment_3)' ~ (St + factor(Re) + factor(Fr) +
##   factor(Re) * factor(Fr)), data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -10.3570  -0.0586   0.4564   0.8018   1.6559
##
## Coefficients: (1 not defined because of singularities)
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      13.3986     0.6241  21.469 < 2e-16 ***
## St               1.1740     0.2737   4.290 4.97e-05 ***
## factor(Re)224    -11.1636     0.7835 -14.249 < 2e-16 ***
## factor(Re)398    -17.0302     0.8534 -19.957 < 2e-16 ***
## factor(Fr)0.3    -12.4781     0.8536 -14.618 < 2e-16 ***
## factor(Fr)Inf    -12.7719     0.8786 -14.536 < 2e-16 ***
## factor(Re)224:factor(Fr)0.3  8.3648     1.1500   7.274 2.10e-10 ***
## factor(Re)398:factor(Fr)0.3      NA         NA      NA      NA
## factor(Re)224:factor(Fr)Inf  8.7718     1.1781   7.446 9.76e-11 ***
## factor(Re)398:factor(Fr)Inf 13.3707     1.2702  10.527 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.991 on 80 degrees of freedom
## Multiple R-squared:  0.8882, Adjusted R-squared:  0.877
## F-statistic: 79.44 on 8 and 80 DF,  p-value: < 2.2e-16
##
##
## Response log(R_moment_4) :
##
## Call:
## lm(formula = 'log(R_moment_4)' ~ (St + factor(Re) + factor(Fr) +
##   factor(Re) * factor(Fr)), data = data_train)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -14.4109   0.0031   0.5741   1.0506   2.2382
##
## Coefficients: (1 not defined because of singularities)
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)     21.6950     0.8354  25.971 < 2e-16 ***
## St              1.4690     0.3663   4.010 0.000135 ***

```

```
## factor(Re)224          -14.9060      1.0487 -14.214 < 2e-16 ***
## factor(Re)398          -22.7148      1.1422 -19.886 < 2e-16 ***
## factor(Fr)0.3          -18.4708      1.1425 -16.166 < 2e-16 ***
## factor(Fr)Inf          -18.8106      1.1760 -15.995 < 2e-16 ***
## factor(Re)224:factor(Fr)0.3 12.2758      1.5393   7.975 9.06e-12 ***
## factor(Re)398:factor(Fr)0.3      NA          NA      NA      NA
## factor(Re)224:factor(Fr)Inf 12.7559      1.5769   8.089 5.40e-12 ***
## factor(Re)398:factor(Fr)Inf 19.5683      1.7001  11.510 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.666 on 80 degrees of freedom
## Multiple R-squared:  0.8917, Adjusted R-squared:  0.8809
## F-statistic: 82.34 on 8 and 80 DF,  p-value: < 2.2e-16
```

Adding the interaction term between Re and Fr improved the fit of the model according to the adjusted R^2 values.

Split data into training and test sets

```
attach(data_train)
set.seed(3)
train_ind <- sample(x = nrow(data_train), size = 0.8 * nrow(data_train))
test_ind_neg <- -train_ind
training <- data_train[train_ind, ]
testing <- data_train[test_ind_neg, ]
training
```

```
##      St  Re   Fr R_moment_1 R_moment_2 R_moment_3 R_moment_4
## 5  0.70 398   Inf 0.00036945 6.2242e-03 1.2649e-01 2.5714e+00
## 58 2.00  90 0.052 0.15433000 1.0269e+03 8.8700e+06 7.6700e+10
## 12 0.30 398   Inf 0.00036022 6.2830e-03 1.3546e-01 2.9211e+00
## 36 0.90 224 0.300 0.00280490 4.1143e-02 7.5132e-01 1.3729e+01
## 88 0.60 224   Inf 0.00291710 4.4317e-02 8.5282e-01 1.6431e+01
## 8  3.00 224   Inf 0.00574730 1.1966e-01 2.7480e+00 6.3159e+01
## 20 0.20  90 0.052 0.11760000 5.1774e+02 3.8100e+06 2.8000e+10
## 74 0.90  90 0.052 0.14184000 8.7019e+02 7.2500e+06 6.0400e+10
## 55 0.40 398 0.052 0.00029691 4.1375e-03 7.6124e-02 1.4014e+00
## 40 0.20 224 0.052 0.00257870 2.6830e-01 3.9080e+01 5.6959e+03
## 48 0.30 224 0.052 0.00256750 2.6547e-01 3.7665e+01 5.3451e+03
## 84 0.90 398 0.052 0.00034145 5.0555e-03 9.4083e-02 1.7522e+00
## 37 0.40 224   Inf 0.00292630 4.6261e-02 9.2914e-01 1.8681e+01
## 66 2.00 398 0.052 0.00039644 6.1040e-03 1.1209e-01 2.0593e+00
## 29 0.30  90 0.052 0.12261000 6.2727e+02 4.9100e+06 3.8500e+10
## 89 1.50 224   Inf 0.00370310 6.0910e-02 1.1829e+00 2.2990e+01
## 77 0.60  90 0.052 0.12946000 7.1816e+02 5.7200e+06 4.5600e+10
## 9  0.90 224   Inf 0.00302150 4.5244e-02 8.4530e-01 1.5809e+01
## 72 0.20 224 0.300 0.00246950 3.4818e-02 6.7088e-01 1.2939e+01
## 18 1.00  90 0.300 0.11236000 1.1261e+00 1.7335e+01 2.8261e+02
## 16 0.60 224 0.300 0.00257400 3.6621e-02 6.7102e-01 1.2309e+01
## 25 0.90 398   Inf 0.00038344 6.4432e-03 1.2925e-01 2.5935e+00
```

```

## 87 0.05 224 0.300 0.00135380 1.0303e-04 5.1400e-05 4.1600e-05
## 80 3.00 90 0.052 0.15538000 1.0443e+03 9.1400e+06 8.0000e+10
## 22 0.50 398 Inf 0.00036800 6.3559e-03 1.3341e-01 2.8013e+00
## 60 0.30 90 Inf 0.07694500 3.2652e-01 3.4052e+00 4.1042e+01
## 51 3.00 90 Inf 0.17234000 2.2386e+00 4.0454e+01 7.6198e+02
## 6 2.00 90 0.300 0.14780000 2.0068e+00 3.6249e+01 6.7167e+02
## 76 0.20 90 0.300 0.07798500 2.5598e-01 2.0965e+00 2.0849e+01
## 15 0.50 90 0.052 0.12670000 6.8596e+02 5.4300e+06 4.2900e+10
## 10 0.60 398 0.052 0.00031431 4.4672e-03 8.2060e-02 1.5077e+00
## 11 0.90 90 Inf 0.09102700 5.9539e-01 7.2454e+00 9.5166e+01
## 75 0.40 398 Inf 0.00036977 6.4986e-03 1.3933e-01 2.9880e+00
## 23 0.20 224 Inf 0.00269160 3.9016e-02 7.6384e-01 1.4978e+01
## 3 0.70 224 Inf 0.00290540 4.3499e-02 8.2200e-01 1.5551e+01
## 73 3.00 398 0.052 0.00040188 5.4492e-03 9.1871e-02 1.5565e+00
## 78 1.50 90 0.300 0.13678000 1.8254e+00 3.2833e+01 6.0903e+02
## 59 0.90 90 0.300 0.10962000 1.0319e+00 1.5797e+01 2.6136e+02
## 4 0.05 90 Inf 0.06352800 9.0653e-02 4.6746e-01 3.2696e+00
## 33 1.50 90 0.052 0.15181000 9.9690e+02 8.5500e+06 7.3300e+10
## 19 0.70 224 0.052 0.00285610 3.1273e-01 4.4529e+01 6.3423e+03
## 38 0.80 398 0.052 0.00033341 4.9036e-03 9.1143e-02 1.6948e+00
## 26 0.50 224 0.052 0.00274240 3.0355e-01 4.3911e+01 6.3530e+03
## 45 0.80 224 0.052 0.00295750 3.3361e-01 4.8161e+01 6.9539e+03
## 7 0.20 90 Inf 0.08127300 3.2450e-01 3.0363e+00 3.2976e+01
## 1 0.10 224 0.052 0.00215700 1.3035e-01 1.4374e+01 1.5865e+03
## 71 0.80 224 0.300 0.00268160 3.7714e-02 6.7549e-01 1.2112e+01
## 41 0.30 224 Inf 0.00283770 4.3589e-02 8.6962e-01 1.7373e+01
## 82 0.05 90 0.052 0.08786800 5.3449e-01 2.2205e+01 1.5679e+03
## 62 0.50 90 0.300 0.08477300 4.9728e-01 6.0317e+00 8.3287e+01
## 31 1.50 224 0.052 0.00341630 4.0300e-01 5.8417e+01 8.4710e+03
## 86 0.05 224 Inf 0.00153380 2.5653e-04 3.0407e-04 5.4466e-04
## 14 1.00 224 0.052 0.00312380 3.6478e-01 5.3322e+01 7.7958e+03
## 43 2.00 224 0.300 0.00381230 6.1927e-02 1.1844e+00 2.2705e+01
## 81 2.00 224 0.052 0.00363470 4.4512e-01 6.5387e+01 9.6105e+03
## 63 0.80 398 Inf 0.00037399 6.2457e-03 1.2542e-01 2.5193e+00
## 67 0.70 224 0.300 0.00260870 3.6438e-02 6.5445e-01 1.1765e+01
## 70 0.90 224 0.052 0.00305410 3.5419e-01 5.1795e+01 7.5758e+03
## 17 0.10 90 Inf 0.07722700 2.2120e-01 1.8833e+00 2.0190e+01
## 69 0.30 398 0.052 0.00030066 4.3488e-03 8.3446e-02 1.6023e+00
## 34 0.05 398 Inf 0.00022202 1.0055e-03 1.0857e-02 1.1782e-01
## 61 0.50 224 0.300 0.00250710 3.5152e-02 6.4378e-01 1.1801e+01
## 44 1.00 90 Inf 0.09691800 6.7696e-01 8.2384e+00 1.0602e+02
## 13 2.00 224 Inf 0.00447250 8.0804e-02 1.6668e+00 3.4408e+01
## 2 3.00 224 0.052 0.00379030 4.7042e-01 6.9940e+01 1.0404e+04
## 21 0.10 90 0.300 0.06125200 6.9867e-02 2.4338e-01 1.1379e+00
## 68 0.60 224 0.052 0.00279390 3.0594e-01 4.3745e+01 6.2554e+03
## 46 1.00 224 0.300 0.00289530 4.2300e-02 7.6755e-01 1.3941e+01
## 52 1.00 224 Inf 0.00309680 4.6454e-02 8.6381e-01 1.6077e+01
## 28 0.40 224 0.052 0.00268090 2.8897e-01 4.1585e+01 5.9861e+03
## 54 0.80 90 0.052 0.13793000 8.2524e+02 6.8000e+06 5.6100e+10

```

testing

```

##      St Re   Fr R_moment_1 R_moment_2 R_moment_3 R_moment_4
## 24 1.50 398 0.052 0.00038321 5.9338e-03 1.1156e-01 2.1004e+00

```



```
## 27 0.10 398 0.052 0.00027479 3.2549e-03 5.8006e-02 1.0344e+00
## 30 0.05 224 0.052 0.00173740 1.6633e-03 2.0228e-02 3.6438e-01
## 32 0.80 90 Inf 0.09107400 6.1825e-01 7.4973e+00 9.7048e+01
## 35 0.80 224 Inf 0.00298090 4.4580e-02 8.3764e-01 1.5759e+01
## 39 1.50 224 0.300 0.00341050 5.4101e-02 1.0222e+00 1.9340e+01
## 42 0.30 224 0.300 0.00250630 3.5881e-02 6.8596e-01 1.3132e+01
## 47 0.70 90 0.300 0.09471100 6.9751e-01 9.1793e+00 1.3187e+02
## 49 0.40 224 0.300 0.00262070 3.9502e-02 7.6851e-01 1.4966e+01
## 50 0.10 224 0.300 0.00221530 2.4475e-02 4.2167e-01 7.2842e+00
## 53 2.00 398 Inf 0.00053647 1.0022e-02 2.1023e-01 4.4109e+00
## 56 0.50 398 0.052 0.00030716 4.3494e-03 8.0143e-02 1.4770e+00
## 57 0.70 90 Inf 0.09217600 5.6482e-01 6.7191e+00 8.8723e+01
## 64 0.20 398 Inf 0.00033521 5.4505e-03 1.1408e-01 2.3884e+00
## 65 0.70 90 0.052 0.13173000 7.3694e+02 5.8700e+06 4.6700e+10
## 79 0.10 90 0.052 0.10464000 1.6015e+02 6.9900e+05 3.0700e+09
## 83 0.40 90 0.300 0.08095700 3.9996e-01 4.3303e+00 5.3618e+01
## 85 3.00 90 0.300 0.16433000 2.3317e+00 4.4516e+01 8.8779e+02
```

Linear model using least squares & no interaction term

```
fit.lm1 <- lm(log(R_moment_1) ~ (St + factor(Re) + factor(Fr)), data = training)
pred.lm1 <- predict(fit.lm1, testing)
mse_test1 <- mean((pred.lm1 - log(testing$R_moment_1))^2)
fit.lm2 <- lm(log(R_moment_2) ~ (St + factor(Re) + factor(Fr)), data = training)
pred.lm2 <- predict(fit.lm2, testing)
mse_test2 <- mean((pred.lm2 - log(testing$R_moment_2))^2)
fit.lm3 <- lm(log(R_moment_3) ~ (St + factor(Re) + factor(Fr)), data = training)
pred.lm3 <- predict(fit.lm3, testing)
mse_test3 <- mean((pred.lm3 - log(testing$R_moment_3))^2)
fit.lm4 <- lm(log(R_moment_4) ~ (St + factor(Re) + factor(Fr)), data = training)
pred.lm4 <- predict(fit.lm4, testing)
mse_test4 <- mean((pred.lm4 - log(testing$R_moment_4))^2)
mse_test1
```

```
## [1] 0.01787931
```

```
mse_test2
```

```
## [1] 3.4922
```

```
mse_test3
```

```
## [1] 10.6892
```

```
mse_test4
```

```
## [1] 21.32186
```

Linear model using least squares & interaction term

```
fit.lm1 <- lm(log(R_moment_1) ~ (St + factor(Re) + factor(Fr) + factor(Re)*factor(Fr)), data = training)
pred.lm1 <- predict(fit.lm1, testing)
```

```
## Warning in predict.lm(fit.lm1, testing): prediction from a rank-deficient fit
## may be misleading
```

```
mse_test1 <- mean((pred.lm1 - log(testing$R_moment_1))^2)
fit.lm2 <- lm(log(R_moment_2) ~ (St + factor(Re) + factor(Fr) + factor(Re)*factor(Fr)), data = training)
pred.lm2 <- predict(fit.lm2, testing)
```

```
## Warning in predict.lm(fit.lm2, testing): prediction from a rank-deficient fit
## may be misleading
```

```
mse_test2 <- mean((pred.lm2 - log(testing$R_moment_2))^2)
fit.lm3 <- lm(log(R_moment_3) ~ (St + factor(Re) + factor(Fr) + factor(Re)*factor(Fr)), data = training)
pred.lm3 <- predict(fit.lm3, testing)
```

```
## Warning in predict.lm(fit.lm3, testing): prediction from a rank-deficient fit
## may be misleading
```

```
mse_test3 <- mean((pred.lm3 - log(testing$R_moment_3))^2)
fit.lm4 <- lm(log(R_moment_4) ~ (St + factor(Re) + factor(Fr) + factor(Re)*factor(Fr)), data = training)
pred.lm4 <- predict(fit.lm4, testing)
```

```
## Warning in predict.lm(fit.lm4, testing): prediction from a rank-deficient fit
## may be misleading
```

```
mse_test4 <- mean((pred.lm4 - log(testing$R_moment_4))^2)
mse_test1
```

```
## [1] 0.008822464
```

```
mse_test2
```

```
## [1] 1.396723
```

```
mse_test3
```

```
## [1] 3.184988
```

```
mse_test4
```

```
## [1] 5.272393
```

Having an interaction term significantly improved the test MSEs of the linear model.

Polynomial Regression

For each of the four moments, we try to fit a polynomial model based on the degree of the numerical variable, St. We also include the other two factored variables in each model.

First moment:

```
polym1 <- lm(log(R_moment_1) ~ poly(St, 2) + factor(Re) + factor(Fr), data = training)
summary(polym1)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ poly(St, 2) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.33265 -0.06610  0.00707  0.07555  0.34096
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  -2.16637    0.03629  -59.702 < 2e-16 ***
## poly(St, 2)1   1.58953    0.14605   10.884 3.38e-16 ***
## poly(St, 2)2  -0.68385    0.14764   -4.632 1.83e-05 ***
## factor(Re)224 -3.64684    0.03907  -93.344 < 2e-16 ***
## factor(Re)398 -5.79385    0.05059 -114.522 < 2e-16 ***
## factor(Fr)0.3 -0.15091    0.04656   -3.241 0.00189 **
## factor(Fr)Inf -0.02023    0.03967   -0.510 0.61171
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1448 on 64 degrees of freedom
## Multiple R-squared:  0.996, Adjusted R-squared:  0.9957
## F-statistic: 2677 on 6 and 64 DF, p-value: < 2.2e-16
```

```
poly2m1 <- lm(log(R_moment_1) ~ poly(St, 3) + factor(Re) + factor(Fr), data = training)
summary(poly2m1)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ poly(St, 3) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.31477 -0.07409 -0.00261  0.09929  0.30537
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  -2.16241    0.03558  -60.781 < 2e-16 ***
## poly(St, 3)1   1.58984    0.14296   11.121 < 2e-16 ***
## poly(St, 3)2  -0.68415    0.14452   -4.734 1.29e-05 ***
## poly(St, 3)3   0.28014    0.14378    1.948 0.05583 .
##
```

```
## factor(Re)224 -3.65344    0.03839   -95.161   < 2e-16 ***
## factor(Re)398 -5.80718    0.04999  -116.163   < 2e-16 ***
## factor(Fr)0.3 -0.14556    0.04565    -3.188   0.00223 **
## factor(Fr)Inf -0.01874    0.03883    -0.482   0.63117
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1418 on 63 degrees of freedom
## Multiple R-squared:  0.9963, Adjusted R-squared:  0.9958
## F-statistic: 2395 on 7 and 63 DF,  p-value: < 2.2e-16
```

```
poly3m1 <- lm(log(R_moment_1) ~ poly(St, 4) + factor(Re) + factor(Fr), data = training)
summary(poly3m1)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ poly(St, 4) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.29739 -0.06934 -0.01242  0.08023  0.31329
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  -2.157680   0.032765  -65.852 < 2e-16 ***
## poly(St, 4)1   1.594005   0.131556   12.117 < 2e-16 ***
## poly(St, 4)2  -0.693114   0.133013   -5.211 2.28e-06 ***
## poly(St, 4)3   0.294630   0.132369    2.226 0.029671 *
## poly(St, 4)4  -0.470535   0.133620   -3.521 0.000811 ***
## factor(Re)224 -3.667027   0.035538 -103.185 < 2e-16 ***
## factor(Re)398 -5.836580   0.046754 -124.837 < 2e-16 ***
## factor(Fr)0.3 -0.137911   0.042067   -3.278 0.001714 **
## factor(Fr)Inf -0.002662   0.036025   -0.074 0.941342
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1304 on 62 degrees of freedom
## Multiple R-squared:  0.9969, Adjusted R-squared:  0.9965
## F-statistic: 2476 on 8 and 62 DF,  p-value: < 2.2e-16
```

```
poly4m1 <- lm(log(R_moment_1) ~ poly(St, 5) + factor(Re) + factor(Fr), data = training)
summary(poly4m1)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ poly(St, 5) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.315418 -0.067990 -0.005822  0.075227  0.307888
##
```

```
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) -2.1666151  0.0312280 -69.380 < 2e-16 ***
## poly(St, 5)1  1.5983470  0.1247464  12.813 < 2e-16 ***
## poly(St, 5)2 -0.6871726  0.1261360  -5.448 9.67e-07 ***
## poly(St, 5)3  0.2913410  0.1255131   2.321 0.023634 *
## poly(St, 5)4 -0.4660782  0.1267042  -3.678 0.000498 ***
## poly(St, 5)5  0.3524325  0.1248844   2.822 0.006433 **
## factor(Re)224 -3.6617252  0.0337487 -108.500 < 2e-16 ***
## factor(Re)398 -5.8223510  0.0446161 -130.499 < 2e-16 ***
## factor(Fr)0.3 -0.1266630  0.0400856  -3.160 0.002457 **
## factor(Fr)Inf  0.0005497  0.0341770   0.016 0.987219
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1237 on 61 degrees of freedom
## Multiple R-squared:  0.9972, Adjusted R-squared:  0.9968
## F-statistic: 2449 on 9 and 61 DF, p-value: < 2.2e-16

poly5m1 <- lm(log(R_moment_1) ~ poly(St, 6) + factor(Re) + factor(Fr), data = training)
summary(poly5m1)

##
## Call:
## lm(formula = log(R_moment_1) ~ poly(St, 6) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.32045 -0.06636 -0.00751  0.07647  0.30827
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) -2.1675450  0.0314175 -68.992 < 2e-16 ***
## poly(St, 6)1  1.5979933  0.1253666  12.747 < 2e-16 ***
## poly(St, 6)2 -0.6862440  0.1267703  -5.413 1.14e-06 ***
## poly(St, 6)3  0.2895551  0.1261676   2.295 0.02525 *
## poly(St, 6)4 -0.4636290  0.1273919  -3.639 0.00057 ***
## poly(St, 6)5  0.3531189  0.1255088   2.814 0.00662 **
## poly(St, 6)6 -0.0793434  0.1255883  -0.632 0.52993
## factor(Re)224 -3.6596637  0.0340727 -107.407 < 2e-16 ***
## factor(Re)398 -5.8189474  0.0451600 -128.852 < 2e-16 ***
## factor(Fr)0.3 -0.1276059  0.0403121  -3.165 0.00243 **
## factor(Fr)Inf -0.0008333  0.0344162  -0.024 0.98076
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1243 on 60 degrees of freedom
## Multiple R-squared:  0.9973, Adjusted R-squared:  0.9968
## F-statistic: 2183 on 10 and 60 DF, p-value: < 2.2e-16

poly6m1 <- lm(log(R_moment_1) ~ poly(St, 7) + factor(Re) + factor(Fr), data = training)
summary(poly6m1)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ poly(St, 7) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.314045 -0.057152 -0.008371  0.071402  0.306723
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  -2.169020   0.031474  -68.915 < 2e-16 ***
## poly(St, 7)1   1.599136   0.125448   12.747 < 2e-16 ***
## poly(St, 7)2  -0.687297   0.126852   -5.418 1.17e-06 ***
## poly(St, 7)3   0.288807   0.126246    2.288 0.025759 *
## poly(St, 7)4  -0.463958   0.127469   -3.640 0.000576 ***
## poly(St, 7)5   0.353746   0.125586    2.817 0.006588 **
## poly(St, 7)6  -0.079363   0.125664   -0.632 0.530121
## poly(St, 7)7   0.120345   0.124960    0.963 0.339446
## factor(Re)224 -3.659404   0.034094 -107.332 < 2e-16 ***
## factor(Re)398 -5.817566   0.045210 -128.679 < 2e-16 ***
## factor(Fr)0.3 -0.127109   0.040340   -3.151 0.002556 **
## factor(Fr)Inf  0.001922   0.034556    0.056 0.955824
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1244 on 59 degrees of freedom
## Multiple R-squared:  0.9973, Adjusted R-squared:  0.9968
## F-statistic: 1982 on 11 and 59 DF, p-value: < 2.2e-16

poly7m1 <- lm(log(R_moment_1) ~ poly(St, 8) + factor(Re) + factor(Fr), data = training)
summary(poly7m1)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ poly(St, 8) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.32396 -0.06248 -0.00834  0.07358  0.30616
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  -2.168615   0.031700  -68.411 < 2e-16 ***
## poly(St, 8)1   1.599062   0.126300   12.661 < 2e-16 ***
## poly(St, 8)2  -0.686162   0.127737   -5.372 1.44e-06 ***
## poly(St, 8)3   0.291206   0.127213    2.289 0.025731 *
## poly(St, 8)4  -0.466124   0.128423   -3.630 0.000601 ***
## poly(St, 8)5   0.353233   0.126444    2.794 0.007052 **
## poly(St, 8)6  -0.077942   0.126556   -0.616 0.540390
## poly(St, 8)7   0.119490   0.125823    0.950 0.346220
## poly(St, 8)8   0.059253   0.130219    0.455 0.650787
## factor(Re)224 -3.659571   0.034328 -106.607 < 2e-16 ***
```

```
## factor(Re)398 -5.821425 0.046300 -125.733 < 2e-16 ***
## factor(Fr)0.3 -0.124911 0.040900 -3.054 0.003406 **
## factor(Fr)Inf 0.001746 0.034792 0.050 0.960145
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1252 on 58 degrees of freedom
## Multiple R-squared: 0.9973, Adjusted R-squared: 0.9968
## F-statistic: 1793 on 12 and 58 DF, p-value: < 2.2e-16
```

```
anova(fit.lm1, polym1, poly2m1, poly3m1, poly4m1, poly5m1, poly6m1, poly7m1)
```

```
## Analysis of Variance Table
##
## Model 1: log(R_moment_1) ~ (St + factor(Re) + factor(Fr) + factor(Re) *
##      factor(Fr))
## Model 2: log(R_moment_1) ~ poly(St, 2) + factor(Re) + factor(Fr)
## Model 3: log(R_moment_1) ~ poly(St, 3) + factor(Re) + factor(Fr)
## Model 4: log(R_moment_1) ~ poly(St, 4) + factor(Re) + factor(Fr)
## Model 5: log(R_moment_1) ~ poly(St, 5) + factor(Re) + factor(Fr)
## Model 6: log(R_moment_1) ~ poly(St, 6) + factor(Re) + factor(Fr)
## Model 7: log(R_moment_1) ~ poly(St, 7) + factor(Re) + factor(Fr)
## Model 8: log(R_moment_1) ~ poly(St, 8) + factor(Re) + factor(Fr)
##   Res.Df    RSS Df Sum of Sq    F    Pr(>F)
## 1      62 1.24014
## 2      64 1.34226 -2 -0.102123 3.2567 0.0456642 *
## 3      63 1.26598 1 0.076284 4.8654 0.0313772 *
## 4      62 1.05498 1 0.211003 13.4576 0.0005319 ***
## 5      61 0.93315 1 0.121830 7.7702 0.0071691 **
## 6      60 0.92698 1 0.006167 0.3933 0.5330320
## 7      59 0.91263 1 0.014347 0.9150 0.3427539
## 8      58 0.90939 1 0.003246 0.2071 0.6507871
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
pred.polym1 <- predict(polym1, testing)
pred.poly2m1 <- predict(poly2m1, testing)
pred.poly3m1 <- predict(poly3m1, testing)
pred.poly4m1 <- predict(poly4m1, testing)
pred.poly5m1 <- predict(poly5m1, testing)
pred.poly6m1 <- predict(poly6m1, testing)
pred.poly7m1 <- predict(poly7m1, testing)
mse_polym1 <- mean((pred.polym1 - log(testing$R_moment_1))^2)
mse_poly2m1 <- mean((pred.poly2m1 - log(testing$R_moment_1))^2)
mse_poly3m1 <- mean((pred.poly3m1 - log(testing$R_moment_1))^2)
mse_poly4m1 <- mean((pred.poly4m1 - log(testing$R_moment_1))^2)
mse_poly5m1 <- mean((pred.poly5m1 - log(testing$R_moment_1))^2)
mse_poly6m1 <- mean((pred.poly6m1 - log(testing$R_moment_1))^2)
mse_poly7m1 <- mean((pred.poly7m1 - log(testing$R_moment_1))^2)
mse_polym1
```

```
## [1] 0.02244211
```

```
mse_poly2m1
```

```
## [1] 0.0250986
```

```
mse_poly3m1
```

```
## [1] 0.027301
```

```
mse_poly4m1
```

```
## [1] 0.02443886
```

```
mse_poly5m1
```

```
## [1] 0.02302476
```

```
mse_poly6m1
```

```
## [1] 0.02203137
```

```
mse_poly7m1
```

```
## [1] 0.02338871
```

Similar to least squares.

Second moment:

```
polym2 <- lm(log(R_moment_2) ~ poly(St, 2) + factor(Re) + factor(Fr), data = training)
summary(polym2)
```

```
##
```

```
## Call:
```

```
## lm(formula = log(R_moment_2) ~ poly(St, 2) + factor(Re) + factor(Fr),
```

```
##     data = training)
```

```
##
```

```
## Residuals:
```

```
##      Min       1Q   Median       3Q      Max
```

```
## -3.2423 -1.0935 -0.1559  1.2966  3.1722
```

```
##
```

```
## Coefficients:
```

```
##              Estimate Std. Error t value Pr(>|t|)
```

```
## (Intercept)      4.1076      0.4209   9.758 2.74e-14 ***
```

```
## poly(St, 2)1      4.6783      1.6942   2.761 0.00750 **
```

```
## poly(St, 2)2     -5.4282      1.7128  -3.169 0.00234 **
```

```
## factor(Re)224    -4.8151      0.4532 -10.624 9.20e-16 ***
```

```
## factor(Re)398    -7.9846      0.5869 -13.605 < 2e-16 ***
```

```
## factor(Fr)0.3    -3.9073      0.5401  -7.235 7.20e-10 ***
```

```
## factor(Fr)Inf    -2.8244      0.4601  -6.138 5.87e-08 ***
```



```
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.68 on 64 degrees of freedom
## Multiple R-squared:  0.8171, Adjusted R-squared:  0.8
## F-statistic: 47.65 on 6 and 64 DF,  p-value: < 2.2e-16

poly2m2 <- lm(log(R_moment_2) ~ poly(St, 3) + factor(Re) + factor(Fr), data = training)
summary(poly2m2)
```

```
##
## Call:
## lm(formula = log(R_moment_2) ~ poly(St, 3) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
```

	Min	1Q	Median	3Q	Max
	-2.7756	-1.1822	-0.1902	1.1267	3.3059

```
##
## Coefficients:
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	4.1625	0.4073	10.219	5.34e-15 ***
poly(St, 3)1	4.6826	1.6368	2.861	0.00573 **
poly(St, 3)2	-5.4325	1.6547	-3.283	0.00168 **
poly(St, 3)3	3.8863	1.6462	2.361	0.02134 *
factor(Re)224	-4.9066	0.4396	-11.163	< 2e-16 ***
factor(Re)398	-8.1695	0.5724	-14.273	< 2e-16 ***
factor(Fr)0.3	-3.8331	0.5227	-7.333	5.24e-10 ***
factor(Fr)Inf	-2.8036	0.4446	-6.306	3.19e-08 ***

```
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.623 on 63 degrees of freedom
## Multiple R-squared:  0.832, Adjusted R-squared:  0.8133
## F-statistic: 44.56 on 7 and 63 DF,  p-value: < 2.2e-16
```

```
poly3m2 <- lm(log(R_moment_2) ~ poly(St, 4) + factor(Re) + factor(Fr), data = training)
summary(poly3m2)
```

```
##
## Call:
## lm(formula = log(R_moment_2) ~ poly(St, 4) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
```

	Min	1Q	Median	3Q	Max
	-2.5999	-1.0636	-0.1464	1.0962	3.0934

```
##
## Coefficients:
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	4.2103	0.3833	10.984	3.51e-16 ***
poly(St, 4)1	4.7247	1.5391	3.070	0.003176 **
poly(St, 4)2	-5.5230	1.5561	-3.549	0.000743 ***

```
## poly(St, 4)3      4.0328      1.5486      2.604 0.011510 *
## poly(St, 4)4     -4.7570      1.5632     -3.043 0.003432 **
## factor(Re)224    -5.0440      0.4158    -12.132 < 2e-16 ***
## factor(Re)398    -8.4668      0.5470    -15.480 < 2e-16 ***
## factor(Fr)0.3    -3.7558      0.4921     -7.632 1.73e-10 ***
## factor(Fr)Inf    -2.6411      0.4215     -6.267 3.92e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.526 on 62 degrees of freedom
## Multiple R-squared:  0.8538, Adjusted R-squared:  0.8349
## F-statistic: 45.26 on 8 and 62 DF,  p-value: < 2.2e-16
```

```
poly4m2 <- lm(log(R_moment_2) ~ poly(St, 5) + factor(Re) + factor(Fr), data = training)
summary(poly4m2)
```

```
##
## Call:
## lm(formula = log(R_moment_2) ~ poly(St, 5) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.8136 -1.0494 -0.3377  1.1077  3.4162
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      4.1380      0.3775  10.960 4.76e-16 ***
## poly(St, 5)1      4.7599      1.5082   3.156 0.00248 **
## poly(St, 5)2     -5.4749      1.5250  -3.590 0.00066 ***
## poly(St, 5)3      4.0062      1.5174   2.640 0.01051 *
## poly(St, 5)4     -4.7209      1.5318  -3.082 0.00309 **
## poly(St, 5)5      2.8550      1.5098   1.891 0.06339 .
## factor(Re)224    -5.0010      0.4080  -12.257 < 2e-16 ***
## factor(Re)398    -8.3515      0.5394  -15.483 < 2e-16 ***
## factor(Fr)0.3    -3.6647      0.4846   -7.562 2.50e-10 ***
## factor(Fr)Inf    -2.6151      0.4132   -6.329 3.25e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.495 on 61 degrees of freedom
## Multiple R-squared:  0.8619, Adjusted R-squared:  0.8415
## F-statistic: 42.3 on 9 and 61 DF,  p-value: < 2.2e-16
```

```
poly5m2 <- lm(log(R_moment_2) ~ poly(St, 6) + factor(Re) + factor(Fr), data = training)
summary(poly5m2)
```

```
##
## Call:
## lm(formula = log(R_moment_2) ~ poly(St, 6) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
```

```
##      Min      1Q  Median      3Q      Max
## -2.8324 -1.0196 -0.2869  1.0730  3.4527
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      4.1345     0.3810  10.852 8.82e-16 ***
## poly(St, 6)1      4.7586     1.5202   3.130 0.002698 **
## poly(St, 6)2     -5.4714     1.5372  -3.559 0.000734 ***
## poly(St, 6)3      3.9995     1.5299   2.614 0.011292 *
## poly(St, 6)4     -4.7117     1.5448  -3.050 0.003403 **
## poly(St, 6)5      2.8575     1.5219   1.878 0.065305 .
## poly(St, 6)6     -0.2969     1.5229  -0.195 0.846073
## factor(Re)224    -4.9933     0.4132 -12.085 < 2e-16 ***
## factor(Re)398    -8.3388     0.5476 -15.227 < 2e-16 ***
## factor(Fr)0.3    -3.6682     0.4888  -7.504 3.45e-10 ***
## factor(Fr)Inf    -2.6202     0.4173  -6.279 4.19e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.507 on 60 degrees of freedom
## Multiple R-squared:  0.862, Adjusted R-squared:  0.839
## F-statistic: 37.47 on 10 and 60 DF, p-value: < 2.2e-16
```

```
poly6m2 <- lm(log(R_moment_2) ~ poly(St, 7) + factor(Re) + factor(Fr), data = training)
summary(poly6m2)
```

```
##
## Call:
## lm(formula = log(R_moment_2) ~ poly(St, 7) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min      1Q  Median      3Q      Max
## -2.7372 -0.9985 -0.2034  0.9639  3.6305
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      4.1126     0.3801  10.818 1.24e-15 ***
## poly(St, 7)1      4.7756     1.5152   3.152 0.002550 **
## poly(St, 7)2     -5.4871     1.5321  -3.581 0.000692 ***
## poly(St, 7)3      3.9884     1.5248   2.616 0.011291 *
## poly(St, 7)4     -4.7166     1.5396  -3.064 0.003294 **
## poly(St, 7)5      2.8668     1.5169   1.890 0.063675 .
## poly(St, 7)6     -0.2972     1.5178  -0.196 0.845423
## poly(St, 7)7      1.7885     1.5093   1.185 0.240782
## factor(Re)224    -4.9895     0.4118 -12.116 < 2e-16 ***
## factor(Re)398    -8.3182     0.5461 -15.233 < 2e-16 ***
## factor(Fr)0.3    -3.6608     0.4872  -7.514 3.65e-10 ***
## factor(Fr)Inf    -2.5793     0.4174  -6.180 6.49e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.502 on 59 degrees of freedom
## Multiple R-squared:  0.8652, Adjusted R-squared:  0.8401
```

```
## F-statistic: 34.42 on 11 and 59 DF, p-value: < 2.2e-16

poly7m2 <- lm(log(R_moment_2) ~ poly(St, 8) + factor(Re) + factor(Fr), data = training)
summary(poly7m2)
```

```
##
## Call:
## lm(formula = log(R_moment_2) ~ poly(St, 8) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.7747 -0.9913 -0.2090  0.9555  3.6222
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    4.1141     0.3835  10.728 2.15e-15 ***
## poly(St, 8)1    4.7753     1.5279   3.125 0.002773 **
## poly(St, 8)2   -5.4828     1.5453  -3.548 0.000777 ***
## poly(St, 8)3    3.9974     1.5390   2.597 0.011883 *
## poly(St, 8)4   -4.7248     1.5536  -3.041 0.003534 **
## poly(St, 8)5    2.8649     1.5297   1.873 0.066127 .
## poly(St, 8)6   -0.2918     1.5310  -0.191 0.849490
## poly(St, 8)7    1.7852     1.5222   1.173 0.245658
## poly(St, 8)8    0.2241     1.5753   0.142 0.887361
## factor(Re)224  -4.9901     0.4153 -12.016 < 2e-16 ***
## factor(Re)398  -8.3328     0.5601 -14.877 < 2e-16 ***
## factor(Fr)0.3  -3.6525     0.4948  -7.382 6.69e-10 ***
## factor(Fr)Inf  -2.5800     0.4209  -6.130 8.33e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.515 on 58 degrees of freedom
## Multiple R-squared:  0.8652, Adjusted R-squared:  0.8374
## F-statistic: 31.03 on 12 and 58 DF, p-value: < 2.2e-16
```

```
anova(fit.lm2, polym2, poly2m2, poly3m2, poly4m2, poly5m2, poly6m2, poly7m2)
```

```
## Analysis of Variance Table
##
## Model 1: log(R_moment_2) ~ (St + factor(Re) + factor(Fr) + factor(Re) *
##     factor(Fr))
## Model 2: log(R_moment_2) ~ poly(St, 2) + factor(Re) + factor(Fr)
## Model 3: log(R_moment_2) ~ poly(St, 3) + factor(Re) + factor(Fr)
## Model 4: log(R_moment_2) ~ poly(St, 4) + factor(Re) + factor(Fr)
## Model 5: log(R_moment_2) ~ poly(St, 5) + factor(Re) + factor(Fr)
## Model 6: log(R_moment_2) ~ poly(St, 6) + factor(Re) + factor(Fr)
## Model 7: log(R_moment_2) ~ poly(St, 7) + factor(Re) + factor(Fr)
## Model 8: log(R_moment_2) ~ poly(St, 8) + factor(Re) + factor(Fr)
##   Res.Df    RSS Df Sum of Sq    F    Pr(>F)
## 1      62  97.46
## 2      64 180.63 -2   -83.174 18.1234 7.686e-07 ***
## 3      63 165.95  1    14.681  6.3980 0.014165 *
```

```
## 4      62 144.39  1      21.566  9.3984  0.003295 **
## 5      61 136.39  1       7.995  3.4840  0.067022 .
## 6      60 136.31  1       0.086  0.0376  0.846856
## 7      59 133.14  1       3.169  1.3808  0.244762
## 8      58 133.09  1       0.046  0.0202  0.887361
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
pred.polym2 <- predict(polym2, testing)
pred.poly2m2 <- predict(poly2m2, testing)
pred.poly3m2 <- predict(poly3m2, testing)
pred.poly4m2 <- predict(poly4m2, testing)
pred.poly5m2 <- predict(poly5m2, testing)
pred.poly6m2 <- predict(poly6m2, testing)
pred.poly7m2 <- predict(poly7m2, testing)
mse_polym2 <- mean((pred.polym2 - log(testing$R_moment_2))^2)
mse_poly2m2 <- mean((pred.poly2m2 - log(testing$R_moment_2))^2)
mse_poly3m2 <- mean((pred.poly3m2 - log(testing$R_moment_2))^2)
mse_poly4m2 <- mean((pred.poly4m2 - log(testing$R_moment_2))^2)
mse_poly5m2 <- mean((pred.poly5m2 - log(testing$R_moment_2))^2)
mse_poly6m2 <- mean((pred.poly6m2 - log(testing$R_moment_2))^2)
mse_poly7m2 <- mean((pred.poly7m2 - log(testing$R_moment_2))^2)
mse_test2
```

```
## [1] 1.396723
```

```
mse_polym2
```

```
## [1] 3.698693
```

```
mse_poly2m2
```

```
## [1] 3.954142
```

```
mse_poly3m2
```

```
## [1] 3.92246
```

```
mse_poly4m2
```

```
## [1] 3.614817
```

```
mse_poly5m2
```

```
## [1] 3.542806
```

```
mse_poly6m2
```

```
## [1] 3.324489
```

```
mse_poly7m2
```

```
## [1] 3.373734
```

Same as linear regression? Polynomial model with degree 7 has lowest MSE, but degree 5 or LSR may be better based on ANOVA.

Third moment:

```
polym3 <- lm(log(R_moment_3) ~ poly(St, 2) + factor(Re) + factor(Fr), data = training)
summary(polym3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ poly(St, 2) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -5.5859 -2.1191 -0.3035  2.2601  5.7511
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   10.9306     0.7634  14.318 < 2e-16 ***
## poly(St, 2)1    6.3124     3.0727   2.054  0.04403 *
## poly(St, 2)2   -8.6934     3.1063  -2.799  0.00677 **
## factor(Re)224  -6.2233     0.8220  -7.571  1.84e-10 ***
## factor(Re)398 -10.5048     1.0644  -9.869  1.77e-14 ***
## factor(Fr)0.3  -7.5429     0.9795  -7.701  1.09e-10 ***
## factor(Fr)Inf  -5.5606     0.8345  -6.663  7.23e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 3.047 on 64 degrees of freedom
## Multiple R-squared:  0.7481, Adjusted R-squared:  0.7245
## F-statistic: 31.68 on 6 and 64 DF,  p-value: < 2.2e-16
```

```
poly2m3 <- lm(log(R_moment_3) ~ poly(St, 3) + factor(Re) + factor(Fr), data = training)
summary(poly2m3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ poly(St, 3) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.9637 -2.2255 -0.3323  2.0431  5.9714
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   11.0211     0.7444  14.805 < 2e-16 ***
```

```
## poly(St, 3)1      6.3195      2.9913      2.113      0.03861 *
## poly(St, 3)2     -8.7005      3.0240     -2.877      0.00547 **
## poly(St, 3)3      6.4023      3.0085      2.128      0.03725 *
## factor(Re)224    -6.3740      0.8033     -7.934 4.65e-11 ***
## factor(Re)398   -10.8095      1.0461   -10.334 3.43e-15 ***
## factor(Fr)0.3    -7.4206      0.9553     -7.768 9.09e-11 ***
## factor(Fr)Inf    -5.5263      0.8126     -6.801 4.44e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.966 on 63 degrees of freedom
## Multiple R-squared:  0.765, Adjusted R-squared:  0.7389
## F-statistic: 29.29 on 7 and 63 DF,  p-value: < 2.2e-16

poly3m3 <- lm(log(R_moment_3) ~ poly(St, 4) + factor(Re) + factor(Fr), data = training)
summary(poly3m3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ poly(St, 4) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.673 -1.985 -0.297   2.055   5.774
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    11.1002     0.7099  15.636 < 2e-16 ***
## poly(St, 4)1     6.3891     2.8503   2.242  0.02858 *
## poly(St, 4)2    -8.8504     2.8819  -3.071  0.00317 **
## poly(St, 4)3     6.6448     2.8679   2.317  0.02382 *
## poly(St, 4)4    -7.8726     2.8950  -2.719  0.00847 **
## factor(Re)224    -6.6014     0.7700  -8.573 4.03e-12 ***
## factor(Re)398   -11.3013     1.0130 -11.157 < 2e-16 ***
## factor(Fr)0.3    -7.2927     0.9114  -8.001 3.94e-11 ***
## factor(Fr)Inf    -5.2574     0.7805  -6.736 6.15e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.826 on 62 degrees of freedom
## Multiple R-squared:  0.79, Adjusted R-squared:  0.7629
## F-statistic: 29.16 on 8 and 62 DF,  p-value: < 2.2e-16
```

```
poly4m3 <- lm(log(R_moment_3) ~ poly(St, 5) + factor(Re) + factor(Fr), data = training)
summary(poly4m3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ poly(St, 5) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
```

```
##      Min      1Q Median      3Q      Max
## -4.940 -1.835 -0.610  1.995  6.333
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    10.9867     0.7050  15.584 < 2e-16 ***
## poly(St, 5)1      6.4443     2.8162   2.288 0.02560 *
## poly(St, 5)2     -8.7749     2.8475  -3.082 0.00309 **
## poly(St, 5)3      6.6031     2.8335   2.330 0.02311 *
## poly(St, 5)4     -7.8160     2.8604  -2.733 0.00821 **
## poly(St, 5)5      4.4768     2.8193   1.588 0.11747
## factor(Re)224    -6.5340     0.7619  -8.576 4.51e-12 ***
## factor(Re)398   -11.1206     1.0072 -11.041 3.53e-16 ***
## factor(Fr)0.3    -7.1498     0.9049  -7.901 6.51e-11 ***
## factor(Fr)Inf    -5.2166     0.7716  -6.761 5.95e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.792 on 61 degrees of freedom
## Multiple R-squared:  0.7984, Adjusted R-squared:  0.7686
## F-statistic: 26.83 on 9 and 61 DF,  p-value: < 2.2e-16
```

```
poly5m3 <- lm(log(R_moment_3) ~ poly(St, 6) + factor(Re) + factor(Fr), data = training)
summary(poly5m3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ poly(St, 6) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min      1Q  Median      3Q      Max
## -4.9366 -1.8405 -0.6204  1.9943  6.3257
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    10.9874     0.7116  15.440 < 2e-16 ***
## poly(St, 6)1      6.4446     2.8396   2.270 0.02684 *
## poly(St, 6)2     -8.7756     2.8714  -3.056 0.00334 **
## poly(St, 6)3      6.6044     2.8577   2.311 0.02428 *
## poly(St, 6)4     -7.8179     2.8854  -2.709 0.00877 **
## poly(St, 6)5      4.4763     2.8428   1.575 0.12060
## poly(St, 6)6      0.0608     2.8446   0.021 0.98302
## factor(Re)224    -6.5356     0.7718  -8.469 7.81e-12 ***
## factor(Re)398   -11.1232     1.0229 -10.874 8.13e-16 ***
## factor(Fr)0.3    -7.1491     0.9131  -7.830 9.57e-11 ***
## factor(Fr)Inf    -5.2155     0.7795  -6.691 8.41e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.815 on 60 degrees of freedom
## Multiple R-squared:  0.7984, Adjusted R-squared:  0.7648
## F-statistic: 23.76 on 10 and 60 DF,  p-value: < 2.2e-16
```



```
poly6m3 <- lm(log(R_moment_3) ~ poly(St, 7) + factor(Re) + factor(Fr), data = training)
summary(poly6m3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ poly(St, 7) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.7756 -1.9581 -0.5718  1.8527  6.6265
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   10.9504     0.7116  15.389 < 2e-16 ***
## poly(St, 7)1    6.4733     2.8362   2.282  0.02609 *
## poly(St, 7)2   -8.8021     2.8680  -3.069  0.00324 **
## poly(St, 7)3    6.5856     2.8543   2.307  0.02457 *
## poly(St, 7)4   -7.8261     2.8819  -2.716  0.00867 **
## poly(St, 7)5    4.4920     2.8394   1.582  0.11898
## poly(St, 7)6    0.0603     2.8411   0.021  0.98314
## poly(St, 7)7    3.0242     2.8252   1.070  0.28879
## factor(Re)224  -6.5291     0.7708  -8.470 8.81e-12 ***
## factor(Re)398 -11.0885     1.0221 -10.848 1.12e-15 ***
## factor(Fr)0.3  -7.1366     0.9120  -7.825 1.08e-10 ***
## factor(Fr)Inf  -5.1463     0.7813  -6.587 1.35e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.812 on 59 degrees of freedom
## Multiple R-squared:  0.8022, Adjusted R-squared:  0.7653
## F-statistic: 21.75 on 11 and 59 DF,  p-value: < 2.2e-16
```

```
poly7m3 <- lm(log(R_moment_3) ~ poly(St, 8) + factor(Re) + factor(Fr), data = training)
summary(poly7m3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ poly(St, 8) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.8894 -1.8271 -0.4686  1.8300  6.6013
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   10.95501     0.71765  15.265 < 2e-16 ***
## poly(St, 8)1    6.47244     2.85928   2.264  0.02735 *
## poly(St, 8)2   -8.78903     2.89182  -3.039  0.00355 **
## poly(St, 8)3    6.61317     2.87995   2.296  0.02529 *
## poly(St, 8)4   -7.85100     2.90735  -2.700  0.00906 **
```

```
## poly(St, 8)5      4.48616      2.86254      1.567      0.12251
## poly(St, 8)6      0.07662      2.86508      0.027      0.97876
## poly(St, 8)7      3.01437      2.84848      1.058      0.29433
## poly(St, 8)8      0.68044      2.94801      0.231      0.81827
## factor(Re)224     -6.53100      0.77714      -8.404      1.29e-11 ***
## factor(Re)398     -11.13280      1.04818     -10.621      3.17e-15 ***
## factor(Fr)0.3     -7.11139      0.92593      -7.680      2.11e-10 ***
## factor(Fr)Inf     -5.14829      0.78766      -6.536      1.75e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.835 on 58 degrees of freedom
## Multiple R-squared:  0.8024, Adjusted R-squared:  0.7615
## F-statistic: 19.62 on 12 and 58 DF,  p-value: 3.66e-16

poly8m3 <- lm(log(R_moment_3) ~ poly(St, 9) + factor(Re) + factor(Fr), data = training)
summary(poly8m3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ poly(St, 9) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.9652 -1.7446 -0.5884  1.8966  6.5355
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   10.97039    0.72562   15.119 < 2e-16 ***
## poly(St, 9)1     6.46980    2.88237    2.245  0.02869 *
## poly(St, 9)2    -8.78986    2.91517   -3.015  0.00383 **
## poly(St, 9)3     6.61846    2.90326    2.280  0.02639 *
## poly(St, 9)4    -7.85103    2.93082   -2.679  0.00964 **
## poly(St, 9)5     4.48454    2.88566    1.554  0.12570
## poly(St, 9)6     0.08032    2.88824    0.028  0.97791
## poly(St, 9)7     3.01047    2.87151    1.048  0.29888
## poly(St, 9)8     0.67828    2.97181    0.228  0.82028
## poly(St, 9)9    -0.78979    2.88552   -0.274  0.78530
## factor(Re)224    -6.55547    0.78850   -8.314  2.07e-11 ***
## factor(Re)398   -11.13557    1.05669  -10.538  5.32e-15 ***
## factor(Fr)0.3    -7.10851    0.93346   -7.615  3.00e-10 ***
## factor(Fr)Inf    -5.15994    0.79516   -6.489  2.25e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.858 on 57 degrees of freedom
## Multiple R-squared:  0.8026, Adjusted R-squared:  0.7576
## F-statistic: 17.83 on 13 and 57 DF,  p-value: 1.612e-15
```

```
anova(fit.lm3, polym3, poly2m3, poly3m3, poly4m3, poly5m3, poly6m3, poly7m3, poly8m3)
```

```
## Analysis of Variance Table
```

```
##
## Model 1: log(R_moment_3) ~ (St + factor(Re) + factor(Fr) + factor(Re) *
##      factor(Fr))
## Model 2: log(R_moment_3) ~ poly(St, 2) + factor(Re) + factor(Fr)
## Model 3: log(R_moment_3) ~ poly(St, 3) + factor(Re) + factor(Fr)
## Model 4: log(R_moment_3) ~ poly(St, 4) + factor(Re) + factor(Fr)
## Model 5: log(R_moment_3) ~ poly(St, 5) + factor(Re) + factor(Fr)
## Model 6: log(R_moment_3) ~ poly(St, 6) + factor(Re) + factor(Fr)
## Model 7: log(R_moment_3) ~ poly(St, 7) + factor(Re) + factor(Fr)
## Model 8: log(R_moment_3) ~ poly(St, 8) + factor(Re) + factor(Fr)
## Model 9: log(R_moment_3) ~ poly(St, 9) + factor(Re) + factor(Fr)
##   Res.Df    RSS Df Sum of Sq    F    Pr(>F)
## 1      62 265.49
## 2      64 594.14 -2   -328.65 20.1227 2.444e-07 ***
## 3      63 554.29  1    39.85  4.8794  0.03121 *
## 4      62 495.23  1    59.07  7.2332  0.00937 **
## 5      61 475.57  1    19.66  2.4073  0.12630
## 6      60 475.56  1     0.00  0.0004  0.98327
## 7      59 466.50  1     9.06  1.1094  0.29665
## 8      58 466.08  1     0.43  0.0524  0.81972
## 9      57 465.46  1     0.61  0.0749  0.78530
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
pred.polym3 <- predict(polym3, testing)
pred.poly2m3 <- predict(poly2m3, testing)
pred.poly3m3 <- predict(poly3m3, testing)
pred.poly4m3 <- predict(poly4m3, testing)
pred.poly5m3 <- predict(poly5m3, testing)
pred.poly6m3 <- predict(poly6m3, testing)
pred.poly7m3 <- predict(poly7m3, testing)
pred.poly8m3 <- predict(poly8m3, testing)
mse_polym3 <- mean((pred.polym3 - log(testing$R_moment_3))^2)
mse_poly2m3 <- mean((pred.poly2m3 - log(testing$R_moment_3))^2)
mse_poly3m3 <- mean((pred.poly3m3 - log(testing$R_moment_3))^2)
mse_poly4m3 <- mean((pred.poly4m3 - log(testing$R_moment_3))^2)
mse_poly5m3 <- mean((pred.poly5m3 - log(testing$R_moment_3))^2)
mse_poly6m3 <- mean((pred.poly6m3 - log(testing$R_moment_3))^2)
mse_poly7m3 <- mean((pred.poly7m3 - log(testing$R_moment_3))^2)
mse_poly8m3 <- mean((pred.poly8m3 - log(testing$R_moment_3))^2)
mse_test3
```

```
## [1] 3.184988
```

```
mse_polym3
```

```
## [1] 11.47799
```

```
mse_poly2m3
```

```
## [1] 12.44993
```

```
mse_poly3m3
```

```
## [1] 12.44521
```

```
mse_poly4m3
```

```
## [1] 11.6731
```

```
mse_poly5m3
```

```
## [1] 11.69897
```

```
mse_poly6m3
```

```
## [1] 11.09748
```

```
mse_poly7m3
```

```
## [1] 11.3553
```

```
mse_poly8m3
```

```
## [1] 11.70741
```

Seem to be slightly worse than linear regression. Optimal model in terms of MSE still seems to be Least Squares.

Fourth moment:

```
polym4 <- lm(log(R_moment_4) ~ poly(St, 2) + factor(Re) + factor(Fr), data = training)
summary(polym4)
```

```
##
```

```
## Call:
```

```
## lm(formula = log(R_moment_4) ~ poly(St, 2) + factor(Re) + factor(Fr),
##     data = training)
```

```
##
```

```
## Residuals:
```

```
##      Min       1Q   Median       3Q      Max
## -7.5706 -3.1427 -0.5878  3.3212  8.1907
```

```
##
```

```
## Coefficients:
```

```
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    17.823      1.093   16.312 < 2e-16 ***
## poly(St, 2)1     7.648      4.398    1.739  0.0868 .
## poly(St, 2)2   -11.584      4.446   -2.606  0.0114 *
## factor(Re)224    -7.693      1.176   -6.539 1.19e-08 ***
## factor(Re)398   -13.109      1.523   -8.605 2.78e-12 ***
## factor(Fr)0.3   -11.123      1.402   -7.935 4.20e-11 ***
```

```
## factor(Fr)Inf    -8.270      1.194   -6.924 2.53e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.361 on 64 degrees of freedom
## Multiple R-squared:  0.7228, Adjusted R-squared:  0.6968
## F-statistic: 27.81 on 6 and 64 DF,  p-value: 4.449e-16

poly2m4 <- lm(log(R_moment_4) ~ poly(St, 3) + factor(Re) + factor(Fr), data = training)
summary(poly2m4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ poly(St, 3) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -7.1120 -3.1859 -0.6285  3.0255  8.4875
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      17.945      1.070  16.774 < 2e-16 ***
## poly(St, 3)1       7.657       4.299   1.781  0.0797 .
## poly(St, 3)2     -11.593       4.346  -2.668  0.0097 **
## poly(St, 3)3       8.623       4.323   1.995  0.0504 .
## factor(Re)224     -7.896       1.154  -6.839 3.80e-09 ***
## factor(Re)398    -13.519       1.503  -8.993 6.65e-13 ***
## factor(Fr)0.3    -10.959       1.373  -7.983 3.83e-11 ***
## factor(Fr)Inf     -8.224       1.168  -7.043 1.68e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.263 on 63 degrees of freedom
## Multiple R-squared:  0.7392, Adjusted R-squared:  0.7103
## F-statistic: 25.51 on 7 and 63 DF,  p-value: 3.788e-16
```

```
poly3m4 <- lm(log(R_moment_4) ~ poly(St, 4) + factor(Re) + factor(Fr), data = training)
summary(poly3m4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ poly(St, 4) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -6.7076 -2.7785 -0.4152  2.8563  8.2559
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      18.052      1.027  17.580 < 2e-16 ***
## poly(St, 4)1       7.752       4.123   1.880  0.06478 .
```

```
## poly(St, 4)2    -11.796      4.168   -2.830   0.00627 **
## poly(St, 4)3      8.952      4.148    2.158   0.03480 *
## poly(St, 4)4    -10.672      4.188   -2.549   0.01331 *
## factor(Re)224    -8.204      1.114   -7.366  4.99e-10 ***
## factor(Re)398   -14.186      1.465   -9.682  5.13e-14 ***
## factor(Fr)0.3   -10.785      1.318   -8.181  1.92e-11 ***
## factor(Fr)Inf    -7.859      1.129   -6.961  2.51e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.088 on 62 degrees of freedom
## Multiple R-squared:  0.764, Adjusted R-squared:  0.7335
## F-statistic: 25.08 on 8 and 62 DF,  p-value: < 2.2e-16
```

```
poly4m4 <- lm(log(R_moment_4) ~ poly(St, 5) + factor(Re) + factor(Fr), data = training)
summary(poly4m4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ poly(St, 5) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -6.9842 -2.5057 -0.8637  2.9498  8.9878
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      17.904      1.024  17.492 < 2e-16 ***
## poly(St, 5)1       7.824      4.089   1.914  0.0604 .
## poly(St, 5)2     -11.698      4.134  -2.829  0.0063 **
## poly(St, 5)3       8.898      4.114   2.163  0.0345 *
## poly(St, 5)4     -10.598      4.153  -2.552  0.0132 *
## poly(St, 5)5       5.856      4.093   1.431  0.1577
## factor(Re)224     -8.116      1.106  -7.337 6.10e-10 ***
## factor(Re)398    -13.949      1.462  -9.539 1.05e-13 ***
## factor(Fr)0.3    -10.598      1.314  -8.066 3.38e-11 ***
## factor(Fr)Inf     -7.806      1.120  -6.968 2.63e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.054 on 61 degrees of freedom
## Multiple R-squared:  0.7716, Adjusted R-squared:  0.7379
## F-statistic: 22.9 on 9 and 61 DF,  p-value: < 2.2e-16
```

```
poly5m4 <- lm(log(R_moment_4) ~ poly(St, 6) + factor(Re) + factor(Fr), data = training)
summary(poly5m4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ poly(St, 6) + factor(Re) + factor(Fr),
##     data = training)
##
```

```
## Residuals:
##      Min       1Q   Median       3Q      Max
## -6.9466 -2.5461 -0.8998  2.9398  8.9150
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    17.9105     1.0330  17.338 < 2e-16 ***
## poly(St, 6)1     7.8266     4.1220   1.899  0.06241 .
## poly(St, 6)2    -11.7046     4.1682  -2.808  0.00672 **
## poly(St, 6)3     8.9109     4.1484   2.148  0.03576 *
## poly(St, 6)4    -10.6163     4.1886  -2.535  0.01389 *
## poly(St, 6)5     5.8505     4.1267   1.418  0.16145
## poly(St, 6)6     0.5934     4.1293   0.144  0.88622
## factor(Re)224    -8.1312     1.1203  -7.258 9.08e-10 ***
## factor(Re)398   -13.9749     1.4849  -9.412 2.02e-13 ***
## factor(Fr)0.3   -10.5913     1.3255  -7.991 5.08e-11 ***
## factor(Fr)Inf    -7.7955     1.1316  -6.889 3.87e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.087 on 60 degrees of freedom
## Multiple R-squared:  0.7717, Adjusted R-squared:  0.7336
## F-statistic: 20.28 on 10 and 60 DF, p-value: 9.727e-16
```

```
poly6m4 <- lm(log(R_moment_4) ~ poly(St, 7) + factor(Re) + factor(Fr), data = training)
summary(poly6m4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ poly(St, 7) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -6.7261 -2.8475 -0.8583  2.7493  9.3269
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    17.8597     1.0341  17.271 < 2e-16 ***
## poly(St, 7)1     7.8659     4.1216   1.908  0.06120 .
## poly(St, 7)2    -11.7408     4.1677  -2.817  0.00658 **
## poly(St, 7)3     8.8852     4.1478   2.142  0.03632 *
## poly(St, 7)4    -10.6276     4.1880  -2.538  0.01382 *
## poly(St, 7)5     5.8720     4.1262   1.423  0.15997
## poly(St, 7)6     0.5927     4.1287   0.144  0.88634
## poly(St, 7)7     4.1414     4.1056   1.009  0.31723
## factor(Re)224    -8.1222     1.1202  -7.251 1.02e-09 ***
## factor(Re)398   -13.9274     1.4854  -9.376 2.71e-13 ***
## factor(Fr)0.3   -10.5742     1.3254  -7.978 5.95e-11 ***
## factor(Fr)Inf    -7.7007     1.1353  -6.783 6.30e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.086 on 59 degrees of freedom
```

```
## Multiple R-squared:  0.7756, Adjusted R-squared:  0.7337
## F-statistic: 18.54 on 11 and 59 DF,  p-value: 2.798e-15
```

```
poly7m4 <- lm(log(R_moment_4) ~ poly(St, 8) + factor(Re) + factor(Fr), data = training)
summary(poly7m4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ poly(St, 8) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -6.9316 -2.6638 -0.7832  2.7083  9.2814
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   17.8681     1.0426  17.138 < 2e-16 ***
## poly(St, 8)1    7.8644     4.1541   1.893  0.06333 .
## poly(St, 8)2  -11.7173     4.2013  -2.789  0.00714 **
## poly(St, 8)3    8.9349     4.1841   2.135  0.03696 *
## poly(St, 8)4  -10.6725     4.2239  -2.527  0.01426 *
## poly(St, 8)5    5.8614     4.1588   1.409  0.16406
## poly(St, 8)6    0.6222     4.1625   0.149  0.88170
## poly(St, 8)7    4.1237     4.1384   0.996  0.32317
## poly(St, 8)8    1.2285     4.2830   0.287  0.77525
## factor(Re)224  -8.1257     1.1291  -7.197 1.37e-09 ***
## factor(Re)398 -14.0074     1.5228  -9.198 6.25e-13 ***
## factor(Fr)0.3 -10.5286     1.3452  -7.827 1.20e-10 ***
## factor(Fr)Inf  -7.7043     1.1443  -6.733 8.23e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.118 on 58 degrees of freedom
## Multiple R-squared:  0.7759, Adjusted R-squared:  0.7295
## F-statistic: 16.73 on 12 and 58 DF,  p-value: 1.197e-14
```

```
poly8m4 <- lm(log(R_moment_4) ~ poly(St, 8) + factor(Re) + factor(Fr), data = training)
summary(poly8m4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ poly(St, 8) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -6.9316 -2.6638 -0.7832  2.7083  9.2814
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   17.8681     1.0426  17.138 < 2e-16 ***
## poly(St, 8)1    7.8644     4.1541   1.893  0.06333 .
```



```
## poly(St, 8)2 -11.7173      4.2013 -2.789  0.00714 **
## poly(St, 8)3   8.9349      4.1841  2.135  0.03696 *
## poly(St, 8)4 -10.6725      4.2239 -2.527  0.01426 *
## poly(St, 8)5   5.8614      4.1588  1.409  0.16406
## poly(St, 8)6   0.6222      4.1625  0.149  0.88170
## poly(St, 8)7   4.1237      4.1384  0.996  0.32317
## poly(St, 8)8   1.2285      4.2830  0.287  0.77525
## factor(Re)224 -8.1257      1.1291 -7.197 1.37e-09 ***
## factor(Re)398 -14.0074      1.5228 -9.198 6.25e-13 ***
## factor(Fr)0.3 -10.5286      1.3452 -7.827 1.20e-10 ***
## factor(Fr)Inf -7.7043      1.1443 -6.733 8.23e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.118 on 58 degrees of freedom
## Multiple R-squared:  0.7759, Adjusted R-squared:  0.7295
## F-statistic: 16.73 on 12 and 58 DF,  p-value: 1.197e-14
```

```
anova(fit.lm4, polym4, poly2m4, poly3m4, poly4m4, poly5m4, poly6m4, poly7m4, poly8m4)
```

```
## Analysis of Variance Table
##
## Model 1: log(R_moment_4) ~ (St + factor(Re) + factor(Fr) + factor(Re) *
##      factor(Fr))
## Model 2: log(R_moment_4) ~ poly(St, 2) + factor(Re) + factor(Fr)
## Model 3: log(R_moment_4) ~ poly(St, 3) + factor(Re) + factor(Fr)
## Model 4: log(R_moment_4) ~ poly(St, 4) + factor(Re) + factor(Fr)
## Model 5: log(R_moment_4) ~ poly(St, 5) + factor(Re) + factor(Fr)
## Model 6: log(R_moment_4) ~ poly(St, 6) + factor(Re) + factor(Fr)
## Model 7: log(R_moment_4) ~ poly(St, 7) + factor(Re) + factor(Fr)
## Model 8: log(R_moment_4) ~ poly(St, 8) + factor(Re) + factor(Fr)
## Model 9: log(R_moment_4) ~ poly(St, 8) + factor(Re) + factor(Fr)
##   Res.Df    RSS Df Sum of Sq    F    Pr(>F)
## 1      62  482.94
## 2      64 1216.95 -2   -734.01 21.6377 9.545e-08 ***
## 3      63 1144.66  1    72.29  4.2619  0.04346 *
## 4      62 1036.12  1   108.54  6.3994  0.01415 *
## 5      61 1002.49  1    33.63  1.9828  0.16443
## 6      60 1002.14  1     0.34  0.0203  0.88710
## 7      59  985.15  1    16.99  1.0017  0.32106
## 8      58  983.76  1     1.40  0.0823  0.77525
## 9      58  983.76  0     0.00
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
pred.polym4 <- predict(polym4, testing)
pred.poly2m4 <- predict(poly2m4, testing)
pred.poly3m4 <- predict(poly3m4, testing)
pred.poly4m4 <- predict(poly4m4, testing)
pred.poly5m4 <- predict(poly5m4, testing)
pred.poly6m4 <- predict(poly6m4, testing)
pred.poly7m4 <- predict(poly7m4, testing)
pred.poly8m4 <- predict(poly8m4, testing)
```

```

mse_polym4 <- mean((pred.polym4 - log(testing$R_moment_4))^2)
mse_poly2m4 <- mean((pred.poly2m4 - log(testing$R_moment_4))^2)
mse_poly3m4 <- mean((pred.poly3m4 - log(testing$R_moment_4))^2)
mse_poly4m4 <- mean((pred.poly4m4 - log(testing$R_moment_4))^2)
mse_poly5m4 <- mean((pred.poly5m4 - log(testing$R_moment_4))^2)
mse_poly6m4 <- mean((pred.poly6m4 - log(testing$R_moment_4))^2)
mse_poly7m4 <- mean((pred.poly7m4 - log(testing$R_moment_4))^2)
mse_poly8m4 <- mean((pred.poly8m4 - log(testing$R_moment_4))^2)
mse_test4

```

```
## [1] 5.272393
```

```
mse_polym4
```

```
## [1] 22.95277
```

```
mse_poly2m4
```

```
## [1] 25.02578
```

```
mse_poly3m4
```

```
## [1] 25.05991
```

```
mse_poly4m4
```

```
## [1] 23.69646
```

```
mse_poly5m4
```

```
## [1] 24.05208
```

```
mse_poly6m4
```

```
## [1] 22.95743
```

```
mse_poly7m4
```

```
## [1] 23.60226
```

```
mse_poly8m4
```

```
## [1] 23.60226
```

The linear regression fit seems to have the minimal MSE for the fourth order.

Splines

```
library(splines)
```

First moment:

```
spline1 <- lm(log(R_moment_1) ~ bs(log(St)) + factor(Re) + factor(Fr), data = training)
summary(spline1)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ bs(log(St)) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.29700 -0.06613 -0.00928  0.09227  0.27652
##
## Coefficients:
##              Estimate Std. Error  t value Pr(>|t|)
## (Intercept)   -2.695985   0.062097  -43.416 < 2e-16 ***
## bs(log(St))1    0.504229   0.151056   3.338 0.001420 **
## bs(log(St))2    0.418550   0.106273   3.938 0.000208 ***
## bs(log(St))3    0.922160   0.076158  12.108 < 2e-16 ***
## factor(Re)224  -3.657326   0.033996 -107.582 < 2e-16 ***
## factor(Re)398  -5.814895   0.044247 -131.418 < 2e-16 ***
## factor(Fr)0.3  -0.131149   0.040266   -3.257 0.001815 **
## factor(Fr)Inf  -0.004388   0.034483   -0.127 0.899143
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1253 on 63 degrees of freedom
## Multiple R-squared:  0.9971, Adjusted R-squared:  0.9968
## F-statistic: 3069 on 7 and 63 DF,  p-value: < 2.2e-16
```

```
pred.spline1 <- predict(spline1, testing)
mse_spline1 <- mean((pred.spline1 - log(testing$R_moment_1))^2)
spline2 <- lm(log(R_moment_1) ~ bs(log(St), df=4) + factor(Re) + factor(Fr), data = training)
summary(spline2)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ bs(log(St), df = 4) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.29645 -0.06942 -0.01147  0.08196  0.28926
##
## Coefficients:
##              Estimate Std. Error  t value Pr(>|t|)
## (Intercept)   -2.70253   0.06363  -42.476 < 2e-16 ***
## bs(log(St), df = 4)1  0.37947   0.14088   2.694 0.00908 **
```

```

## bs(log(St), df = 4)2  0.39201    0.12706    3.085  0.00304 **
## bs(log(St), df = 4)3  0.78764    0.10080    7.814 8.32e-11 ***
## bs(log(St), df = 4)4  0.91380    0.07815   11.693 < 2e-16 ***
## factor(Re)224         -3.65536    0.03438 -106.310 < 2e-16 ***
## factor(Re)398         -5.81008    0.04539 -127.998 < 2e-16 ***
## factor(Fr)0.3         -0.13334    0.04070  -3.276  0.00173 **
## factor(Fr)Inf         -0.00420    0.03468  -0.121  0.90400
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.126 on 62 degrees of freedom
## Multiple R-squared:  0.9971, Adjusted R-squared:  0.9967
## F-statistic: 2655 on 8 and 62 DF,  p-value: < 2.2e-16

pred.spline2 <- predict(spline2, testing)
mse_spline2 <- mean((pred.spline2 - log(testing$R_moment_1))^2)
spline3 <- lm(log(R_moment_1) ~ bs(log(St), df=5) + factor(Re) + factor(Fr), data = training)
summary(spline3)

##
## Call:
## lm(formula = log(R_moment_1) ~ bs(log(St), df = 5) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.32045 -0.06353 -0.00529  0.07553  0.30925
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   -2.687214   0.062790  -42.797 < 2e-16 ***
## bs(log(St), df = 5)1  0.094829   0.161492   0.587  0.55923
## bs(log(St), df = 5)2  0.549311   0.109090   5.035 4.51e-06 ***
## bs(log(St), df = 5)3  0.491589   0.088726   5.541 6.81e-07 ***
## bs(log(St), df = 5)4  0.920682   0.105136   8.757 2.22e-12 ***
## bs(log(St), df = 5)5  0.879542   0.078427  11.215 < 2e-16 ***
## factor(Re)224     -3.659384   0.033675 -108.668 < 2e-16 ***
## factor(Re)398     -5.818879   0.044594 -130.486 < 2e-16 ***
## factor(Fr)0.3     -0.128906   0.039884  -3.232  0.00198 **
## factor(Fr)Inf     -0.001217   0.033956  -0.036  0.97154
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1232 on 61 degrees of freedom
## Multiple R-squared:  0.9973, Adjusted R-squared:  0.9969
## F-statistic: 2467 on 9 and 61 DF,  p-value: < 2.2e-16

pred.spline3 <- predict(spline3, testing)
mse_spline3 <- mean((pred.spline3 - log(testing$R_moment_1))^2)
spline4 <- lm(log(R_moment_1) ~ bs(log(St), df=6) + factor(Re) + factor(Fr), data = training)
summary(spline4)

##

```

```
## Call:
## lm(formula = log(R_moment_1) ~ bs(log(St), df = 6) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.32354 -0.06220 -0.00659  0.07268  0.31040
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    -2.685613   0.063433  -42.338 < 2e-16 ***
## bs(log(St), df = 6)1    0.047771   0.176694   0.270 0.787809
## bs(log(St), df = 6)2    0.479295   0.131253   3.652 0.000548 ***
## bs(log(St), df = 6)3    0.505514   0.088456   5.715 3.66e-07 ***
## bs(log(St), df = 6)4    0.599654   0.104721   5.726 3.50e-07 ***
## bs(log(St), df = 6)5    0.934388   0.124194   7.524 3.19e-10 ***
## bs(log(St), df = 6)6    0.877153   0.079039  11.098 3.58e-16 ***
## factor(Re)224         -3.659994   0.034006 -107.629 < 2e-16 ***
## factor(Re)398         -5.819792   0.045046 -129.196 < 2e-16 ***
## factor(Fr)0.3         -0.128687   0.040149  -3.205 0.002163 **
## factor(Fr)Inf         -0.000969   0.034402  -0.028 0.977622
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.124 on 60 degrees of freedom
## Multiple R-squared:  0.9973, Adjusted R-squared:  0.9968
## F-statistic: 2194 on 10 and 60 DF, p-value: < 2.2e-16

pred.spline4 <- predict(spline4, testing)
mse_spline4 <- mean((pred.spline4 - log(testing$R_moment_1))^2)
spline5 <- lm(log(R_moment_1) ~ bs(log(St), df=7) + factor(Re) + factor(Fr), data = training)
summary(spline5)
```

```
##
## Call:
## lm(formula = log(R_moment_1) ~ bs(log(St), df = 7) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.32523 -0.06066 -0.00016  0.07307  0.30946
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    -2.684805   0.064194  -41.823 < 2e-16 ***
## bs(log(St), df = 7)1    0.032301   0.193549   0.167 0.86803
## bs(log(St), df = 7)2    0.437879   0.134680   3.251 0.00190 **
## bs(log(St), df = 7)3    0.496630   0.089607   5.542 7.33e-07 ***
## bs(log(St), df = 7)4    0.528333   0.092052   5.739 3.48e-07 ***
## bs(log(St), df = 7)5    0.720740   0.166629   4.325 5.96e-05 ***
## bs(log(St), df = 7)6    0.920564   0.158934   5.792 2.85e-07 ***
## bs(log(St), df = 7)7    0.877690   0.080121  10.955 7.56e-16 ***
## factor(Re)224         -3.659271   0.034375 -106.451 < 2e-16 ***
## factor(Re)398         -5.819057   0.045823 -126.990 < 2e-16 ***
```

```
## factor(Fr)0.3      -0.128912  0.040597  -3.175  0.00238 **
## factor(Fr)Inf      -0.002093  0.034711  -0.060  0.95212
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1253 on 59 degrees of freedom
## Multiple R-squared:  0.9973, Adjusted R-squared:  0.9968
## F-statistic: 1954 on 11 and 59 DF, p-value: < 2.2e-16
```

```
pred.spline5 <- predict(spline5, testing)
mse_spline5 <- mean((pred.spline5 - log(testing$R_moment_1))^2)
mse_spline1
```

```
## [1] 0.02050534
```

```
mse_spline2
```

```
## [1] 0.01902618
```

```
mse_spline3
```

```
## [1] 0.02246655
```

```
mse_spline4
```

```
## [1] 0.02302992
```

```
mse_spline5
```

```
## [1] 0.02305703
```

Second moment:

```
spline1m2 <- lm(log(R_moment_2) ~ bs(log(St)) + factor(Re) + factor(Fr), data = training)
summary(spline1m2)
```

```
##
## Call:
## lm(formula = log(R_moment_2) ~ bs(log(St)) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.5892 -0.9503 -0.1786  0.9750  3.6233
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    0.3434     0.7347   0.467 0.641799
## bs(log(St))1    4.8146     1.7872   2.694 0.009040 **
```

```

## bs(log(St))2      4.3767      1.2574      3.481 0.000913 ***
## bs(log(St))3      4.3560      0.9011      4.834 8.95e-06 ***
## factor(Re)224     -4.9356      0.4022     -12.271 < 2e-16 ***
## factor(Re)398     -8.2172      0.5235     -15.696 < 2e-16 ***
## factor(Fr)0.3     -3.7197      0.4764      -7.808 7.74e-11 ***
## factor(Fr)Inf     -2.6518      0.4080      -6.500 1.48e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.482 on 63 degrees of freedom
## Multiple R-squared:  0.8598, Adjusted R-squared:  0.8443
## F-statistic: 55.21 on 7 and 63 DF,  p-value: < 2.2e-16

pred.spline1m2 <- predict(spline1m2, testing)
mse_spline1m2 <- mean((pred.spline1m2 - log(testing$R_moment_2))^2)
spline2m2 <- lm(log(R_moment_2) ~ bs(log(St), df=4) + factor(Re) + factor(Fr), data = training)
summary(spline2m2)

##
## Call:
## lm(formula = log(R_moment_2) ~ bs(log(St), df = 4) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.6030 -0.9729 -0.1833  0.9724  3.6160
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      0.3747    0.7543   0.497 0.621127
## bs(log(St), df = 4)1  2.8433    1.6701   1.703 0.093668 .
## bs(log(St), df = 4)2  4.8044    1.5062   3.190 0.002234 **
## bs(log(St), df = 4)3  4.1510    1.1949   3.474 0.000941 ***
## bs(log(St), df = 4)4  4.3959    0.9265   4.745 1.27e-05 ***
## factor(Re)224      -4.9450    0.4076  -12.132 < 2e-16 ***
## factor(Re)398      -8.2402    0.5381  -15.313 < 2e-16 ***
## factor(Fr)0.3      -3.7092    0.4825   -7.688 1.38e-10 ***
## factor(Fr)Inf      -2.6527    0.4111   -6.452 1.89e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.494 on 62 degrees of freedom
## Multiple R-squared:  0.8599, Adjusted R-squared:  0.8419
## F-statistic: 47.58 on 8 and 62 DF,  p-value: < 2.2e-16

pred.spline2m2 <- predict(spline2m2, testing)
mse_spline2m2 <- mean((pred.spline2m2 - log(testing$R_moment_2))^2)
spline3m2 <- lm(log(R_moment_2) ~ bs(log(St), df=5) + factor(Re) + factor(Fr), data = training)
summary(spline3m2)

##
## Call:
## lm(formula = log(R_moment_2) ~ bs(log(St), df = 5) + factor(Re) +

```

```

##      factor(Fr), data = training)
##
## Residuals:
##      Min        1Q    Median        3Q        Max
## -2.8236 -0.9019 -0.1415  0.9843  3.5600
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      0.4618     0.7617   0.606 0.546608
## bs(log(St), df = 5)1  1.0563     1.9591   0.539 0.591722
## bs(log(St), df = 5)2  4.9700     1.3234   3.755 0.000389 ***
## bs(log(St), df = 5)3  3.6529     1.0764   3.394 0.001216 **
## bs(log(St), df = 5)4  4.8500     1.2754   3.803 0.000334 ***
## bs(log(St), df = 5)5  4.1883     0.9514   4.402 4.39e-05 ***
## factor(Re)224      -4.9664     0.4085 -12.157 < 2e-16 ***
## factor(Re)398      -8.2879     0.5410 -15.320 < 2e-16 ***
## factor(Fr)0.3      -3.6842     0.4839  -7.614 2.03e-10 ***
## factor(Fr)Inf       -2.6362     0.4119  -6.400 2.47e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.495 on 61 degrees of freedom
## Multiple R-squared:  0.8619, Adjusted R-squared:  0.8416
## F-statistic: 42.31 on 9 and 61 DF,  p-value: < 2.2e-16

pred.spline3m2 <- predict(spline3m2, testing)
mse_spline3m2 <- mean((pred.spline3m2 - log(testing$R_moment_2))^2)
spline4m2 <- lm(log(R_moment_2) ~ bs(log(St), df=6) + factor(Re) + factor(Fr), data = training)
summary(spline4m2)

##
## Call:
## lm(formula = log(R_moment_2) ~ bs(log(St), df = 6) + factor(Re) +
##      factor(Fr), data = training)
##
## Residuals:
##      Min        1Q    Median        3Q        Max
## -2.7853 -0.9687 -0.2396  1.0630  3.5767
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      0.4504     0.7688   0.586 0.560172
## bs(log(St), df = 6)1  1.1751     2.1416   0.549 0.585256
## bs(log(St), df = 6)2  3.7787     1.5909   2.375 0.020749 *
## bs(log(St), df = 6)3  4.5589     1.0721   4.252 7.52e-05 ***
## bs(log(St), df = 6)4  3.4480     1.2693   2.717 0.008607 **
## bs(log(St), df = 6)5  5.3150     1.5053   3.531 0.000803 ***
## bs(log(St), df = 6)6  4.1677     0.9580   4.350 5.36e-05 ***
## factor(Re)224      -4.9869     0.4122 -12.099 < 2e-16 ***
## factor(Re)398      -8.3178     0.5460 -15.234 < 2e-16 ***
## factor(Fr)0.3      -3.6887     0.4866  -7.580 2.55e-10 ***
## factor(Fr)Inf       -2.6116     0.4170  -6.263 4.45e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```



```
##
## Residual standard error: 1.503 on 60 degrees of freedom
## Multiple R-squared:  0.8628, Adjusted R-squared:  0.8399
## F-statistic: 37.73 on 10 and 60 DF,  p-value: < 2.2e-16

pred.spline4m2 <- predict(spline4m2, testing)
mse_spline4m2 <- mean((pred.spline4m2 - log(testing$R_moment_2))^2)
spline5m2 <- lm(log(R_moment_2) ~ bs(log(St), df=7) + factor(Re) + factor(Fr), data = training)
summary(spline5m2)
```

```
##
## Call:
## lm(formula = log(R_moment_2) ~ bs(log(St), df = 7) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.8207 -0.8912 -0.1957  1.0151  3.5749
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      0.4674     0.7783   0.601 0.550432
## bs(log(St), df = 7)1  0.8766     2.3465   0.374 0.710053
## bs(log(St), df = 7)2  3.7224     1.6328   2.280 0.026250 *
## bs(log(St), df = 7)3  4.2751     1.0863   3.935 0.000222 ***
## bs(log(St), df = 7)4  4.1639     1.1160   3.731 0.000430 ***
## bs(log(St), df = 7)5  3.7003     2.0201   1.832 0.072040 .
## bs(log(St), df = 7)6  5.2197     1.9268   2.709 0.008820 **
## bs(log(St), df = 7)7  4.1633     0.9713   4.286 6.82e-05 ***
## factor(Re)224        -4.9803     0.4167 -11.950 < 2e-16 ***
## factor(Re)398        -8.3183     0.5555 -14.973 < 2e-16 ***
## factor(Fr)0.3        -3.6941     0.4922  -7.506 3.76e-10 ***
## factor(Fr)Inf        -2.6262     0.4208  -6.241 5.14e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.519 on 59 degrees of freedom
## Multiple R-squared:  0.8622, Adjusted R-squared:  0.8365
## F-statistic: 33.57 on 11 and 59 DF,  p-value: < 2.2e-16
```

```
pred.spline5m2 <- predict(spline5m2, testing)
mse_spline5m2 <- mean((pred.spline5m2 - log(testing$R_moment_2))^2)
mse_spline1m2
```

```
## [1] 2.977825
```

```
mse_spline2m2
```

```
## [1] 3.063367
```

```
mse_spline3m2
```

```
## [1] 3.290766
```

```
mse_spline4m2
```

```
## [1] 3.288646
```

```
mse_spline5m2
```

```
## [1] 3.29419
```

Third moment:

```
spline1m3 <- lm(log(R_moment_3) ~ bs(log(St)) + factor(Re) + factor(Fr), data = training)
summary(spline1m3)
```

```
##
## Call:
## lm(formula = log(R_moment_3) ~ bs(log(St)) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.6115 -1.8244 -0.3367  1.8706  6.5840
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      5.0661      1.3745   3.686 0.000476 ***
## bs(log(St))1       7.4719      3.3436   2.235 0.028995 *
## bs(log(St))2       7.2474      2.3523   3.081 0.003058 **
## bs(log(St))3       6.4098      1.6858   3.802 0.000326 ***
## factor(Re)224     -6.4233      0.7525  -8.536 4.14e-12 ***
## factor(Re)398    -10.8893      0.9794 -11.118 < 2e-16 ***
## factor(Fr)0.3     -7.2476      0.8913  -8.132 2.10e-11 ***
## factor(Fr)Inf     -5.2838      0.7633  -6.923 2.73e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.773 on 63 degrees of freedom
## Multiple R-squared:  0.7946, Adjusted R-squared:  0.7717
## F-statistic: 34.81 on 7 and 63 DF,  p-value: < 2.2e-16
```

```
pred.spline1m3 <- predict(spline1m3, testing)
mse_spline1m3 <- mean((pred.spline1m3 - log(testing$R_moment_3))^2)
spline2m3 <- lm(log(R_moment_3) ~ bs(log(St), df=4) + factor(Re) + factor(Fr), data = training)
summary(spline2m3)
```

```
##
## Call:
```

```
## lm(formula = log(R_moment_3) ~ bs(log(St), df = 4) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.6192 -1.8419 -0.3788  1.9047  6.5627
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      5.1568     1.4103   3.656 0.000529 ***
## bs(log(St), df = 4)1  4.0616     3.1228   1.301 0.198196
## bs(log(St), df = 4)2  8.1167     2.8164   2.882 0.005424 **
## bs(log(St), df = 4)3  6.0914     2.2343   2.726 0.008317 **
## bs(log(St), df = 4)4  6.5256     1.7323   3.767 0.000370 ***
## factor(Re)224      -6.4505     0.7622  -8.463 6.24e-12 ***
## factor(Re)398     -10.9560     1.0062 -10.889 5.01e-16 ***
## factor(Fr)0.3      -7.2173     0.9022  -8.000 3.96e-11 ***
## factor(Fr)Inf      -5.2864     0.7687  -6.877 3.51e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.793 on 62 degrees of freedom
## Multiple R-squared:  0.7949, Adjusted R-squared:  0.7685
## F-statistic: 30.04 on 8 and 62 DF,  p-value: < 2.2e-16

pred.spline2m3 <- predict(spline2m3, testing)
mse_spline2m3 <- mean((pred.spline2m3 - log(testing$R_moment_3))^2)
spline3m3 <- lm(log(R_moment_3) ~ bs(log(St), df=5) + factor(Re) + factor(Fr), data = training)
summary(spline3m3)

##
## Call:
## lm(formula = log(R_moment_3) ~ bs(log(St), df = 5) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.9780 -1.6688 -0.3055  1.8169  6.4613
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      5.3141     1.4252   3.729 0.000424 ***
## bs(log(St), df = 5)1  1.0225     3.6654   0.279 0.781215
## bs(log(St), df = 5)2  8.1947     2.4760   3.310 0.001571 **
## bs(log(St), df = 5)3  5.5471     2.0138   2.755 0.007736 **
## bs(log(St), df = 5)4  7.3421     2.3863   3.077 0.003131 **
## bs(log(St), df = 5)5  6.1503     1.7801   3.455 0.001007 **
## factor(Re)224      -6.4885     0.7643  -8.489 6.36e-12 ***
## factor(Re)398     -11.0411     1.0121 -10.909 5.76e-16 ***
## factor(Fr)0.3      -7.1720     0.9053  -7.923 5.98e-11 ***
## factor(Fr)Inf      -5.2573     0.7707  -6.821 4.69e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
```

```
## Residual standard error: 2.797 on 61 degrees of freedom
## Multiple R-squared:  0.7976, Adjusted R-squared:  0.7678
## F-statistic: 26.71 on 9 and 61 DF,  p-value: < 2.2e-16

pred.spline3m3 <- predict(spline3m3, testing)
mse_spline3m3 <- mean((pred.spline3m3 - log(testing$R_moment_3))^2)
spline4m3 <- lm(log(R_moment_3) ~ bs(log(St), df=6) + factor(Re) + factor(Fr), data = training)
summary(spline4m3)

##
## Call:
## lm(formula = log(R_moment_3) ~ bs(log(St), df = 6) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.9031 -1.7160 -0.5931  2.0268  6.4936
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      5.2917     1.4383   3.679 0.000502 ***
## bs(log(St), df = 6)1  1.4354     4.0064   0.358 0.721397
## bs(log(St), df = 6)2  5.9311     2.9760   1.993 0.050822 .
## bs(log(St), df = 6)3  7.3568     2.0057   3.668 0.000521 ***
## bs(log(St), df = 6)4  5.0078     2.3744   2.109 0.039124 *
## bs(log(St), df = 6)5  8.2355     2.8160   2.925 0.004861 **
## bs(log(St), df = 6)6  6.1113     1.7921   3.410 0.001167 **
## factor(Re)224        -6.5278     0.7710  -8.466 7.88e-12 ***
## factor(Re)398       -11.0984     1.0214 -10.866 8.38e-16 ***
## factor(Fr)0.3        -7.1808     0.9103  -7.888 7.61e-11 ***
## factor(Fr)Inf        -5.2098     0.7800  -6.679 8.80e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.811 on 60 degrees of freedom
## Multiple R-squared:  0.7989, Adjusted R-squared:  0.7654
## F-statistic: 23.84 on 10 and 60 DF,  p-value: < 2.2e-16

pred.spline4m3 <- predict(spline4m3, testing)
mse_spline4m3 <- mean((pred.spline4m3 - log(testing$R_moment_3))^2)
spline5m3 <- lm(log(R_moment_3) ~ bs(log(St), df=7) + factor(Re) + factor(Fr), data = training)
summary(spline5m3)

##
## Call:
## lm(formula = log(R_moment_3) ~ bs(log(St), df = 7) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.9734 -1.6798 -0.4138  1.8793  6.4911
##
## Coefficients:
```

```
##               Estimate Std. Error t value Pr(>|t|)
## (Intercept)      5.3255     1.4557   3.658 0.000543 ***
## bs(log(St), df = 7)1  0.8432     4.3891   0.192 0.848316
## bs(log(St), df = 7)2  5.9099     3.0541   1.935 0.057784 .
## bs(log(St), df = 7)3  6.8045     2.0320   3.349 0.001419 **
## bs(log(St), df = 7)4  6.5568     2.0875   3.141 0.002631 **
## bs(log(St), df = 7)5  5.2793     3.7787   1.397 0.167602
## bs(log(St), df = 7)6  8.1363     3.6042   2.257 0.027694 *
## bs(log(St), df = 7)7  6.0994     1.8169   3.357 0.001384 **
## factor(Re)224        -6.5166     0.7795  -8.360 1.35e-11 ***
## factor(Re)398       -11.1024     1.0391 -10.684 2.03e-15 ***
## factor(Fr)0.3        -7.1917     0.9206  -7.812 1.14e-10 ***
## factor(Fr)Inf        -5.2371     0.7872  -6.653 1.04e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.841 on 59 degrees of freedom
## Multiple R-squared:  0.7981, Adjusted R-squared:  0.7605
## F-statistic: 21.21 on 11 and 59 DF, p-value: < 2.2e-16
```

```
pred.spline5m3 <- predict(spline5m3, testing)
mse_spline5m3 <- mean((pred.spline5m3 - log(testing$R_moment_3))^2)
mse_spline1m3
```

```
## [1] 9.972745
```

```
mse_spline2m3
```

```
## [1] 10.4218
```

```
mse_spline3m3
```

```
## [1] 11.13734
```

```
mse_spline4m3
```

```
## [1] 11.12919
```

```
mse_spline5m3
```

```
## [1] 11.14938
```

Fourth moment:

```
spline1m4 <- lm(log(R_moment_4) ~ bs(log(St)) + factor(Re) + factor(Fr), data = training)
summary(spline1m4)
```

```
##
## Call:
```

```
## lm(formula = log(R_moment_4) ~ bs(log(St)) + factor(Re) + factor(Fr),
##     data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -6.648 -2.759 -0.479  2.731  9.242
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      10.152      1.997   5.083 3.57e-06 ***
## bs(log(St))1       9.668      4.859   1.990  0.05096 .
## bs(log(St))2       9.837      3.418   2.878  0.00546 **
## bs(log(St))3       8.127      2.450   3.318  0.00151 **
## factor(Re)224      -7.964      1.093  -7.283 6.41e-10 ***
## factor(Re)398     -13.629      1.423  -9.576 6.60e-14 ***
## factor(Fr)0.3     -10.737      1.295  -8.290 1.11e-11 ***
## factor(Fr)Inf      -7.903      1.109  -7.126 1.21e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.03 on 63 degrees of freedom
## Multiple R-squared:  0.7669, Adjusted R-squared:  0.741
## F-statistic: 29.61 on 7 and 63 DF,  p-value: < 2.2e-16

pred.spline1m4 <- predict(spline1m4, testing)
mse_spline1m4 <- mean((pred.spline1m4 - log(testing$R_moment_4))^2)
spline2m4 <- lm(log(R_moment_4) ~ bs(log(St), df=4) + factor(Re) + factor(Fr), data = training)
summary(spline2m4)

##
## Call:
## lm(formula = log(R_moment_4) ~ bs(log(St), df = 4) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -6.6611 -2.7934 -0.5599  2.8229  9.2050
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      10.308      2.049   5.032 4.44e-06 ***
## bs(log(St), df = 4)1   4.933      4.536   1.087  0.28109
## bs(log(St), df = 4)2  11.136      4.091   2.722  0.00841 **
## bs(log(St), df = 4)3   7.674      3.246   2.365  0.02120 *
## bs(log(St), df = 4)4   8.327      2.516   3.309  0.00156 **
## factor(Re)224        -8.011      1.107  -7.236 8.40e-10 ***
## factor(Re)398       -13.744      1.462  -9.404 1.52e-13 ***
## factor(Fr)0.3       -10.685      1.310  -8.153 2.15e-11 ***
## factor(Fr)Inf        -7.908      1.117  -7.082 1.55e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.057 on 62 degrees of freedom
## Multiple R-squared:  0.7675, Adjusted R-squared:  0.7375
```

```
## F-statistic: 25.58 on 8 and 62 DF, p-value: < 2.2e-16
```

```
pred.spline2m4 <- predict(spline2m4, testing)
mse_spline2m4 <- mean((pred.spline2m4 - log(testing$R_moment_4))^2)
spline3m4 <- lm(log(R_moment_4) ~ bs(log(St), df=5) + factor(Re) + factor(Fr), data = training)
summary(spline3m4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ bs(log(St), df = 5) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -7.0554 -2.4879 -0.4701  2.6401  9.0583
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      10.5359     2.0704   5.089 3.70e-06 ***
## bs(log(St), df = 5)1    0.7063     5.3250   0.133  0.89491
## bs(log(St), df = 5)2   11.0977     3.5971   3.085  0.00306 **
## bs(log(St), df = 5)3    7.1141     2.9256   2.432  0.01798 *
## bs(log(St), df = 5)4    9.4775     3.4667   2.734  0.00818 **
## bs(log(St), df = 5)5    7.7845     2.5860   3.010  0.00379 **
## factor(Re)224         -8.0653     1.1104  -7.263 8.16e-10 ***
## factor(Re)398        -13.8665     1.4704  -9.430 1.60e-13 ***
## factor(Fr)0.3         -10.6192     1.3151  -8.075 3.27e-11 ***
## factor(Fr)Inf          -7.8663     1.1197  -7.026 2.09e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.064 on 61 degrees of freedom
## Multiple R-squared:  0.7705, Adjusted R-squared:  0.7366
## F-statistic: 22.76 on 9 and 61 DF, p-value: 2.284e-16
```

```
pred.spline3m4 <- predict(spline3m4, testing)
mse_spline3m4 <- mean((pred.spline3m4 - log(testing$R_moment_4))^2)
spline4m4 <- lm(log(R_moment_4) ~ bs(log(St), df=6) + factor(Re) + factor(Fr), data = training)
summary(spline4m4)
```

```
##
## Call:
## lm(formula = log(R_moment_4) ~ bs(log(St), df = 6) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -6.9436 -2.4784 -0.8562  2.9676  9.1064
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      10.502     2.089   5.027 4.80e-06 ***
## bs(log(St), df = 6)1    1.463     5.820   0.251  0.8024
```

```

## bs(log(St), df = 6)2      7.760      4.323      1.795      0.0777 .
## bs(log(St), df = 6)3      9.832      2.913      3.375      0.0013 **
## bs(log(St), df = 6)4      6.231      3.449      1.806      0.0759 .
## bs(log(St), df = 6)5     10.802      4.091      2.641      0.0105 *
## bs(log(St), df = 6)6      7.727      2.603      2.968      0.0043 **
## factor(Re)224             -8.123      1.120     -7.253 9.27e-10 ***
## factor(Re)398            -13.951      1.484     -9.403 2.09e-13 ***
## factor(Fr)0.3            -10.632      1.322     -8.040 4.18e-11 ***
## factor(Fr)Inf             -7.796      1.133     -6.880 4.00e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.084 on 60 degrees of freedom
## Multiple R-squared:  0.772, Adjusted R-squared:  0.7341
## F-statistic: 20.32 on 10 and 60 DF, p-value: 9.309e-16

pred.spline4m4 <- predict(spline4m4, testing)
mse_spline4m4 <- mean((pred.spline4m4 - log(testing$R_moment_4))^2)
spline5m4 <- lm(log(R_moment_4) ~ bs(log(St), df=7) + factor(Re) + factor(Fr), data = training)
summary(spline5m4)

##
## Call:
## lm(formula = log(R_moment_4) ~ bs(log(St), df = 7) + factor(Re) +
##     factor(Fr), data = training)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -7.0487 -2.4752 -0.6338  2.7261  9.1034
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      10.5528     2.1146   4.990 5.64e-06 ***
## bs(log(St), df = 7)1    0.5787     6.3757   0.091  0.92799
## bs(log(St), df = 7)2    7.7837     4.4365   1.754  0.08454 .
## bs(log(St), df = 7)3    9.0110     2.9517   3.053  0.00340 **
## bs(log(St), df = 7)4    8.6249     3.0323   2.844  0.00611 **
## bs(log(St), df = 7)5    6.5057     5.4889   1.185  0.24067
## bs(log(St), df = 7)6   10.7158     5.2354   2.047  0.04514 *
## bs(log(St), df = 7)7    7.7074     2.6392   2.920  0.00495 **
## factor(Re)224          -8.1077     1.1323  -7.160 1.45e-09 ***
## factor(Re)398         -13.9591     1.5095  -9.248 4.43e-13 ***
## factor(Fr)0.3         -10.6487     1.3373  -7.963 6.32e-11 ***
## factor(Fr)Inf          -7.8358     1.1434  -6.853 4.80e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.126 on 59 degrees of freedom
## Multiple R-squared:  0.7712, Adjusted R-squared:  0.7285
## F-statistic: 18.07 on 11 and 59 DF, p-value: 4.848e-15

pred.spline5m4 <- predict(spline5m4, testing)
mse_spline5m4 <- mean((pred.spline5m4 - log(testing$R_moment_4))^2)
mse_spline1m4

```



```
## [1] 20.67205
```

```
mse_spline2m4
```

```
## [1] 21.77453
```

```
mse_spline3m4
```

```
## [1] 23.19761
```

```
mse_spline4m4
```

```
## [1] 23.18499
```

```
mse_spline5m4
```

```
## [1] 23.22217
```

Methodology (to include in writeup)