

601.220 Intermediate Programming, Spring 2021

Day 3 Homework and projects submission workflow

<https://piazza.com/jhu/spring2021/601220>

Outline

- Copy files in Unix and remotely
- Submission workflow

Copying files in Unix

- `cp` command in Unix is how we copy files within one machine
- `scp`/`pscp` command is *secure copy*; it's a way to transfer copies from one machine to another
- In Mac Terminal or Windows Power Shell use `scp <source> <destination>`
- Windows with PuTTY installed: Find Command Prompt by searching for `cmd`, then type `pscp <source> <destination>`
- Note that file paths on a Windows machine use a backslash `\` instead of the forward slash `/` used in unix environments

scp sources and destinations

- To copy a file named file.c from your home directory on ugrad to a local machine, use the command *on the local machine*
- we can refer to the networked ugrad server from our laptops, but we can't address the laptop from the ugrad server

scp <username>@ugradx.cs.jhu.edu:file.c . (in Mac Terminal or Windows Power Shell)

pscp <username>@ugradx.cs.jhu.edu:file.c . (in Windows Command Prompt, after pscp has been downloaded and installed)

If file resides in subfolder HW1 on ugradx and should go into subfolder xyz on local machine, type

scp <username>@ugradx.cs.jhu.edu:HW1/file.c xyz/ (on Mac)

[p]scp <username>@ugradx.cs.jhu.edu:HW1/file.c xyz\ (on Windows)

Bundling files on ugradx with zip

- To pack up several files, type `zip zipped_files.zip file1.c file2.c gitlog.txt`
 - creates `zipped_files.zip` containing `file1.c` `file2.c` and `gitlog.txt`
- confirm that it contains what you wanted (without unpacking it) by typing `unzip -l zipped_files.zip`
- To actually unpack the zip file (i.e. extract its files), type `unzip zipped_files.zip`
- move and unpack in a new/different folder to avoid overwriting the original files!

Unix Tip: I/O redirection

- When executing a command that produces output, we can redirect the result to a textfile instead of having it displayed on the screen using '> outfile', for example `ls > myfiles.txt`
- When executing a command that takes input, we can redirect the input to come from a plain text file instead of the user typing it interactively using '< infile', for example `less < infile.txt`
- We can also use both at once, or use a pipe command '|' to send the standard output of one command directly into standard input for another command. For example, to list your files but view the list one screenful at a time type `ls | less`

Homework workflow

- Write source code, compile and test it, edit as needed until it is correct (continuously add, commit, push your changes to your personal git repo)
- Generate gitlog.txt file documenting your commits `git log > gitlog.txt`
- Bundle files for submission with `zip hw0.zip file1.c file2.c gitlog.txt`
- Confirm that your zip file contains everything you need with `unzip -l hw0.zip`
- Transfer the bundle onto local machine, if zip file is in a directory named HW0 `scp <username>@ugradx.cs.jhu.edu:HW0/hw0.zip .`
- Upload hw0.zip to Gradescope, wait for autograder feedback; resubmit?

In-class exercise

- Find link for Exercises 1-2 and 1-3 on course website and follow instructions there
- Follow the instructions; raise your hand if you get stuck

For next meeting

- (If not already done) Complete Exercises 1-2 and 1-3
- (If not already done) Go to github.com and sign up for a free account