

# Intermediate Programming

## Day 6

# Outline

- File I/O
- Assertions
- Writing functions
- Command line arguments
- Review questions

# File I/O

- To read to / write from the command line, we use the commands
  - `int printf( const char format_str[] , ... );`
  - `int scanf( const char format_str[] , ... );`
- These are special instances of more general functions:
  - `int printf( format_str[] , ... ) = fprintf( stdout , format_str , ... );`
  - `int scanf( format_str[] , ... ) = fscanf( stdin , format_str , ... );`
- `stdout` and `stdin` are instances of file-handles

# File-handles

- Different operating systems store data in different ways
- To avoid having to tailor code to the OS, C supports *file-handles*
  - These are abstract representations of objects we can read from / write to
    - Files on disk
    - Command line
    - Sockets across a network
    - etc.

# File-handles

- When working with file handles we:
  1. Create a file handle
  2. Access the file's contents
  3. Close the handle

```
#include <stdio.h>
int main( void )
{
    FILE* fp = fopen( "foo.txt" , "w" );
    if( !fp )
    {
        fprintf( stderr , ... );
        return 1;
    }
    fprintf( fp , "hello\n" );
    fclose( fp );
    return 0;
}
```

# File-handles (opening)

`FILE* fopen( const char file_name[] , const char mode[] );`

```
#include <stdio.h>
int main( void )
{
    FILE* fp = fopen( "foo.txt" , "w" );
    if( !fp )
    {
        fprintf( stderr , ... );
        return 1;
    }
    fprintf( fp , "hello\n" );
    fclose( fp );
    return 0;
}
```

# File-handles (opening)

`FILE* fopen( const char file_name[] , const char mode[] );`

- Input:
  - The name of the file

```
#include <stdio.h>
int main( void )
{
    FILE* fp = fopen( "foo.txt" , "w" );
    if( !fp )
    {
        fprintf( stderr , ... );
        return 1;
    }
    fprintf( fp , "hello\n" );
    fclose( fp );
    return 0;
}
```

# File-handles (opening)

`FILE* fopen( const char file_name[] , const char mode[] );`

- Input:
  - The name of the file
  - The mode in which to open the file  
This is a string consisting of characters indicating access intent
    - 'r': read
    - 'w': write
    - 'a': append
    - 'b': binary\*

```
#include <stdio.h>
int main( void )
{
    FILE* fp = fopen( "foo.txt" , "w" );
    if( !fp )
    {
        fprintf( stderr , ... );
        return 1;
    }
    fprintf( fp , "hello\n" );
    fclose( fp );
    return 0;
}
```

\*More on binary file I/O later



# File-handles (opening)

FILE\* fopen( const char file\_name[] , const char mode[] );

- Input:
  - The name of the file
  - The mode in which to open the file  
This is a string of characters indicating intent
- Output:
  - A pointer to a file-handle\*

```
#include <stdio.h>
int main( void )
{
    FILE* fp = fopen( "foo.txt" , "w" );
    if( !fp )
    {
        fprintf( stderr , ... );
        return 1;
    }
    fprintf( fp , "hello\n" );
    fclose( fp );
    return 0;
}
```

\*More on pointers soon

# File-handles (opening)

FILE\* fopen( const char file\_name[] , const char mode[] );

- Input:
  - The name of the file
  - The mode in which to open the file  
This is a string of characters indicating intent
- Output:
  - A pointer to a file-handle
    - The function returns **NULL** (zero) if the system couldn't open the file
      - reading: file doesn't exist
      - writing: file/directory isn't ours
      - writing: the file is already open

```
#include <stdio.h>
int main( void )
{
    FILE* fp = fopen( "foo.txt" , "w" );
    if( !fp )
    {
        fprintf( stderr , ... );
        return 1;
    }
    fprintf( fp , "hello\n" );
    fclose( fp );
    return 0;
}
```

# File-handles (opening)

FILE\* fopen( const char file\_name[] , const char mode[] );

- Input:
  - The name of the file
  - The mode in which to open the file  
This is a string of characters indicating intent
- Output:
  - A pointer to a file-handle
    - The function returns **NULL** (zero) if the system couldn't open the file  
⇒ Check to make sure the command succeeded

```
#include <stdio.h>
int main( void )
{
    FILE* fp = fopen( "foo.txt" , "w" );
    if( !fp )
    {
        fprintf( stderr , ... );
        return 1;
    }
    fprintf( fp , "hello\n" );
    fclose( fp );
    return 0;
}
```

# File-handles (accessing)

- Commands for reading from / writing to a file

- Writing:

- `int fprintf( FILE *fp , const char format_str[] , ... );`

- Writes a formatted string to the specified file-handle

- Returns the number of characters written (a negative value if the write failed)

```
#include <stdio.h>
int main( void )
{
    FILE* fp = fopen( "foo.txt" , "w" );
    if( !fp ) ...
    fprintf( fp , "hello\n" );
    fclose( fp );
    return 0;
}
```

# File-handles (accessing)

- Commands for reading from / writing to a file

- Reading:

- `int fscanf( FILE *fp , const char format_str[] , ... );`

- Reads a formatted string from the specified file-handle
      - Returns the number of variables successfully set

```
#include <stdio.h>
int main( void )
{
    char word[512];
    FILE* fp = fopen( "foo.txt" , "r" );
    if( !fp ) ...
    while( fscanf( fp , "%s" , word )==1 )
        printf( "Read: %s\n" , word );
    fclose( fp );
    return 0;
}
```

# File-handles (accessing)

- Commands for reading from / writing to a file

- Reading:

- `int fscanf( FILE *fp , const char format_str[] , ... );`

- Reads a formatted string from the specified file-handle
      - Returns the number of variables successfully set

```
#include <stdio.h>
int main( void )
{
    char word[512];
    FILE* fp = fopen( "foo.txt" , "r" );
    if( !fp ) ...
    while( fscanf( fp , "%s" , word )==1 )
        printf( "Read: %s\n" , word );
    fclose( fp );
    return 0;
}
```

[NOTE] This function could be unsafe as we might read in a string longer than `word`

# File-handles (closing)

```
int fclose( FILE *fp );
```

- Input:
  - The file-handle
- Output:
  - Returns 0 if the file was successfully closed (EOF if it wasn't)

```
#include <stdio.h>
int main( void )
{
    char word[512];
    FILE* fp = fopen( "foo.txt" , "r" );
    if( !fp ) ...
    while( fscanf( fp , "%s" , word )==1 )
        printf( "Read: %s\n" , word );
    fclose( fp );
    return 0;
}
```

# File-handles (testing)

```
int feof( FILE *fp );
```

- Input:
  - The file-handle
- Output:
  - Returns non-zero if we have read to the end of the file.

```
int ferror( FILE *fp );
```

- Input:
  - The file-handle
- Output:
  - Returns non-zero if the file is in an error state



# `stdin`, `stdout`, and `stderr`

- C defines three file-handles:
  - standard input (`stdin`): the command prompt, for reading
  - standard output (`stdout`): the command prompt, for writing
  - standard error (`stderr`): the command prompt, for writing error messages

# stdin, stdout, and stderr

`stdout` and `stderr` are both file-handles that allow writing to the command prompt

```
#include <stdio.h>
int main( void )
{
    fprintf( stdout, "This is not an error message\n" );
    fprintf( stderr, "This is an error message\n" );
    return 0;
}
```

```
>> ./a.out
This is not an error message
This is an error message
>>
```

# stdin, stdout, and stderr

`stdout` and `stderr` are both file-handles that allow writing to the command prompt

- These are separate file-handles! (e.g. You can redirect them separately)

```
#include <stdio.h>
int main( void )
{
    fprintf( stdout, "This is not an error message\n" );
    fprintf( stderr, "This is an error message\n" );
    return 0;
}
```

```
>> ./a.out > foo.txt
This is an error message
>>
```

# stdin, stdout, and stderr

`stdout` and `stderr` are both file-handles that allow writing to the command prompt

- These are separate file-handles! (e.g. You can redirect them separately)

```
#include <stdio.h>
int main( void )
{
    fprintf( stdout, "This is not an error message\n" );
    fprintf( stderr, "This is an error message\n" );
    return 0;
}
```

```
>> ./a.out > foo.txt
This is an error message
>> more foo.txt
This is not an error message
>>
```

# Outline

- File I/O
- **Assertions**
- Writing functions
- Command line arguments
- Review questions

# assert

- Although your code compiles and runs, it doesn't mean that it does the right thing.
- Sometimes you would like to verify (sanity check) that the code does the right thing.

```
#include <stdio.h>
```

```
int main( void )
```

```
{
```

```
    int a[] = { 11 , 7 , 9 , 5 , 8 , 4 , 2 };
```

```
    int d , sz = sizeof( a ) / sizeof( int );
```

```
    // Sort the integers (poorly)
```

```
    ...
```

```
    // Print the differences
```

```
    for( int i=0 ; i<sz-1 ; i++ )
```

```
    {
```

```
        d = a[i+1]-a[i];
```

```
        printf( "%d\n" , d );
```

```
    }
```

```
    return 0;
```

```
}
```

# assert

- Although your code compiles and runs, it doesn't mean that it does the right thing.
- Sometimes you would like to verify (sanity check) that the code does the right thing.
- C allows you to “assert” that a desired behavior is preserved.
  - Include the `assert.h` header file
  - **assert** the validity of a test
    - If the argument is true, nothing happens
    - Otherwise, the code aborts and a core dump file is generated

```
#include <stdio.h>
#include <assert.h>
int main( void )
{
    int a[] = { 11 , 7 , 9 , 5 , 8 , 4 , 2 };
    int d , sz = sizeof( a ) / sizeof( int );
    // Sort the integers (poorly)
    ...

    // Print the differences
    for( int i=0 ; i<sz-1 ; i++ )
    {
        d = a[i+1]-a[i];
        assert( d>=0 );
        printf( "%d\n" , d );
    }
    return 0;
}
```

# assert

- Although your code compiles and runs, it doesn't mean that it does the right thing.
- Sometimes you would like to verify (sanity check) that the code does the right thing.
- C allows you to “assert” that a desired behavior is preserved.
  - Include the `assert.h` header file
  - **assert** the validity of a test

```
#include <stdio.h>
#include <assert.h>
int main( void )
{
    int a[] = { 11 , 7 , 9 , 5 , 8 , 4 , 2 };
    int d , sz = sizeof( a ) / sizeof( int );
    // Sort the integers (poorly)
    ...

    // Print the differences
    for( int i=0 ; i<sz-1 ; i++ )
    {
        d = a[i+1]-a[i];
        assert( d>=0 );
        printf( "%d\n" , d );
    }
    return 0;
}
```

- If the argument

```
>> ./a.out
```

- Otherwise, the

```
a.out: foo.c:15: main: Assertion `d>=0' failed.Abort (core dumped)
>>
```



# assert

- **assert** is defined as a macro\*
  - ✓ Once we are convinced that the code is correct, we can disable all **assert** statements so they are not evaluated.
    - This can make the code execute more efficiently.

```
#include <stdio.h>
#include <assert.h>
int main( void )
{
    int a[] = { 11 , 7 , 9 , 5 , 8 , 4 , 2 };
    int d , sz = sizeof( a ) / sizeof( int );
    // Sort the integers (poorly)
    ...

    // Print the differences
    for( int i=0 ; i<sz-1 ; i++ )
    {
        d = a[i+1]-a[i];
        assert( d>=0 );
        printf( "%d\n" , d );
    }
    return 0;
}
```

# assert

- **assert** is defined as a macro\*
  - ✓ Once we are convinced that the code is correct, we can disable all **assert** statements so they are not evaluated.
    - This can make the code execute more efficiently.
  - ✗ If the assert statement sets (in addition to testing), that will be ignored.

```
#include <stdio.h>
#include <assert.h>
int main( void )
{
    int a[] = { 11 , 7 , 9 , 5 , 8 , 4 , 2 };
    int d , sz = sizeof( a ) / sizeof( int );
    // Sort the integers (poorly)
    ...

    // Print the differences
    for( int i=0 ; i<sz-1 ; i++ )
    {
        assert( (d = a[i+1]-a[i])>=0 );
        printf( "%d\n" , d );
    }
    return 0;
}
```

# assert

- **assert** is defined as a macro\*
  - ✓ Once we are convinced that the code is correct, we can disable all **assert** statements so they are not evaluated.
    - This can make the code execute more efficiently.
  - ✗ If the assert statement sets (in addition to testing), that will be ignored.

You should use assert to sanity check your code.  
⇒ If your code is correct, the **assert** should never be triggered.

You should not use it to handle malformed user input:

- Failing to open a file for reading.
- Failing to convert a string to a number
- Etc.

```
#include <stdio.h>
#include <assert.h>
int main( void )
{
    int a[] = { 11 , 7 , 9 , 5 , 8 , 4 , 2 };
    int d , sz = sizeof( a ) / sizeof( int );
    // Sort the integers (poorly)
    ...

    // Print the differences
    for( int i=0 ; i<sz-1 ; i++ )
    {

        assert( (d = a[i+1]-a[i])>=0 );
        printf( "%d\n" , d );
    }
    return 0;
}
```

\*more on this later

# Outline

- File I/O
- Assertions
- **Writing functions**
- Command line arguments
- Review questions

# Functions

- A function takes multiple arguments and returns (at most) one value

```
int foo( char c , int i )  
{  
    return i;  
}
```

# Functions

- A function takes multiple arguments and returns (at most) one value

```
int foo( char c , int i )  
{  
    return i;  
}
```

- The function name

# Functions

- A function takes multiple arguments and returns (at most) one value

```
int foo( char c , int i )  
{  
    return i;  
}
```

- The function name
- The return type (could be `void` if nothing is returned)

# Functions

- A function takes multiple arguments and returns (at most) one value

```
int foo(char c , int i)  
{  
    return i;  
}
```

- The function name
- The return type (could be `void` if nothing is returned)
- The list of argument types



# Functions

- A function takes multiple arguments and returns (at most) one value

```
int foo( char c , int i )  
{  
    return i;  
}
```

- The function name
- The return type (could be `void` if nothing is returned)
- The list of argument types
- The function body
  - Needs to be in braces, even if the function is just one command
  - Needs to return what something of the type it promised to return

# Functions

- We've seen that `string.h` provides a number of useful functions for processing strings:
  - `size_t strlen( const char str[] ){ ... }`
    - Returns the length of a string
  - `char* strcpy( char destination[] , const char source[] ){ ... }`
    - Copies the source string into the destination
  - `char* strcat( char destination[] , const char source[] ){ ... }`
    - Concatenates the source string to the destination
  - etc.

# Functions

- Similarly `math.h` provides a number of useful functions for processing numbers:
  - `double sqrt( double x )`
    - Returns the square-root,  $\sqrt{x}$
  - `double exp( double x )`
    - Returns the exponential,  $e^x$
  - `double pow( double x , double y )`
    - Returns the exponential of the base,  $x^y$
  - `double cos( double x )`
    - Returns the cosine of an angle (in radians)
  - `double ceil( double x )`
    - Returns the ceiling of a number,  $\lceil x \rceil$
  - etc.

# Functions

- Similarly `math.h` provides a number of mathematical functions:
  - `double sqrt( double x )`
    - Returns the square-root,  $\sqrt{x}$
  - `double exp( double x )`
    - Returns the exponential,  $e^x$
  - `double pow( double x , double y )`
    - Returns the exponential of the base,  $x^y$
  - `double cos( double x )`
    - Returns the cosine of an angle (in radians)
  - `double ceil( double x )`
    - Returns the ceiling of a number,  $\lceil x \rceil$
  - etc.

```
#include <stdio.h>
#include <stdlib.h>
#include <math.h>
int main( void )
{
    char str[16];
    printf( "Enter a number: " );
    if( scanf( " %s" , str )!=1 )
        printf( "Failed to read in number\n" );
    else
        printf( "Sqrt( %f ) = %f\n" ,
                atof(str) , sqrt( atof( str ) ) );
    return 0;
}
```

```
>> gcc temp.c -std=c99 -pedantic -Wall -Wextra
/tmp/cc1JmVjw.o: In function `main':
temp.c:(.text+0x3a): undefined reference to `sqrt'
collect2: error: ld returned 1 exit status
>>
```

To access the math functionality, need to include the math library (add `"-lm"` at compile time).

# Functions

- Similarly `math.h` provides a number of functions:
  - `double sqrt( double x )`
    - Returns the square-root,  $\sqrt{x}$
  - `double exp( double x )`
    - Returns the exponential,  $e^x$
  - `double pow( double x , double y )`
    - Returns the exponential of the base,  $x^y$
  - `double cos( double x )`
    - Returns the cosine of an angle (in radians)
  - `double ceil( double x )`
    - Returns the ceiling of a number,  $\lceil x \rceil$
  - etc.

```
#include <stdio.h>
#include <stdlib.h>
#include <math.h>
int main( void )
{
    char str[16];
    printf( "Enter a number: " );
    if( scanf(str)!=1 )
        printf( "Failed to read in number\n" );
    else
        printf( "Sqrt( %f ) = %f\n" ,
                atof(str) , sqrt( atof( str ) ) );
    return 0;
}
```

```
>> gcc temp.c -std=c99 -pedantic -Wall -Wextra -lm
>> ./a.out
Enter a number: 12345
Sqrt( 12345.000000 ) = 111.108056
>>
```

# Functions

You can also write your own:

- (For now) define the function before `main`

```
#include <stdio.h>
#include <stdlib.h>
double CelsiusToFahrenheit( double c ){ return c * 1.8 + 32.; }
int main( void )
{
    char str[16];
    printf( "Enter a temperature in Celsius: " );
    if( scanf( " %s" , str )!=1 ) printf( "Failed to read temperature\n" );
    else printf( "%f -> %f\n" , atof(str) , CelsiusToFahrenheit( atof( str ) ) );
    return 0;
}
```

# Functions

Factoring your code into functions – instead of putting everything in `main` – has major advantages:

- Keeps you concentrating on smaller problems
- Makes code more readable
- Helps with testing
  - Can test *functions* one by one
  - Tests are easy to write; call function with certain inputs, assert something about return value
- Easier to collaborate
  - “I’ll write functions X and Y, you write everything else assuming you have X and Y.”

# Functions

Argument values in C are passed by value

⇒ The function sees a copy of the value passed in as an argument

⇒ Changes made to the argument within the function will not be seen when the function returns.

```
#include <stdio.h>
void increment( int i ) { i += 1; }
int main( void )
{
    int i = 1;
    printf( "i = %d\n" , i );
    increment( i );
    printf( "i = %d\n" , i );
    return 0;
}
```

```
>> gcc temp.c -std=c99 -pedantic -Wall -Wextra
>> ./a.out
i = 1
i = 1
>>
```



# Functions

- A function can return (at most) one value:  
`double exp( double exponent )`
- What happens if we want the function to return two values?
  - E.g. Divide two integers and return both the quotient and the remainder.

# Outline

- File I/O
- Assertions
- Writing functions
- **Command line arguments**
- Review questions

# Command line arguments

One way to get input to an executable is to enter it in `STDIN` and have the program read it in using `scanf`.

But we can also pass arguments directly to the `main` function.

- These will necessarily be strings
- We need to let the `main` function know how many were specified.

# Command line arguments

```
int main( void ){...}
```



```
int main( int argc , char *argv[] ){ ... }
```

Input:

# Command line arguments

```
int main( void ){...}  
    ↓
```

```
int main( int argc , char *argv[] ){ ... }
```

## Input:

- The first argument gives the number command linear arguments provided  
*The executable name is always the first command line argument*

# Command line arguments

```
int main( void ){...}  
  ↓
```

```
int main( int argc , char *argv[] ){ ... }
```

## Input:

- The first argument gives the number command linear arguments provided  
*The executable name is always the first command line argument*
- The second argument is an array of strings, corresponding to the different command line arguments.

# Command line arguments

```
int main( v  
↓  
int main( int argc , c  
#include <stdio.h>  
int main( int argc , char *argv[] )  
{  
    for( int i=0 ; i<argc ; i++ )  
        printf( "%d] %s\n" , i , argv[i] );  
    return 0;  
}
```

## Input:

- The first argument gives the number of

*The executable name is always*

- The second argument is an array of  
command line arguments.

```
>> ./a.out all the other slim shadys are just imitating  
0] ./a.out  
1] all  
2] the  
3] other  
4] slim  
5] shadys  
6] are  
7] just  
8] imitating  
>>
```

# Outline

- File I/O
- Assertions
- Writing functions
- Command line arguments
- Review questions



# Review questions

1. Is `fprintf( stdout, "xxx")` the same as `printf("xxx")`?

# Review questions

2. When should we use assertions instead of an *if* statement?

# Review questions

3. What will happen if you pass an `int` variable to a function that takes a `double` as its parameter?  
What will happen if a `double` is passed to an `int` parameter?

# Review questions

4. What is “pass by value”?

# Review questions

5. How do you change the `main` function so that it can accept command-line arguments?

# Exercise 2-3

- Website -> Course Materials -> Ex2-3