

# MA677HW3

Jiahao Xu

03/08/2019


1.

```
Df1=read.table("maybe_uniform.txt")
```

```
## Warning in read.table("maybe_uniform.txt"): incomplete final line found by  
## readTableHeader on 'maybe_uniform.txt'
```

```
test1=c(Df1$V1,Df1$V2,Df1$V3,Df1$V4,Df1$V5)  
ks.test(test1,"punif")
```

```
##  
## One-sample Kolmogorov-Smirnov test  
##  
## data: test1  
## D = 0.18, p-value = 0.3501  
## alternative hypothesis: two-sided  
x<-seq(-5, 5, by=0.01)  
fx <- ifelse(x > 0 & x <=0.5, 2/3,  
  ifelse(x > 0.5 & x < 1, 0.5, 0))  
plot(x,fx)
```



```
ks.test(fx,"punif")
```

```
## Warning in ks.test(fx, "punif"): ties should not be present for the  
## Kolmogorov-Smirnov test
```

```
##  
## One-sample Kolmogorov-Smirnov test
```

```
##
## data:  fx
## D = 0.9011, p-value < 2.2e-16
## alternative hypothesis: two-sided
```

According to result of ks-test(P-value bigger than 0.05, fail to reject), therefore, these data is distributed as a Uniform distribution on  $[0,1]$ . Since in ks-test, the D value of fx is bigger than that of data, the model below is not better than the Uniform

2.

```
Df2=read.table("maybe_normal.txt")
```

```
## Warning in read.table("maybe_normal.txt"): incomplete final line found by
## readTableHeader on 'maybe_normal.txt'
```

```
d=c(Df2$V1,Df2$V2,Df2$V3,Df2$V4,Df2$V5)
```

```
test2=(c(Df2$V1,Df2$V2,Df2$V3,Df2$V4,Df2$V5)-rep(26,4))/2
```

```
## Warning in c(Df2$V1, Df2$V2, Df2$V3, Df2$V4, Df2$V5) - rep(26, 4):
```

```
##
```

```
ks.test(test2,"pnorm")
```

```
##
```

```
## One-sample Kolmogorov-Smirnov test
```

```
##
```


```
## data:  test2
```

```
## D = 1, p-value = 3.331e-16
```


```
## alternative hypothesis: two-sided
```

```
qqnorm(d)
```

**Normal Q-Q Plot**



```
hist(d)
```



According to Ks-test (p smaller than 0.05 fail to reject) and qqnorm, the data generally follow normal distribution.

3.

```
Df31=read.table("maybe_same_1.txt")
```

```
## Warning in read.table("maybe_same_1.txt"): incomplete final line found by  
## readTableHeader on 'maybe_same_1.txt'
```

```
x=c(Df31$V1,Df31$V2,Df31$V3,Df31$V4,Df31$V5)  
Df32=read.table("maybe_same_2.txt")
```

```
## Warning in read.table("maybe_same_2.txt"): incomplete final line found by  
## readTableHeader on 'maybe_same_2.txt'
```

```
y=c(Df32$V1,Df32$V2,Df32$V3,Df32$V4,Df32$V5)  
ks.test(x,y)
```

```
## Warning in ks.test(x, y): cannot compute exact p-value with ties
```

```
##  
## Two-sample Kolmogorov-Smirnov test  
##  
## data: x and y  
## D = 0.15, p-value = 0.9639  
## alternative hypothesis: two-sided
```

```
ks.test(x+2,y)
```

```
## Warning in ks.test(x + 2, y): cannot compute exact p-value with ties
```

```
##
## Two-sample Kolmogorov-Smirnov test
##
## data:  x + 2 and y
## D = 0.85, p-value = 2.129e-07
## alternative hypothesis: two-sided
```


Since p-value of  $ks.test(X,Y)$  is much larger than 0.05. Then we fail to reject the null hypotheses, thus  $X$  and  $Y$  are from the same distribution. Since p-value of  $ks.test(X+2,Y)$  is much smaller than 0.05. Then we reject the null hypotheses, therefore  $X+2$  and  $Y$  are not from the same distribution

4.

```
Df4=readRDS("norm_sample.Rdata")
Df4_ecdf=ecdf(Df4)
summary(Df4_ecdf)
```

```
## Empirical CDF:      25 unique values with summary
##   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## -2.4600 -0.2100  0.4000  0.2448  1.0700  1.7600
```

```
plot.ecdf(Df4)
```





```
us=rnorm(25)
ks.test(Df4,us)
```

```
##
## Two-sample Kolmogorov-Smirnov test
##
## data:  Df4 and us
## D = 0.24, p-value = 0.4755
## alternative hypothesis: two-sided
```

5.

```
#Find a 95for  $F(4.9) - F(4.3)$ .
Df51=read.table("faithful.dat",header=TRUE,skip=25,sep="")
Df52=read.table("fijiquakes.dat",header=T,sep="")
mag<-Df52$mag
par(mfrow=c(2,1))
hist( mag,main="Earthquake Fiji data")
u<-ecdf(mag)
plot(u)
```



```
print(th<-u(4.9)-u(4.3))
```

```
## [1] 0.526
```

```
# Estimate a 90 percent confidence interval for the mean waiting time
ecdf.ksCI(Df51$waiting)
```

