PowerSDR Setting

15 Sep, 2019 JI1UDD

[Hardware Config]

- If ATU (eg. ICOM AH-4) control function is disabled, Select Alex. If enabled, Select Apollo.



[HPSDR]

- If AK4951 Speaker output is enabled, Select Random Enabled.



[Option]

- CW Delay Key-Up and Key Down is adjustable.
- Refer to https://github.com/ji1udd/Hermes-Lite/blob/6M/audiocodec/docs/Keyer_Sequece_and_setting.pdf



[Hermes Ctrl]

- No need to setup.



[Alex - HPF/LPF]

・If Auto filter mode is enabled (recommended), Select Firmware.



・If Manual filter mode is enabled, Select Manual and Set HPF and LPF freq.



[Apollo]

- If Apollo is selected on Hardware Config tab, Select Enable Filters.
- If ATU (eg. ICOM AH-4) control function is enabled, Select Enable Tuner. Refer to https://github.com/ji1udd/Hermes-Lite2/tree/ATU



[DSP - CW]

- Select Radio on Primary pull-down menu.
- Refer to https://github.com/ji1udd/Hermes-Lite/blob/6M/audiocodec/docs/Keyer_Sequece_and_setting.pdf



[Transmit]

- Select Mic In.
- If Mic Boost is needed, Select 20dB Mic Boost .



[PA Settings]

- Set 38.8dB (all band).