Plan of the Lecture

- Review: prototype 2nd-order system
- Today's topic: transient response specifications

Goal: develop formulas and intuition for various features of the transient response: rise time, overshoot, settling time.

Reading: FPE, Sections 3.3–3.4; lab manual

Prototype 2nd-Order System

DC gain = 1

$\zeta \in (0, \infty)$

$$H(s) = \frac{\omega_n^2}{s^2 + 2\zeta\omega_n s + \omega_n^2}$$

By the quadratic formula, the poles are:

$$\begin{aligned} s &= -\zeta\omega_n \pm \omega_n\sqrt{\zeta^2 - 1} \\ &= -\omega_n\left(\zeta \pm \underbrace{\sqrt{\zeta^2 - 1}}_{\Delta}\right) \end{aligned}$$

$\zeta^2 > 1 \Rightarrow \Delta > 0$

$\sqrt{\zeta^2 - 1} < \zeta$

The nature of the poles changes depending on ζ:

- $\zeta > 1$ both poles are real and negative
- $\zeta = 1$ one negative pole
- $\zeta < 1$ two complex poles with negative real parts

$$s = -\sigma \pm j\omega_d$$

where $\sigma = \zeta\omega_n, \;\; \omega_d = \omega_n\sqrt{1 - \zeta^2}$

Prototype 2nd-Order System

$$H(s) = \frac{\omega_n^2}{s^2 + 2\zeta\omega_n s + \omega_n^2}, \qquad \zeta < 1$$

The poles are

$$s = -\zeta\omega_n \pm j\omega_n\sqrt{1-\zeta^2} = -\sigma \pm j\omega_d$$



Note that

$$\begin{aligned} \sigma^2 + \omega_d^2 &= \zeta^2\omega_n^2 + \omega_n^2 - \zeta^2\omega_n^2 \\ &= \omega_n^2 \end{aligned}$$

$$\cos\varphi = \frac{\zeta\omega_n}{\omega_n} = \zeta$$

$\cos\varphi = \zeta$

2nd-Order Response

Let's compute the system's impulse and step response:

$$H(s) = \frac{\omega_n^2}{s^2 + 2\zeta\omega_n s + \omega_n^2} = \frac{\omega_n^2}{(s+\sigma)^2 + \omega_d^2}$$

- Impulse response:

$$h(t) = \mathscr{L}^{-1}\{H(s)\} = \mathscr{L}^{-1}\left\{\frac{(\omega_n^2/\omega_d)\omega_d}{(s+\sigma)^2 + \omega_d^2}\right\}$$

$$= \frac{\omega_n^2}{\omega_d} e^{-\sigma t} \sin(\omega_d t) \qquad \text{(table, \# 20)}$$

step!

- Step response:

$$\mathscr{L}^{-1}\left\{\frac{H(s)}{s}\right\} = \mathscr{L}^{-1}\left\{\frac{\sigma^2 + \omega_d^2}{s[(s+\sigma)^2 + \omega_d^2]}\right\}$$

$$= 1 - e^{-\sigma t}\left(\cos(\omega_d t) + \frac{\sigma}{\omega_d}\sin(\omega_d t)\right) \qquad \text{(table, \#21)}$$

2nd-Order Step Response

$$H(s) = \frac{\omega_n^2}{s^2 + 2\zeta\omega_n s + \omega_n^2} = \frac{\omega_n^2}{(s+\sigma)^2 + \omega_d^2}$$

$$u(t) = 1(t) \qquad \longrightarrow \qquad y(t) = 1 - e^{-\sigma t}\left(\cos(\omega_d t) + \frac{\sigma}{\omega_d}\sin(\omega_d t)\right)$$

where $\sigma = \zeta\omega_n$ and $\omega_d = \omega_n\sqrt{1-\zeta^2}$ (damped frequency)



The parameter ζ is called the *damping ratio*

- $\zeta > 1$: system is overdamped 2 real, <0 roots
- $\zeta < 1$: system is underdamped
- $\zeta = 0$: no damping ($\omega_d = \omega_n$) periodic behavior

$\zeta = 0 \Rightarrow \sigma = 0.$

2nd-Order Step Response

$$H(s) = \frac{\omega_n^2}{s^2 + 2\zeta\omega_n s + \omega_n^2} = \frac{\omega_n^2}{(s+\sigma)^2 + \omega_d^2}$$

$$u(t) = 1(t) \qquad \longrightarrow \qquad y(t) = 1 - e^{-\sigma t}\left(\cos(\omega_d t) + \frac{\sigma}{\omega_d}\sin(\omega_d t)\right)$$

where $\sigma = \zeta\omega_n$ and $\omega_d = \omega_n\sqrt{1-\zeta^2}$ (damped frequency)

We will see that the parameters ζ and ω_n determine certain important features of the transient part of the above step response.

We will also learn how to pick ζ and ω_n in order to *shape* these features according to given *specifications*.

using PFE, a complicated (ie high degree) TF can be decomposed as a sum of linear & quadratic TF

Transient Response Specifications: Rise Time

Let's first take a look at *1st-order step response*

$$H(s) = \frac{a}{s+a}, \qquad a > 0 \qquad \text{(stable pole)}$$

DC gain $= 1$ (by FVT)

$H(s) = \frac{1}{s+a} + \frac{bs+d}{s^2+\dots}$

using linearity of $\mathcal{L}$, $\mathcal{L}^{-1} H(s)$ $\mathcal{L}^{-1}$ of the terms

Step response: $$Y(s) = \frac{H(s)}{s} = \frac{a}{s(s+a)} = \frac{1}{s} - \frac{1}{s+a}$$

$$y(t) = \mathscr{L}^{-1}\{Y(s)\} = 1(t) - e^{-at}$$

$\mathcal{L}^{-1}(1/s) = 1_s$

$\mathcal{L}^{-1}\left(\frac{1}{s+a}\right) = e^{-at}$



$y(t) = 1$ only at $t = \infty$

Rise time t_r: the time it takes to get from 10% of steady-state value to 90%

Rise Time

Step response: $y(t) = 1(t) - e^{-at}$



Rise time t_r: the time it takes to get from 10% of steady-state value to 90%

In this example, it is easy to compute t_r analytically:

$$1 - e^{-at_{0.1}} = 0.1 \qquad e^{-at_{0.1}} = 0.9 \qquad t_{0.1} = -\frac{\ln 0.9}{a}$$

$$1 - e^{-at_{0.9}} = 0.9 \qquad e^{-at_{0.9}} = 0.1 \qquad t_{0.9} = -\frac{\ln 0.1}{a}$$

$$t_r = t_{0.9} - t_{0.1} = \frac{\ln 0.9 - \ln 0.1}{a} = \frac{\ln 9}{a} \approx \frac{2.2}{a}$$

a large → small rise time.

Transient Response Specs

H(s) = 1st order + 2nd order

Now let's consider the more interesting case: *2nd-order response*

$$\rightarrow H(s) = \frac{\omega_n^2}{s^2 + 2\zeta\omega_n s + \omega_n^2} = \frac{\omega_n^2}{(s+\sigma)^2 + \omega_d^2}$$

where $\sigma = \zeta\omega_n$ $\omega_d = \omega_n\sqrt{1-\zeta^2}$ $\qquad (\zeta < 1)$



Step response: $$y(t) = 1 - e^{-\sigma t}\left(\cos(\omega_d t) + \frac{\sigma}{\omega_d}\sin(\omega_d t)\right)$$

Transient-Response Specs

Step response: $$y(t) = 1 - e^{-\sigma t}\left(\cos(\omega_d t) + \frac{\sigma}{\omega_d}\sin(\omega_d t)\right)$$



- rise time t_r — time to get from $0.1y(\infty)$ to $0.9y(\infty)$
- overshoot M_p and peak time t_p
- settling time t_s — first time for transients to decay to within a specified small percentage of $y(\infty)$ and stay in that range (we will usually worry about 5% settling time)

Transient-Response (or Time-Domain) Specs



Do we want these quantities to be large or small?

- t_r small ✓
- M_p small ✓
- t_p small ✓
- t_s small ✓

$t_p < t_s$

Trade-offs among specs: decrease $t_r \longrightarrow$ increase M_p, etc.



y(t)
1.4
1.2
1.0
0.8
0.6
0.4
0.2
M_p
1.05
.95
ω_n t_r
ω_n t_p
ω_n t_s
2
4
6
8
10
12
14
ω_n t

Formulas for TD Specs: Rise Time



$$t_r = \frac{1.8}{\omega_n}$$

Rise time t_r — hard to calculate analytically.
Empirically, on the normalized time scale ($t \to \omega_n t$), rise times are *approximately* the same

$$\boxed{w_n t_r \approx 1.8} \qquad \text{(exact for } \zeta = 0.5\text{)}$$

So, we will work with $t_r \approx \dfrac{1.8}{\omega_n}$ (good approx. when $\zeta \approx 0.5$)

Formulas for TD Specs: Overshoot & Peak Time



t_p is the *first time* $t > 0$ when $y'(t) = 0$

$$y(t) = 1 - e^{-\sigma t}\left(\cos(\omega_d t) + \frac{\sigma}{\omega_d}\sin(\omega_d t)\right)$$

$$\frac{d\,y(t)}{dt} = y'(t) = \left(\frac{\sigma^2}{\omega_d} + \omega_d\right) e^{-\sigma t}\sin(\omega_d t) = 0 \text{ when } \omega_d t = 0, \pi, 2\pi, \ldots$$

$\sin(x) = 0 \iff x = k\pi$

so $t_p = \dfrac{\pi}{\omega_d}$

Formulas for TD Specs: Overshoot & Peak Time

$\omega_d t = \pi$

M_p



$$M_p = \exp\left(\frac{-\pi\zeta}{\sqrt{1-\zeta^2}}\right)$$

We have just computed $\boxed{t_p = \dfrac{\pi}{\omega_d}}$

To find M_p, plug this value into $y(t)$: $t \leftarrow t_p = \pi/\omega_d$

$$M_p = y(t_p) - 1 = -e^{-\frac{\sigma\pi}{\omega_d}} \left(\underbrace{\cos\left(\omega_d \frac{\pi}{\omega_d}\right)}_{=-1} + \frac{\sigma}{\omega_d} \underbrace{\sin\left(\omega_d \frac{\pi}{\omega_d}\right)}_{0} \right)$$

$$= \exp\left(-\frac{\sigma\pi}{\omega_d}\right) = \exp\left(-\frac{\pi\zeta}{\sqrt{1-\zeta^2}}\right) \quad \text{— exact formula}$$

Formulas for TD Specs: Settling Time



$$\boxed{t_s = 3/\sigma}$$

$$t_s = \min\left\{ t > 0 : \frac{|y(t') - y(\infty)|}{y(\infty)} \le 0.05 \text{ for all } t' \ge t \right\}$$ (here, $y(\infty) = 1$)

$\le .05$ $|y(t)-1|$ bounded

$$|y(t) - 1| = e^{-\sigma t} \left| \cos(\omega_d t) + \frac{\sigma}{\omega_d} \sin(\omega_d t) \right| \le .05$$

$\le 1.$

here, $e^{-\sigma t}$ is what matters (sin and cos are bounded between ± 1), so $e^{-\sigma t_s} \le 0.05$ this gives $t_s = -\dfrac{\ln 0.05}{\sigma} \approx \dfrac{3}{\sigma}$

Formulas for TD Specs

$$H(s) = \frac{\omega_n^2}{s^2 + 2\zeta\omega_n s + \omega_n^2} = \frac{\sigma^2 + \omega_d^2}{(s+\sigma)^2 + \omega_d^2}$$

$$t_r \approx \frac{1.8}{\omega_n}$$

$$t_p = \frac{\pi}{\omega_d}$$

$$M_p = \exp\left(-\frac{\pi\zeta}{\sqrt{1-\zeta^2}}\right)$$

$$t_s \approx \frac{3}{\sigma}$$

TD Specs in Frequency Domain

We want to *visualize* time-domain specs in terms of *admissible pole locations* for the 2nd-order system

$$H(s) = \frac{\omega_n^2}{s^2 + 2\zeta\omega_n s + \omega_n^2} = \frac{\sigma^2 + \omega_d^2}{(s+\sigma)^2 + \omega_d^2}$$

where $\sigma = \zeta\omega_n$

$$\omega_d = \omega_n\sqrt{1-\zeta^2}$$

Step response: $y(t) = 1 - e^{-\sigma t}\left(\cos(\omega_d t) + \frac{\sigma}{\omega_d}\sin(\omega_d t)\right)$



. express poles in terms of σ, ω_d, ζ, ω_n

$$\omega_n^2 = \sigma^2 + \omega_d^2$$

$$\zeta = \cos\varphi$$

. similarly for time specs

Rise Time in Frequency Domain

Suppose we want $t_r \leq c$ (c is some desired given value)

$$t_r \approx \frac{1.8}{\omega_n} \leq c \qquad \Longrightarrow \qquad \omega_n \geq \frac{1.8}{c}$$

I want a system with a rise time $\leq C$.

Geometrically, we want poles to lie in the shaded region:



pole positions that meet requirement!

(recall that ω_n is the *magnitude of the poles*)

Overshoot in Frequency Domain

Suppose we want $M_p \le c$

M_p small $\to$

$$M_p = \underbrace{\exp\left(-\frac{\pi\zeta}{\sqrt{1-\zeta^2}}\right)}_{\text{decreasing function}} \le c$$

— need large damping ratio

$$-\frac{\pi\zeta}{\sqrt{1-\zeta^2}} \le \ln c$$

$$\Rightarrow -\cot\varphi \le \frac{\ln c}{\pi}.$$

φ^*

Geometrically, we want poles to lie in the shaded region:



$$\frac{\zeta}{\sqrt{1-\zeta^2}} = \frac{\omega_n\zeta}{\omega_n\sqrt{1-\zeta^2}}$$

$$= \frac{\sigma}{\omega_d} = \cot\varphi$$

— need φ to be small

Cot φ large
$\Rightarrow$ σ large & ω_d small
$\Rightarrow$ φ small.

Intuition: good damping $\to$ good decay in 1/2 period

Settling Time in Frequency Domain

Suppose we want $t_s \leq c$

$$\boxed{t_s \approx \frac{3}{\sigma}} \leq c \qquad \Longrightarrow \qquad \sigma \geq \frac{3}{c}$$

Want poles to be sufficiently fast (large enough magnitude of real part):



Intuition: poles far to the left $\rightarrow$ transients decay faster $\rightarrow$ smaller t_s

$H(s) = \frac{A}{s+a} + \frac{bs^r}{\cdots}$

Combination of Specs

If we have specs for any combination of t_r, M_p, t_s, we can easily relate them to allowed pole locations:



The shape and size of the region for admissible pole locations will change depending on which specs are more severely constrained.

This is very appealing to engineers: easy to visualize things, no such crisp visualization in time domain.

But: not very rigorous, and also only valid for our prototype 2nd-order system, which has only 2 poles and no zeros ...