

The Feasibility of Small-Scale Wind Power Generation at Kent School, Connecticut: An economic, environmental, and aesthetic analyses

Jiajun Mao, Chun Lam Cheng

1 Macedonia Rd., Kent, CT

Abstract

Carbon-based energy source in electricity generation has already been challenged, in multiple researches, not only for their scarcity(Höök & Tang (2013)) but also their negative impacts on earth's environment. In face of severe environmental challenges such as global warming and its resulting problems such as extreme weathers(Höök & Tang (2013)) and dramatically increasing species, such as amphibian's, extinction rate(Alan Pounds et al. (2006)), a clean and environmentally-friendly energy source is in need. It is evidence through multiple researches that wind power has the potential of subsidizing, if not replacing, the role of power generation by those traditional energy sources. In light of the development of wind power worldwide, it is important for Kent School to also consider using wind power to fulfill parts of the electricity consumption on campus and hopefully reduce campus' environmental footprint. This study specifically focuses on the feasibility of a small-scale wind farm on Kent School's campus through economic, environmental and aesthetic perspectives.

Keywords: Wind, Kent School, Small-scale, Energy, Economic-feasibility

¹Since 1880.

1. Introduction

Kent School receives its electricity from the CT state grid [CONFIRM] (the solar power generated is sold back to the power company), which means that according to the energy sources profile of the CT state grid, 63.7% of the electricity that Kent School uses comes from natural gas and 31.2% comes from nuclear. Also, the data obtained from Kent School's Maintenance Department shows that the annual power consumption is [CONFIRM] MWh. Calculating from the average commercial electricity rates in the state of Connecticut, which is 14.65 cents/kWh, the annual spending of Kent School on electricity consumption is roughly [CONFIRM]. Therefore, the incentives for the installation of wind power generation facility on campus can be concluded into two following parts:

- ***environmental incentives.*** Reduction of school's overall environmental footprint in hope of contributing to the alleviation of environmental problems caused by electricity consumption worldwide.
- ***economic incentives.*** Reduction of school's growing expenditure incurred by student's growing demand in electricity so that school can reach tuition/expenditure balance with each student.

1.1. *environmental incentives*

Though natural gas is a comparably cleaner energy source than traditional carbon-based sources such as coal or petroleum, the burning of natural gas nevertheless still releases carbon dioxide (Laboratory (2010)), one of the most notorious greenhouse gases that are causing the global warming (Shakun et al. (2012)). Therefore, for environmental concerns, the burning of carbon-based energy source should be avoided as much as possible. Wind power, despite the carbon emission generated during the manufacturing processes of the turbines (Kaldellis & Apostolou (2017)), release minimum, if not none, additional greenhouse gases once they become functional (Denny & O'Malley (2006)).

Several reviews have been done regarding the potential or achievement of
30 wind power in reducing the overall carbon emission and other environmentally
harmful gas for electricity generation, as well as our reliance on fossil fuels.
These studies, including Samal & Tripathy (2019)'s Cost savings and emission
reduction capability of wind-integrated power systems and Denny & O'Malley
(2006)'s Wind Generation, Power System Operation, and Emission Reduction
35 demonstrate the possibility and potential of reduction in Kent School's carbon
footprint if wind-power generating facilities are installed on campus, which will
in turn further Kent's path on making the school's operations more environ-
mentally sustainable.

1.2. economic incentives

40 It is evident that to provide students with quality education, Kent School
needs to possess certain degree of financial affluency. However, according to
various sources, including the Headmaster of the school, Fr. Shell, and the
annual report of Kent School [NEED], there is a substantial gap existing between
the tuition and cost for a student. Therefore, to make Kent education truly
45 available to everyone, the operational cost gap for each student must be reduced.
Using wind energy to subsidize the electricity consumption on campus might
make the cost reduction possible.

Again, several studies, including Maria Isabel Blanco's The economics of
wind energy (Blanco (2009)), and The Economics of Wind Energy: A report by
50 the European Wind Energy Association (Awerbuch & Morthorst), prove that
the average cost of operating wind farm could be substantially lower compared
to the cost of buying electricity from the regional power. Therefore, through
the utilization of wind power on campus, Kent School can possibility reduce
the operation cost for a single student become more financially self-sufficient, in
55 turn providing future Kent students a better education.

2. Methods

2.1. Location Determination Factors

When determining the location of the possible wind farm, the location must satisfy the requirements including but not limited to the listed below. When
60 considering a location, requirement 1 and 2 are strict requirement, meaning that if these two requirements are not fulfilled, a location should not be considered even if they satisfy requirement 3 and 4. Requirement 3 and 4 in turn, are loose requirements that do not necessarily have to be fulfilled if economic and environmental benefit of constructing a wind farm outweigh the negative in-
65 fluence. However, if there is a statistically significant portion of student body voicing against the constructin of the wind farm for the reason mentioned in requirement 3 and 4, these two requirements will be weighted more heavily into consideration of the location of the wind farm.

1. *Power and consistent wind.* Whether that location has consistent and
70 powerful wind to make the construction of a wind farm viable. The rough wind speed of that location is reported by students on campus and Jiajun and Chu Lam's personal experience around the campus.
2. *Feasible location.* Whether that location has enough space on the ground and in the air to support the construction of a wind farm. This factor is
75 determined by the proximity to another physical object on the ground level or in the air, such as dormitories, academic/religious buildings, mountains, etc.
3. *Minimal influence on school operations.* Whether the prescence of a wind farm at that location will cause disturbance or negative influence on nor-
80 mal daily school operations. For example, the noise generated by the wind turbine is factored into considerations.
4. *Minimal influence on aesthetic beauty.* Whether the construction of a wind farm at that location will decrease the beauty of the lovely valley land of Kent. This factor is majorly based on Jiajun and Chu Lam's subjectie
85 defintion of beauty.

2.2. Location Determination Process

In order to obtain a general location on campus where the wind is consistent and powerful, a study is done with students population on campus. By assigning each of CL and Jiajun's 54 friends a number and by using a random number
90 generator, we were able to select 30 students to respond to the question of "Where on campus do you think the wind is strongest? And another location where the wind is the second strong?". From the all the responses we receive, we will determine two location with the highest vote and consider them for the second requirement of location feasibility. Taking the second requirement
95 into consideration - location feasibility, we will analyze both sites' proximity to another physical object and conclude whether the two sites from the requirement above satisfy the criteria of having a clear ground level and aerial zone for the construction of a possible wind farm. If any location does not satisfy the criteria for this requirement, it will be eliminated from consideration. Then, from the
100 remaining locations we will analyze their potential influence on school's normal operation, including but not limited to academic activities, atheletic activities, and recreational activities. The negative effects of wind farm will be analyzed and considered such as the noise generated and the space required on the ground level. At last, the remaining sites might cause influence on the aesthetic beauty
105 of the Housatonic valley. A study identical to the one described in requirement one is conducted again with the question "Do you think the construction of a wind farm at site A and/or B will have negative impact on the aesthetic beauty of the surrouding area and the Kent campus?" From the answers received we will analyze the majority side and take that into consideration.

110 2.3. Feasibility Determination Process

After the location is determined by the process described in section 2.2, they will be analyzed for the feasbility of actually constructing a wind farm. Relevant data such as flow volume and wind speed will be collected. To collect such data, HoldPeak's wind anemometer 856A will be used. The device will be setup in
115 the chosen location and the fan that will be measuring the wind speedwill be

setup on top of a tripod 2m above ground level. After a continuous 24 hours of data collection, the data from the wind anemometer is then transferred to the computer and a graph of wind speed/flow volume against time will be plotted.

From the plotted graph as well as the wind speed/flow volume's relationship
120 with the amount of electricity generated we can estimate the economic benefit from the construction of such a wind farm and its possible environmental benefits and consequences. At last we can compare the wind speed and flow volume, as well as the economic/environmental benefit of different locations across campus with each other and other locations in the United States where commercial
125 wind farms are in operation to determine the final feasibility of constructing a wind farm on Kent School's property at a chosen location.


3. Results

3.1. Location Determination Results

After sending out requests to 60 students on campus with the question *Where*
130 *do you think the wind is strongest on campus?* and the options as following,

1. Club Field
2. Headmaster's Field
3. South Field
4. Boardwalk/Main


135 we received 17 response from those 60 questionnaires sent, a response rate of 28.3%. The result of the survey is demonstrated in *Figure 1-1* with Club Field, South Field, and Boardwalk each receiving 5 votes and Headmaster's Field Receiving 2.



From the 60 survey we sent out to random Kent students with the question
 140 *Will Installing Wind Turbines at Following Locations Disrupt the Beautiful Kent Scenery* and the following choices,

1. Club Field
2. South Field
3. Boardwalk/Main

145 we received 12 responses from those 60 questionnaires, a response rate of 20%. The result of the survey is demonstrated in *Figure1-2* with 58% of responses saying yes for Club Field, 8.3% of responses saying yes to South Field, and 33.4% of responses saying yes to Boardwalk.





150 *3.2. Location Wind Speed Result*

For reasons mentioned Section X.X of the error analysis, only wind speed data from the anemometer on top of Dickinson Auditorium is preserved and recorded. We have managed to obtain the wind data for a single day (5/22/2019), an entire week (5/15-5/22/2019) and an entire month (4/22-5/22/2019). For
155 each individual time period we plotted the detail wind speed data averaged for relatively small time frame to accurately reflect the wind speed during that period of time while preserving the visibility in the graphed plots. Then for each time frame we plotted an extra graph using a moving average of a longer period of time, which shows the general trend of the wind speed.

160 It can be seen from *Figure 2-1-2*(single day) that for a single day during spring time, highest wind speed occurs during midday with wind speed reaching as high as 2m/s while the wind speed during morning and evening are only around 0.5m/s. It can also be seen from *Figure 2-2-2*(entire week) that the general trend of wind speed during a week corresponds to daily trend without
165 a clear weekly trend. At last, we can see from *Figure 2-3-2* that wind speed is generally higher at the end of a month.

Graphs are on next page for better formatting







Figure 7: Wind Speed(Boardwalk) 4/22-5/22/2019 Averaged for 2hr





Figure 8: Wind Speed(Boardwalk) 4/22-5/22/2019 Averaged for 1 day



3.3. Location Power Output Result

Figure 9: Instantaneous Power Generation(Boardwalk) on 5/22/2019 Averaged for 10m




Figure 10: Instantaneous Power Generation((Boardwalk) 5/15-5/22/2019 Averaged for 30m





Figure 11: Instantaneous Power Generation((Boardwalk) 4/22-5/22/2019 Averaged for 2hr



4. Analysis

170 4.1. Error Analysis

Though we tried for our best to consider potential locations around the campus that will qualify for the construction of a wind farm, huge experimental error is introduced when determining the feasibility of the location. Most of the experimental errors are introduced during the feasibility determination process
175 when the wind speed at South Field, Club Field and Boardwalk are measured.

4.1.1. Unrealistic height of anemometer

For the HoldPeak 856B anemometer, we installed the anemometer on top of a normal commercial camera tripod. Therefore, the maxium height of measurement for the anemometer was 2m above ground level. A usual commercial
180 wind turbine is not located at this height, apparently, since at this level, the movement of wind is going to be obstructed by surrounding physical objects, such as buildings (Hoerle Hall and Hockey Rink) and natural objects(Trees), and the wind speed pattern is going to be erratic. As the result, the wind speed

measured by the HoldPeak instrument at South Field and Club Field do not
185 accurately reflect the actual wind speed and wind speed pattern a commercial
wind turbine installed at those locations will experience.

The same bias also exist in the data obtained from the AQM65 located on
top of Dickinson Auditorium. Although AQM65 is located substaintially higher
than the HoldPeak instrument measuring the wind speed at Club Field and
190 South Field, it is still at a much lower altitutde than a normal wind turbine,
which on average is about 100m from the ground. Therefore, the data obtianed
from AQM65 also does not reflect the wind speed and wind speed pattern at
the height where a wind turbine will be installed.

However, due to limited measuring equipment, we can only measure the
195 wind speed close to ground level. Therefore, the wind speed data obtained from
AQM65 and HoldPeak 865B will be used as indicators for the wind speed at
higher altitude of that location.

4.1.2. Single direction measurement

Though not a problem for the AQM65 on top of Dickinson Auditorium,
200 the fact that wind speed can only be measured from a constant angle by the
measuring fan is a problem for the HoldPeak instrument. Modern wind turbines
all possess the ability to yaw, pitch and rotate horizontally to match up to the
direction of wind to obtain greatest wind speed thus optimal amount of power
generation. The fan-like design of the HoldPeak 865B make it only capable
205 of measuring the speed of wind coming from one direction. When the wind
changes direction, it will register on HoldPeak as decreased wind speed rather
than change of direction. Contributing bias in the final wind speed data.

4.2. Data Destruction

4.3. Feasibility Analysis

210 Combining the result shown in *Figure 1* the processses described in *Section*
2.2, Club Field, South Field and Boardwalk all satisfy the the location determi-
nation factors 1 (powerful and consitent wind) from the survey result and thus



Figure 12: Picture of HoldPeak 822B

qualify for being considered for the location determination factor 2 (feasible location).

215 Both South Field and Club Field do not have any buildings or natural landscape such as Mount Algos in proximity, therefore they have a clear ground level that would be suitable for the construction of wind farm. We can also see that both South Field and Club Field satisfy the entirety of the location determination factor 2 by not only having a clear ground level but a clear air space above. On
220 the other hand, boardwalk/main is in close proximity to Dickinson Auditorium, Foley Hall and North Dorm, which makes it an impossible location to construct a wind farm due to unclear ground level, thus removed from consideration. As the result, only South Field and Club Field qualify for being considered for location determination factor 3 (minimal influence on school operations).

225 South Field and Club Field are fields actively used for majority of outdoor athletic trainings and events during the fall and spring terms of Kent School. Hence, having a wind farm at those two locations might have impacts on school operations during the construction phase, operation phase, and decommission phase. During the construction phase, areas on both of the fields will be ap-
230 propriated for the construction of roads for transportation of building materials

and passage of construction vehicles, as well as temporary placement of building materials. Therefore, no athletic events and trainings can be carried out during the construction phase. After the construction ended and the wind turbines are in operation, both fields still need to go through recovery period for all the grass
235 that is necessary for athletic events and trainings to grow back. Therefore, we can predict that athletic programs of Kent School are going to be severely disrupted if the construction happens during an academic school year. A solution does exist for the school to construct the wind farm during summer session, which gives Kent School 3 months to finish construction. However, if the construction does not finish in that time frame, disturbances to school operations
240 described above are still going to happen.

Because 91.7% of the people responded think that constructing a wind farm at South Field would not disrupt the landscape of Kent School, South Field satisfies location determination factor 4 and qualify to become one of the potential site for the construction of the wind farm. Surprisingly, though being an
245 open field similar to South Field, 58% of people responded think that constructing a wind farm at Club Field would actually disrupt the beautiful landscape of Kent School. This might be caused by Club Field's close proximity to the main campus so that students will be able to have the wind farm in visual at a higher frequency whereas students rarely visit South Field other than athletic
250 trainings and events and South Field is relatively far away from the main campus. However, since 58% is not statistically significantly higher than 50%, we cannot arrive at the conclusion that majority of the Kent Students will think that constructing a wind farm at Club Field will have negative impacts on the
255 Kent landscape. As the result, Club Field will also be considered as a qualifying location for building a wind farm.

To our surprise, only 33.4% of people responded think that having a wind farm at Boardwalk is going to have negative impacts on Kent scenery considering the location of the Boardwalk - at the center of the main campus and in
260 close proximity to areas of frequency academic activities and student life (dormitories, dining hall, chapel, etc.). Therefore, because of the reason mentioned

in Section X.X of error analysis, we kept Boardwalk/main for the feasibility analysis despite the fact that it does not satisfy location determination factor 2, which is a strict requirement.

265 To conclude, Club Field, South Field and Boardwalk/Main all will be considered as qualifying locations for the construction of a wind farm for Kent School and all three locations will be analyzed for their wind speed to determine whether the economic and environmental benefits of building a wind farm at that location will outweigh the environmental cost and disturbances to the
270 school operation.

References

- Alan Pounds, J., Bustamante, M. R., Coloma, L. A., Consuegra, J. A., Fogden,
M. P. L., Foster, P. N., La Marca, E., Masters, K. L., Merino-Viteri, A.,
Puschendorf, R., Ron, S. R., Sánchez-Azofeifa, G. A., Still, C. J., & Young,
275 B. E. (2006). Widespread amphibian extinctions from epidemic disease driven
by global warming. *Nature*, *439*, 161–167. URL: <https://doi.org/10.1038/nature04246>. doi:10.1038/nature04246.
- Awerbuch, S., & Morthorst, P.-E. (). The economics of wind energy. *The
European Wind Energy Association*, . URL: <http://www.ewea.org>.
- 280 Blanco, M. I. (2009). The economics of wind energy. *Renewable
and Sustainable Energy Reviews*, *13*, 1372 – 1382. URL: [http:
//www.sciencedirect.com/science/article/pii/S1364032108001299](http://www.sciencedirect.com/science/article/pii/S1364032108001299).
doi:<https://doi.org/10.1016/j.rser.2008.09.004>.
- Denny, E., & O'Malley, M. (2006). Wind generation, power system operation,
285 and emissions reduction. *IEEE Transactions on Power Systems*, *21*, 341–347.
doi:10.1109/TPWRS.2005.857845.
- Höök, M., & Tang, X. (2013). Depletion of fossil fuels and anthropogenic
climate change—a review. *Energy Policy*, *52*, 797 – 809. URL: [http:
//www.sciencedirect.com/science/article/pii/S0301421512009275](http://www.sciencedirect.com/science/article/pii/S0301421512009275).
290 doi:<https://doi.org/10.1016/j.enpol.2012.10.046>. Special Section:
Transition Pathways to a Low Carbon Economy.
- Kaldellis, J., & Apostolou, D. (2017). Life cycle energy and car-
bon footprint of offshore wind energy. comparison with onshore
counterpart. *Renewable Energy*, *108*, 72 – 84. URL: [http:
295 //www.sciencedirect.com/science/article/pii/S0960148117301258](http://www.sciencedirect.com/science/article/pii/S0960148117301258).
doi:<https://doi.org/10.1016/j.renene.2017.02.039>.
- Laboratory, N. E. T. (2010). *Volume 1: Bituminous Coal and Natural Gas to
Electricity* volume 1. URL: <https://www.nrc.gov/docs>.

- Samal, R. K., & Tripathy, M. (2019). Cost savings and emission reduction capability of wind-integrated power systems. *International Journal of Electrical Power & Energy Systems*, 104, 549 – 561. URL: <http://www.sciencedirect.com/science/article/pii/S0142061517312814>. doi:<https://doi.org/10.1016/j.ijepes.2018.07.039>.
- Shakun, J. D., Clark, P. U., He, F., Marcott, S. A., Mix, A. C., Liu, Z., Otto-Bliesner, B., Schmittner, A., & Bard, E. (2012). Global warming preceded by increasing carbon dioxide concentrations during the last deglaciation. *Nature*, 484, 49 EP –. URL: <https://doi.org/10.1038/nature10915>. Article.