Supplementary Information: Learning Molecular Response Landscapes Across Bioassays

Anonymous Authors

Supplementary Methods: response and decision implementation

This section specifies SAGP implementation summarized in Materials and Methods. Source potency is normalized as $p = (pIC_{50,A} - 6)/2$; d is the signed A-to-B shift. References are restricted to permitted training compounds and query assay-B values remain hidden.

Slopes are exponentiated clipped log-slopes, adjusted by reference moments; conditional adjustment is suppressed at one reference and fully enabled from three references. The implied prior assay-B potency trend is monotone; the signed shift itself need not increase with source potency. Monotonicity constrains this shared mean, not each molecule's posterior ordering. The chemical residual permits reversals.

Detached reference-conditioned decision adapters

Each query receives an eight-coordinate context summary: reference mean and standard deviation of $|d_s - c|$; reference signed-shift standard deviation; query source-potency displacement from $\bar{p}$; maximum reference Tanimoto similarity; similarity-weighted signed-shift standard deviation; similarity-weighted source-potency distance; and $\log(v)/3$. Weights are proportional to $T(x, x_s)^4 + 10^{-6}$ and normalized over references. These are input summaries, not an independently trained kNN predictor. Coordinates are clipped to $[-5, 5]$. For Task 1, c is the selected-reference median and the two query summaries are averaged. For Task 2, c is the full training-only pair median. No query shift enters these features.

Three independent adapters each contain an $8 \to 12 \to o$ network with SiLU activation, where $o = 2$ for SAR calibration, $o = 2$ for sensitivity magnitude and $o = 1$ for sensitivity risk. Their final layers start at zero. The base event logit is $\ell(h, v) = b + Th/\sqrt{\lambda v + f^2}$, with positive learned T, λ, f. For SAR adapter output u, the risk is

$$P_1 = \text{sigmoid}\{e^{0.5 \tanh u_2} \ell(h_1, v_g) + \tanh u_1\}. \tag{1}$$

For Task 2, the GP signed residual is $e_i = \mu_i - \widetilde{d}_{pair}$. Let $M(e, s)$ be the median of $|N(e, s^2)|$, obtained by five Newton iterations on its folded-normal CDF. A three-parameter global action first produces $q_0 = \max\{0, aM(e_i, \sqrt{\lambda_a \Sigma_{ii}}) + b_a\}$; the contextual magnitude adapter output z gives

$$q_i = \max\{0, e^{0.5 \tanh z_1} q_0 + 0.25 \tanh z_2\}, \qquad P_2 = \text{sigmoid}\{\ell(q_i - 0.5, \Sigma_{ii}) + \tanh t_i\}, \tag{2}$$

where t_i is the independent sensitivity-risk adapter output. GP moments and context features are detached before all decision losses. The magnitude is further detached before sensitivity classification, so binary gradients cannot change its adapter. This separates continuous response learning, magnitude decisions and event decisions. P_1 and P_2 are discriminative risk scores. The variance Σ_{ii} describes signed-shift uncertainty; q_i is the calibrated magnitude.

Objectives, optimization and validation selection

Separate gradient clipping for GP and adapter groups prevents decision gradients from changing GP clipping scales. The initialization checkpoint competes with later checkpoints under the validation rule described in the main text; training completes the full update budget without early stopping.

SAGP stores 1,883 parameters, including 400 contextual decision parameters. The initialization checkpoint remains eligible; it was selected for seed 17, while the other fits selected steps 800, 700, 900 and 900 for seeds 23, 41, 71 and 101. Final-step results are reported separately.

Supplementary Methods: frozen interventions and evaluation

Frozen reference interventions and applicability diagnostics

Additional analyses retain the same five scaffold splits, selected model weights and test queries. Molecular uncertainty and applicability-domain studies motivate assessing prediction confidence separately from point accuracy [Scalia et al., 2020, Liu et al., 2019, Norinder et al., 2014]; regression-calibration methods likewise evaluate whether uncertainty matches observed outcomes [Kuleshov et al., 2018]. Historical supports use the exact original training-only reference manifest capped at 100 observations per assay pair. A deterministic ordering within each split defines nested sets capped at 3, 10, 30 and 100; pairs below a cap retain all available references. Full-cap inference restores the original matrix ordering and reproduces the original predictions to tolerance 2×10^{-4}. A separate full-cap control permutes signed shifts among historical compounds within each pair, preserving the marginal shift distribution and source potencies while disrupting compound–response associations. Task 2 retains its original full-training-pool pair offset and labels at every cap; this tests posterior/readout reference dependence, not end-to-end learning from only k measurements. Task 1's historical replicate-width summary varies with support. One deterministic support order and one shuffle per split are evaluated.

Differences reuse the same 2,000 connected assay/document-component bootstrap draws, with shared weights across dependent seeds. Chemical applicability uses nearest training-reference Tanimoto similarity; SAR comparisons use the smaller of the two molecules' maxima. Global bins retain the original strict within-pair AUROC eligibility rule and leave unevaluable bins missing. Probability reliability is assessed using Brier score and log loss as proper scoring rules [Gneiting and Raftery, 2007], together with ten equal-width-bin ECE [Guo et al., 2017], without test-time recalibration.

Target-concentration diagnostics remove test observations for the ten most frequent targets in each split's capped training-reference pool, without refitting. Selective prediction retains the least uncertain queries by decision entropy or signed-response/contrast posterior variance, with a deterministic random ordering as control. Global retention is complemented by selecting $\lceil f n_{pair} \rceil$ queries from every assay pair, at least one per pair, for $f \in \{0.2, 0.4, 0.6, 0.8, 1.0\}$. All comparator models are scored on identical masks. Pair composition is fixed in the latter analysis, while query class prevalence can still change. Continuous sensitivity rankings are also evaluated at fixed 0.3, 0.5, 1.0 and 1.5 pIC_{50} thresholds.

Bootstrap estimation [Efron, 1979] is adapted to the shared-source dependence: known-pair revision and controlled-ablation differences use 2,000 resamples of connected assay/document components, reusing identical component weight vectors across models and all five dependent seeds. AP is pooled within a seed and then seed-averaged; pair AUROC and MAE are pair-macro then seed-macro. An unevaluable seed invalidates that metric draw rather than changing seed weights.

Response-component implementation

The compact main-text analysis compares fixed-kernel response estimation, a neural response mean, global and reference-conditioned structured means, and SAGP. These share the scaffold evaluation and permitted historical measurements; their response training objectives are not identical. The plot summarizes existing per-query evaluations without fitting new models.

Response-model training variants

The variants share the five splits, identical test cohorts, root-shift training pool, reference sampling, warm starts, 1,000-step budget and validation rule. They include Task-1-only and Task-2-only response supervision, removal of the molecular residual, signed mean slopes, independent contrast variance, and a shared encoder with separate output heads. Episode tensors are checked by SHA-256 within each seed. The first five variants store 1,483 parameters; the shared-encoder control adds 58. The task-level comparison includes different supervision and output constructions.

SAGP final-step sensitivity AP is 0.6436 and MAE is 0.1585. Selected and final-step checkpoints are reported separately to show training-budget sensitivity.

Table S1: Response-model training variants at validation-selected checkpoints. Mean ± split SD; all variants complete 1,000 updates. The SAGP is reported separately.

	Task 1			Task 2		
Model	AP	Pair AUROC	MAE	AP	Pair AUROC	MAE
A: Task 1 only + root	0.538 ± 0.151	0.742 ± 0.055	0.322 ± 0.026	0.646 ± 0.046	0.698 ± 0.036	0.177 ± 0.020
B: Task 2 only + root	0.540 ± 0.152	0.744 ± 0.052	0.322 ± 0.027	0.641 ± 0.040	0.695 ± 0.033	0.172 ± 0.020
D: No chemical residual	0.531 ± 0.149	0.727 ± 0.051	0.329 ± 0.022	0.602 ± 0.058	0.632 ± 0.031	0.175 ± 0.018
E: Signed mean slopes	0.541 ± 0.149	0.744 ± 0.055	0.322 ± 0.027	0.640 ± 0.035	0.698 ± 0.034	0.175 ± 0.025
F: Independent contrast variance	0.539 ± 0.148	0.744 ± 0.056	0.322 ± 0.027	0.647 ± 0.047	0.695 ± 0.034	0.168 ± 0.016
G: Shared encoder, separate heads	0.535 ± 0.152	0.741 ± 0.054	0.324 ± 0.027	0.647 ± 0.049	0.695 ± 0.039	0.164 ± 0.016

Final-step robustness

Table S2: Final-step robustness: test results after the complete 1,000-update budget, without test-based checkpoint switching. Mean ± SD across the same five splits.

	Task 1			Task 2		
Model	AP	Pair AUROC	MAE	AP	Pair AUROC	MAE
A: Task 1 only + root	0.537 ± 0.150	0.743 ± 0.052	0.321 ± 0.027	0.647 ± 0.048	0.699 ± 0.037	0.174 ± 0.018
B: Task 2 only + root	0.541 ± 0.146	0.743 ± 0.054	0.320 ± 0.027	0.647 ± 0.046	0.692 ± 0.032	0.166 ± 0.016
D: No chemical residual	0.528 ± 0.149	0.727 ± 0.051	0.329 ± 0.022	0.605 ± 0.059	0.631 ± 0.031	0.173 ± 0.017
E: Signed mean slopes	0.537 ± 0.148	0.743 ± 0.052	0.321 ± 0.027	0.646 ± 0.049	0.692 ± 0.033	0.169 ± 0.015
F: Independent contrast variance	0.538 ± 0.148	0.744 ± 0.053	0.321 ± 0.027	0.647 ± 0.049	0.693 ± 0.033	0.167 ± 0.016
G: Shared encoder, separate heads	0.534 ± 0.152	0.743 ± 0.052	0.322 ± 0.027	0.646 ± 0.051	0.693 ± 0.038	0.163 ± 0.016
SAGP (ours)	0.537 ± 0.151	0.747 ± 0.052	0.321 ± 0.026	0.644 ± 0.046	0.698 ± 0.044	0.159 ± 0.011

References

B. Efron. Bootstrap Methods: Another Look at the Jackknife. *The Annals of Statistics*, 7(1):1–26, 1979. doi: 10.1214/aos/1176344552.

Tilmann Gneiting and Adrian E Raftery. Strictly Proper Scoring Rules, Prediction, and Estimation. *Journal of the American Statistical Association*, 102(477):359–378, 2007. doi: 10.1198/016214506000001437.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On Calibration of Modern Neural Networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pages 1321–1330, 2017. URL `https://proceedings.mlr.press/v70/guo17a.html`.

Volodymyr Kuleshov, Nathan Fenner, and Stefano Ermon. Accurate Uncertainties for Deep Learning Using Calibrated Regression. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, pages 2796–2804, 2018. URL `https://proceedings.mlr.press/v80/kuleshov18a.html`.

Ruifeng Liu, Hao Wang, Kyle P. Glover, Michael G. Feasel, and Anders Wallqvist. Dissecting Machine-Learning Prediction of Molecular Activity: Is an Applicability Domain Needed for Quantitative Structure–Activity Relationship Models Based on Deep Neural Networks? *Journal of Chemical Information and Modeling*, 59(1):117–126, 2019. doi: 10.1021/acs.jcim.8b00348.

Ulf Norinder, Lars Carlsson, Scott Boyer, and Martin Eklund. Introducing Conformal Prediction in Predictive Modeling. A Transparent and Flexible Alternative to Applicability Domain Determination. *Journal of Chemical Information and Modeling*, 54(6):1596–1603, 2014. doi: 10.1021/ci5001168.

Gabriele Scalia, Colin A. Grambow, Barbara Pernici, Yi-Pei Li, and William H. Green. Evaluating Scalable Uncertainty Estimation Methods for Deep Learning-Based Molecular Property Prediction. *Journal of Chemical Information and Modeling*, 60(6):2697–2717, 2020. doi: 10.1021/acs.jcim.9b00975.