



✓ **Congratulations! You passed!**  
TO PASS 80% or higher

Keep Learning

GRADE  
80%

## Neural Network Basics

LATEST SUBMISSION GRADE

80%

1. What does a neuron compute?

1 / 1 point

- ☐ A neuron computes the mean of all features before applying the output to an activation function
- ☒ A neuron computes a linear function ( $z = Wx + b$ ) followed by an activation function
- ☐ A neuron computes an activation function followed by a linear function ( $z = Wx + b$ )
- ☐ A neuron computes a function  $g$  that scales the input  $x$  linearly ( $Wx + b$ )

✓ **Correct**

Correct, we generally say that the output of a neuron is  $a = g(Wx + b)$  where  $g$  is the activation function (sigmoid, tanh, ReLU, ...).

2. Which of these is the "Logistic Loss"?

1 / 1 point

- ☐  $\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = |y^{(i)} - \hat{y}^{(i)}|^2$
- ☐  $\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = \max(0, y^{(i)} - \hat{y}^{(i)})$
- ☒  $\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = -(y^{(i)} \log(\hat{y}^{(i)}) + (1 - y^{(i)}) \log(1 - \hat{y}^{(i)}))$
- ☐  $\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = |y^{(i)} - \hat{y}^{(i)}|$

✓ **Correct**

Correct, this is the logistic loss you've seen in lecture!

3. Suppose `img` is a (32,32,3) array, representing a 32x32 image with 3 color channels red, green and blue. How do you reshape this into a column vector?

1 / 1 point

- ☐ `x = img.reshape((1,32*32,*3))`
- ☐ `x = img.reshape((3,32*32))`
- ☒ `x = img.reshape((32*32*3,1))`
- ☐ `x = img.reshape((32*32,3))`

✓ **Correct**

4. Consider the two following random arrays "a" and "b":

1 / 1 point

`a = np.random.randn(2, 3)` # `a.shape = (2, 3)` `b = np.random.randn(2, 1)` # `b.shape = (2, 1)` `c = a + b`

What will be the shape of "c"?

- ☒ `c.shape = (2, 3)`
- ☐ `c.shape = (2, 1)`
- ☐ `c.shape = (3, 2)`

☐ The computation cannot happen because the sizes don't match. It's going to be "Error"!

✓ **Correct**

Yes! This is broadcasting. b (column vector) is copied 3 times so that it can be summed to each column of a.

5. Consider the two following random arrays "a" and "b":

0 / 1 point

```
a = np.random.randn(4, 3) # a.shape = (4, 3)
b = np.random.randn(3, 2) # b.shape = (3, 2)
c = a*b
```

What will be the shape of "c"?

☐ c.shape = (4, 3)

☐ c.shape = (3, 3)

☒ c.shape = (4, 2)

☐ The computation cannot happen because the sizes don't match. It's going to be "Error"!

✗ **Incorrect**

No! In numpy the "\*" operator indicates element-wise multiplication. It is different from "np.dot()". If you would try "c = np.dot(a,b)" you would get c.shape = (4, 2).

Also, the broadcasting cannot happen because of the shape of b. b should have been something like (4, 1) or (1, 3) to broadcast properly. So a\*b leads to an error!

6. Suppose you have  $n_x$  input features per example. Recall that  $X = [x^{(1)} x^{(2)} \dots x^{(m)}]$ . What is the dimension of X?

1 / 1 point

☐  $(m, 1)$

☐  $(1, m)$

☐  $(m, n_x)$

☒  $(n_x, m)$

✓ **Correct**

7. Recall that "np.dot(a,b)" performs a matrix multiplication on a and b, whereas "a\*b" performs an element-wise multiplication.

1 / 1 point

Consider the two following random arrays "a" and "b":

```
a = np.random.randn(12288, 150) # a.shape = (12288, 150)
b = np.random.randn(150, 45) # b.shape = (150, 45)
c = np.dot(a,b)
```

What is the shape of c?

☐ The computation cannot happen because the sizes don't match. It's going to be "Error"!

☒ c.shape = (12288, 45)

☐ c.shape = (12288, 150)

☐ c.shape = (150, 150)

✓ **Correct**

Correct, remember that a np.dot(a, b) has shape (number of rows of a, number of columns of b). The sizes match because :

"number of columns of a = 150 = number of rows of b"

8. Consider the following code snippet:

1 / 1 point

```
# a.shape = (3,4)# b.shape = (4,1)for i in range(3): for j in range(4): c[i][j] = a[i][j] + b[j]
```

How do you vectorize this?

- ☐  $c = a.T + b$
- ☒  $c = a + b.T$
- ☐  $c = a + b$
- ☐  $c = a.T + b.T$

✓ Correct

9. Consider the following code:

0 / 1 point

```
a = np.random.randn(3, 3)b = np.random.randn(3, 1)c = a*b
```


What will be c? (If you're not sure, feel free to run this in python to find out).

- ☒ This will invoke broadcasting, so b is copied three times to become (3, 3), and \* invokes a matrix multiplication operation of two 3x3 matrices so c.shape will be (3, 3)
- ☐ This will invoke broadcasting, so b is copied three times to become (3,3), and \* is an element-wise product so c.shape will be (3, 3)
- ☐ It will lead to an error since you cannot use "\*" to operate on these two matrices. You need to instead use np.dot(a,b)
- ☐ This will multiply a 3x3 matrix a with a 3x1 vector, thus resulting in a 3x1 vector. That is, c.shape = (3,1).

✗ Incorrect

10. Consider the following computation graph.

1 / 1 point



What is the output J?

- ☒  $J = (a - 1) * (b + c)$
- ☐  $J = (c - 1) * (b + a)$
- ☐  $J = (b - 1) * (c + a)$
- ☐  $J = a*b + b*c + a*c$

✓ Correct

Yes.  $J = u + v - w = a*b + a*c - (b + c) = a * (b + c) - (b + c) = (a - 1) * (b + c)$ .