

# 目录

|  |   |
|--|---|
| 订单模块API文档  | 2 |
| 注：GET请求需要将参数写在请求头(Header)中，POST、PUT、DELETE的参数写在请求体(Body)中。 | 2 |
| 在Body中添加JSON参数时，一定要在头部加上Content-Type: application/json这个字段 | 2 |
| 服务分类代码含义解释   | 2 |
| 0-跑腿,1-悬赏提问,2-学习辅导,3-技术服务,4-生活服务,5-其他                      | 2 |
| 服务状态代码含义解释   | 2 |
| 0-等待接单,1-正在服务,2-服务完成                                       | 2 |
| 关于用户登录认证的几个通用API返回结果                                       | 2 |
| 订单首页获取所有订单   | 2 |
| 确认完成订单   | 3 |
| 评价订单   | 4 |
| 获取订单详情   | 5 |
| 取消订单   | 6 |

# 订单模块API文档

注：GET请求需要将参数写在请求头(Header)中，POST、PUT、DELETE的参数写在请求体(Body)中。

在Body中添加JSON参数时，一定要在头部加上Content-Type: application/json这个字段

## 服务分类代码含义解释

- 0-跑腿,1-悬赏提问,2-学习辅导,3-技术服务,4-生活服务,5-其他

## 服务状态代码含义解释

- 0-等待接单,1-正在服务,2-服务完成

## 关于用户登录认证的几个通用API返回结果

```
参数缺失: { "status":400, "msg":"need phone or token" }
token不存在: { "status":404,"msg":"token not exists"}
token不正确: { "status":402,"msg":"wrong login token" }
```

## 订单首页获取所有订单

投递方式: GET

投递路径: <http://Bang.cloudshm.com/order/getOrders>

请求样例:

```
GET /order/getOrders HTTP/1.1
cache-control: no-cache
Postman-Token: 539fc243-5e22-41fb-8172-1e920323d1e7
Content-Type: application/json
phone: 15968804215 (手动添加)
token: $2y$10$v5TNNyHCkC1IhG1XFdIdbO4MGhYUDoZA3fZ2z5SFEjdr3rUL (手动添加)
User-Agent: PostmanRuntime/6.1.6
Accept: */*
Host: Bang.cloudshm.com
accept-encoding: gzip, deflate
Connection: keep-alive
```

返回结果:

```
用户不存在: {"status":404,"msg":"user not exists"}
订单获取成功:
```

```
{
  "status": 200,
  "msg": "orders required successfully",
  "data": [
    {
      "id": 3,
      "title": "求帮忙买东西",
      "category": 0,
      "state": 1,
      "content": "内容是买东西",
      "close_time": "2017-07-06 12:00:00",
      "money": "2.50",
      "created_at": null,
      "updated_at": null,
      "applicant": "18645234817",
      "servant": "15968804215"
    },
    {
      "id": 4,
      "title": "求帮忙取快递",
      "category": 0,
      "state": 2,
      "content": "内容是取快递",
      "close_time": "2017-07-06 12:00:00",
      "money": "2.50",
      "created_at": null,
      "updated_at": null,
      "applicant": "18645234817",
      "servant": "15968804215"
    }
  ]
}
```

## 确认完成订单

投递方式: GET

投递路径: <http://Bang.cloudshm.com/order/finishService>

请求样例:

```
GET /order/finishService HTTP/1.1
cache-control: no-cache
Postman-Token: 5e3ebcc6-e6e4-499e-ad26-1c480a1bfada
Content-Type: application/json
phone: 15968804215 (手动添加)
token: $2y$10$v5TNNyHCkC1IhG1XFdIdbO4MGhYUDoZA3fZ2z5SFEjdr3rUL (手动添加)
id: 1 (手动添加)
User-Agent: PostmanRuntime/6.1.6
Accept: */*
```

```
Host: Bang.cloudshm.com
accept-encoding: gzip, deflate
Connection: keep-alive
```

#### 返回结果:

```
参数缺失: { "status":400, "msg":"need id" }
订单不存在: {"status":404,"msg":"order not exists"}
订单状态错误: {"status":402,"msg":"wrong state, the service is not running"}
完成订单成功: {"status":200,"msg":"finish service successfully"}
```

## 评价订单

投递方式: POST

投递路径: <http://Bang.cloudshm.com/order/comment>

请求样例:

```
POST /order/comment HTTP/1.1
cache-control: no-cache
Postman-Token: 86c56331-1cde-4a72-b1c3-d0252ae73857
Content-Type: application/json (手动添加)
User-Agent: PostmanRuntime/6.1.6
Accept: */*
Host: Bang.cloudshm.com
accept-encoding: gzip, deflate
content-length: 125
Connection: keep-alive

{
  "phone" : "15968804215",
  "token" : "$2y$10$v5TNNyHCkC1IhG1XFdIdbO4MGhYUDoZA3fZ2z5SFEjdr3r",
  "id" : 1,
  "star" : 2
}
```

#### 返回结果:

```
参数缺失: { "status":400, "msg":"need star or id" }
订单不存在: {"status":404,"msg":"order not exists"}
用户不存在: {"status":404,"msg":"user not exists"}
评价失败: {"status":402,"msg":"comment failed"}
评价成功: {"status":200,"msg":"comment successfully"}
```

# 获取订单详情

投递方式: GET

投递路径: <http://Bang.cloudshm.com/order/showDetail>

请求样例:

```
GET /order/showDetail HTTP/1.1
cache-control: no-cache
Postman-Token: d15d9ebc-ca24-4bea-814f-ff5150630858
Content-Type: application/json
phone: 15968804215 (手动添加)
token: $2y$10$v5TNNyHCkC1IhG1XFdIdbO4MGhYUDoZA3fZ2z5SFEjdr3rUL (手动添加)
id: 1 (手动添加)
User-Agent: PostmanRuntime/6.1.6
Accept: */*
Host: Bang.cloudshm.com
accept-encoding: gzip, deflate
Connection: keep-alive
```

返回结果:

```
参数缺失: { "status":400, "msg":"need id" }
订单不存在: {"status":404,"msg":"order not exists"}
订单详情获取成功:
{
  "status": 200,
  "msg": "order required successfully",
  "data1": {
    "id": 1,
    "title": "求帮忙取快递",
    "category": 0,
    "state": 2,
    "content": "内容是取快递到12号楼",
    "close_time": "2017-07-06 12:00:00",
    "money": "2.50",
    "created_at": null,
    "updated_at": "2017-07-05 15:06:13",
    "applicant": "15968804215",
    "servant": "18645234817"
  },
  "data2": {
    "applicant_name": "蒋佰言",
    "servant_name": "gaojingran"
  }
}
```

---

# 取消订单

投递方式: DELETE

投递路径: <http://Bang.cloudshm.com/order/cancelOrder>

请求样例:

```
DELETE /order/cancelOrder HTTP/1.1
cache-control: no-cache
Postman-Token: 85200188-065b-43e9-a0f2-21a2497813b8
Content-Type: application/json (手动添加)
User-Agent: PostmanRuntime/6.1.6
Accept: */*
Host: Bang.cloudshm.com
accept-encoding: gzip, deflate
content-length: 111
Connection: keep-alive

{
  "phone" : "15968804215",
  "token" : "$2y$10$v5TNNyHCkC1IhG1XFdIdbO4MGhYUDoZA3fZ2z5SFEjdr3r",
  "id" : 1
}
```

返回结果:

```
参数缺失: { "status":400, "msg":"need id" }
订单表数据删除失败: {"status":402,"msg":"order deleted failed"}
订单取消成功: {"status":200,"msg":"order deleted successfully"}
```

---