

# 目录

求支援API文档	2
注1: GET请求需要将参数写在请求头(Header)中, POST、PUT、DELETE的参数写在请求体(Body)中。	2
注2: 在Body中添加JSON参数时, 一定要在头部加上Content-Type: application/json这个字段	2
服务分类代码含义解释	2
0-跑腿,1-悬赏提问,2-学习辅导,3-技术服务,4-生活服务,5-其他	2
服务状态代码含义解释	2
0-等待接单,1-正在服务,2-服务完成	2
关于用户登录认证的几个通用API返回结果	2
求支援模块提交新订单	2

# 求支援API文档

注1: GET请求需要将参数写在请求头(Header)中, POST、PUT、DELETE的参数写在请求体(Body)中。

注2: 在Body中添加JSON参数时, 一定要在头部加上Content-Type: application/json这个字段

## 服务分类代码含义解释

- 0-跑腿,1-悬赏提问,2-学习辅导,3-技术服务,4-生活服务,5-其他

## 服务状态代码含义解释

- 0-等待接单,1-正在服务,2-服务完成

## 关于用户登录认证的几个通用API返回结果

```
参数缺失: { "status":400, "msg":"need phone or token" }
token不存在: { "status":404,"msg":"token not exists"}
token不正确: { "status":402,"msg":"wrong login token" }
```

## 求支援模块提交新订单

- 投递方式: POST
- 投递路径: <http://Bang.cloudshm.com/askForHelp/createOrder>
- 请求样例:

```
POST /askForHelp/createOrder HTTP/1.1
cache-control: no-cache
Postman-Token: 85200188-065b-43e9-a0f2-21a2497813b8
Content-Type: application/json (手动添加)
User-Agent: PostmanRuntime/6.1.6
Accept: */*
Host: Bang.cloudshm.com
accept-encoding: gzip, deflate
content-length: 111
Connection: keep-alive

{
  "phone" : "15968804215",
  "token" : "$2y$10$v5TNNyHCkC1IhG1XfIdbO4MGhYUDoZA3fZ2z5SFEjdr3r",
  "title": "求帮忙取快递",
  "category": 0,
  "content": "内容是取快递",
  "close_time": "2017-07-06 12:00:00",
  "money": "2.50",
}
```

---

- 返回结果:

```
参数缺失: {"status":400,"msg":"need title or content or category or close_time or money"}
```

```
订单创建失败: {"status":402,"msg":"order created failed"}
```

```
订单创建成功: {"status":200,"msg":"order created successfully"}
```

---