

系统环境：Centos7

1.下载tomcat8.5

- wget <http://mirrors.tuna.tsinghua.edu.cn/apache/tomcat/tomcat-8/v8.5.45/bin/apache-tomcat-8.5.45.tar.gz>

```
1 [root@localhost home]# wget http://mirrors.tuna.tsinghua.edu.cn/apache/tomcat/tomcat-8/v8.5.45/bin/apache-tomcat-8.5.45.tar.gz
2 --2019-09-18 13:25:16-- http://mirrors.tuna.tsinghua.edu.cn/apache/tomcat/tomcat-8/v8.5.45/bin/apache-tomcat-8.5.45.tar.gz
3 正在解析主机 mirrors.tuna.tsinghua.edu.cn (mirrors.tuna.tsinghua.edu.cn)... 101.6.8.193, 2402:f000:1:408:8100::1
4 正在连接 mirrors.tuna.tsinghua.edu.cn (mirrors.tuna.tsinghua.edu.cn)|101.6.8.193|:80... 已连接。
5 已发出 HTTP 请求，正在等待回应... 200 OK
6 长度: 9722154 (9.3M) [application/x-gzip]
7 正在保存至: "apache-tomcat-8.5.45.tar.gz"
8
9 100%[=====
10
11 2019-09-18 13:25:27 (14.9 MB/s) - 已保存 "apache-tomcat-8.5.45.tar.gz" [9722154/9722154]
```

2.解压

```
1 [root@localhost home]# tar -zxvf apache-tomcat-8.5.45.tar.gz
2 apache-tomcat-8.5.45/conf/
3 .....
4 [root@localhost home]# ls -l
5 总用量 9496
6 drwxr-xr-x 9 root root    220 9月 18 13:26 apache-tomcat-8.5.45
7 -rw-r--r-- 1 root root 9722154 8月 15 06:46 apache-tomcat-8.5.45.tar.gz
```


3.运行

```
1 [root@localhost home]# cd apache-tomcat-8.5.45/bin
2 [root@localhost bin]# ./startup.sh
3 Using CATALINA_BASE:   /home/apache-tomcat-8.5.45
4 Using CATALINA_HOME:   /home/apache-tomcat-8.5.45
5 Using CATALINA_TMPDIR: /home/apache-tomcat-8.5.45/temp
6 Using JRE_HOME:        /home/jdk/jre
7 Using CLASSPATH:       /home/apache-tomcat-8.5.45/bin/bootstrap.jar:/home/apache-tomcat-8.5.45/bin/tomcat-juli.jar
8 Tomcat started.
```

浏览器访问：<http://192.168.8.162:8080>，tomcat安装成功

[Home](#) [Documentation](#) [Configuration](#) [Examples](#) [Wiki](#) [Mailing Lists](#) [Find Help](#)

Apache Tomcat/8.5.45



If you're seeing this, you've successfully installed Tomcat. Congratulations!

Recommended Reading:

- [Security Considerations How-To](#)
- [Manager Application How-To](#)
- [Clustering/Session Replication How-To](#)

[Server Status](#)

[Manager App](#)

[Host Manager](#)

Developer Quick Start

[Tomcat Setup](#)
[First Web Application](#)

[Realms & AAA](#)
[JDBC Data Sources](#)

[Examples](#)

[Servlet Specifications](#)
[Tomcat Versions](#)

Managing Tomcat

For security, access to the [manager webapp](#) is restricted. Users are defined in:

```
$CATALINA_HOME/conf/tomcat-users.xml
```

In Tomcat 8.5 access to the manager application is split between different users.
[Read more...](#)

[Release Notes](#)

[Changelog](#)

[Migration Guide](#)

[Security Notices](#)

Documentation

[Tomcat 8.5 Documentation](#)

[Tomcat 8.5 Configuration](#)

[Tomcat Wiki](#)

Find additional important configuration information in:

```
$CATALINA_HOME/RUNNING.txt
```

Developers may be interested in:

- [Tomcat 8.5 Bug Database](#)
- [Tomcat 8.5 JavaDocs](#)
- [Tomcat 8.5 SVN Repository](#)

Getting Help

[FAQ and Mailing Lists](#)

The following mailing lists are available:

[tomcat-announce](#)
Important announcements, releases, security vulnerability notifications. (Low volume).

[tomcat-users](#)
User support and discussion

[taglibs-user](#)
User support and discussion for [Apache Taglibs](#)

[tomcat-dev](#)
Development mailing list, including commit messages

Other Downloads

- [Tomcat Connectors](#)
- [Tomcat Native](#)
- [Taglibs](#)
- [Deployer](#)

Other Documentation

- [Tomcat Connectors](#)
- [mod_jk Documentation](#)
- [Tomcat Native](#)
- [Deployer](#)

Get Involved

- [Overview](#)
- [SVN Repositories](#)
- [Mailing Lists](#)
- [Wiki](#)

Miscellaneous

- [Contact](#)
- [Legal](#)
- [Sponsorship](#)
- [Thanks](#)

Apache Software Foundation

- [Who We Are](#)
- [Heritage](#)
- [Apache Home](#)
- [Resources](#)

Copyright © 2000-2019 Apache Software Foundation. All Rights Reserved.

4.关闭tomcat

```
1 [root@localhost bin]# pwd
2 /home/apache-tomcat-8.5.45/bin
3 [root@localhost bin]# ./shutdown.sh
4 Using CATALINA_BASE:   /home/apache-tomcat-8.5.45
5 Using CATALINA_HOME:   /home/apache-tomcat-8.5.45
6 Using CATALINA_TMPDIR: /home/apache-tomcat-8.5.45/temp
7 Using JRE_HOME:        /home/jdk/jre
8 Using CLASSPATH:       /home/apache-tomcat-8.5.45/bin/bootstrap.jar:/home/apache-tomcat-8.5.45/bin/tomcat-juli.jar
```

5.修改tomcat端口号

修改conf文件下的server.xml，将port端口改成其他端口即可。

```
1 [root@localhost conf]# pwd
2 /home/apache-tomcat-8.5.45/conf
3 [root@localhost conf]# vi server.xml

<Connector port="8080" protocol="HTTP/1.1"
  connectionTimeout="20000"
  redirectPort="8443" />
```

6.tomcat发布服务

将需要发布的静态文件或者war包放在tomcat的webapps路径下，启动tomcat服务即可。

发布多个服务

server.xml配置文件<Host>中添加 <Context path="" docBase="/opt/tomcat/webapps/****"/>