

Assured Machine Learning

Xiaozhe Gu, Arvind Easwaran

School of Computer Science and Engineering
Energy Research Institute (ERI@N)


Nanyang Technological University, Singapore

June, 2018

Machine Learning Applications in Safety-Critical Environments

- ▶ Decision making in life-threatening conditions (Machine-Learning (ML) based medical decision support systems)

Figure: ML Based Brain Disease Diagnosis¹



Machine Learning Applications in Safety-Critical Environments

- ▶ Decision making in life-threatening conditions (Machine-Learning (ML) based medical decision support systems)
- ▶ Robots (surgical robots, industrial robots, etc.)

Figure: ML Based Brain Disease Diagnosis¹




Figure: Surgical Robots²



Machine Learning Applications in Safety-Critical Environments

- ▶ Decision making in life-threatening conditions (Machine-Learning (ML) based medical decision support systems)
- ▶ Robots (surgical robots, industrial robots, etc.)
- ▶ Autonomous vehicles

Figure: Autonomous Shuttle



Figure: ML Based Brain Disease Diagnosis¹




Figure: Surgical Robots²



Challenges to Safety Assurance

- ▶ **Non-transparency**: It is difficult to assess the reliability if the reasoning behind these models cannot be understood

Challenges to Safety Assurance

- ▶ **Non-transparency**: It is difficult to assess the reliability if the reasoning behind these models cannot be understood
- ▶ **Error Rate**: The estimate of error rate of a ML model with respect to the test data is not reliable

Challenges to Safety Assurance

- ▶ **Non-transparency**: It is difficult to assess the reliability if the reasoning behind these models cannot be understood
- ▶ **Error Rate**: The estimate of error rate of a ML model with respect to the test data is not reliable
- ▶ **Instability**: A small change in the training process may produce a different result, and hence it is difficult to debug models or reuse parts of previous safety assessments.

Challenges to Safety Assurance

- ▶ **Non-transparency**: It is difficult to assess the reliability if the reasoning behind these models cannot be understood
- ▶ **Error Rate**: The estimate of error rate of a ML model with respect to the test data is not reliable
- ▶ **Instability**: A small change in the training process may produce a different result, and hence it is difficult to debug models or reuse parts of previous safety assessments.
- ▶ **Difficulty in verification**: Formal verification of ML components is a difficult, and somewhat ill-posed, problem due to the complexity of the underlying ML algorithms and large feature spaces

Potential Strategies for Safety Assurance

- **Interpretability & Transparency:** Improve the interpretability & transparency of the ML component

Figure: Explanations improve trust in prediction [3]



Potential Strategies for Safety Assurance

- ▶ **Interpretability & Transparency**: Improve the interpretability & transparency of the ML component
- ▶ **Fail-Safe**: The model reports that it cannot reliably give a prediction and does not attempt to do so, thereby failing safely

Figure: Explanations improve trust in prediction [3]



Technique used in ML when predictions cannot be given confidently is the **reject option** [4]

$$\hat{y}(x) = \begin{cases} -1 & \text{if } \phi(x) \leq t \\ \text{reject, if } \phi(x) \in (-t, t) \\ 1 & \text{if } \phi(x) \geq t \end{cases}$$

Potential Strategies for Safety Assurance





- ▶ **Interpretability & Transparency:** Improve the interpretability & transparency of the ML component
- ▶ **Fail-Safe:** The model reports that it cannot reliably give a prediction and does not attempt to do so, thereby failing safely
- ▶ **Abstract:** Abstract the ML component and input feature space, and identify scenarios that could cause violation of safety specifications

Figure: Explanations improve trust in prediction [3]



Technique used in ML when predictions cannot be given confidently is the **reject option** [4]

$$\hat{y}(x) = \begin{cases} -1 & \text{if } \phi(x) \leq t \\ \text{reject, if } \phi(x) \in (-t, t) \\ 1 & \text{if } \phi(x) \geq t \end{cases}$$

-  <http://mlcenter.postech.ac.kr/healthcare>
-  <https://www.wired.com/2015/03/google-robot-surgery/>
-  Ribeiro, Marco Tulio, Sameer Singh, and Carlos Guestrin. "Why should i trust you?: Explaining the predictions of any classifier." Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. ACM, 2016.
-  Bartlett P L, Wegkamp M H. Classification with a reject option using a hinge loss[J]. Journal of Machine Learning Research, 2008, 9(Aug): 1823-1840.