

# Machine Learning in Safety-Critical Domain

Arvind Easwaran


Nanyang Technological University, Singapore

July 8, 2015

# Machine Learning Application in Safety Critical Environments

- Decision making in life-threatening conditions (diagnosis, prognosis, machine learning-based medical decision support systems).

Figure: Machine Learning Based Brain Disease Diagnosis<sup>1</sup>



# Machine Learning Application in Safety Critical Environments

- Decision making in life-threatening conditions (diagnosis, prognosis, machine learning-based medical decision support systems).
- Robots (surgical robots, industrial robots, etc)

Figure: Machine Learning Based Brain Disease Diagnosis<sup>1</sup>




Figure: Surgical Robots<sup>2</sup>



# Machine Learning Application in Safety Critical Environments

- Decision making in life-threatening conditions (diagnosis, prognosis, machine learning-based medical decision support systems).
- Robots (surgical robots, industrial robots, etc)
- Autonomous vehicles.

Figure: Autonomous Bus



Figure: Machine Learning Based Brain Disease Diagnosis<sup>1</sup>




Figure: Surgical Robots<sup>2</sup>



NANYANG  
TECHNOLOGICAL  
UNIVERSITY  
SINGAPORE

# Challenges to Achieve Safety

- **Non-transparency**: It is difficult to assess the reliability if the reasoning behind these models could not be understood.

# Challenges to Achieve Safety

- **Non-transparency**: It is difficult to assess the reliability if the reasoning behind these models could not be understood.
- **Error Rate**: The estimate of error rate of a ML model with respect to the test data is not reliable.

# Challenges to Achieve Safety

- **Non-transparency**: It is difficult to assess the reliability if the reasoning behind these models could not be understood.
- **Error Rate**: The estimate of error rate of a ML model with respect to the test data is not reliable.
- **Instability**: A small change in the training process may produce a different result, and hence it is difficult to debug models or reuse parts of previous safety assessments.

# Challenges to Achieve Safety


- **Non-transparency**: It is difficult to assess the reliability if the reasoning behind these models could not be understood.
- **Error Rate**: The estimate of error rate of a ML model with respect to the test data is not reliable.
- **Instability**: A small change in the training process may produce a different result, and hence it is difficult to debug models or reuse parts of previous safety assessments.
- **Difficulty in verification**: Formal verification of machine learning components is a difficult, and somewhat ill-posed problem due to the complexity of the underlying machine learning algorithms, large feature spaces.



# Potential Strategies for Achieving Safety

- **Interpretability & Transparency:**  
Improve the interpretability & transparency of the ML component.

Figure: Explanations make the user to trust the prediction [3]



# Potential Strategies for Achieving Safety

- **Interpretability & Transparency:** Improve the interpretability & transparency of the ML component.
- **Safe Fail:** The model reports that it cannot reliably give a prediction and does not attempt to do so, thereby failing safely.

Figure: Explanations make the user to trust the prediction [3]




A technique used in machine learning when predictions cannot be given confidently is the **reject option** [4].

$$\hat{y}(x) = \begin{cases} -1 & \text{if } \phi(x) \leq t \\ \text{reject, if } \phi(x) \in (-t, t) \\ 1 & \text{if } \phi(x) \geq t \end{cases}$$

# Potential Strategies for Achieving Safety

- **Interpretability & Transparency:** Improve the interpretability & transparency of the ML component.
- **Safe Fail:** The model reports that it cannot reliably give a prediction and does not attempt to do so, thereby failing safely.
- **Abstract.** Abstract the ML component and input feature space and identify scenarios that could cause violation of safety specification.

Figure: Explanations make the user to trust the prediction [3]



A technique used in machine learning when predictions cannot be given confidently is the **reject option** [4].

$$\hat{y}(x) = \begin{cases} -1 & \text{if } \phi(x) \leq t \\ \text{reject, if } \phi(x) \in (-t, t) \\ 1 & \text{if } \phi(x) \geq t \end{cases}$$

