


Safe Machine Learning

ML Component Aspect

- Interpretable Models
 - **Advantage:**
 - **Easier for formal verification (reachability analysis)?** (for rule/dt) The input space is naturally partitioned and the output space is relative small (or can be made linear)
 - Not black box, deterministic ,easy to debug
 - **Disadvantage** The performance is not comparable to deep neural network, and can only handle easy task.
 - **Guess :**
 - Can we use Interpretable Models to bound the output of dnn for ease of verification
 - (From verifying AV paper) Level of ML usage : an end to-end use of ML not be encouraged.
 - it is unclear what the “tells” are for a machine exhibiting safe behavior vs. getting lucky with unsafe behavior. Being able to reasonably infer causality of actions from explicit system information can reduce testing costs compared to a brute force statistical approach.
- **Model Explanation -> Locally interpretable models**
 - **basic idea:** In the vicinity of an instance, the decision boundary of a classifier can be interpretable locally.
 - **anchors:** The anchors (a set of rules) can also compute the coverage of the local model for approximating the black box models
 - **Wild Guess :** the idea of coverage for anchors is interesting. The anchors only approximate the black model based on sampling around the instance. In practice, the coverage of a model should be based on both the data density and the accuracy of the local models.
 - **Question:** How to apply explain regression models?
- Feature Extract: compute the global importance of each feature in the model by either removing the features that are not of interest or the switch the values of features from different samples.
- Reject Option: Use reject option to avoid low-confidence prediction.
 - **Advantage:**

- Obviously, it can avoid unsafe action.
- **Guess:** can it be used to make the verification more easier **if** we can identify confident region and unconfident. However, the confident region is not 100 percent confident
- **Problem**
 - How it can be directly applied. Any application scenario (of course, for decision sciene, it can be directly applied)? What action to take if an rejection happens.
 - How to measure the confidence level of a prediction.
 - Existing approach train multiple models and study the variance. (But is it always true if low vairance means confident)
 - For ensemble models, based on votes (is it always true ? data point from the empty space is not such case)
 - How to indentify confident region and unconfident, how to measure confidence level?
- **Wild Guess** : we can partition the empty space with the data by sampling the empty space




- **Rarity** : Rare class/ rare classes could cause small disjuncts where most errors occurs. Most existing works do not favor rare class while error of rare objects could cause more severe problems.
 - **Reasons:**
 - Evaluation metric accuracy does not favor rarity
 - Difficult to generate regularities/decision boundary for rare cases.
 - Difficult to distinguish between real rare cases or noisy
 - The general bias is not suitable for rarity.
 - **Potential Strategies**

- Detect the small disjuncts and more powerful method for small disjuncts.
- Learn only the Rare Class:
- Increase the cost of rare objects
- Over sample (over fit) and under sample (loss of information)
- (But we still know the state of art, and whether the mentioned techniques have already been applied.).

Verifying ML using formal methods

- The **high dimension original data** was extracted to **low-dimension feature vector** so that the region of uncertain can be found, and counter examples can be found from the uncertain region
 - **Reason:** Formal methods can not handle high dimension large input space and complicated models (the approximate algorithm it use is **interpolation**)



Region of Uncertainty (yellow)

- **Problem**
 - Need to find **good representation of the origin data** so that most information is still kept, and the simplified function can approximate the original model.
 - Why not to use the approximated model directly?
 - **Essence:** It use a simpler model with few features for verification hoping that the simple model can approximate the black box model.
 - **More complicated Abstraction**

- A hierarchical model instead of end-to-end model. A low level model can extract the feature distance between cars, pedestrians. A high level simple model predict and take actions.
 - It is difficult abstract features for more complicated tasks.
- Reachability analysis+Neural network:
 - The space of input is partitioned and for each partition of input space, the upper and lower bound of the output is then computed for that layer.
 - **Guess** Instead, can we use a more simple model to bound the output for each input space partition? For example: for an DNN, all its output for a input space is bounded by a simple linear model or decision tree based model (used as a safety envelope?).

Verifying AV Process

- **Characteristics of ML that can impact safety or safety assessment**
 - Non-transparency
 - Error rate
 - **Training-based** : Training sets used in place of a safety requirement specification,
 - Instability: difficult to debug models or reuse parts of previous safety assessments.
- Controllability and Observability

Controllability is the ability of a tester to control the initial state and the workload executed by a system under test. Observability is the ability of the tester to observe the state of the system to determine whether a test passed or failed.
- Level of ML usage : an end to-end use of ML not be encouraged.
- Passing Tests for the Right Reason: Interpretability

For HAV, it is unclear what the “tells” are for a machine exhibiting safe behavior vs. getting lucky with unsafe behavior. Being able to reasonably infer causality of actions from explicit system information can reduce testing costs compared to a brute force statistical approach.