CS3230 Lecture 10

Dynamic Programming

(stevenhalim@gmail.com)

Lecture Topics and Readings (may spill to Week 11)

- CUT-ROD Problem, CLRS Ch15.1, "**Exponential" to Polynomial**
  - Steps in Dynamic Programming [CLRS] Ch15.1, CP3 Sec3.5
- 0-1 Knapsack Problem, **Pseudo-Polynomial**,
  CLRS Ex 16. 2-2, CP3 Sec3.5
- **Exponential** DP-TSP (review for ex CS2010), CP3 Sec3.5
- **Polynomial** *Bitonic* TSP, CLRS Problem 15-1, CP3 Sec9.3

Richard Bellman

Began the systematic study of dynamic programming (tabular method)

- The dynamic programming equation is also called Bellman equation

Also one of the inventor of Bellman-Ford's algorithm

- SSSP algorithm for a weighted directed graph
  - Runs in O(|V||E|) time in the worst case, usually can be terminated earlier in practice
  - Can be used to detect negative weight cycle in the graph

Dynamic Programming Basics

The basic idea

(review for ex CS2010 S1+CS2020 students)

Optimization Problems

Many real-life problems are optimization problems
(not just decision problems)

Typical techniques used in optimization problems:

- Dynamic programming (today, Week 10, early part of Week 11)
- Greedy Algorithm (next week, Week 11)
- Approximation (*deferred* to Week 12)
- Complete Search (and Local Search + Heuristics, Week 13)

Rod Cutting Problem (CUT-ROD)

You have a rod of length **n**

You can cut it into pieces and sell the pieces

Assume that $\mathbf{p_i}$ is the price for a rod of length **i**

You hope to maximize the profit

How should we cut the rod?



Example

Length i	1	2	3	4	5	6	7	8	9	10
Price p_i	1	5	8	9	10	17	17	20	24	30

INPUT: A rod of length 4

There are 8 possible ways to cut the rod as shown below

Optimal solution!



Problem Formulation of CUT-ROD

INPUT: **n** and $\mathbf{p_i}$ for **i** = 1, 2, …, n

OUTPUT: Among all possible ways to cut **n**
(i.e. all possible sets of lengths $\{i_1, i_2, \ldots, i_k\}$),
we aim to maximize $r_n = p_{i_1} + \cdots + p_{i_k}$

For the previous example, we have these observations:

Length i	1	2	3	4	5	6	7	8	9	10
Price p_i	1	5	8	9	10	17	17	20	24	30
r_i	1	5	8	10	13	17	18	22	25	30
Pieces	1	2	3	2+2	2+3	6	1+6	2+6	3+6	10

Simple (But Slow) Solution

INPUT: **n** and $\mathbf{p_i}$ for **i** = 1, 2, …, n

```
set r = p_n; // at least the price to sell with no cut
for each way to cut a length-n rod to {i_1, i_2, …, i_k}
   compute c = p_{i_1} + p_{i_2} + ⋯ + p_{i_k}; // O(n)
   if (c > r) // if this cut is more profitable
      r = c;
return r;
```

Why the Simple Solution is Slow?

For a length-**n** rod, we can choose <u>to cut</u> or <u>not to cut</u> at position **x** for **x** = 1, 2, …, **n**-1



Hence, there are EXPONENTIAL: $\mathbf{2^{n-1}}$ ways to cut the rod and the simple solution runs in $\mathbf{O(n * 2^{n-1})}$ time

- It is very slow…

Can we do better or is CUT-ROD $\in$ NP-Complete?

Observation 1: Optimal Substructure

Consider a length-**n** rod, suppose we know the optimal solution will cut at position **i**

$r_n =$



Then, we have two subproblems:

$r_i =$

$r_{n-i} =$

Observe that $r_n = r_i + r_{n-i}$

If overall optimal solution is formed by the optimal solution of two (or more) related subproblems, we say that the problem exhibits <u>optimal substructure</u>

Recursive Formula

However, we do <u>NOT</u> know the optimal cut!

No problem! We can check every cut!

Base case:

- $r_0 = 0$ (the revenue of having length-0 rod is obviously 0)

Recursive case:

- $r_n = \max \{ p_n, r_1+r_{n-1}, r_2+r_{n-2}, \ldots, r_{n-2}+r_2, r_{n-1}+r_1 \}$
- $r_n = \max \{ p_n, r_1+r_{n-1}, r_2+r_{n-2}, \ldots, r_{\lfloor n/2 \rfloor}+r_{\lceil n/2 \rceil} \}$
- $r_n = \max \{ p_n, \max_{i=1,\ldots,\lfloor n/2 \rfloor} (r_i+r_{n-i}) \}$

Recursive Algorithm

```
CUT-ROD(n)
if n = 0 // base case
   q = 0;
else // recursive case
   q = p_n; // price to sell with no cut
   for i = 1 to ⌊n/2⌋
      q = max{ q, CUT-ROD(i) + CUT-ROD(n-i) };
return q;
```

Observation 2: Overlapping Subproblems

Example: CUT-ROD(5)



$r_5 = \max \{ p_5, r_1+r_4, r_2+r_3 \}$
$r_4 = \max \{ p_4, r_1+r_3, r_2+r_2 \}$
$r_3 = \max \{ p_3, r_1+r_2 \}$
$r_2 = \max \{ p_2, r_1+r_1 \}$
$r_1 = \max \{ p_1 \}$

Notice the redundant **re-computations**

How to avoid redundant computation?

When there are overlapping computations,
we can use dynamic programming instead of recursion

Idea: We store the computed results in a table

- For the second computation of the same CUT-ROD(n),
  we extract the stored result instead of calling recursion

This approach is called **memoized algorithm**

Memoized Algorithm

```
set r_i = -∞ for i = 0, 1, …, n; // initialize with -∞
output CUT-ROD-Memoized(n);

CUT-ROD-Memoized(n)
    if r_n ≥ 0 return r_n; // has been computed before
    if n = 0 // base case
        q = 0;
    else // recursive case
        q = p_n; // price to sell with no cut
        for i = 1 to ⌊n/2⌋
            q = max { q, CUT-ROD-Memoized(i) +
                         CUT-ROD-Memoized(n-i) };
    r_n = q;
    return q;
```

Bottom-up Dynamic Programming

CUT-ROD-DP(n)

```
r_0 = 0;
for j = 1 to n // start from small to large
   q = p_j;
   for k = 1 to ⌊j/2⌋
      q = max{ q, r_k + r_{j-k} };
   r_j = q;
return r_n;
```

Bottom-Up DP Demo

```
r_0 = 0; // base case
r_n = max{ p_n, max_{i=1,…,⌊n/2⌋} (r_i+r_{n-i}) } // recursive case
```

More detailed example for r_5 =

$\max\{ p_5, \max_{i=1,2} (r_i+r_{5-i}) \}$ =

$\max \{10, \max(r_1+r_4, r_2+r_3)\}$ =

$\max \{10, \max(1+10, 5+8)\} = 13$

Length i	0	1	2	3	4	5	6	7	8	9	10
Price p_i		1	5	8	9	10	17	17	20	24	30
r_i	0	1	5	8	10	13	17	18	22	25	30

Running Time

We need to fill-in $\mathbf{r_i}$ for $\mathbf{i} = 0, 1, \ldots, \mathbf{n}$

To compute $\mathbf{r_i}$, we process a maximum of $\mathbf{n}$ numbers

Hence, CUT-ROD-DP(n) runs in $O(n^2)$ time

Subproblem (Directed Acyclic) Graph

A DP problem can be described as a subproblem (Directed Acyclic) Graph

- Each vertex is a subproblem
- For two subproblems x and y, (x, y) is an edge if x depends on y

$$r_5 = \max \{ p_5, r_1+r_4, r_2+r_3 \}$$
$$r_4 = \max \{ p_4, r_1+r_3, r_2+r_2 \}$$
$$r_3 = \max \{ p_3, r_1+r_2 \}$$
$$r_2 = \max \{ p_2, r_1+r_1 \}$$
$$r_1 = \max \{ p_1 \}$$

CUT-ROD(5)



Top-Down DP (Memoization)

Solve problem in DFS order

$$r_5 = \max \{ p_5, r_1+r_4, r_2+r_3 \}$$
$$r_4 = \max \{ p_4, r_1+r_3, r_2+r_2 \}$$
$$r_3 = \max \{ p_3, r_1+r_2 \}$$
$$r_2 = \max \{ p_2, r_1+r_1 \}$$
$$r_1 = \max \{ p_1 \}$$



Bottom-Up DP

Solve the problem in reverse topological order in the subproblem DAG



Running Time of CUT-ROD DP

Running time is the number of edges =

$(n-1) + (n-2) + \ldots + 1 =$

$O(n^2)$

(both top-down and bottom-up DP)

CUT-ROD(5)



Reconstructing (One*) Optimal Solution

```
Call cut-rod-DP(n);
Call print-Cut-Rod(n);

print-Cut-Rod(n)
  if r_n = p_n
    print "i(p_n)";
  else
    for i = 1 to ⌊n/2⌋
      if (r_n = r_i+r_{n-i}) then break;
    print-Cut-Rod(i);
    print-Cut-Rod(n-i);
```

Example: n=7



Length i	0	1	2	3	4	5	6	7	8	9	10
Price p_i		1	5	8	9	10	17	17	20	24	30
r_i	0	1	5	8	10	13	17	18	22	25	30

Recursion versus DP

All DP problem can be solved by just recursion

- i.e. if you can write recursive solution,
  you should already have the optimal subproblem property

So, when should we use DP?

- Answer: The recursive solution contains a *small number** of distinct subproblems <u>"repeated" (many time)</u>

* Later we will see that sometimes this is not necessarily polynomial…

Example (1)

$L(n) = L(n/2) + c_n$

Shall we use DP or recursion?

Recursion running time:

- O(log n)

(Bottom-Up) DP running time:

- O(n)

(Top-Down) DP running time:

- O(log n), but we waste O(n) of table space



Example (2)

$L(n) = L(\lfloor n/2 \rfloor) + \ldots + L(1) + c_n$

Shall we use DP or recursion?

Recursion running time:

- Super-polynomial time

DP (either version) running time:

- $O(n^2)$



Current Summary for DP Technique

Steps:

1. Characterize the structure of an optimal solution
2. Define the recursive formula and check if there are small number of distinct subproblems repeated many times
3. Develop the algorithm to fill-in the dynamic programming table (either with top-down or bottom-up strategy)
4. Reconstruct the optimal solution (optional)

0-1 Knapsack Problem

Introducing the term
Pseudo-Polynomial

0-1 Knapsack Problem



Max value:
$15

What is the maximum value you can get?

0-1 Knapsack (CLRS Ex 16.2-2)

This problem finds application in resource allocation

Formal definition:

INPUT: $(v_1, w_1), (v_2, w_2), \ldots, (v_n, w_n)$, and W

OUTPUT: A subset $S \subseteq \{1, 2, \ldots, n\}$ that maximizes $\sum_{i \in S} v_i$ such that $\sum_{i \in S} w_i \leq W$

Simple (but Slow) Solution

Knapsack($\{v_1, v_2, \ldots, v_n\}$, $\{w_1, w_2, \ldots, w_n\}$, W)

```
maxV = 0;
for every subset S ⊆ {1, 2, …, n},
    if ∑_{i∈S} w_i ≤ W and ∑_{i∈S} v_i > maxV, then
        maxV = ∑_{i∈S} v_i;
return maxV;
```

Running time:

- There are 2^n possible subsets S of $\{1, 2, \ldots, n\}$
- It takes O(n) time to compute $\sum_{i \in S} w_i$ and $\sum_{i \in S} v_i$
- Hence, the running time is $O(n * 2^n)$

Knapsack Problem is in NPC

(0-1) Knapsack problem is NP-Complete

- Proof omitted (it is related to SUBSET-SUM)
- (see your HW3 later)

But, when the weights $\mathbf{w_i}$ are integers and $\mathbf{W}$ is bounded, can we solve the problem in polynomial time?

Step 1: Optimal substructure

Problem: $(\{v_1, v_2, \ldots, v_n\}, \{w_1, w_2, \ldots, w_n\}, W)$



Two cases:

- Case 1: Item n (the last one) is taken

  Problem: $(\{v_1, v_2, \ldots, v_{n-1}\}, \{w_1, w_2, \ldots, w_{n-1}\}, W-w_n)$





- Case 2: Item n (the last one) is not taken

  Problem: $(\{v_1, v_2, \ldots, v_{n-1}\}, \{w_1, w_2, \ldots, w_{n-1}\}, W)$



Observation

Good news so far!

- For both cases, the problems are <u>smaller</u> knapsack problems

Hence, knapsack problem exhibits optimal substructure

- This is one of the key requirement for DP

Recursive formula for Knapsack (1)

Let **m(i, wt)** be the max value that can be attained using subset of items in **{1, 2, …, i}** whose total weight $\leq$ **wt**

Problem: $(\{v_1, v_2, \ldots, v_i\}, \{w_1, w_2, \ldots, w_i\}, wt)$



Recursive formula for Knapsack (2)

Recursive case 1: $\mathbf{m(i, wt) = m(i\text{-}1, wt\text{-}w_i) + v_i}$

if $\mathbf{w_i \leq wt}$

Problem: $(\{v_1, v_2, \ldots, v_{i-1}\}, \{w_1, w_2, \ldots, w_{i-1}\}, wt\text{-}w_i)$





Recursive case 2: $\mathbf{m(i, wt) = m(i\text{-}1, wt)}$

Problem: $(\{v_1, v_2, \ldots, v_{i-1}\}, \{w_1, w_2, \ldots, w_{i-1}\}, wt)$



Recursive formula for Knapsack (3)

Base case 1: If **wt = 0**, then **m(i, wt) = 0**





Base case 2: If **i = 0**, then **m(i, wt) = 0**

No item!

Recursive formula for Knapsack (4)

Recursive cases:

$$m(i, wt) = max \begin{cases} m(i-1, wt - w_i) + v_i \; if \; w_i \leq wt \\ m(i-1, wt) \end{cases}$$

Base cases:

If wt = 0, then m(i, wt) = 0

If I = 0, then m(i, wt) = 0

Recursive algorithm

```
KS_recur(i, wt)
     if (i = 0)  val = 0;
else if (wt = 0) val = 0;
else
  val = KS_recur(i-1, wt);
  if (wt > w_i), then
    val = max{ val, KS_recur(i-1, wt-w_i)+v_i };
  return val;
```

INPUT: $\{v_1, v_2, \ldots, v_n\}$, $\{w_1, w_2, \ldots, w_n\}$ and W

```
return KS_recur(n, W);
```

Time analysis

$\text{Time}(n, W) = \text{Time}(n-1, W) + \text{Time}(n-1, W-w_n) + O(1)$

Assume $W \geq w_1+\ldots+w_n$

$\text{Time}(n, W) = O(2^n)$… erm…

Why the algorithm is slow?

v[1..5] = {4, 2, 10, 1, 2}

w[1..5] = {12, 1, 4, 1, 2}

W = 15





Memoized (Top-down DP) solution

```
KS_memoized(i, wt)
if (m[i, wt] ≥ 0) return m[i, wt];
     if (i = 0)  val = 0;
else if (wt = 0) val = 0;
else
  val = KS_memoized(i-1, wt);
  if (wt>w_i), then
  val = max{ val, KS_memoized(i-1, wt-w_i)+v_i };
m[i, wt] = val;
return val;
```

INPUT: $\{v_1, v_2, \ldots, v_n\}$, $\{w_1, w_2, \ldots, w_n\}$ and W

```
set m[i, w] = -∞
for i=1,2,…,n and w = 0,1,…,W;
return KS_memoized(n, W);
```

Bottom-up DP solution

```
DP_KS({v1, v2, …, vn}, {w1, w2, …, wn}, W)
for w = 0 to W
  m[0, w] = 0;
for i = 1 to n
  m[i, 0] = 0;
for i = 1 to n
  for j = 0 to W
    if j >= wi then
      m[i, j] = max(m[i-1, j], m[i-1, j-w[i]] + vi);
    else
      m[i, j] = m[i-1, j];
return m[n,W];
```

Demo (1)



v[1..5] = {4, 2, 10, 1, 2}

w[1..5] = {12, 1, 4, 1, 2}

W = 15

```
for w = 0 to W
    m[0, w] = 0;
```

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1																
2																
3																
4																
5																

Demo (2)



v[1..5] = {4, 2, 10, 1, 2}

w[1..5] = {12, 1, 4, 1, 2}

W = 15

```
for i = 1 to n
    m[i, 0] = 0;
```

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1	0															
2	0															
3	0															
4	0															
5	0															

Demo (3)



v[1..5] = {4, 2, 10, 1, 2}

w[1..5] = {12, 1, 4, 1, 2}

W = 15

```
for i = 1 to n
  for j = 0 to W
    if j >= w_i then
      m[i, j] = max(m[i-1, j],
          m[i-1, j-w[i]] + vi);
    else
      m[i, j] = m[i-1, j];
```

E.g. m[3,5] = max(m[3-1,5], m[3-1,5-w_3]+v_3)
= max(m[2,5],m[2,2]+10)

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1	0	0	0	0	0	0	0	0	0	0	0	0	4	4	4	4
2	0	2	2	2	2	2	2	2	2	2	2	2	4	6	6	6
3	0	2	2	2	10	12										
4																
5																

Demo (4)



v[1..5] = {4, 2, 10, 1, 2}

w[1..5] = {12, 1, 4, 1, 2}

W = 15

```
for i = 1 to n
  for j = 0 to W
    if j >= w_i then
      m[i, j] = max(m[i-1, j],
          m[i-1, j-w[i]] + vi);
    else
      m[i, j] = m[i-1, j];
```

E.g. $m[4,5] = \max(m[4-1,5], m[4-1,5-w_4]+v_2)$
$= \max(m[3,5], m[3,4]+1)$

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1	0	0	0	0	0	0	0	0	0	0	0	0	4	4	4	4
2	0	2	2	2	2	2	2	2	2	2	2	2	4	6	6	6
3	0	2	2	2	10	12	12	12	12	12	12	12	12	12	12	12
4	0	2	3	3	10	12										
5																

Demo (5)



v[1..5] = {4, 2, 10, 1, 2}

w[1..5] = {12, 1, 4, 1, 2}

W = 15

```
return m[n,W];
```

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1	0	0	0	0	0	0	0	0	0	0	0	0	4	4	4	4
2	0	2	2	2	2	2	2	2	2	2	2	2	4	6	6	6
3	0	2	2	2	10	12	12	12	12	12	12	12	12	12	12	12
4	0	2	3	3	10	12	13	13	13	13	13	13	13	13	13	13
5	0	2	3	4	10	12	13	14	15	15	15	15	15	15	15	15

Running time

Step 1: O(W) time

Step 2: O(n) time

Step 3: O(nW) time

Step 4: O(1) time

In total: O(nW) time

Is Knapsack problem in P?

We have showed that Knapsack problem can be solved in O(nW) time, is it a polynomial algorithm?

- Only when W is O(n), then it runs in polynomial time

This DP solution is usually referred as a **pseudo-polynomial** time algorithm

- Actually, Knapsack problem is not in P since W can have O(n) digits, i.e. $W = 10^{O(n)}$
- In such case, this algorithm runs in exponential time

Traveling Salesman Problem

A DP algorithm can still have exponential time complexity…

Traveling Salesman Problem (TSP)

dist	0	1	…	n-1
0				
1				
…				
n-1				

The decision version of this problem is shown to be in NP-Complete (Lecture 08)

Indeed, there are O(N!) possible tours to try…

Is all n! permutations distinct?

Yes, but the <u>partial tours</u> can overlap:

Example, for an instance with N cities:

1. Tour 1: A-B-C-**<u>(N-3) other cities</u>**-return to A
2. Tour 2: A-C-B-**<u>the same (N-3) other cities</u>**-return to A

Overlapping subproblems!

TSP Top-Down DP algorithm

State: **tsp(pos, bitmask)**, start from **tsp(0, 1)**

- bitmask is a compact representation of a set of **N** items using the binary representation of integer (details in the diagrams)

Base case (if every cities have been visited):

- tsp(pos, 2^N-1) = dist[pos][0]

Recursive case, try visiting unvisited cities one by one:

- tsp(pos, bitmask) =
  min(dist[pos][nxt] + tsp(nxt, bitmask | (1 << nxt)))
  $\forall$nxt $\in$ [0..N-1], nxt != pos, bitmask & (1 << nxt) == 0

For self study of bitmask technique: http://rosemarietan.com/fyp/bitmask.html


20
A
B
42
34
30
35
C
D
12

TSP DAG (1)


35
(goes back
from D to A)
B,
{AB}
30
C,
{ABC}
12
D,
{ABCD}
20
34
34
A,
{A}
42
C,
{AC}
30
D,
{ABD}
12
C,
{ABCD}
B,
{ABC}
42
(goes back
from C to A)



TSP DAG (2)



The path in red (it is a tour actually) has the minimum total weight of 97

35
(goes back from D to A)

42
(goes back from C to A)

20
(goes back from B to A)

There are **lots** of overlapping sub problems on **larger instance** of TSP DAG



TSP DAG (3)



35
(goes back from 3 to 0)

42
(goes back from 2 to 0)

20
(goes back from 1 to 0)

The path in red (it is a tour actually) has the minimum total weight of 97

There are **lots** of overlapping sub problems on **larger instance** of TSP DAG



TSP DAG (4)



The path in red (it is a tour actually) has the minimum total weight of 97

35
(goes back from 3 to 0)

42
(goes back from 2 to 0)

20
(goes back from 1 to 0)

There are **lots** of overlapping sub problems on **larger instance** of TSP DAG

Analysis of Top-Down tsp DP

How many vertices are there in this DAG?

- Up to $O(N * 2^N)$
  - N is the current vertex
  - 2^N is the size of the set of visited vertices

How many edges are there in this DAG?

- Up to O(N) outgoing edges per vertex as we must check all neighbors of a vertex as the input is a complete graph, each vertex has out-degree N-1
- $O((N * 2^N) * N) = O(N^2 * 2^N)$, still exponential :O
  - But still faster than O(N!)

Larger TSP Instances

N	N!	$N^2 * 2^N$ (Held and Karp's algorithm)	Improvement
9	362,880	81 * 512 = 41,472	8.75 x
10	3,628,800	100 * 1024 = 102,400	35.44 x
11	39,916,800	121 * 2048 = 247,808	161.07 x
12	479,001,600	144 * 4096 = 589,824	812.11 x
13	6,227,020,800	169 * 8192 = 1,384,448	4,497.84 x
14	87,178,291,200	196 * 16384 = 3,211,264	27,147.66 x
15	1,307,674,368,000	225 * 32,768 = 7,372,800	177,364.69 x
16	20,922,789,888,000	256 * 65,536 = 16,777,216	1,247,095.46 x
17	355,687,428,096,000	289 * 131,072 = 37,879,808	9,389,895.22 x
20?	~$2.4 * 10^{18}$	400 * 1,048,576 = 419,430,400	$5.8 * 10^9$ x
51	Hm…	5,856,931,315,395,330,048 ☹	…
105?	My PhD thesis ☺	4.47227131760519332848036e+35 ☹	
		TSP (decision version) $\in$ NP-complete	

Bitonic TSP

Additional (relaxing) constraint can sometime simplify the problem…
by a lot…

Bitonic TSP (1)

Bitonic tour: Starts the tour from the **leftmost vertex**, then goes **strictly from left to right**. Upon reaching the **rightmost vertex**, the tour goes **strictly from right to left** back to the starting vertex



Bitonic TSP (2)

That additional constraint of TSP (the bitonic tour) actually simplifies the problem so that we can solve Bitonic TSP in polynomial $O(n^3)$ time

- PS: $O(n^2)$ solution is possible



Decompose tour to LR and RL paths

Left-to-Right (LR) path start at the **leftmost vertex 0** and ends at the **rightmost vertex N-1** (vertex 6 below), and Right-to-Left (RL) path is the reverse



Decide membership of vertex v = 1, 2,… , n-2

For each vertex **v**, we decide if vertex **v** should belong to LR path (extending the LR path further to the right) or RL path (the RL path starts at **v** and goes back to 0)



Base case: Vertex v = n-1

We simply connect the two paths together to form the Bitonic Tour



The Algorithm

```
BTSP(v, p1, p2) // called with BTSP(1, 0, 0)
if (v = n-1) return d[p1][v] + d[v][p2];
if (memo[v][p1][p2] != blank) return memo[v][p1][p2];

memo[v][p1][p2] = min(
  d[p1][v] + BTSP(v+1, v, p2),
  // extend LR path: p1->v, RL stays: p2
  d[v][p2] + BTSP(v+1, p1, v));
  // LR stays, extend RL path: p2<-v

return memo[v][p1][p2];
```

Analysis of Top-Down BTSP DP

How many vertices are there in this DAG?

- Up to $O(N^3)$ as we record v, p1, p2
  and each of them can range from [0 .. N-1]

How many edges are there in this DAG?

- Up to 2 outgoing edges per vertex as we only have two options, put vertex v in LR path or in RL path
- $O(N^3 * 1) = O(N^3)$, now polynomial :O
  - Simple improvement can be used to reach $O(N^2)$ time (CP3, Sec 9.3)

This special case of TSP is in **P**!

More DP problems in [CLRS/CP3]

On **P** problems

- Range Sum
- Matrix-chain multiplication
- Longest common subsequence
- Optimal binary search tree
- All-Pairs Shortest Path (Floyd Warshall's)
- (Small) Graph Matching* (DP solution turns this P problem to exponential)

On **NP** problems (pseudo-polynomial/exponential/special-case)

- SUBSET-SUM (similar with Knapsack)
- COIN-CHANGE
- INDEPENDENT-SET/VERTEX-COVER (on tree)

Summary

- Dynamic Programming is a powerful problem solving technique for problems that exhibit:
  1. Optimal Substructure
  2. Overlapping Subproblems
- We can use Top-Down or Bottom-Up DP formulation
  - Simplified time complexity analysis:
    - Bottom-up: # of cells * effort to fill that cell
    - Top-down: # of vertices * # out-edges/vertex in recursion DAG
- DP solution can still have pseudo-polynomial or exponential time complexity!