Neural Networks 8

CS 3244
Machine Learning

Pre

NUS | Computing

Recap and Forecast

- **Markov Decision Processes** (MDP) embody RL
- **Bellman equations** are a recursive form for calculating rewards and state values.



Learning outcomes for this week:

- Describe the basic idea of Artificial Neural Networks (ANN or NN):
  - Explain how neural networks combine linear units with a non-linear activation function;
  - Explain the topology of a NN.
- Name potential problems with NNs.
- Describe how a neural network is trained using the backpropagation algorithm.
- Name NN regularization techniques.
- Obtain practical experience constructing NNs using PyTorch.

Revisiting XOR

CS3244 Machine Learning

NUS National University of Singapore
Department of Computer Science
School of Computing

Biological Inspiration





Diagram credits: Dhp1080 - Own work, CC BY-SA 3.0 via Wikimedia Commons.

Combining Perceptrons



$\text{sign}(\theta^\top \boldsymbol{x})$ $\quad y = \pm 1$





Creating Layers





Creating Layers





The Multilayer Perceptron

3 layers

"feedforward" ≡ no loops



A Powerful Model



Target | 8 perceptrons | 16 perceptrons

2 red flags:

A Powerful Model



Target | 8 perceptrons | 16 perceptrons

2 red flags:

for generalization and

for optimization

NN Topology

CS3244 Machine Learning

NUS National University of Singapore
Department of Computer Science
School of Computing

The Neural Network



1	~~1~~
tanh	~~logistic~~
-1	~~0~~



Input $\boldsymbol{x}$ Hidden layers $1 \leq l < L$ Output layer $l = L$

NN Indices



$$\Theta_{i,j}^{[l]} \begin{cases} l \text{ layers}, 1 \le l \le L. \\ i \text{ outputs}, 1 \le i \le d^{[l]} \\ j \text{ inputs}, 0 \le j \le d^{[l-1]} \end{cases}$$

If a network has $d^{[l-1]}$ units in layer $l-1$, $d^{[l]}$ units at layer l, then $\Theta^{[l]}$ will be of dimension $(d^{[l-1]}+1)\times d^{[l]}$.

NN Activations



$$a_2^{[1]} = g(\Theta_{2,0}^{[1]} \cdot 1 + \Theta_{2,1}^{[1]} x_1 + \Theta_{2,2}^{[1]} x_2 + \ldots + \Theta_{2,d}^{[1]} x_d)$$

$$a_1^{[2]} = g(\Theta_{1,0}^{[2]} \cdot 1 + \Theta_{1,1}^{[2]} a_1^{[1]} + \Theta_{1,2}^{[2]} a_2^{[1]} + \Theta_{1,3}^{[2]} a_3^{[1]})$$

How the Network Operates



$$g(s) = \tanh(s) = \frac{e^{s} - e^{-s}}{e^{s} + e^{-s}}$$

How the Network Operates

$$\Theta_{i,j}^{[l]} \begin{cases} 1 \le l \le L & \text{layers} \\ 1 \le i \le d^{[l]} & \text{outputs} \\ 0 \le j \le d^{[l-1]} & \text{inputs} \end{cases}$$

$$x_i^{[l]} = a_i^{[l]} = g\left(s_i^{[l]}\right) = g\left(\sum_{j=0}^{d^{[l-1]}} \Theta_{i,j}^{[l]} x_j^{[l-1]}\right)$$

$$= g((\Theta_i^{[l]})^\top \boldsymbol{x}^{[l-1]})$$



$$g(s) = \tanh(s) = \frac{e^s - e^{-s}}{e^s + e^{-s}}$$

Feedforward: Apply $\boldsymbol{x}$ to $x_1^{[0]} \dots x_{d^{[0]}}^{[0]} \to x_1^{[L]} = h(\boldsymbol{x})$

Multiclass classification



Multiple output units:
$h_\Theta(\boldsymbol{x}) \in \mathbb{R}^3$

Want $h_\Theta(\boldsymbol{x}) \approx \begin{bmatrix} 1 \\ -1 \\ -1 \end{bmatrix}$ when *setosa*, $h_\Theta(\boldsymbol{x}) \approx \begin{bmatrix} -1 \\ 1 \\ -1 \end{bmatrix}$ when *versicolor* and $h_\Theta(\boldsymbol{x}) \approx \begin{bmatrix} -1 \\ -1 \\ 1 \end{bmatrix}$ when *virginica*.

Diagram credits: Frank Mayfield, Danielle Langlois & Radomił Binek, Own work, CC BY-SA 3.0 via Wikimedia Commons.