EE4204 Question & Answer Session

Mehul Motani NUS/ECE

Q1

The ____ layer lies between the network layer and the application layer.

A: None of the choices

B: Transport

C: Data link

D: Physical

Q2

When an IP router between two Ethernet segments forwards an IP packet, it does not modify the destination MAC address.

A: True B: False Q3

When an IP router between two Ethernet segments forwards an IP packet, it does not modify the destination IP address.

A: False B: True

Q4

An organization is granted a block of classless addresses with the starting address 199.34.32.0/27. How many addresses are granted?

A: None of the choices

B: 32 C: 8 D: 16 Q5

An IPv4 datagram is fragmented into three smaller datagrams. Which of the following is true?

A: The do not fragment bit is set to 1 for all three datagrams.

B: The identification field is the same for all three datagrams.

C: The more fragment bit is set to 0 for all three datagrams.

D: The offset field is the same for all three datagrams.

Q6

The value in the sequence number field of a TCP segment defines the number of the ____ data byte contained in that segment.

A: None of the choices

B: last C: next D: first Q7

The value of the acknowledgment field in a TCP segment defines the number of the _____ byte a party expects to receive.

A: None of the choices

B: next

C: first

D: last

7

Q8

If the ACK value in the TCP header is 200, then byte _____ has been received successfully.

A: 199 B: 201 C: 200

D: None of the choices

Q9

Which of the following algorithms solves the single source shortest path routing problem?

A: Floyd's algorithm

B: Bellman-Ford algorithm

C: Dijkstra's algorithm

D: Prim's algorithm


9

Q10

Dijkstras algorithm may not terminate if the graph contains negative-weight edges.

A: False B: True Q11

For what values of x will Dijkstra's algorithm work and not work?



Q12

Without knowing the values of *cwnd* or window advertisement, by only observing the sequence numbers of successive segments transmitted, is it possible to determine whether flow control or congestion control is operating at any given time in a connection?

Q13

Explain the TCP slow-start. What is its goal and how does it work?

13

Q14

- Assuming that the available link capacity and the receiver window are infinite how many round-trip times does it take in TCP to send the first 10 packets?
- In general, how many round-trip times does it take to send the first k packets?

Q15

A router with the following forwarding table receives a packet with destination 128.195.3.10. Which will be the outgoing interface of the packet?

|128.195.0.0/8 |eth2| |128.195.0.0/16 |eth0| |128.195.0.0/24 |eth1| |0.0.0.0/0 |eth3|

15

Q16

TCP uses a 3-way handshake to open a connection. A two way handshake could be potentially even more practical in terms of saving packets. Think about routing on the internet and suggest why a 3 way handshake is used rather than a 2 way or 4 way handshake.

Q17

Differences between Link State, Vector and Vector Path routing protocols

- Which generates more network traffic in a large network?
- Which protocol uses the least router memory?
- Which protocol handles link additions better than failures?
- Which protocol is typically used for 802.3 LAN networks?

16

Q18

The fundamental reason for which loops form in the Distance Vector protocol is that a node A decides to use a neighbor B as the next hop for a destination based on routing information that was, at some point, propagated by A itself. Give an example of this - draw a simple topology, break a link, and show a sequence of updates triggered by the distance vector protocol.

Q19

If TCP provides reliable, in-order delivery of bytes end-to-end, why would you want to use UDP? Give an application that might be better off using UDP. Explain why?

Q20

- In 2008, a Pakistani ISP was able to prevent about two thirds of the Internet from reaching a slice of YouTube's addresses, by hijacking part of YouTube's prefix. What does this mean?
- Explain how preference for more specific routes makes this easier. What do we call this preference for more specific routes?

Q21

Aggregate the following set of four /24 IP network addresses to the highest degree possible.

212.56.132.0/24 212.56.133.0/24

212.56.134.0/24

212.56.135.0/24