This is how Web API normally did the table.

```
<div class="panel panel-default">
    <div class="panel-body">
        <div class="form-group"  style="margin-top:-42px">
           <table id="itemdetails" class="table table-striped table-bordered table-hover" cellspacing="0" width="100%">
           <thead>
               <tr>
                   <th></th>
                   <th>Item Code</th>
                   <th>Description</th>
                   <th>Quantity</th>
                   <th>UoM</th>
                   <th>Price</th>
                   <th>Tax Code</th>
                   <th>Tax Rate</th>
                   <th>Line Total</th>
               </tr>
           </thead>
           </table>
        </div>
    </div>
</div>
```

Code:

```
<div class="panel panel-default">
                    <div class="panel-body">
                         <div class="form-group"  style="margin-top:-42px">
                            <table id="itemdetails" class="table table-striped table-
bordered table-hover" cellspacing="0" width="100%">
                            <thead>
                                <tr>
                                    <th></th>
                                    <th>Item Code</th>
                                    <th>Description</th>
                                    <th>Quantity</th>
                                    <th>UoM</th>
                                    <th>Price</th>
                                    <th>Tax Code</th>
                                    <th>Tax Rate</th>
                                    <th>Line Total</th>
                                </tr>
                            </thead>
                            </table>
                        </div>
                    </div>
                </div>
```

How do use script to format the table? Below are the code. 1st column is delete button to delete the row.

```
var itemdetails = $('#itemdetails').DataTable({
    columnDefs: [{
        targets: "_all",
        createdCell: function (td, cellData, rowData, row, col) {
            $(td).attr('data-label', $(this).closest('table').find('th').eq(col).html());
        },
    }],
    "columns": [
        {
            mRender: function (data, type, row) {
                return "<button class ='btn-link js-delete ' data-itemcode='" + row[itemcode_column] + "'  >Delete</button>";
            }
        }, // Delete button
        null, // Item Code
        null, // Item Name
        {
            mRender: function (data, type, row) {
                return "<input type='text' class='form-control js-quantity'  id='txtQuantity' onkeydown='return onlyDecimal(this,3);' style='width:100%; ' value='" + data + "' /> "
            }
        }, // Quantity
        null, // UoM
        {
            mRender: function (data, type, row) {
                return "<input type='text' class='form-control js-price'  id='txtPrice' onkeydown='return onlyDecimal(this,3);' style='width:100%' value='" + data + "' /> "
            }
        }, //Price
        null,
        null,
        null //LineTotal
    ],
    paging: false, bFilter: false, "bInfo": false
}); //Sales Order Item Contents
```

Code

```
var itemdetails = $('#itemdetails').DataTable({
            columnDefs: [{
                targets: "_all",
                createdCell: function (td, cellData, rowData, row, col) {
                    $(td).attr('data-label',
$(this).closest('table').find('th').eq(col).html());
                },
            }],
            "columns": [
                {
                    mRender: function (data, type, row) {
                        return "<button class ='btn-link js-delete ' data-itemcode='"
+ row[itemcode_column] + "'  >Delete</button>";
                    }
                }, // Delete button
                null, // Item Code
                null, // Item Name
                {
                    mRender: function (data, type, row) {
                        return "<input type='text' class='form-control js-quantity'
id='txtQuantity' onkeydown='return onlyDecimal(this,3);' style='width:100%; ' value='"
+ data + "' /> "
                    }
                }, // Quantity
                null, // UoM
                {
                    mRender: function (data, type, row) {
                        return "<input type='text' class='form-control js-price'
id='txtPrice' onkeydown='return onlyDecimal(this,3);' style='width:100%' value='" +
data + "' /> "
                    }
                }, //Price
                null,
                null,
                null //LineTotal
            ],
            paging: false, bFilter: false, "bInfo": false
        }); //Sales Order Item Contents
```

How to add row into the table? 1st you need to create button.

```
$("#btnSelectItem").on("click", function (e) {
        itemdetails.row.add([
            null, // delete
            '', // item code
            '',// item name
            1, // Quantity
            '', // UoM
            '',// Price
            '',//Tax Code
            '',//Tax Percent
            0.00, // LineTotal
        ]).draw(false);
});
```

Code:

```
$("#btnSelectItem").on("click", function (e) {
        itemdetails.row.add([
            null, // delete
            '', // item code
            '',// item name
            1, // Quantity
            '', // UoM
            '',// Price
            '',//Tax Code
            '',//Tax Percent
            0.00, // LineTotal
        ]).draw(false);
});
```

How to delete? Just know we have define one column for delete button.

```
$("#itemdetails").on("click", ".js-delete", function (e) {
    e.preventDefault();
    var button = $(this);
    itemdetails.row(button.parents('tr')).remove().draw();
    if (itemdetails.rows().data().length == 0) {
        itemdetails.destroy();
        itemdetails = $('#itemdetails').DataTable({
            "columnDefs": [{
              // "targets": "_all",
               "orderable": false,
               "visible": false,
               //"targets": [9, 10, 11, 12]
            }],
            "columns": [
                {
                    mRender: function (data, type, row) {
                        return "<button class ='btn-link js-delete ' data-itemcode='" + row[itemcode_column] + "'  >Delete</button>";
                    }
                }, // Delete button
                null, // Item Code
                null, // Item Name
                {
                    mRender: function (data, type, row) {
                        return "<input type='text' class='form-control js-quantity'  id='txtQuantity' onkeydown='return onlyDecimal(this,3);' style='width:100%; ' value='" + data + "' /> "
                    }
                }, // Quantity
                null, // UoM
                {
                    mRender: function (data, type, row) {
                        return "<input type='text' class='form-control js-price'  id='txtPrice' onkeydown='return onlyDecimal(this,3);' style='width:100%' value='" + data + "' /> "
                    }
                }, //Price
```

```
                {
                    mRender: function (data, type, row) {
                        return "<input type='text' class='form-control js-price'  id='txtPrice' onkeydown='return onlyDecimal(this,3);' style='width:100%' value='" + data + "' /> "
                    }
                }, //Price
                null,
                null,
                {
                    //data: 0.00,
                    //mRender: function (data, type, row) {
                    //    return data;
                    //}
                    mRender: function (data, type, row) {
                        return "<input type='text' class='form-control js-price'  id='txtPrice' onkeydown='return onlyDecimal(this,3);' style='width:100%' value='" + data + "' /> "
                    }
                } //LineTotal
            ],
            paging: false, bFilter: false, "bInfo": false
        });
    }

});
```

Code:

```
        $("#itemdetails").on("click", ".js-delete", function (e) {
            e.preventDefault();
            var button = $(this);
            itemdetails.row(button.parents('tr')).remove().draw();
            if (itemdetails.rows().data().length == 0) {
                itemdetails.destroy();
                itemdetails = $('#itemdetails').DataTable({
                    "columnDefs": [{
                       // "targets": "_all",
                        "orderable": false,
                        "visible": false,
                        //"targets": [9, 10, 11, 12]
                    }],
                    "columns": [
                        {
                            mRender: function (data, type, row) {
                                return "<button class ='btn-link js-delete ' data-
itemcode='" + row[itemcode_column] + "'  >Delete</button>";
                            }
                        }, // Delete button
                        null, // Item Code
                        null, // Item Name
                        {
                            mRender: function (data, type, row) {
                                return "<input type='text' class='form-control js-
quantity'  id='txtQuantity' onkeydown='return onlyDecimal(this,3);' style='width:100%;
' value='" + data + "' /> "
                            }
```

```
                        }, // Quantity
                        null, // UoM
                        {
                            mRender: function (data, type, row) {
                                return "<input type='text' class='form-control js-
price'  id='txtPrice' onkeydown='return onlyDecimal(this,3);' style='width:100%'
value='" + data + "' /> "
                            }
                        }, //Price
                        null,
                        null,
                        {
                            //data: 0.00,
                            //mRender: function (data, type, row) {
                            //    return data;
                            //}
                            mRender: function (data, type, row) {
                                return "<input type='text' class='form-control js-
price'  id='txtPrice' onkeydown='return onlyDecimal(this,3);' style='width:100%'
value='" + data + "' /> "
                            }
                        } //LineTotal
                    ],
                    paging: false, bFilter: false, "bInfo": false
                });
            }

        });
```

How to load data back to table? If you are using ajax, this is the way. Inside the control, I will call out the “Store Procedure”. Like we did in the Page.

```
var table2 = $('#itemdetails2').DataTable({
    ajax: {
        url: pathinfo.api + "ttfsalesorderportal/opendetails/" + sono2, //this is how we use ajax to call the controller
        dataSrc: ''
    },

    columnDefs: [{
        targets: "_all",
        createdCell: function (td, cellData, rowData, row, col) {
            $(td).attr('data-label', $(this).closest('table').find('th').eq(col).html());
        },
    }],
    columns: [
        { data: "itemcode" },
        { data: "itemname" },
        { data: "quantity" },
        { data: "uom" },
        { data: "priceafterdisc" },
        { data: "taxcode" },
        { data: "taxrate" },
        { data: "linetotal" },
    ], paging: true, bFilter: true, "bInfo": true
});
```

Code

```
var table2 = $('#itemdetails2').DataTable({
            ajax: {
                url: pathinfo.api + "ttfsalesorderportal/opendetails/" + sono2, //this
is how we use ajax to call the controller
                dataSrc: ''
            },

            columnDefs: [{
                targets: "_all",
                createdCell: function (td, cellData, rowData, row, col) {
                    $(td).attr('data-label',
$(this).closest('table').find('th').eq(col).html());
                },
            }],
            columns: [
                { data: "itemcode" },
                { data: "itemname" },
                { data: "quantity" },
                { data: "uom" },
                { data: "priceafterdisc" },
                { data: "taxcode" },
                { data: "taxrate" },
                { data: "linetotal" },
            ], paging: true, bFilter: true, "bInfo": true
        });
```

How do we save back to database? For ajax, I will also use store procedure and call SQL and update back to database.

```
$("#btnAdd").on("click", function (e) {
    //define array
    var lines = [];
    var linenum = 0;

    //1st will check the table got data or not
    if (itemdetails.data().length == 0) {
        alert("No item");

        return false;
    };

    var test = 0;
    if (itemdetails.data().length > 0) {
        var itemdata = itemdetails.rows().data();

        //loop the table
        itemdata.each(function (value, index) {
            var quantity = itemdetails.cell(index, quantity_column).node();
            var price = itemdetails.cell(index, price_column).node();
            var linetotal = parseFloat($('input', quantity).val()) * parseFloat($('input', price).val());

            if ($.isNumeric($('input', quantity).val()) && $('input', quantity).val() != 0) {
                lines.push({
                    //the name must be same as Model name (docentry, itemcode and etc is the model name)
                    //we push the value into the array
```

```
            if ($.isNumeric($('input', quantity).val()) && $('input', quantity).val() != 0) {
                lines.push({
                    //the name must be same as Model name (docentry, itemcode and etc is the model name)
                    //we push the value into the array
                    docentry: 0,
                    itemcode: itemdetails.cell(index, itemcode_column).data(),
                    itemdesc: itemdetails.cell(index, itemdesc_column).data(),
                    quantity: $('input', quantity).val(),
                    uom: itemdetails.cell(index, uom_column).data,
                    priceafterdiscount: $('input', price).val(),
                    unitprice: $('input', price).val(),
                    taxcode: itemdetails.cell(index, taxcode_column).data(),
                    vatsum: 0.00,
                    vatprcnt: 0.00,
                    linetotal: linetotal,
                    linenum: linenum
                });
                linenum = linenum + 1;
            }
        });
```

```
    var pr = {
        //header data
        id: id.val(),
        cardcode: cardcode.val(),
        cardname: cardname.val(),
        numatcard: numatcard.val(),
        contactperson: attn.val(),
        docdate: docdate.val(),
        doctype: doctype.val(),
        billadd4: billadd4.val(),

        //details or table
        lines: lines // the the loop data
    }


    //now we use ajax to call control and post to database.
    $.ajax({
        url: pathinfo.api + "ttfdocuments/portal/ordr",
        method: "POST",
        data: JSON.stringify(pr),
        contentType: "application/json; charset=utf-8",
        success: function (data) {
            alert("Successfully added Sales Order");

            window.location.reload();

        },
        error: function (data) {
            alert(data);
            //window.location.reload();
        }
    });
}
```

Code:

```
$("#btnAdd").on("click", function (e) {
            //define array
            var lines = [];
            var linenum = 0;

            //1st will check the table got data or not
            if (itemdetails.data().length == 0) {
                alert("No item");

                return false;
            };

            var test = 0;
            if (itemdetails.data().length > 0) {
                var itemdata = itemdetails.rows().data();

                //loop the table
                itemdata.each(function (value, index) {
                    var quantity = itemdetails.cell(index, quantity_column).node();
                    var price = itemdetails.cell(index, price_column).node();
                    var linetotal = parseFloat($('input', quantity).val()) *
parseFloat($('input', price).val());

                    if ($.isNumeric($('input', quantity).val()) && $('input',
quantity).val() != 0) {
                        lines.push({
                            //the name must be same as Model name (docentry, itemcode
and etc is the model name)
                            //we push the value into the array
```

```
                    docentry: 0,
                    itemcode: itemdetails.cell(index, itemcode_column).data(),
                    itemdesc: itemdetails.cell(index, itemdesc_column).data(),
                    quantity: $('input', quantity).val(),
                    uom: itemdetails.cell(index, uom_column).data,
                    priceafterdiscount: $('input', price).val(),
                    unitprice: $('input', price).val(),
                    taxcode: itemdetails.cell(index, taxcode_column).data(),
                    vatsum: 0.00,
                    vatprcnt: 0.00,
                    linetotal: linetotal,
                    linenum: linenum
                });
                linenum = linenum + 1;
            }
        });

        var pr = {
            //header data
            id: id.val(),
            cardcode: cardcode.val(),
            cardname: cardname.val(),
            numatcard: numatcard.val(),
            contactperson: attn.val(),
            docdate: docdate.val(),
            doctype: doctype.val(),
            billadd4: billadd4.val(),

            //details or table
            lines: lines // the the loop data
        }


        //now we use ajax to call control and post to database.
        $.ajax({
            url: pathinfo.api + "ttfdocuments/portal/ordr",
            method: "POST",
            data: JSON.stringify(pr),
            contentType: "application/json; charset=utf-8",
            success: function (data) {
                alert("Successfully added Sales Order");

                window.location.reload();

            },
            error: function (data) {
                alert(data);
                //window.location.reload();
            }
        });
    }

});
```

Controller:

```
        [HttpPost]
        [Route("api/ttfdocuments/portal/{tableName}")]
        public HttpResponseMessage Portal_POST(string tableName, [FromBody]ft_ORDR u)
        {
            ActionModel action = new ActionModel();
            HttpStatusCode stsCode = HttpStatusCode.OK;

            try
            {

                    ft_ORDR ordr_p = new ft_ORDR();
                    //Portal
                    ordr_p.CardCode = u.CardCode;
                    ordr_p.CardName = u.CardName;
                    ordr_p.DocDate = u.DocDate;
                    ordr_p.DocStatus = u.DocStatus;
                    ordr_p.DocType = u.DocType;
                    ordr_p.BillAdd4 = u.BillAdd4;


                    ordr_p.Lines = new List<ft_RDR1>();
                    ft_RDR1 rdr1_p = null;
                    List<ft_RDR1> lines_p = new List<ft_RDR1>();
                    lines_p = u.Lines == null ? ordr_p.Lines : u.Lines;

                    foreach (ft_RDR1 q in lines_p)
                    {
                        rdr1_p = new ft_RDR1();
                        rdr1_p.DocEntry = q.DocEntry;
                        rdr1_p.LineNum = q.LineNum;
                        rdr1_p.ItemCode = q.ItemCode;
                        rdr1_p.ItemDesc = q.ItemDesc;
                        rdr1_p.Quantity = q.Quantity;
                        rdr1_p.UoM = q.UoM;
                        rdr1_p.TaxCode = q.TaxCode;
                        rdr1_p.LineTotal = q.LineTotal;
                        ordr_p.Lines.Add(rdr1_p);
                    }
                    ordr_p.Save();
            }
            catch (Exception ex)
            {
                stsCode = HttpStatusCode.NotAcceptable;
                action.ActionSuccess = false;
                action.Message = ex.Message;
                action.ActionResult = "";
            }

            return Request.CreateResponse<ActionModel>(stsCode, action);
        }
```

Model:

Header

```
public int Save()
        {
            int id = 0;

            DataTable dt = new DataTable();

            try
            {
                using (TransactionScope t = new TransactionScope())
                {

                    string spName = "SaveORDR_sp";

                    dt = DAC.ExecuteDataTable(spName,
                        DAC.Parameter(CN_DocEntry, DocEntry),
                        DAC.Parameter(CN_DocNum, DocNum),
                        DAC.Parameter(CN_DocDate, DocDate),
                        DAC.Parameter(CN_DocType, DocType),
                        DAC.Parameter(CN_DocStatus, DocStatus),
                        DAC.Parameter(CN_NumAtCard, NumAtCard),
                        DAC.Parameter(CN_UpdateDate, UpdateDate),
                        DAC.Parameter(CN_UserSign, UserSign),
                        DAC.Parameter(CN_BillAdd4, BillAdd4)
                        );

                    if (Lines != null)
                    {
                        ft_RDR1 d = new ft_RDR1();

                        foreach (ft_RDR1 i in Lines)
                        {
                            d.Save(i);
                        }
                    }

                    t.Complete();
                }
            }
            catch (Exception ex)
            {
                throw new Exception(ex.ToString());
            }


            return id;
        }
```

Details

```
public Boolean Save(ft_RDR1 d)
        {
            Boolean result = false;
            DataTable dt = new DataTable();
            string spName = "SaveRDR1_sp";

            try
            {
                dt = DAC.ExecuteDataTable(spName,
                       DAC.Parameter(CN_DocEntry, d.DocEntry),
                       DAC.Parameter(CN_LineNum, d.LineNum),
                       DAC.Parameter(CN_ItemCode, d.ItemCode),
                       DAC.Parameter(CN_ItemDesc, d.ItemDesc),
                       DAC.Parameter(CN_Quantity, d.Quantity),
                       DAC.Parameter(CN_UpdateQuantity, d.UpdateQuantity),
                       DAC.Parameter(CN_UoM, d.UoM),
                       DAC.Parameter(CN_InvUom, d.InvUom),
                       DAC.Parameter(CN_PriceAfterDiscount, d.PriceAfterDiscount),
                       DAC.Parameter(CN_UnitPrice, d.UnitPrice),
                       DAC.Parameter(CN_VatPrcnt, d.VatPrcnt),
                       DAC.Parameter(CN_VatSum, d.VatSum),
                       DAC.Parameter(CN_TaxCode, d.TaxCode),
                       DAC.Parameter(CN_LineTotal, d.LineTotal),
                       DAC.Parameter(CN_OcrCode, d.OcrCode),
                       DAC.Parameter(CN_OcrCode2, d.OcrCode2),
                       DAC.Parameter(CN_OcrCode3, d.OcrCode3),
                       DAC.Parameter(CN_OcrCode4, d.OcrCode4));
                result = true;
            }
            catch (Exception ex)
            {
                throw new Exception(ex.Message);
            }
            return result;
        }
```