

Flask SocketIO

General Information & Licensing

Code Repository	https://github.com/miguelgrinberg/Flask-SocketIO/blob/main/LICENSE
License Type	MIT License
License Description	<ul style="list-style-type: none">• A short and simple permissive license with conditions only requiring preservation of copyright and license notices. Licensed works, modifications, and larger works may be distributed under different terms and without source code.
License Restrictions	<ul style="list-style-type: none">• Liability• Warranty
Who worked with this?	Richard, Kelly, Jieli

SocketIO Class

Purpose

- Using SocketIO along with Flask allows us to set up a TCP connection between our client and server allowing for bidirectional communication.
- In line 33 of our code in app.py we initialise our socketio class.

- This technology does what it is supposed to do by using the socketIO Library in conjunction with our Flask app to successfully handle TCP sockets.
- The code that handles this tech is located in line 165 of server.py
<https://github.com/miguelgrinberg/python-socketio/blob/main/src/socketio/server.py>
 - If the received event is “connect” the function `_handle_connect` on line 648 of server.py is called. This function will successfully set up a TCP socket for users.
 - If the received event is “disconnect” the function `_handle_disconnect` on line 691 will be called in server.py and it will successfully remove the TCP socket for the user.
 - If the received event is neither of the two, the function `_handle_event` on line 701 will be called in server.py and it will respond to the given TCP connection based on what our server is responding with. This could be sending a message, etc. The function sends the tcp connection the values we sent to the TCP socket with our event handler.

run()

Purpose

- Runs our Flask app, but uses the socketIO framework to allow for TCP socket connections. The app is being run on port 5000, but docker runs it on 5050.
- This tech is located on line 396 in our app.py file.

Magic ★★°°) °↪° ★≡★°

- This technology runs the SocketIO web server by taking in the parameters for our flask app object, hostname, and a port. This now allows us to use our Flask object to respond and create TCP sockets via the SocketIO library.
- This code is located on line 516 of `__init__.py`
 - It serves forever and is actively looking to establish new TCP sockets with any users that connect.