ECE 544NA HW5

Jiaqi Mu jiaqimu2

Department of Electrical and Computer Engineering

November 12, 2016

1 TensorFlow

In this portion of the assignment, you will use a vanilla RNN and a LSTM to perform digit classification on the MNIST dataset.

- Setting 1 (Sequence of Pixels): It is assumed that each 28×28 image, x, in the MNIST dataset is a sequence of single pixels, x(1), ..., x(784), where x(t) is a single scalar value. The network reads one pixel at a time from the top left corner of the image to the bottem right of the image.
- Setting 2 (Sequence of Columns): It is assumed that each 28×28 image, x, in the MNIST dataset is a sequence of vectors, x(1), ..., x(28), where x(t) is a 28×1 vector representing one column in the image. The network reads one column at a time from left to right.

Train a basic (vanilla) RNN and a LSTM for each the two settings using a single layer RNN and LSRM with 100 hidden nodes. Perform classification on the last frame using cross entropy loss.

Revelant Tensorflow Doc: Tensorflow provides some API for recurrent neural network, please use the following:

- tf.nn.rnn: https://github.com/tensorflow/tensorflow/blob/master/tensorflow/g3doc/api_docs/python/functions_and_classes/shard0/tf.nn.rnn.md
- tf.nn.rnn_cell: https://www.tensorflow.org/versions/r0.11/api_docs/python/rnn_cell.html#neural-network-rnn-cells

1.1 Methods

• Describe the functions you wrote, and the overall structure of your code.

1.2 Results

- Provide one figure with four subfigures, showing convergence plots of all four (2 settings, 2 models) classifiers (abscissa = training iteration, ordinate = training-corpus accuracy)
- Provide a table reporting the testing accuracies.