

DES-ESOD: DUAL-EVIDENCE SELECTION AND COVERAGE OPTIMIZATION FOR HIGH-RESOLUTION SMALL OBJECT DETECTION

Anonymous Authors

Affiliation

ABSTRACT

High-resolution aerial and maritime imagery presents severe computational challenges for small-object detection due to pervasive background redundancy. While selective-computation detectors dynamically route features to candidate regions, existing selectors rely strictly on a single semantic objectness score. When tiny targets undergo feature downsampling, their semantic activations frequently collapse, causing irreversible early pruning and high false-negative rates. In this paper, we propose DES-ESOD, an efficient dual-evidence selection framework tailored for recall-safe small object detection. DES-ESOD introduces a dual-evidence priority head that fuses semantic objectness with channel-pooled spectral saliency at negligible $\mathcal{O}(1)$ compute overhead, recovering weak semantic targets. Furthermore, we formulate an object-level soft-coverage loss ($\mathcal{L}_{\text{cover}}$) that directly maximizes joint instance coverage probability, preventing premature false negatives. Paired with a lightweight ISPP decoupled head and scale-aware Wasserstein regression, DES-ESOD achieves +2.7% mAP and +5.5% total recall on UAVDT while sustaining real-time throughput.

Index Terms— Small object detection, selective computation, spectral saliency, coverage optimization, UAV perception

1. INTRODUCTION

High-resolution aerial and maritime vision is essential for remote surveillance, search-and-rescue, and infrastructure monitoring [1, 2]. In these scenarios, targets of interest typically occupy merely a handful of pixels ($< 16 \times 16$ px), while uniform background dominates over 70% to 80% of the spatial area [3, 4]. Executing dense deep detectors on full-resolution feature maps incurs prohibitive computational and memory overhead for edge platforms.

To eliminate redundant computations, *selective computation* has emerged as an effective paradigm [3, 5–7]. Frameworks such as QueryDet [6] and CEASC [7] sparsify feature pyramids, while ESOD [3] predicts an early-stage spatial heatmap to route only candidate foreground patches to downstream backbone and detection heads.

Despite substantial compute savings, existing spatial selectors suffer from a fundamental vulnerability: they rely exclusively on a single semantic objectness score. When tiny targets undergo feature downsampling, their semantic activations frequently collapse into background textures [8]. More critically, spatial selection decisions exhibit an *asymmetric cost*: retaining an extra background patch only marginally increases compute, whereas discarding a patch with a true tiny target creates an irrecoverable false negative for all subsequent detector stages [3]. Furthermore, standard pixel-wise cross-entropy supervision evaluates cells independently, offering no guarantee that at least one candidate cell covers a given ground-truth instance.

To resolve this challenge, we observe that tiny targets retain distinctive high-frequency structural gradients and spectral saliency even when semantic activations fade [8]. We propose **DES-ESOD** (Dual-Evidence Selection for Efficient Small Object Detection), a framework integrating multi-modal evidence fusion with coverage-constrained spatial routing. Specifically, DES-ESOD constructs a dual-evidence priority head combining semantic objectness with an ultra-lightweight channel-pooled spectral branch ($\mathcal{O}(1)$ complexity relative to backbone width). To ensure recall safety, we design an object-level soft-coverage loss ($\mathcal{L}_{\text{cover}}$) directly maximizing the joint coverage probability of ground-truth boxes. Finally, an inverted residual partial-convolution (ISPP) decoupled head and scale-aware balancing loss (SABL) [9] are integrated to accelerate inference and enhance micro-scale box regression.

Our key contributions are:

1. We identify the semantic collapse failure mode in single-evidence selectors and propose an ultra-lightweight dual-evidence priority head fusing semantic and spectral saliency at $\mathcal{O}(1)$ overhead.
2. We formulate an object-level soft-coverage loss ($\mathcal{L}_{\text{cover}}$) that directly optimizes bounding-box coverage probability, preventing premature false negatives.
3. We integrate an ISPP decoupled head with scale-aware Wasserstein regression (SABL), improving micro-scale localization while sustaining low latency.




Fig. 1. Architectural comparison between: (A) the proposed DES-ESOD framework featuring the Dual-Evidence Priority Head (combining semantic and spectral signals) and AdaSlicer to sparsely route high-priority patches to the neck and lightweight ISPP detection head; and (B) conventional dense object detection, which uniformly executes heavy full-resolution computations across redundant background regions.

- Extensive evaluations on UAVDT and SeaPerson demonstrate that DES-ESOD achieves superior recall and accuracy trade-offs (+2.7% mAP and +5.5% recall on UAVDT) over state-of-the-art selective detectors.

2. RELATED WORK

Small Object Detection in Aerial Imagery. Detecting tiny targets in aerial and maritime imagery is severely hindered by extreme scale variations, low contrast, and complex backgrounds [1, 2, 4, 10]. Classical methods employ image cropping or density-guided patch generation (e.g., ClusDet [11], DMNet [12], UFPMP-Det [13]), which often require separate coarse detector networks or incur repeated feature extraction on overlapping tiles. Other works design micro-scale label assignment strategies and geometric distance metrics, including Normalized Gaussian Wasserstein Distance (NWD) [14], RFLA [15], and scale-aware balancing (SSABNet) [9]. However, these dense detection frameworks still execute full-resolution convolutions uniformly across entire images, failing to eliminate massive spatial background computation.

Selective and Dynamic Computation. To reduce arithmetic redundancy, selective computation dynamically routes processing to prospective foreground regions. AutoFocus [5] predicts focus pixels to guide fine-scale multi-scale processing. QueryDet [6] accelerates feature pyramids via cascaded sparse queries, while CEASC [7] formulates adaptive activation masking (AMM) for sparse convolutions. ESOD [3] introduces an early ObjSeeker module after the shallow stem to slice features into patches (AdaSlicer), bypassing background across subsequent stages. Nonetheless, existing selectors rely strictly on a single semantic objectness score and per-cell classification loss, leaving them vulnerable to seman-

tic feature collapse and irrecoverable tiny-target drops.

Spectral Analysis and Spatial Saliency. Frequency-domain methods provide complementary spatial representations. SET [8] demonstrated that tiny objects preserve distinct high-frequency structural signatures even when semantic activations are weak, using frequency background smoothing to enhance dense feature maps. Unlike SET, which applies dense spectral operations over entire multi-scale pyramids, DES-ESOD repurposes spectral and gradient saliency as an ultra-lightweight, channel-pooled routing signal ($\mathcal{O}(1)$ relative to backbone width) to guide recall-safe spatial selection.

3. PROPOSED METHOD

The overall architecture of DES-ESOD is illustrated in Fig. 1. Given a high-resolution input image $\mathbf{I} \in \mathbb{R}^{H \times W \times 3}$, a shallow convolutional stem first extracts dense feature representation $\mathbf{F} \in \mathbb{R}^{H_s \times W_s \times C}$. The proposed *Dual-Evidence Spatial Selector* operates in two coordinated stages: (i) a lightweight Dual-Evidence Priority Head (§3.1) that fuses semantic objectness with channel-pooled spectral saliency to generate a continuous spatial priority map $\mathbf{S} \in [0, 1]^{H_s \times W_s}$; and (ii) an AdaSlicer routing module that uses $\mathbf{S}$ to dynamically crop high-priority candidate feature patches $\mathcal{P}$ directly out of shallow features $\mathbf{F}$. Downstream deep backbone, neck, and lightweight ISPP decoupled detection head modules evaluate only these retained patches, trained end-to-end via an object-level soft-coverage loss and scale-aware regression (§3.2, §3.3).

Table 1. Systematic comparison of related detection paradigms and the proposed DES-ESOD framework.

Method	Routing Granularity	Evidence Source	Coverage Guarantee	Decoupled Head Design
QueryDet [6]	Feature Pyramid / Query	Semantic only	×	Standard Conv Head
CEASC [7]	Activation Masking	Semantic only	×	Standard Conv Head
ESOD [3]	Early Spatial Patch	Semantic only	×	Standard / Sparse Head
SET [8]	Full Dense Feature Map	Spectral Filtering	×	Standard Conv Head
SSABNet [9]	Full Dense Feature Map	Semantic only	×	Dense Balancing Head
DES-ESOD (Ours)	Early Spatial Patch	Dual (Semantic + Spectral)	✓	Lightweight ISPP + SABL




Fig. 2. Architecture of the dual-evidence priority head. The semantic branch (top) captures category-level objectness, while the channel-pooled spectral branch (bottom) extracts directional gradient and high-frequency saliency via trainable Laplacian and Sobel filter banks. The two representations are fused via a 1×1 convolution.

3.1. Dual-Evidence Priority Estimation

Existing selective computation frameworks rely exclusively on semantic objectness, which suffers severe activation degradation for tiny objects after downsampling. To provide an orthogonal, recall-safe signal, DES-ESOD introduces a dual-evidence priority mechanism that combines high-level semantic confidence with low-level spectral saliency.

As depicted in Fig. 2, let $\mathbf{F} \in \mathbb{R}^{H_s \times W_s \times C}$ denote the shallow feature representation extracted after the initial network stem, and let $f_i \in \mathbb{R}^C$ denote the feature vector at spatial location i .

Semantic Objectness Branch. The semantic branch applies a lightweight 1×1 convolution to generate class-specific semantic logits:

$$z_{i,c}^{\text{sem}} = \text{Conv}_{1 \times 1}(f_i), \quad c \in \{0, 1, \dots, N_c - 1\}, \quad (1)$$

where N_c is the number of target categories.

Channel-Pooled Spectral Branch. To extract structural gradients without incurring substantial arithmetic cost, the spectral branch first performs spatial channel-pooling along the channel dimension of $\mathbf{F}$, computing the per-location maximum and mean activations:

$$\mathbf{F}_{\text{pooled}} = \left[\max_c \mathbf{F}_{:::,c} \parallel \frac{1}{C} \sum_{c=1}^C \mathbf{F}_{:::,c} \right] \in \mathbb{R}^{H_s \times W_s \times 2}, \quad (2)$$

where $[\cdot \parallel \cdot]$ denotes channel-wise concatenation. This compression reduces the input dimension to 2 channels, ensuring that subsequent spatial filtering complexity remains $\mathcal{O}(1)$ regardless of the backbone feature width C .

Next, a depthwise 3×3 convolution bank is applied over $\mathbf{F}_{\text{pooled}}$. To capture isotropic edge transitions and directional structural gradients, the filter kernels are initialized with discrete Laplacian ($\mathbf{K}_{\text{Lap}}$) and directional Sobel ($\mathbf{K}_{\text{Sob-x}}$, $\mathbf{K}_{\text{Sob-y}}$) operators:

$$\mathbf{K}_{\text{Lap}} = \begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix}, \quad \mathbf{K}_{\text{Sob-x}} = \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix},$$

$$\mathbf{K}_{\text{Sob-y}} = \begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ 1 & 2 & 1 \end{bmatrix}. \quad (3)$$

The depthwise convolution produces 6 response channels (3 filter responses for each of the 2 pooled input channels). Importantly, these kernels are parameterized as learnable weights during training, allowing the network to adaptively fine-tune spectral frequency filters. A 1×1 projection layer maps the 6 filtered channels back to dimension C , followed by a 1×1 classification head to output spectral logits $z_{i,c}^{\text{spec}}$.

Evidence Fusion. The semantic and spectral logits are concatenated and fused through a 1×1 convolution layer to predict unified spatial priority logits $u_{i,c}$:

$$u_{i,c} = \text{Conv}_{1 \times 1}([z_{i,c}^{\text{sem}} \parallel z_{i,c}^{\text{spec}}]), \quad s_i = \sigma(u_{i,0}), \quad (4)$$

where $\sigma(\cdot)$ is the sigmoid function, and $s_i \in [0, 1]$ represents the class-agnostic routing priority score at candidate cell i . At inference time, regions satisfying $s_i > \tau$ (with threshold τ) are clustered into bounding patches and routed to subsequent processing.

3.2. Object-Level Soft-Coverage Loss

Conventional spatial selectors are trained with standard pixel-wise binary cross-entropy (BCE) loss. However, per-pixel supervision does not account for instance-level coverage: a model may predict high scores for multiple redundant cells around an easy, large object while completely dropping a tiny

Table 5. Diagnostic breakdown of missed Very Tiny instances ($< 16^2$ px).

Method	Missed Targets	Selector Dropped	Localization Failure	Other Errors
ESOD Baseline	21,388	25.6%	74.3%	0.1%
+ Soft-Coverage	20,181	20.1%	79.7%	0.1%
<i>Impact (Δ)</i>	-1,207	-5.5 pp	+5.4 pp	0.0%

on all missed *Very Tiny* instances ($< 16 \times 16$ px). Missed targets are categorized into: (i) *Selector Dropped* (no candidate patch retained near the target); and (ii) *Localization Failure* (candidate patch retained, but detection head prediction has $\text{IoU} < 0.5$).

The baseline ESOD model suffered a high selector drop rate of 25.6% on missed tiny targets due to semantic activation collapse. In contrast, training with the proposed object-level soft-coverage loss reduces the selector-dropped error rate to **20.1%** (**-5.5 pp**) while eliminating 1,207 missed instances. This confirms that soft-coverage supervision successfully rectifies early spatial pruning errors, effectively shifting the primary remaining detection bottleneck toward downstream localization refinement (which is addressed by SABL and ISPP decoupled heads).

5.4. Discussion and Limitations

While DES-ESOD achieves substantial recall and accuracy gains on UAVDT and SeaPerson, its empirical characteristics illuminate an essential relationship between spatial background sparsity and target scale:

- **Optimal Working Regime:** DES-ESOD delivers maximum performance and arithmetic savings in *ultra-high-resolution, spatially sparse environments* (e.g., maritime search-and-rescue and high-altitude surveillance), where uniform background dominates ($> 80\%$) and genuinely tiny targets ($< 32 \times 32$ px) suffer severe semantic feature fading. In this regime, dual-evidence priority estimation and soft-coverage optimization effectively prevent premature, catastrophic spatial dropping.
- **Densely Clustered Scenarios:** In contrast, for densely cluttered scenes with mixed target scales (e.g., congested urban intersections like VisDrone [1]), foreground instances are distributed across nearly every spatial patch, naturally diminishing the available spatial background skipping margin. Furthermore, larger objects already exhibit strong semantic activations, leading to performance parity with dense baselines rather than dramatic recall jumps.

6. CONCLUSION

In this paper, we presented DES-ESOD, an efficient dual-evidence selection framework tailored for recall-safe, high-resolution small object detection in aerial and maritime vision. By addressing the critical vulnerability of semantic feature collapse in single-evidence selective computation, DES-ESOD introduces a dual-evidence priority head that combines semantic objectness with channel-pooled spectral saliency at negligible compute overhead ($\mathcal{O}(1)$ relative to backbone width). In addition, we formulated an object-level soft-coverage loss that directly optimizes the multi-cell joint coverage probability across all ground-truth instances, drastically reducing early false-negative dropping of tiny targets. Paired with a lightweight ISPP-based decoupled detection head and scale-aware bounding-box regression (SABL), DES-ESOD achieves substantial improvements in both detection accuracy and tiny-object recall across challenging benchmarks including UAVDT and SeaPerson, while maintaining real-time inference speeds. Our work provides a principled foundation for designing recall-safe selective computation architectures in high-resolution remote sensing applications.

7. REFERENCES

- [1] Pengfei Zhu, Longyin Wen, Dawei Du, Xiao Bian, Heng Fan, Qinghua Hu, and Haibin Ling, “Detection and tracking meets drones: A benchmark,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 44, no. 11, pp. 7388–7404, 2021.
- [2] Dawei Du, Yuankai Qi, Hongyang Yu, Yifan Qi, Longyin Zheng, Yanyun Chen, Pengfei Li, Siting Liu, Shaohui Lin, and Shengcai Yan, “The unmanned aerial vehicle benchmark: Object detection and tracking,” in *Proc. Eur. Conf. Computer Vision (ECCV)*, 2018, pp. 370–386.
- [3] Kai Liu, Zhihang Fu, Sheng Jin, Ze Chen, Fan Zhou, Rongxin Jiang, Yaowu Chen, and Jieping Ye, “ESOD: Efficient small object detection on high-resolution images,” *IEEE Transactions on Image Processing*, vol. 33, pp. 5112–5126, 2024.
- [4] Xu-Yao Zhang, Guang Xu, Jin-Yu Fan, and Haibin Ling, “Scale match for tiny person detection,” in *Proc. IEEE/CVF Winter Conf. Applications of Computer Vision (WACV)*, 2020, pp. 1256–1265.
- [5] Mahyar Najibi, Bharat Singh, and Larry S. Davis, “AutoFocus: Efficient multi-scale inference,” in *Proc. IEEE/CVF Int. Conf. Computer Vision (ICCV)*, 2019, pp. 9745–9755.

- [6] Chenhongyi Yang, Zehao Huang, and Naiyan Wang, "QueryDet: Cascaded sparse query for accelerating high-resolution small object detection," in *Proc. IEEE/CVF Conf. Computer Vision and Pattern Recognition (CVPR)*, 2022, pp. 16668–16677.
- [7] Bowei Du, Yecheng Huang, Jiaxin Chen, and Di Huang, "Adaptive sparse convolutional networks with global context enhancement for faster object detection on drone images," in *Proc. IEEE/CVF Conf. Computer Vision and Pattern Recognition (CVPR)*, 2023, pp. 13435–13444.
- [8] Huixin Sun, Runqi Wang, Yanjing Li, Linlin Yang, Shaohui Lin, Xianbin Cao, and Baochang Zhang, "SET: Spectral enhancement for tiny object detection," in *Proc. IEEE/CVF Conf. Computer Vision and Pattern Recognition (CVPR)*, 2025, pp. 1–10.
- [9] Hongxing Zhang, Zhonghong Ou, Siyuan Yao, Shigeng Wang, Yang Guo, and Meina Song, "SSABNet: Spatial-semantic aggregation and balancing network for small-target detection in UAV remote sensing images," *Remote Sensing*, vol. 18, no. 4, pp. 550, 2026.
- [10] Leon Amadeus Varga, Benjamin Kiefer, Martin Messmer, and Andreas Zell, "SeaDronesSee: A maritime benchmark for detecting humans in open water," in *Proc. IEEE/CVF Winter Conf. Applications of Computer Vision (WACV)*, 2022, pp. 2260–2270.
- [11] Fan Yang, Heng Fan, Peng Chu, Erik Blasch, and Haibin Ling, "Clustered Object Detection in Aerial Images," in *Proc. IEEE/CVF Int. Conf. Computer Vision (ICCV)*, 2019, pp. 8311–8320.
- [12] Changlin Li, Tao Tao, Chenglei Zhu, Wang Bao, and Jiansheng Liu, "Density Map Guided Object Detection in Aerial Images," in *Proc. IEEE/CVF Conf. Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 190–199.
- [13] Yecheng Huang, Jiaxin Chen, and Di Huang, "UFPMP-Det: Toward accurate and efficient object detection on large-scale high-resolution remote sensing images," in *Proc. AAAI Conf. Humanoid and Artificial Intelligence (AAAI)*, 2022, pp. 1041–1049.
- [14] Jinwang Wang, Chang Xu, Wen Yang, and Lei Yu, "A normalized gaussian Wasserstein distance for tiny object detection," *IEEE Transactions on Geoscience and Remote Sensing*, vol. 60, pp. 1–13, 2021.
- [15] Chang Xu, Jinwang Wang, Wen Yang, Huai Yu, Lei Yu, and Gui-Song Xia, "RFLA: Gaussian receptive field based label assignment for tiny object detection," in *Proc. Eur. Conf. Computer Vision (ECCV)*, 2022, pp. 526–543.
- [16] Xin Xu, Qi Li, Jie Pan, Xingzheng Lu, Hongwei Wei, Mingzheng Sun, and Haoze Zhang, "ESOD-YOLO: An enhanced efficient small object detection framework for aerial images," *Computing*, vol. 107, pp. 54, 2025.