

SIGIR 5 Papers

09/19/2018

Xiaosong Jia




Sentiment Analysis of Peer Review Texts for Scholarly Papers

Ke Wang and Xiaojun Wan

Institute of Computer Science and Technology, Peking University
The MOE Key Laboratory of Computational Linguistics, Peking University
Beijing, China

wangke17@pku.edu.cn, wanxiaojun@pku.edu.cn

Author



Xiaojun Wan

[Peking University](#)

Verified email at pku.edu.cn - [Homepage](#)

[Natural Language Processing](#) [Text Mining](#) [Artificial Intelligence](#)

Cited by

[VIEW ALL](#)

| | All | Since 2013 |
|-----------|------|------------|
| Citations | 3764 | 2702 |
| h-index | 27 | 25 |
| i10-index | 68 | 57 |

| TITLE | CITED BY | YEAR |
|---|----------|------|
| Co-training for cross-lingual sentiment classification X Wan Proceedings of the Joint Conference of the 47th Annual Meeting of the ACL ... | 405 | 2009 |
| Multi-document summarization using cluster-based link analysis X Wan, J Yang Proceedings of the 31st annual international ACM SIGIR conference on ... | 275 | 2008 |
| Manifold-Ranking Based Topic-Focused Multi-Document Summarization. X Wan, J Yang, J Xiao IJCAI 7, 2903-2908 | 223 | 2007 |
| Single Document Keyphrase Extraction Using Neighborhood Knowledge. X Wan, J Xiao AAAI 8, 855-860 | 219 | 2008 |




Motivation

- Whether the review texts and the recommendation scores are consistent with each other or not
- Help the chair to write a comprehensive meta-review
- Be convenient for authors to further improve their paper

- There is very few researches
- Long
- Mixture of non-opinionated and opinionated texts.
- Mixture of pros and cons.

Model



• Memory

$$e'_t = LSTM(\hat{h}_{t-1}, M_t), (\hat{h}_0 = I_i, t = 1, \dots, m)$$


$$e_t^{(i)} = \frac{\exp(e'_t)}{\sum_j \exp(e'_j)}$$

$$E^{(i)} = [e_t^{(i)}]_{t=1}^m$$

$$R^{(i)} = \sum_{t=1}^m e_t^{(i)} M_t$$

$$V_i = f_{mlp}(I_i || R^{(i)}; \theta_{mlp}).$$

Model



- Review classifier

$$P_i = \text{softmax}(W_p \cdot V_i + b_p),$$

$$P_i = [p_i^1, \dots, p_i^C]$$

$$\vec{h}_i = \overrightarrow{LSTM}(V_i)$$

$$\overleftarrow{h}_i = \overleftarrow{LSTM}(V_i)$$

$$h_i = \vec{h}_i || \overleftarrow{h}_i$$

$$h'_i = \tanh(W_a \cdot h_i + b_a)$$

$$a_i = \frac{\exp(h'_i)}{\sum_j \exp(h'_j)}$$


$$P_{review}^{(c)} = \sum_i a_i P_i^{(c)}, c \in [1, C]$$

Model

- Objective Function
the categorical cross-entropy loss

$$L(\theta) = \sum_{T_{review}} \sum_{c=1}^C -P_{review}^{(c)} \log(\bar{P}_{review}^{(c)}) \quad (17)$$

where T_{review} is the review text in the training data, $P_{review}^{(c)}$ and $\bar{P}_{review}^{(c)}$ are the true and predicted probabilities of belonging to the c -th class, respectively. We use Adam [21] with minibatch to learn the model parameter θ .





Experiment

- ICLR, NIPS workshops, ICML workshops on the OpenReview website(<https://openreview.net/>)
- Only ICLR 2017 and ICLR 2018 provided both peer reviews and the corresponding overall recommendation scores for each submission
- K-fold cross validation($k=10$)
- Google's 300-dimensional word vectors

Result

This paper presents low-rank bilinear pooling that uses Hadamard product. The paper implements . . .

.....

I like the insights about low-rank bilinear pooling using Hadamard product presented in the paper. *However, it could not be justified that low-rank bilinear pooling leads to better performance than compact bilinear pooling. It does lead to reduction in number of parameters but it is justification of why low-rank bilinear pooling is better than other forms of pooling.*

Prediction: **Accept**

Summary:

[+0.19] I like the insights about low-rank bilinear pooling leads . . .

[+0.12] The paper presents new insights into element-wise . . .

[+0.06] The paper presents a new model for the task of VQA . . .

[+ . . .] . . .

[- 0.12] it could not be experimentally verified that low-rank . . .

[- 0.11] I would like the authors to provide experimental . . .

[- 0.05] It is not very clear from reading the paper.

[- . . .] . . .

| Methods | ICLR-2017 | ICLR-2018 |
|-------------------|---------------------------|---------------------------|
| SVM(Uni) | 70.14% (+/- 4.37%) | 71.02% (+/- 3.81%) |
| SVM(Uni&Bi) | 71.56% (+/- 2.52%) | 73.23%(+/- 5.29%) |
| SVM(Uni&Bi&Senti) | 74.23% (+/- 3.21%) | 75.24% (+/- 2.36%) |
| CNN | 68.93% (+/- 5.24%) | 73.31% (+/- 2.70%) |
| LSTM | 65.24% (+/- 4.21%) | 69.25% (+/- 3.82%) |
| CNN+Bi-LSTM | 74.35% (+/- 3.51%) | 76.21% (+/- 4.08%) |
| CNN+Bi-LSTM+Att | 75.64% (+/- 3.42%) | 77.85% (+/- 3.72%) |
| MIL | 75.02% (+/- 2.85%) | 76.57% (+/- 2.31%) |
| MILAM | 78.24% (+/- 4.92%) | 80.32% (+/- 5.43%) |



A Co-Memory Network for Multimodal Sentiment Analysis

Nan Xu

Institute of Automation, Chinese
Academy of Sciences
University of Chinese Academy of
Sciences, Beijing, China
xunan2015@ia.ac.cn

Wenji Mao

Institute of Automation, Chinese
Academy of Sciences
University of Chinese Academy of
Sciences, Beijing, China
wenji.mao@ia.ac.cn

Guandan Chen

Institute of Automation, Chinese
Academy of Sciences
University of Chinese Academy of
Sciences, Beijing, China
chenguandan2014@ia.ac.cn



Motivation

- As visual and textual information in multimodal data can mutually **reinforce and complement** each other in analyzing the sentiment of people, previous research all ignores this mutual influence between image and text.

Model


- Image Feature:

$$M = \{m_1, m_2, \dots, m_L\}, m_i \in \mathbb{R}^{D_{img}}$$

$$h_i^1 = \tanh(w_{img}^1 m_i + b_{img}^1)$$

$$\alpha_i^1 = \frac{\exp(h_i^{1T} q_{img})}{\sum_{j=1}^L \exp(h_j^{1T} q_{img})}$$

$$v_{img}^1 = \sum_{i=1}^L \alpha_i^1 m_i$$



Model


- Text Feature:

$$X = \{x_1, x_2, \dots, x_T\}, x_t \in \mathbb{R}^{D_{text}}$$


$$g_t^1 = \tanh(w_{text}^1 x_t + b_{text}^1)$$

$$\beta_t^1 = \frac{\exp(g_t^{1T} q_{text})}{\sum_{r=1}^T \exp(g_r^{1T} q_{text})}$$

$$v_{text}^1 = \sum_{t=1}^T \beta_t^1 x_t$$



Model



- Co-Memory Network:
- 1. Text-guided Visual Memory Network (TgVMN):


$$h_i^2 = \tanh(w_{img}^2[m_i, v_{text}^1] + b_{img}^2)$$

$$\alpha_i^2 = \frac{\exp(h_i^2)}{\sum_{j=1}^L \exp(h_j^2)}$$

$$v_{img}^2 = \sum_{i=1}^L \alpha_i^2 m_i$$

Model

- 2. Image-guided Textual Memory Network (IgTMN):




$$g_t^2 = \tanh(w_{text}^2[x_t, v_{img}^1] + b_{text}^2)$$

$$\beta_t^2 = \frac{\exp(g_t^2)}{\sum_{r=1}^T \exp(g_r^2)}$$

$$v_{text}^2 = \sum_{t=1}^T \beta_t^2 x_t$$

Model



- Stacked Co-Memory Network:

$$v_{text}^k = IgTMN([x_t, v_{img}^{k-1}])$$

$$v_{img}^k = TgVMN([m_i, v_{text}^{k-1}])$$

- Sentiment Classification:

$$y = \text{Softmax}(w_s[v_{text}^K, v_{img}^K] + b_s)$$

Experiment

| Method | MVSA-Single | | MVSA-Multi | |
|-------------------------|--------------|--------------|--------------|--------------|
| | Acc | F1 | Acc | F1 |
| SentiBank+SentiStrength | 52.05 | 50.08 | 65.62 | 55.36 |
| CBOW+DA+LR | 63.86 | 63.52 | 64.22 | 63.73 |
| CNN-Multi | 61.20 | 58.37 | 66.39 | 64.19 |
| DNN-LR | 61.42 | 61.03 | 67.86 | 66.33 |
| HSAN | 66.83 | 66.9 | 68.16 | 67.76 |
| MultiSentiNet | 69.84 | 69.63 | 68.86 | 68.11 |
| MN-Hop1 | 64.31 | 63.12 | 67.16 | 66.48 |
| MN-Hop2 | 64.84 | 63.96 | 67.32 | 66.57 |
| MN-Hop2+text2img | 65.19 | 64.37 | 67.80 | 67.01 |
| MN-Hop2+img2text | 68.07 | 65.19 | 67.92 | 67.16 |
| CoMN-Hop2 | 70.07 | 68.03 | 68.68 | 68.06 |
| CoMN-Hop3 | 69.62 | 65.95 | 69.39 | 68.57 |
| CoMN-Hop4 | 69.18 | 68.29 | 69.92 | 69.83 |
| CoMN-Hop5 | 69.40 | 69.71 | 69.68 | 69.31 |
| CoMN-Hop6 | 70.51 | 70.01 | 68.92 | 68.83 |



RT @IraqiSecurity: Car bomb in Aden Sq, Kadhimiyah, N. #Baghdad. Initial reports suggest at least 5 martyrs & 22 wounded. #ShiaGenocide httбн



RT @IraqiSecurity: Car bomb in Aden Sq, Kadhimiyah, N. #Baghdad. Initial reports suggest at least 5 martyrs & 22 wounded. #ShiaGenocide httбн



Convolution-based Memory Network for Aspect-based Sentiment Analysis

Chuang Fan^{*}

Shenzhen Graduate School,
Harbin Institute of Technology

Qinghong Gao^{*}

Shenzhen Graduate School,
Harbin Institute of Technology

Jiachen Du

Shenzhen Graduate School,
Harbin Institute of Technology

Lin Gui

Aston University


Ruifeng Xu[†]

Shenzhen Graduate School,
Harbin Institute of Technology
xuruifeng@hit.edu.cn

Kam-Fai Wong

The Chinese University of Hong
Kong

Author



kam-Fai Wong

[chinese university of hong kong](#)

Verified email at se.cuhk.edu.hk - [Homepage](#)

[natuural language processing database](#)

Cited by

[VIEW ALL](#)

| | All | Since 2013 |
|-----------|------|------------|
| Citations | 4250 | 2252 |
| h-index | 32 | 23 |
| i10-index | 95 | 56 |

TITLE

CITED BY

YEAR

[Interpreting tf-idf term weights as making relevance decisions](#)

478

2008

HC Wu, RWP Luk, KF Wong, KL Kwok

ACM Transactions on Information Systems (TOIS) 26 (3), 13

[Component-based software engineering: technologies, development frameworks, and quality assurance schemes](#)

215

2000

X Cai, MR Lyu, KF Wong, R Ko

Software Engineering Conference, 2000. APSEC 2000. Proceedings. Seventh Asia ...

[Extractive summarization using supervised and semi-supervised learning](#)

148

2008

KF Wong, M Wu, W Li

Proceedings of the 22nd International Conference on Computational ...

[A genetic algorithm-based clustering approach for database partitioning](#)

130

2002

CH Cheng, WK Lee, KF Wong


IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and ...



Motivation

- Ordinary memory networks only capture word-level information and lack the capacity for modeling complicated expressions which consist of multiple words

Model



- Pre-processing:

$$M = \{m_1, m_2, \dots, m_n\}$$


- Attention:

$$g_i = w^T \left(\sum_{j=i-t}^{i+t} (m_j \oplus T) \right)$$

$$\alpha_i = \frac{\exp(g_i)}{\sum_{i'} \exp(g_{i'})}$$

$$o_j = T + \sum_{i=1}^n \alpha_i \cdot m_{i+j} \quad (j = -t, \dots, 0, \dots, t)$$

Model



- Multi-hop:

$$g_i = w^T (\sum_{j=i-t}^{i+t} (m_j \oplus o_{j-i}^{h-1}))$$

- Prediction:

$$o = o_{-t} \oplus o_{-t+1} \dots o_t$$

$$\hat{o} = \text{softmax}(W_m \cdot o)$$

- Objective function:

$$L = \sum_{(x,y) \in D} \sum_{c \in C} y^c \log f^c(x; \theta)$$

Experiment

Table 1: Experimental performance

| Method | Laptop | | Restaurant | | Tweet | |
|--------------------|---------------|---------------|---------------|---------------|---------------|---------------|
| | ACC | Macro-F1 | ACC | Macro-F1 | ACC | Macro-F1 |
| SVM | 0.7049 | NA | 0.8016 | NA | 0.6340 | 0.6330 |
| TD-LSTM | 0.7183 | 0.6843 | 0.7800 | 0.6673 | 0.6662 | 0.6401 |
| MemNet | 0.7033 | 0.6409 | 0.7816 | 0.6583 | 0.6850 | 0.6691 |
| RAM | 0.7449 | 0.7135 | 0.8023 | 0.7080 | 0.6936 | 0.6730 |
| Conv-Memnet | 0.7637 | 0.7210 | 0.7826 | 0.6838 | 0.7211 | 0.7080 |

| No. of Hops | Laptop | Restaurant | Tweet |
|--------------|---------------|---------------|---------------|
| Hop 1 | 0.6775 | 0.6689 | 0.6735 |
| Hop 2 | 0.7000 | 0.6752 | 0.6767 |
| Hop 3 | 0.7210 | 0.6838 | 0.7080 |
| Hop 4 | 0.6869 | 0.6741 | 0.6948 |
| Hop 5 | 0.6694 | 0.6406 | 0.6795 |
| Hop 6 | 0.6655 | 0.6226 | 0.6631 |




Figure 2: The changes in each hop of attention



SAAN: A Sentiment-Aware Attention Network for Sentiment Analysis

Zeyang Lei

Graduate School at Shenzhen,
Tsinghua University
leizy16@mails.tsinghua.edu.cn

Yujiu Yang

Graduate School at Shenzhen,
Tsinghua University
yang.yujiu@sz.tsinghua.edu.cn

Min Yang

Shenzhen Institutes of Advanced
Technology,
Chinese Academy of Sciences
min.yang1129@gmail.com

Motivation

- make full use of the prior sentiment knowledge (e.g., sentiment lexicon, negation words, intensity words)

Word-level correlation modeling

- Pre-processing:

$$x^c = [x_1^c, x_2^c, \dots, x_i^c, \dots, x_n^c]$$

$$x^s = [x_1^s, x_2^s, \dots, x_j^s, \dots, x_m^s]$$

$$R = (x^c)^T \cdot x^s \in \mathbb{R}^{n \times m} \quad (1)$$

where each element $R_{i,j}$ refers to the correlation between the i -th word x_i^c in the context and j -th word x_j^s in the sentiment resource words.

- Attention: $\phi = \text{softmax}\left(\frac{\sum_{h=1}^m R[:,h]}{m}\right)$ $\varphi = \text{softmax}\left(\frac{\sum_{k=1}^n R[k,:]}{n}\right)$
 $\mathbf{v}^\phi = \sum_{i=1}^n \phi_i \mathbf{x}_i^c$ $\mathbf{v}^\varphi = \sum_{i=1}^m \varphi_i \mathbf{x}_i^s$


Word-level correlation modeling

- Enhanced representation:

$$E^c = \tilde{f}_{\text{semantics}}(x^c + \mathbf{e}_n \otimes \mathbf{v}^\phi) \quad (2)$$

$$E^s = \tilde{f}_{\text{semantics}}(x^s + \mathbf{e}_m \otimes \mathbf{v}^\phi) \quad (4)$$

$$\tilde{f}_{\text{semantics}}(x) = \begin{cases} x & x > 0 \\ \xi(\exp(x) - 1) & x \leq 0, \xi > 0 \end{cases} \quad (3)$$



Phrase-Level Correlation Modeling

- CNN

$$P^c = P_{\ell_1}^c \oplus P_{\ell_2}^c \cdots \oplus P_{\ell_q}^c \quad (5)$$

$$P^s = P_{\ell_1}^s \oplus P_{\ell_2}^s \cdots \oplus P_{\ell_q}^s \quad (6)$$

$$P_{\ell_i}^c = \gamma(E^c * W^{\ell_i} + b) \in \mathbb{R}^{(n-\ell_i+1) \times k} \quad (7)$$

$$P_{\ell_i}^s = \gamma(E^s * W^{\ell_i} + b) \in \mathbb{R}^{(m-\ell_i+1) \times k}, i = 1, 2, \dots, q \quad (8)$$

- Attention

$$S = P^s \odot \{(P^c)^T \text{softmax}(P^c(P^s)^T)\}$$

$$\bar{s} = \frac{\sum_{j=1}^m S[:, j]}{m}$$



Final Model

- Sentence-level Semantic Modeling

$$\rho = Q^T \tanh(\tilde{U}(P^c + e_n \otimes \bar{s}))$$

$$B = \frac{\exp(\rho)}{\sum_{i=1}^n \exp(\rho)}$$

$$\tilde{\mathbf{o}} = \text{flatten}(BP^s)$$

- Sentence Classifier


$$\hat{y} = \frac{\exp(U_o^T \tilde{\mathbf{o}} + b_o)}{\sum_{k=1}^C \exp(U_o^T \tilde{\mathbf{o}} + b_o)}$$

- Loss function


$$L(\hat{y}, y) = - \sum_{i=1}^N \sum_{j=1}^C y_i^j \log(\hat{y}_i^j) + \lambda \left(\sum_{\theta \in \Theta} \theta^2 \right)$$

Experiment

| Methods | MR | SST(sent.-level) |
|-------------------------|--------------|------------------|
| RNTN [10] | 75.9% | 45.7% |
| LSTM [2] | 77.4% | 45.6% |
| BiLSTM | 79.3% | 46.5% |
| Tree-LSTM [11] | 80.7% | 48.1% |
| CNN [4] | 81.5% | 48.0% |
| NSCL [12] | 82.9% | 47.1% |
| LR-LSTM [8] | 81.5% | 48.3% |
| LR-Bi-LSTM [8] | 82.1% | 48.6% |
| Self-attention [6] | 82.5%* | 48.7%* |
| SAAN (our model) | 84.3% | 49.7% |



(a) MR



(b) SST



Measuring Influence on Instagram: a Network-oblivious Approach

Noam Segev, Noam Avigdor, Eytan Avigdor




Motivation


- Graphs information are not always available, and building them for Instagram users require a great deal of resources, e.g., crawling time and computing costs.
- Infer the underlying network structure using the user activity logs
- Instagram content, however, is “pulled”

Method


- Collected feature
 - $likes_c$ - Number of likes awarded to post c .
 - $comments_c$ - Number of comments given to post c .
 - v_c - Number of Instagrammers who watched part of the video.
- Instagram statistics



(a) Views Histogram



(b) Views per Followers



(c) Views per Likes



Method

- Features controlled

likes - The average number of user post likes.

comments - The average number of comments per user post.

followers - The users audience size.

$\sqrt{likes \cdot followers}$ - Geometric mean of likes and followers, taken as neither statistic is an exact representation of influence.

$\frac{followers}{post}$ - Used to suggest odd behavior as same level influencers should have similar ratios.

$\frac{comments}{likes}$ - Another odd behavior indicator as bought engagements tend to effect likes more than comments.

focus - The difference and ratio between most and least engaged post, these features were designed to test the variance and stability of a user engagement level.



Model

- Regression model
 - Ridge Regression(RR)
 - Random Forests(RF)

- Tricks

K-means

$$f(x) = \frac{x}{\ln x}$$

Experiment

| | Regression | | Multi-Regression | |
|--------------------------|--------------|--------------|------------------|--------------|
| | R^2 | r_s | R^2 | r_s |
| full Ridge Regression | 0.725 | 0.848 | 0.727 | 0.821 |
| full Random Forest | 0.626 | 0.869 | 0.621 | 0.861 |
| minimal Ridge Regression | 0.723 | 0.818 | 0.727 | 0.818 |
| minimal Random Forest | 0.616 | 0.864 | 0.611 | 0.859 |
| Followers Baseline | 0.211 | 0.757 | 0.204 | 0.725 |
| Likes Baseline | 0.666 | 0.859 | 0.654 | 0.853 |

Thanks!