

原CS61B Homework5作业回顾（附代码）

2018年03月07日 11:13:04vincent_chan7 阅读数：408 标签：CS61bJava

HW5一开始做不出来的同学可以继续先看Lecture，Encapsulated List那一节老师会回顾一下HW5，对作业有启发思路的作用。

Part1.

HW5的DListNode增加一个myList的field，用于确认node位于哪个list，同时也为后面的isValidNode()服务。

remove()之后需要将myList, prev, next 统统指向null，不然这个node的prev和next仍指向前后，后导致后面如果insertAfter出错。

Part2.

insert(), union(), intersection()等方法中的对比需要使用compareTo(), 因为求并交集时要比较字典序lexicographically，比如“3”在“5”的前面。而.equals(), compareTo()的用法

a==b	比较a和b是否指向同一个object
a.equals(b)	验证a和b是否相等。允许a.equals(null)
a.compareTo(b)	比较a和b的字典序， 1. a<b, 返回负数; 2.a=b,返回0； 3.a>b,返回正数。 a.compareTo(null)会返回NullPointerException

用了compareTo()之后要将item强制转换成Comparable
DListNode

```
1  /* DListNode.java */
2
3  package com.homework5;
4
5  /**
6   * A DListNode is a mutable node in a DList (doubly-linked list).
7   */
8
9  public class DListNode extends ListNode {
10
11     /**
12      * (inherited) item references the item stored in the current node.
13      * (inherited) myList references the List that contains this node.
14      * prev references the previous node in the DList.
15      * next references the next node in the DList.
16      *
17      * DO NOT CHANGE THE FOLLOWING FIELD DECLARATIONS.
18      */
19
20     protected DListNode prev;
21     protected DListNode next;
22
23     /**
24      * DListNode() constructor.
25      * @param i the item to store in the node.
26      * @param l the list this node is in.
27      * @param p the node previous to this node.
28      * @param n the node following this node.
29      */
30     DListNode(Object i, DList l, DListNode p, DListNode n) {
31         item = i;
32         myList = l;
33         prev = p;
34         next = n;
35     }
36
37     /**
38      * isValidNode returns true if this node is valid; false otherwise.
```

```

42 | *
43 | * @return true if this node is valid; false otherwise.
44 | *
45 | * Performance: runs in O(1) time.
46 | */
47 | public boolean isValidNode() {
48 |     return myList != null;
49 | }
50 |
51 | /**
52 | * next() returns the node following this node. If this node is invalid,
53 | * throws an exception.
54 | *
55 | * @return the node following this node.
56 | * @exception InvalidNodeException if this node is not valid.
57 | *
58 | * Performance: runs in O(1) time.
59 | */
60 | public ListNode next() throws InvalidNodeException {
61 |     if (!isValidNode()) {
62 |         throw new InvalidNodeException("next() called on invalid node");
63 |     }
64 |     return next;
65 | }
66 |
67 | /**
68 | * prev() returns the node preceding this node. If this node is invalid,
69 | * throws an exception.
70 | *
71 | * @return the node preceding this node.
72 | * @exception InvalidNodeException if this node is not valid.
73 | *
74 | * Performance: runs in O(1) time.
75 | */
76 | public ListNode prev() throws InvalidNodeException {
77 |     if (!isValidNode()) {
78 |         throw new InvalidNodeException("prev() called on invalid node");
79 |     }
80 |     return prev;
81 | }
82 |
83 | /**
84 | * insertAfter() inserts an item immediately following this node. If this
85 | * node is invalid, throws an exception.
86 | *
87 | * @param item the item to be inserted.
88 | * @exception InvalidNodeException if this node is not valid.
89 | *
90 | * Performance: runs in O(1) time.
91 | */
92 | public void insertAfter(Object item) throws InvalidNodeException {
93 |     if (!isValidNode()) {
94 |         throw new InvalidNodeException("insertAfter() called on invalid node");
95 |     }
96 |     // Your solution here. Will look something like your Homework 4 solution,
97 |     // but changes are necessary. For instance, there is no need to check if
98 |     // "this" is null. Remember that this node's "myList" field tells you
99 |     // what DList it's in. You should use myList.newNode() to create the
100 |    // new node.
101 |    DListNode new_node = ((DList)myList).newNode(item,(DList)myList,this,this.next);
102 |    this.next.prev = new_node;
103 |    this.next = new_node;
104 |    this.myList.size++;
105 | }
106 |
107 | /**
108 | * insertBefore() inserts an item immediately preceding this node. If this
109 | * node is invalid, throws an exception.
110 | *
111 | * @param item the item to be inserted.
112 | * @exception InvalidNodeException if this node is not valid.

```

```

113 | *114 | * Performance: runs in O(1) time.
115 | */
116 | public void insertBefore(Object item) throws InvalidNodeException {
117 |     if (!isValidNode()) {
118 |         throw new InvalidNodeException("insertBefore() called on invalid node");
119 |     }
120 |     // Your solution here. Will look something like your Homework 4 solution,
121 |     // but changes are necessary. For instance, there is no need to check if
122 |     // "this" is null. Remember that this node's "myList" field tells you
123 |     // what DList it's in. You should use myList.newNode() to create the
124 |     // new node.
125 |     DListNode new_node = ((DList)myList).newNode(item, (DList)myList, this.prev, this);
126 |     this.prev.next = new_node;
127 |     this.prev = new_node;
128 |     this.myList.size++;
129 | }
130 |
131 | /**
132 |  * remove() removes this node from its DList. If this node is invalid,
133 |  * throws an exception.
134 |  *
135 |  * @exception InvalidNodeException if this node is not valid.
136 |  *
137 |  * Performance: runs in O(1) time.
138 |  */
139 | public void remove() throws InvalidNodeException {
140 |     if (!isValidNode()) {
141 |         throw new InvalidNodeException("remove() called on invalid node");
142 |     }
143 |     // Your solution here. Will look something like your Homework 4 solution,
144 |     // but changes are necessary. For instance, there is no need to check if
145 |     // "this" is null. Remember that this node's "myList" field tells you
146 |     // what DList it's in.
147 |     this.prev.next = this.next;
148 |     this.next.prev = this.prev;
149 |     this.myList.size--;
150 |
151 |
152 |
153 |     // Make this node an invalid node, so it cannot be used to corrupt myList.
154 |     myList = null;
155 |     // Set other references to null to improve garbage collection.
156 |     next = null;
157 |     prev = null;
158 | }
159 |
160 | }

```

DList

```

1 | /* DList.java */
2 |
3 | package com.homework5;
4 |
5 | /**
6 |  * A DList is a mutable doubly-linked list ADT. Its implementation is
7 |  * circularly-linked and employs a sentinel node at the head of the list.
8 |  *
9 |  * DO NOT CHANGE ANY METHOD PROTOTYPES IN THIS FILE.
10 |  */
11 |
12 | public class DList extends List {
13 |
14 |     /**
15 |      * (inherited) size is the number of items in the list.
16 |      * head references the sentinel node.
17 |      * Note that the sentinel node does not store an item, and is not included
18 |      * in the count stored by the "size" field.
19 |      *

```

```

20 | * DO NOT CHANGE THE FOLLOWING FIELD DECLARATION. 21 | **/
22 |
23 | protected DListNode head;
24 |
25 | /* DList invariants:
26 | * 1) head != null.
27 | * 2) For every DListNode x in a DList, x.next != null.
28 | * 3) For every DListNode x in a DList, x.prev != null.
29 | * 4) For every DListNode x in a DList, if x.next == y, then y.prev == x.
30 | * 5) For every DListNode x in a DList, if x.prev == y, then y.next == x.
31 | * 6) For every DList l, l.head.myList = null. (Note that l.head is the
32 | * sentinel.)
33 | * 7) For every DListNode x in a DList l EXCEPT l.head (the sentinel),
34 | * x.myList = l.
35 | * 8) size is the number of DListNodes, NOT COUNTING the sentinel,
36 | * that can be accessed from the sentinel (head) by a sequence of
37 | * "next" references.
38 | **/
39 |
40 | /**
41 | * newNode() calls the DListNode constructor. Use this method to allocate
42 | * new DListNodes rather than calling the DListNode constructor directly.
43 | * That way, only this method need be overridden if a subclass of DList
44 | * wants to use a different kind of node.
45 | *
46 | * @param item the item to store in the node.
47 | * @param list the list that owns this node. (null for sentinels.)
48 | * @param prev the node previous to this node.
49 | * @param next the node following this node.
50 | **/
51 | protected DListNode newNode(Object item, DList list,
52 |                             DListNode prev, DListNode next) {
53 |     return new DListNode(item, list, prev, next);
54 | }
55 |
56 | /**
57 | * DList() constructs for an empty DList.
58 | **/
59 | public DList() {
60 |     // Your solution here. Similar to Homework 4, but now you need to specify
61 |     // the 'list' field (second parameter) as well.
62 |     head = newNode(null,null,null,null);
63 |     head.next = head;
64 |     head.prev = head;
65 |     size = 0;
66 | }
67 |
68 | /**
69 | * insertFront() inserts an item at the front of this DList.
70 | *
71 | * @param item is the item to be inserted.
72 | *
73 | * Performance: runs in O(1) time.
74 | **/
75 | public void insertFront(Object item) {
76 |     // Your solution here. Similar to Homework 4, but now you need to specify
77 |     // the 'list' field (second parameter) as well.
78 |     DListNode new_node = newNode(item,this,head,head.next);
79 |     head.next.prev = new_node;
80 |     head.next = new_node;
81 |     size++;
82 | }
83 |
84 | /**
85 | * insertBack() inserts an item at the back of this DList.
86 | *
87 | * @param item is the item to be inserted.
88 | *
89 | * Performance: runs in O(1) time.
90 | **/

```

```

91 | public void insertBack(Object item) { 92 |
    // Your solution here. Similar to Homework 4, but now you need to specify 93 |
    // the 'list' field (second parameter) as well. 94 |
    DListNode new_node = newNode(item, this, head.prev, head); 95 |
    head.prev.next = new_node; 96 | head.prev = new_node;
97 |     size++;
98 | }
99 |
100 | /**
101 |  * front() returns the node at the front of this DList. If the DList is
102 |  * empty, return an "invalid" node--a node with the property that any
103 |  * attempt to use it will cause an exception. (The sentinel is "invalid".)
104 |  *
105 |  * DO NOT CHANGE THIS METHOD.
106 |  *
107 |  * @return a ListNode at the front of this DList.
108 |  *
109 |  * Performance: runs in O(1) time.
110 |  */
111 | public ListNode front() {
112 |     return head.next;
113 | }
114 |
115 | /**
116 |  * back() returns the node at the back of this DList. If the DList is
117 |  * empty, return an "invalid" node--a node with the property that any
118 |  * attempt to use it will cause an exception. (The sentinel is "invalid".)
119 |  *
120 |  * DO NOT CHANGE THIS METHOD.
121 |  *
122 |  * @return a ListNode at the back of this DList.
123 |  *
124 |  * Performance: runs in O(1) time.
125 |  */
126 | public ListNode back() {
127 |     return head.prev;
128 | }
129 |
130 | /**
131 |  * toString() returns a String representation of this DList.
132 |  *
133 |  * DO NOT CHANGE THIS METHOD.
134 |  *
135 |  * @return a String representation of this DList.
136 |  *
137 |  * Performance: runs in O(n) time, where n is the length of the list.
138 |  */
139 | public String toString() {
140 |     String result = "[ ";
141 |     DListNode current = head.next;
142 |     while (current != head) {
143 |         result = result + current.item + " ";
144 |         current = current.next;
145 |     }
146 |     return result + "]";
147 | }
148 |
149 | private static void testInvalidNode(ListNode p) {
150 |     System.out.println("p.isValidNode() should be false: " + p.isValidNode());
151 |     try {
152 |         p.item();
153 |         System.out.println("p.item() should throw an exception, but didn't.");
154 |     } catch (InvalidNodeException lbe) {
155 |         System.out.println("p.item() should throw an exception, and did.");
156 |     }
157 |     try {
158 |         p.setItem(new Integer(0));
159 |         System.out.println("p.setItem() should throw an exception, but didn't.");
160 |     } catch (InvalidNodeException lbe) {
161 |         System.out.println("p.setItem() should throw an exception, and did.");
162 |     }

```

```

163 |     try {
164 |         p.next();
165 |         System.out.println("p.next() should throw an exception, but didn't.");
166 |     } catch (InvalidNodeException lbe) {
167 |         System.out.println("p.next() should throw an exception, and did.");
168 |     }
169 |     try {
170 |         p.prev();
171 |         System.out.println("p.prev() should throw an exception, but didn't.");
172 |     } catch (InvalidNodeException lbe) {
173 |         System.out.println("p.prev() should throw an exception, and did.");
174 |     }
175 |     try {
176 |         p.insertBefore(new Integer(1));
177 |         System.out.println("p.insertBefore() should throw an exception, but " +
178 |             "didn't.");
179 |     } catch (InvalidNodeException lbe) {
180 |         System.out.println("p.insertBefore() should throw an exception, and did."
181 |             );
182 |     }
183 |     try {
184 |         p.insertAfter(new Integer(1));
185 |         System.out.println("p.insertAfter() should throw an exception, but " +
186 |             "didn't.");
187 |     } catch (InvalidNodeException lbe) {
188 |         System.out.println("p.insertAfter() should throw an exception, and did."
189 |             );
190 |     }
191 |     try {
192 |         p.remove();
193 |         System.out.println("p.remove() should throw an exception, but didn't.");
194 |     } catch (InvalidNodeException lbe) {
195 |         System.out.println("p.remove() should throw an exception, and did.");
196 |     }
197 | }
198 |
199 | private static void testEmpty() {
200 |     List l = new DList();
201 |     System.out.println("An empty list should be [ ]: " + l);
202 |     System.out.println("l.isEmpty() should be true: " + l.isEmpty());
203 |     System.out.println("l.length() should be 0: " + l.length());
204 |     System.out.println("Finding front node p of l.");
205 |     ListNode p = l.front();
206 |     testInvalidNode(p);
207 |     System.out.println("Finding back node p of l.");
208 |     p = l.back();
209 |     testInvalidNode(p);
210 |     l.insertFront(new Integer(10));
211 |     System.out.println("l after insertFront(10) should be [ 10 ]: " + l);
212 | }
213 |
214 | public static void main(String[] argv) {
215 |     testEmpty();
216 |     List l = new DList();
217 |     l.insertFront(new Integer(3));
218 |     l.insertFront(new Integer(2));
219 |     l.insertFront(new Integer(1));
220 |     System.out.println("l is a list of 3 elements: " + l);
221 |     try {
222 |         ListNode n;
223 |         int i = 1;
224 |         for (n = l.front(); n.isValidNode(); n = n.next()) {
225 |             System.out.println("n.item() should be " + i + ": " + n.item());
226 |             n.setItem(new Integer(((Integer) n.item()).intValue() * 2));
227 |             System.out.println("n.item() should be " + 2 * i + ": " + n.item());
228 |             i++;
229 |         }
230 |         System.out.println("After doubling all elements of l: " + l);
231 |         testInvalidNode(n);
232 |
233 |         i = 6;

```

```

234     for (n = l.back(); n.isValidNode(); n = n.prev()) {
235         System.out.println("n.item() should be " + i + ": " + n.item());
236         n.setItem(new Integer((Integer) n.item().intValue() * 2));
237         System.out.println("n.item() should be " + 2 * i + ": " + n.item());
238         i = i - 2;
239     }
240     System.out.println("After doubling all elements of l again: " + l);
241     testInvalidNode(n);
242
243     n = l.front().next();
244     System.out.println("Removing middle element (8) of l: " + n.item());
245     n.remove();
246     System.out.println("l is now: " + l);
247     testInvalidNode(n);
248     n = l.back();
249     System.out.println("Removing end element (12) of l: " + n.item());
250     n.remove();
251     System.out.println("l is now: " + l);
252     testInvalidNode(n);
253
254     n = l.front();
255     System.out.println("Removing first element (4) of l: " + n.item());
256     n.remove();
257     System.out.println("l is now: " + l);
258     testInvalidNode(n);
259 } catch (InvalidNodeException lbe) {
260     System.err.println ("Caught InvalidNodeException that should not happen."
261         );
262     System.err.println ("Aborting the testing code.");
263 }
264 }
265 }

```

Set

```

1 package com.homework5; /* Set.java */
2
3
4 /**
5  * A Set is a collection of Comparable elements stored in sorted order.
6  * Duplicate elements are not permitted in a Set.
7  */
8 public class Set {
9     /* Fill in the data fields here. */
10     List setList;
11
12     /**
13      * Set ADT invariants:
14      * 1) The Set's elements must be precisely the elements of the List.
15      * 2) The List must always contain Comparable elements, and those elements
16      *    must always be sorted in ascending order.
17      * 3) No two elements in the List may be equal according to compareTo().
18      */
19
20     /**
21      * Constructs an empty Set.
22      *
23      * Performance: runs in O(1) time.
24      */
25     public Set() {
26         // Your solution here.
27         setList = new DList();
28     }
29
30     /**
31      * cardinality() returns the number of elements in this Set.
32      *
33      * Performance: runs in O(1) time.
34      */
35     public int cardinality() {

```

```

36 // Replace the following line with your solution. 37 | return setList.length();
38 }
39
40 /**
41  * insert() inserts a Comparable element into this Set.
42  *
43  * Sets are maintained in sorted order. The ordering is specified by the
44  * compareTo() method of the java.lang.Comparable interface.
45  *
46  * Performance: runs in O(this.cardinality()) time.
47  */
48 public void insert(Comparable c) {
49     // Your solution here.
50     if (setList.isEmpty()){
51         setList.insertFront(c);
52     } else {
53         ListNode current = setList.front();
54         try {
55
56             while(current != setList.back() && ((Comparable)(current.item)).compareTo(c) < 0){
57                 current = current.next();
58             }
59             if(((Comparable)(current.item)).compareTo(c) > 0){
60                 current.insertBefore(c);
61             } else if(current == setList.back() && ((Comparable)(current.item)).compareTo(c) < 0){
62                 current.insertAfter(c);
63             }
64
65         } catch (InvalidNodeException e){
66             System.out.println("Exception caught");
67         }
68     }
69 }
70
71 /**
72  * union() modifies this Set so that it contains all the elements it
73  * started with, plus all the elements of s. The Set s is NOT modified.
74  * Make sure that duplicate elements are not created.
75  *
76  * Performance: Must run in O(this.cardinality() + s.cardinality()) time.
77  *
78  * Your implementation should NOT copy elements of s or "this", though it
79  * will copy _references_ to the elements of s. Your implementation will
80  * create new _nodes_ for the elements of s that are added to "this", but
81  * you should reuse the nodes that are already part of "this".
82  *
83  * DO NOT MODIFY THE SET s.
84  * DO NOT ATTEMPT TO COPY ELEMENTS; just copy _references_ to them.
85  */
86 public void union(Set s) {
87     // Your solution here.
88     if(s != null && !s.setList.isEmpty()){
89         ListNode curNode = this.setList.front();
90         ListNode sNode = s.setList.front();
91         Comparable curItem, sItem;
92         try {
93             while (curNode.isValidNode() && sNode.isValidNode()){
94                 curItem = (Comparable)curNode.item;
95                 sItem = (Comparable)sNode.item;
96                 if (curItem.compareTo(sItem) == 0){
97                     curNode = curNode.next();
98                     sNode = sNode.next();
99                 } else if (curItem.compareTo(sItem) < 0){
100                     curNode = curNode.next();
101                 } else {
102                     curNode.insertBefore(sNode);
103                     curNode = curNode.next();
104                 }
105             }
106

```



```

107         while (sNode.isValidNode()){108             sItem = (Comparable)sNode.item;
109             setList.insertBack(sItem);
110             sNode = sNode.next();
111         }
112     } catch (InvalidNodeException e){
113         System.out.println("Union Failed");
114     }
115 }
116
117 }
118
119 /**
120  * intersect() modifies this Set so that it contains the intersection of
121  * its own elements and the elements of s. The Set s is NOT modified.
122  *
123  * Performance: Must run in O(this.cardinality() + s.cardinality()) time.
124  *
125  * Do not construct any new ListNodes during the execution of intersect.
126  * Reuse the nodes of "this" that will be in the intersection.
127  *
128  * DO NOT MODIFY THE SET s.
129  * DO NOT CONSTRUCT ANY NEW NODES.
130  * DO NOT ATTEMPT TO COPY ELEMENTS.
131  */
132 public void intersect(Set s) {
133     // Your solution here.
134     if (!s.setList.isEmpty() && s != null){
135         ListNode curNode = this.setList.front();
136         ListNode sNode = s.setList.front();
137         Comparable curItem, sItem;
138         try {
139             while(curNode.isValidNode() && sNode.isValidNode()){
140                 curItem = (Comparable)curNode.item;
141                 sItem = (Comparable)sNode.item;
142                 if (curItem.compareTo(sItem) == 0){
143                     curNode = curNode.next();
144                     sNode = sNode.next();
145                 } else if (curItem.compareTo(sItem) < 0) {
146                     if (curNode != setList.back()){
147                         curNode = curNode.next();
148                         curNode.prev().remove();
149                     } else{
150                         curNode.remove();
151                     }
152                 } else {
153                     sNode = sNode.next();
154                 }
155             }
156         }
157
158         while (curNode.isValidNode()){
159             if (curNode != setList.back()){
160                 curNode = curNode.next();
161                 curNode.prev().remove();
162             } else {
163                 curNode.remove();
164             }
165         }
166
167     }catch (InvalidNodeException e){
168         System.out.println("Intersect Failed");
169     }
170 }
171 }
172
173 /**
174  * toString() returns a String representation of this Set. The String must
175  * have the following format:
176  * { } for an empty Set. No spaces before "{" or after "}"; two spaces
177  * between them.
178  * { 1 2 3 } for a Set of three Integer elements. No spaces before

```


CS61B+CS170

UCB的本科课程CS61B和CS170是利用java语言对数据结构与算法进行了详细的讲... 来自： 一只小包子的博客

 免费开源CRM客户关系管理软件系统

百度广告

Berkeley CS61B_Data_Structures Video Lecture

recorded from: http://webcast.berkeley.edu/course_details.php?seriesid=19069783... 来自： ramboisme的专栏

CS61B sp2018笔记 | Lists

Lists 1. IntLists 下面我们来一步一步的实现List类，首先你可以实现一个最简单... 来自： 隐秀_

下载

final review for berkeley cs61b

关于伯克利公开课cs61b的期末复习文档

07-2

（原创笔记）加州伯克利大学CS61b数据结构（Java描述）一：对象

OOP(object-oriented programming): object: a repository of data; class: type of objec... 来自： Emacsor的博客

CS61B Homework9作业回顾（附代码）

本次作业主要学会运用Disjoin Sets，DisjointSets的class作业已经写好给出。class... 来自： everest115的博客

股市第三次机会来了！不看就亏大了！

唐煌投资 · 爆赚

cs61a spring 2018 Container笔记和补充 - CSDN博客

个人分类: CS61A Spring 2018 版权声明:欢迎交流学习...separating items with commas: [a], [a, b, c...HW5一开...

cs61a 2018 spring Lab4 Lists and Data Abstraction ..._CSDN博客

cs61a 2018 spring Lab4 Lists and Data Abstraction...('Stanford', 34.05, 118.25) >>> closer_...term) return temp...

CS61B sp2018笔记 | Introduction to Java

Introduction to Java Essentials 1. Reading 1.1 Hello World 这门课程虽然是用Ja... 来自： 隐秀_

文章热词

java记录目录树 javaweb 博客源码 java 用户登录挤下线 java开发直播平台 int数字比较 java

相关热词

cs61b是什么 cs61b课程 cs61b作业 cs61b字幕

LeetCode刷题笔记——LeetCode使用介绍

转载自http://blog.csdn.net/tostq 又到了一年毕业就业季了，三年前的校招季我逃... 来自： seabiscuity的博客

 麦哲思科技任甲林

关注

303篇文章

 温柔狼角色

关注

264篇文章

 zmycoco2

关注

444篇文章

CS61B sp2018笔记 | Efficient Programming - 隐秀_ - CSDN博客

05-14 Efficient C Programming Techniques.pdf Efficient...Spring IoC容器浅析及简单实现 Linux 基本操作总结(.....

CS61A 系列课程笔记(一) - CSDN博客

2018年05月06日 19:33:54 哈哈哈哈哈奇VIP 阅读...a,b=0,1 ... for i in range(2,n+1):cs61a 2018 spring Lab4 ...

下载

CS61B 教材2 Algorithms 4th Edition

CS61B 教材2 Algorithms 4th Edition - Robert Sedgewick and Kevin Wayne 高清英文原版

04-10

下载

【伯克利CS61B教材——Java 学习教程】 Head First Java 中文版

中文版的伯克利CS61B教材——经典Java 学习教程 《Head First Java 第二版》

05-08

cs61a课程总结--lecture7 递归（和一种数据结构）

数据结构 tuple 是一种至类型 来自： vczhfan的专栏

北京股王8年不亏铁律“1272”曝光，震惊众人！

陕西信息科技 · 燦燦

CS61A 系列课程笔记（一）

👁 1338

嗯 今天刚看第二周的课程，大量的 reading 材料我是真的要崩溃了，全英。。。... 来自：[柠檬黄先生的博客](#)

C++实现控制台版2048（内附彩蛋）

👁 124

前言 之前做过一个JavaScript版本的2048游戏，最近在学习C++，昨天晚上突然... 来自：[隐秀_](#)

cs61a 2018 spring Lab4 Lists and Data Abstraction 笔记

👁 89

list Lists are Python data structures that can store multiple values. list comprehensi... 来自：[Siucaan](#)

Homework6

👁 31

智能巡逻兵游戏规则游戏规则 使用WSAD或方向键上下左右移动player，进入巡逻兵... 来自：[qq_36335897的...](#)

【深入浅出】| 基于深度学习的机器翻译（附PDF+视频下载）

👁 1012

微信公众号关键字全网搜索最新排名【机器学习算法】：排名第一【机器学习】：排... 来自：[机器学习算法与...](#)



别再用MongoDB了

百度广告

leetcode全部题目答案

👁 1.3万

32. Longest Valid Parentheses Given a string containing just the characters '(' and ')... 来自：[陈善亮的博客](#)

LeetCode 答案(Easy) (1-100)

👁 1984

7. Reverse IntegerReverse digits of an integer.Example1: x = 123, return 321 Exa... 来自：[CapMiachael的...](#)

漫画：如何实现抢红包算法？

👁 1.2万

...

来自：[程序员小灰的博客](#)

微信红包的随机算法是怎样实现的？

👁 1.9万

导语：今天看到有人问：关于微信红包的随机算法！就查阅资料看了一下“微信红包... 来自：[精彩人生从此刻...](#)

LeetCode51——N-Queens

👁 1396

LeetCode51——N-Queens 求N皇后问题的所有解。经典的算法，从大三刚开始学... 来自：[上善若水](#)

股市第三次机会来了！不看就亏大了！

唐煌投资 · 燦燦

CS61B Homework4作业回顾（附代码）

👁 122

这次作业没有测试代码，一亩地上有测试数据链接:<http://pan.baidu.com/s/1dD5ql4P...> 来自：[everest115的博客](#)

java compareTo() 用法注意点

👁 1.9万

转自：<http://www.2cto.com/kf/201305/210466.html> compareTo就是比较两个值，如... 来自：[风随星月](#)

compareTo返回值为-1、1、0的排序问题

👁 1.2万

首先，先看代码内容：（希望大家自己可以运行尝试，以加深记忆和理解） packag... 来自：[狼郎](#)

达内课程-集合之LinkedList

👁 401

达内课程-集合之LinkedList 来自：[Errol's Blog](#)

Java中Collections.sort()排序详解

👁 3.5万

java中Collections.sort排序详解java基础—— Collections.sort的两种用法，简单明了 ... 来自：[薛瑾的博客](#)



php学习要多久

百度广告

代码回顾：编程中一些经验性的问题 👁 186

一、结构体编程：(1) 结构体初始化 今天在编程过程中。一个结构体定义 struct bss... 来自： [Something of a...](#)

下载 **Data Structures Lecture Notes (UCB CS61b)** 10-20
Data Structures Lecture Notes (UCB CS61b) Data Structures Lecture Notes (UCB CS61b)

一次git事故的回顾和学习 👁 240
此次回顾是针对之前在上海开发过程中，吕鹏提交的代码被我覆盖掉的事故。希望通... 来自： [渣va搬砖路](#)

下载 **中国中文信息学会发布《2018知识图谱发展报告》** 09-08
中国中文信息学会发布《2018知识图谱发展报告》报告目录如下（文末附下载链接） 第一章 知识表示与建模 第二章 知识表示学习 第三章 实体识别与链接 第四章 实体关系学习 第...

下载 **Data structure and algorithms in java** 05-29
CS61B课程中的配套课本，十分经典，涵盖数据结构和算法知识，以java语言的方式实现代码，赞！

靠死工资怎么买房买车，他们是这样赚钱的...

虹服 · 熯燄

LeetCode总结 👁 13.3万
最近完成了www.leetcode.com的online judge中151道算法题目。除各个题目有特殊... 来自： [Allan的专栏](#)

LeetCode刷题指南（一） 👁 8万
以下是我个人做题过程中的一些体会： 1. LeetCode的题库越来越大，截止到目前， ... 来自： [Lnho的专栏](#)

leetcode官网及使用 👁 6594
官网:leetcode 来自： [BoomMan](#)

刷了两遍LeetCode之后，我拿了9个offer 👁 2万
官方网站：http://leetcode.com/LeetCode是一个美国的在线编程网站，上面主要收集... 来自： [haimianjie2012...](#)

LeetCode所有题目答案汇总 👁 3623
最近再刷leetcode题目，找到了这个大神的博客总结，收藏一下 LeetCode All in One... 来自： [蘇丶的博客](#)

股市彻底变天了，不看你就要亏了！

陕西信息科技 · 熯燄

回顾2016，工作总结！ 👁 740
在2016年里，还记得最初自己的工作态度并不是非常的好，随着工作时间的累积， ... 来自： [~JackoChan](#)

团队敏捷实践：迭代回顾会议 👁 2867
迭代回顾会议（不超过1个小时） 1. 上一次的行动完成的证据。没有完成要怎么办... 来自： [xuesiyuan的专栏](#)

leetcode的开始—两数之和，c++ 👁 1401
给定一个整数数列，找出其中和为特定值的那两个数。你可以假设每个输入都只会有一... 来自： [prime_lee的博客](#)

我们的敏捷之路——回顾会议 👁 638
前言我们引入敏捷已经超过2年了，经过长时间的不断尝试逐渐摸索出一套适应于我... 来自： [zhaoenweiex的...](#)

CS61B sp2018笔记 | Generics and Autoboxing 👁 79
1. Automatic Conversions 1.1 Autoboxing and Unboxing Java中的泛型用到了&... 来自： [隐秀_](#)



电脑配置组装
百度广告

leetcode_812_ 最大三角形面积 👁 194
给定包含多个点的集合，从其中取三个点组成三角形，返回能组成的最大三角形的面... 来自： [Snow_Jie的博客](#)

LeetCode85——Maximal Rectangle

1820

初看这道题有点不知所措，但是其实是LeetCode84——Largest Rectangle in Histogram

来自： 上善若水

LeetCode84——Largest Rectangle in Histogram

1470

在柱状图中找到面积最大的矩形。

来自： 上善若水

【LeetCode-数据库】分数排名

1874

178. Rank Scores（中等） 题目：编写一个sql语句来实现分数排名，如果两个分数...

来自： 小白壮壮的博客

Google面经，已拿到offer哦！

2509

我面的职位是Software Engineer, Tools and Infrastructure, 所以开发和测试的问题都...

来自： UU小站



什么是核心期刊 核心期刊有哪些

百度广告

下载

软件工程作业 现代银行业务系统 UML C++

06-02

软件工程作业 内附用C++开发的代码、UML图及文档

肖仰华 | 知识图谱研究的回顾与展望

894

本文转载自公众号知识工场。

本文整理自2017年1...

来自： 开放知识图谱



vincent_chan7

关注

原创	粉丝	喜欢	评论
11	3	2	0

等级：  博客 已

访问： 991

积分： 118

排名： 126万+

勋章： 



十佳笔记本电脑



最新文章

前端学习笔记-BBC网站复刻

CS61B Homework9作业回顾（附代码）

CS61B Homework8 作业回顾（附代码）

CS61B Homework7作业回顾(附代码)

CS61B Homework6作业回顾（附代码）

归档

2018年5月	1篇
2018年4月	1篇
2018年3月	9篇

热门文章

- CS61B Homework5作业回顾（附代码）

阅读量：406
- CS61BHomework3作业回顾（附代码）

阅读量：127
- CS61B Homework4作业回顾（附代码）

阅读量：122
- CS61B Homework6作业回顾（附代码）

阅读量：92
- CS61B Homework9作业回顾（附代码）

阅读量：57



联系我们



扫码联系客服



区块链大本营

 QQ客服

 kefu@csdn.net

 客服论坛

 400-660-0108

工作时间 8:00-22:00

关于我们 招聘 广告服务 网站地图

 百度提供站内搜索 京ICP证09002463号

©2018 CSDN版权所有

网络110报警服务 经营性网站备案信息

北京互联网违法和不良信息举报中心

中国互联网举报中心