

Appendix R5: Variable Selection

Multi-Collinearity, Subset Selection and Step Methods

J. Alberto Espinosa

2024-06-22

This Quarto document contains R code examples about testing for violations of the OLS assumption of predictor independence and also to begin the process of selecting variables for your model. We illustrate a few popular methods to do systematic variable selection. For the corresponding conceptual material associated with these appendices, consult the main book [Predictive Analytics and Machine Learning for Managers](#).

Table of contents

Overview	1
1. Multicollinearity	2
Condition Index (CI)	2
Variance Inflation Factors (VIFs) and Tolerance	5
2. Variable Selection	7
Subset Selection	7
Step Methods	10
Forward Selection	12
Backward Selection	21
Stepwise Selection	26
Best Subset Selection	33

This script was created by J. Alberto Espinosa for educational and training purposes. Feel free to use this material for your own work, but please do not share or duplicate without the author's permission.

Overview

Dimensionality is an important issue in predictive modeling. As we add predictors and complex transformations in our model, the bias of the model decreases while the explanatory power of the model increases, but the model variance also increases. This is the well known **bias vs. variance trade-off** in predictive modeling. This is not really a problem when the multicollinearity of the model is tolerable, but it really affects its performance when multicollinearity is severe. In such cases, we need to pay close attention to how we select our predictors and whether multicollinearity is a concern. The methods described in this script can help correct for multicollinearity when predictors causing the problem can be removed. If not, please refer to the methods described in Ch. 7, which are ideally suited for predictive modeling in the presence of multicollinearity. I first discuss how to diagnose multicollinearity and then illustrate how to do subset selection and run various step methods for variable selection.

1. Multicollinearity

High multicollinearity causes a lot of variance in the model. Multicollinearity is tolerable, unless it is severe, in which case it causes the the model to have high variance and become unstable to be reliable. If you drop a few observations, the resulting coefficients should not change much. But if they change substantially, chances are that your model suffers from high multicollinearity.

Multicollinearity can be tested in two ways:

- Evaluate the **entire model** as a whole using the **Condition Index (CI)**. The multicollinearity condition of a model is an evaluation of the linear association of all the predictors together. This means two important things: (1) we don't need to evaluate the outcome variable, just the predictors; and (2) some variables may or may not have strong pairwise correlation, but the entire covariance structure of the predictors may exhibit multivariate linear associations that are not so easy to identify from the correlation matrix. For this purpose, we use the **CI**, which evaluates the overall linear association of all the predictors together.
- When the CI indicates that there is multicollinearity in the model's predictors, you can then inspect which specific predictors contribute the most to collinearity by inspecting the **Variance Inflation Variable (VIF)** of **each predictor**.

Technical Note: Multicollinearity refers to the overall linear relationship relations in a set of predictors. In turn, collinearity refers to the correlation of pairs of predictors. The general process when testing for multicollinearity is to evaluate the CI of the full set of predictors in the model. If the CI suggests that multicollinearity is tolerable, you can move on. If the CI indicates severe multicollinearity beyond tolerable levels, you can then inspect each predictor with their respective VIFs. I discuss this in more detail below.

Condition Index (CI)

Technical Note: The Condition Index (CI) is a general multicollinearity statistic for the full set of predictors in the model. The CI takes the covariance matrix of the predictors and computes its corresponding eigenvalues. As I discuss in more detail in Chapter 7, you can evaluate the dimensionality of a set of predictors by evaluating its eigenvalues. For example, if you have 3 predictors, you could draw a three-dimensional scatter plot of all your data points. You could then move the axes to the center of the data (i.e., all variables are at their means) and then rotate the axes until you find the direction in which the variance the largest. This direction is called the **First Eigenvector** and the variance along this direction is called the **First Eigenvalue**. You then keep this axis fixed and rotate the remaining 2 axes until you find the direction in which the variance is the second largest, which will yield the **Second Eigenvector-Eigenvalue** pair. And so ond. When the data has strong multicollinearity, the first few eigenvectors will be easy to visualize because you will see the data points aligning in one or few directions. When there is little multicollinearity, the scatter plot will look like a cloud of data points with no visible alignment in any direction.

In sum, a set of p predictors will have p eigenvalues, one for each dimension of the data. We can look at the largest eigenvalue and compare it to the smallest eigenvalue. If the difference is small, then multicollinearity is low. In contrast, if this difference is large, it means that there are obvious directions in which the data align, thus providing evidence of multicollinearity.

The **CI** is a simple statistic, computed as the **square root** of the **ratio of the largest to the smallest eigenvalue**. Based on numerous empirical studies, the rules of thumb about the CI are:

CI < 30 -> Multicollinearity is **not a concern** 30 < CI < 50 -> Multicollinearity is a concern, but is **somewhat tolerable** 50 < CI -> Multicollinearity is **severe** and **must be addressed**

In the examples below I use the `ols_eigen_cindex()` function in the `{olsrr}` package to compute the **CI** using the **Boston** housing data set in the `{MASS}` package. But there are other packages like `{klaR}`, `{car}` and `{perturb}` with similar diagnostic tools.

```
library(olsrr) # Tools for OLS regressions
library(MASS) # Contains the Boston housing market data set
```

Let's first fit the full model:

```
lm.fit <- lm(medv ~ ., data = Boston)
summary(lm.fit)
```

Call:

```
lm(formula = medv ~ ., data = Boston)
```

Residuals:

	Min	1Q	Median	3Q	Max
	-15.595	-2.730	-0.518	1.777	26.199

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)	
(Intercept)	3.646e+01	5.103e+00	7.144	3.28e-12	***
crim	-1.080e-01	3.286e-02	-3.287	0.001087	**
zn	4.642e-02	1.373e-02	3.382	0.000778	***
indus	2.056e-02	6.150e-02	0.334	0.738288	
chas	2.687e+00	8.616e-01	3.118	0.001925	**
nox	-1.777e+01	3.820e+00	-4.651	4.25e-06	***
rm	3.810e+00	4.179e-01	9.116	< 2e-16	***
age	6.922e-04	1.321e-02	0.052	0.958229	
dis	-1.476e+00	1.995e-01	-7.398	6.01e-13	***
rad	3.060e-01	6.635e-02	4.613	5.07e-06	***
tax	-1.233e-02	3.760e-03	-3.280	0.001112	**
ptratio	-9.527e-01	1.308e-01	-7.283	1.31e-12	***
black	9.312e-03	2.686e-03	3.467	0.000573	***
lstat	-5.248e-01	5.072e-02	-10.347	< 2e-16	***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 4.745 on 492 degrees of freedom

Multiple R-squared: 0.7406, Adjusted R-squared: 0.7338

F-statistic: 108.1 on 13 and 492 DF, p-value: < 2.2e-16

Now let's compute the CI:

```
coll <- ols_eigen_cindex(lm.fit)
coll[, 1:2] # Eigenvalues are in column 1 and CI in column 2
```

	Eigenvalue	Condition Index
1	10.092840813	1.000000
2	1.594070113	2.516245
3	0.959881737	3.242633
4	0.661730799	3.905405
5	0.241115274	6.469852
6	0.166505870	7.785597
7	0.108356145	9.651169
8	0.074488723	11.640227
9	0.041575247	15.580784
10	0.025639575	19.840440
11	0.013189367	27.662710
12	0.012073860	28.912366
13	0.007208734	37.417710
14	0.001323741	87.318288

Technical Note: There seems to be a glitch in R Studio's Visual mode in that it displays 10 rows at a time and when you click 2 or Next to see the rest of the display nothing shows. This appears to be working correctly in Source mode. So, if you need to see more than 10 rows, you have a few options and workarounds:

- (1) Click on the "Show in New Window" icon on the top-right of the chunk display to open a zoom window with the results.
- (2) Run your code chunk in Source mode.
- (3) Run the display command in the R console. You can go to the Console and press the up arrow key, which will bring up previously executed commands. Or you can just copy/paste the command to the Console. The Console will display all rows.
- (4) Show the few last 6 values with the `tail()` function.

```
tail(coll[, 1:2])
```

	Eigenvalue	Condition	Index
9	0.041575247	15.58078	
10	0.025639575	19.84044	
11	0.013189367	27.66271	
12	0.012073860	28.91237	
13	0.007208734	37.41771	
14	0.001323741	87.31829	

- (4) With the CI object, we are only interested in the last value of `coll` which is the actual CI. To display the only last value enter:

```
coll[nrow(coll), 1:2]
```

	Eigenvalue	Condition	Index
14	0.001323741	87.31829	

As I discussed earlier in class, if the eigenvalues change substantially, it is an indication that multicollinearity is present. The output in the example above shows all 14 eigenvalues, from largest to smallest. For example, the CI for the second eigenvalue is the $\sqrt{10.09 / 1.59} = 2.51$, which is OK. But we don't need to evaluate all eigenvalues relative to each other, but only need to **focus on the largest CI**, which is the CI for the entire predictor set in the model, which is the square root of the ratio of the largest eigenvalue to the lowest, or $\sqrt{10.09 / 0.0013} = 87.32$. This value is above 50, so we need to make some corrections. Also note that the function above computes the CI on the correlation, rather than the covariance matrix, which is equivalent to running the CI on a standardized data set with `scale = T` and `center = F`.

In Chapter 7 I will discuss a few methods to address dimensionality issues like multicollinearity. For now, let's see if we can address this multicollinearity issue by removing non-significant predictors. Before you try other modeling approaches, it is a good practice to explore adding and removing predictor, which is at the heart of most **variable selection** methods.

Let's try a reduced model, by removing a few non-significant predictors:

```
lm.fit.red <- lm(medv ~ crim + zn + chas + rm + dis +  
                 rad + tax + ptratio + black + lstat,  
                 data = Boston)  
summary(lm.fit.red)
```

```
Call:
lm(formula = medv ~ crim + zn + chas + rm + dis + rad + tax +
    ptratio + black + lstat, data = Boston)
```

Residuals:

	Min	1Q	Median	3Q	Max
	-16.980	-2.869	-0.693	1.732	26.674

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	22.605365	4.324998	5.227	2.55e-07 ***
crim	-0.096497	0.033446	-2.885	0.004082 **
zn	0.052811	0.013759	3.838	0.000140 ***
chas	2.380299	0.871150	2.732	0.006513 **
rm	3.940596	0.414703	9.502	< 2e-16 ***
dis	-1.054766	0.166731	-6.326	5.63e-10 ***
rad	0.282595	0.064772	4.363	1.56e-05 ***
tax	-0.015723	0.003351	-4.692	3.51e-06 ***
ptratio	-0.756520	0.125988	-6.005	3.71e-09 ***
black	0.010239	0.002729	3.753	0.000196 ***
lstat	-0.570699	0.047475	-12.021	< 2e-16 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 4.846 on 495 degrees of freedom
Multiple R-squared: 0.7279, Adjusted R-squared: 0.7224
F-statistic: 132.4 on 10 and 495 DF, p-value: < 2.2e-16

Let's look at the CI

```
coll.red <- ols_eigen_cindex(lm.fit.red)
coll.red[nrow(coll.red), 1:2]
```

	Eigenvalue	Condition Index
11	0.001814812	64.01555

Conclusion: The reduced model did not totally solve the multicollinearity since the CI = 64.02, which is greater than 50, so the multicollinearity condition is severe. Note that the predictor **nox** was significant in the full model, but it became non-significant when I removed the other non-significant predictors. The fact that **nox** lost its significance when I removed a few predictor is further evidence multicollinearity is a concern. So, I removed **nox** too. Now, let's find out which predictors contribute the most to multi-collinearity by examining the VIF's.

Variance Inflation Factors (VIFs) and Tolerance

VIFs and **Tolerance** help analyze each variable's individual contribution to multicollinearity. There is one VIF and Tolerance value for each predictor. A predictor's VIF measures how much is the standard error of its coefficient, compared to the standard error of the coefficient for the same variable, if it were modeled as a single-predictor model. It also measures how much of the variance of the predictor can be explained by the remaining predictors. The concept of Tolerance helps explain this. $\text{Tolerance}(i) = 1 - R_i^2$, where R_i^2 is the R-Squared of a regression with predictor i as an outcome and all other variables as predictors. In other words, it is the percent of the **variance** of predictor i that is **explained** by the other predictors.

Conversely, **Tolerance** measures the percent of the variance of predictor i that is **not** accounted by the other predictors. The **VIF** of predictor i is simply the inverse of Tolerance or $\text{VIF}_i = 1 / \text{Tolerance}(i) = 1 / (1 - R_i^2)$. Therefore, if $R_i^2 = 0$ (no correlation, perfectly independent) then $\text{Tolerance}(i) = 1$ and $\text{VIF}_i = 1$ (i.e.,

the coefficient of predictor i is not inflated at all). At the other extreme, $R_i^2 = 1$ (i.e., perfectly correlated, mathematically) will yield $\text{Tolerance}(i) = 0$ and $\text{VIF}_i = \text{infinite}$, with predictor i 's coefficient's **standard error** = **infinite**, and a model with no solution. A $R_i^2 = 0.8$ and 0.9 translate to $\text{Tolerance}(i) = 0.2$ and 0.1 and $\text{VIF}_i = 5$ and 10 , respectively. When examining VIF's, the typical rule of thumb thresholds are:

- $\text{VIF} < 5$ ($\text{Tolerance} > 0.2$) - No concern, little or **no contribution to multicollinearity**
- $5 < \text{VIF} < 10$ ($0.2 > \text{Tolerance} > 0.1$) - Some concern, but **tolerable**
- $\text{VIF} > 10$ ($\text{Tolerance} < 0.1$) - The variable **contributes** significantly to **multicollinearity**

To test VIF's, we can use the `vif()` function in the `{car}` (Companion to Applied Regression) package or the `ols_vif_tol()` function in the `{olsrr}` package. They are both equally good at reporting VIF's but the second function also reports the tolerance for each variable.

```
ols_vif_tol(lm.fit) # Full model
```

	Variables	Tolerance	VIF
1	crim	0.5579761	1.792192
2	zn	0.4350175	2.298758
3	indus	0.2505263	3.991596
4	chas	0.9311027	1.073995
5	nox	0.2275976	4.393720
6	rm	0.5171314	1.933744
7	age	0.3224948	3.100826
8	dis	0.2527841	3.955945
9	rad	0.1336095	7.484496
10	tax	0.1110056	9.008554
11	ptratio	0.5558384	1.799084
12	black	0.7415531	1.348521
13	lstat	0.3399636	2.941491

```
ols_vif_tol(lm.fit.red) # Reduced model
```

	Variables	Tolerance	VIF
1	crim	0.5618248	1.779914
2	zn	0.4515421	2.214633
3	chas	0.9497271	1.052934
4	rm	0.5476704	1.825916
5	dis	0.3772279	2.650918
6	rad	0.1461844	6.840676
7	tax	0.1457620	6.860500
8	ptratio	0.6250006	1.599998
9	black	0.7493034	1.334573
10	lstat	0.4045582	2.471832

Interestingly, the CI is severe in both models, but none of the VIF's are greater than 10 in either model. This suggests strongly that the collinearity is probably between one or two predictors and the constant. This issue can be resolved by centering all the variables, including the outcome, in addition to scaling, and fitting the model this way. Generally, if the CI is severe, but the VIF's are not, there is less of a concern because none of the predictor coefficients' standard errors are severely inflated.

Technical Note: You don't need to do this, but if you wish to inspect the R_i^2 alongside the Tolerance and VIFs, say for `lm.fit`, you can do it this way:

```
vi <- ols_vif_tol(lm.fit)
data.frame("Variable" = vi[,1],
```

```
"Ri-Squared" = 1-vi[,2],
"Tolerance" = vi[,2],
"VIF" = vi[,3])
```

	Variable	Ri.Squared	Tolerance	VIF
1	crim	0.44202393	0.5579761	1.792192
2	zn	0.56498252	0.4350175	2.298758
3	indus	0.74947367	0.2505263	3.991596
4	chas	0.06889725	0.9311027	1.073995
5	nox	0.77240242	0.2275976	4.393720
6	rm	0.48286858	0.5171314	1.933744
7	age	0.67750523	0.3224948	3.100826
8	dis	0.74721589	0.2527841	3.955945
9	rad	0.86639048	0.1336095	7.484496
10	tax	0.88899439	0.1110056	9.008554
11	ptratio	0.44416160	0.5558384	1.799084
12	black	0.25844689	0.7415531	1.348521
13	lstat	0.66003636	0.3399636	2.941491

One final note is that the function `ols_coll_diag()` of the `{olsrr}` package will run the CI and VIF test in one pass. So, if you are interested in both statistics together, you can use that instead.

2. Variable Selection

We explore two approaches to select predictors for a model with statistical methods. As discussed in the main chapter, these methods only work when the models are nested. If the model specifications are not nested (i.e., they involve different predictors), if the models are of different types, or if they are not OLS or GLM models, these methods don't work and you will need to use **cross-validation** to select the best models, which is discussed in depth in Chapter 6. In this section, I discuss two approaches to variable selection: (1) **Subset Selection**, which are applicable when you have a finite number of nested models and you want to test which one has the strongest explanatory power; and (2) **Step Methods**, which are useful when you have many predictors and no pre-defined idea of how to select the most appropriate ones.

Technical Note – Bias vs. Variance: I discuss this in more depth in Chapter 6, but this is one of the most fundamental trade offs in predictive modeling and it is important to understand it well. **Bias** means that the effects of one or more predictors deviates from the actual effects. This can happen due to a number of reasons, but one frequent cause is when we omit one or more predictors that should have been in the model, particularly when they have some correlation with one or more of the retained predictors. For example, if I'm trying to predict the mileage performance of a vehicle and I include vehicle weight as a predictor, but omit including vehicle power, then the effect of vehicle weight may be biased because the actual effect may be due to vehicle power, more than vehicle weight. Omitting vehicle power, will cause the effect of vehicle weight to pick up some of the effect of vehicle power, which will bias the effect of vehicle weight. **Variance** means that if we remove a few observations or if we get new data, the observed effect will vary substantially, thus making the model correct on average (i.e., not biased) but unstable and perhaps unreliable. Modeling is about striking the **optimal balance** of bias and variance. In general, smaller and less complex models tend to have higher bias and smaller variance. As we add predictors and complexity in a model, the bias gets reduced, but the variance increases. Somewhere in between, there is an optimal model. I discuss this in more depth in Chapter 6.

Subset Selection

The most effective way to compare the difference in explanatory power of two or more nested models is with an ANOVA F-Test. Smaller models are more biased, but large models can have more variance due to dimensionality, particularly if the multicollinearity condition is severe. So, this is a balancing act. The best approach is to select the

best predictors based on business knowledge and then test various subsets. When comparing two models, the larger model **always** has more explanatory power than the smaller model because we have added explanatory predictors to the model. But if the increase in explanatory power is not significant, then the added complexity of the larger model is undesirable, and the smaller model is preferred. But if the difference is significant, we would select the larger model. Naturally, after a model has been selected, it is important to test for multicollinearity. Let's use the baseball data to illustrate these concepts and fit three models: reduced, large and full.

Reduced Model, 3 Predictors:

```
library(ISLR) # Contains the Hitters baseball player salary data set
Hitters <- na.omit(Hitters) # Let's remove missing values
lm.reduced <- lm(Salary ~ AtBat + Hits + Walks,
                 data = Hitters)
summary(lm.reduced) # Take a look
```

Call:

```
lm(formula = Salary ~ AtBat + Hits + Walks, data = Hitters)
```

Residuals:

Min	1Q	Median	3Q	Max
-1007.5	-245.4	-70.8	165.4	2039.1

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	121.0590	73.2481	1.653	0.09960 .
AtBat	-2.0862	0.6324	-3.299	0.00111 **
Hits	8.9252	1.9922	4.480	1.12e-05 ***
Walks	7.1645	1.4097	5.082	7.16e-07 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 386.1 on 259 degrees of freedom

Multiple R-squared: 0.2758, Adjusted R-squared: 0.2674

F-statistic: 32.88 on 3 and 259 DF, p-value: < 2.2e-16

Large Model, 5 Predictors:

```
lm.large <- lm(Salary ~ AtBat + Hits + Walks + Division + PutOuts, # 5 predictors
               data = Hitters)
summary(lm.large) # Take a look
```

Call:

```
lm(formula = Salary ~ AtBat + Hits + Walks + Division + PutOuts,
    data = Hitters)
```

Residuals:

Min	1Q	Median	3Q	Max
-907.58	-216.89	-62.37	169.87	1965.55

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	173.02126	75.85170	2.281	0.02336 *
AtBat	-2.01116	0.62016	-3.243	0.00134 **
Hits	8.28040	1.95398	4.238	3.15e-05 ***
Walks	6.47059	1.38568	4.670	4.87e-06 ***

```

DivisionW    -120.43396    46.83854   -2.571   0.01070 *
PutOuts       0.26542     0.08795    3.018   0.00280 **
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

Residual standard error: 376.3 on 257 degrees of freedom
Multiple R-squared:  0.3176,    Adjusted R-squared:  0.3043
F-statistic: 23.92 on 5 and 257 DF,  p-value: < 2.2e-16

```

Full Model, 6 predictors

```

lm.full <- lm(Salary ~ AtBat + Hits + Walks + Division + PutOuts + Errors,
              data = Hitters)
summary(lm.full) # Take a look

```

Call:

```

lm(formula = Salary ~ AtBat + Hits + Walks + Division + PutOuts +
    Errors, data = Hitters)

```

Residuals:

```

      Min       1Q   Median       3Q      Max
-875.38 -208.93  -61.53   186.63  1980.81

```

Coefficients:

```

              Estimate Std. Error t value Pr(>|t|)
(Intercept)  183.51751    76.18550   2.409  0.01671 *
AtBat        -1.79757     0.64097  -2.804  0.00543 **
Hits         7.90088     1.97334   4.004 8.17e-05 ***
Walks        6.15433     1.40529   4.379 1.74e-05 ***
DivisionW    -120.78703    46.77802  -2.582  0.01038 *
PutOuts       0.26459     0.08784    3.012  0.00285 **
Errors       -4.93036     3.81042  -1.294  0.19686
---

```

```

Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

Residual standard error: 375.8 on 256 degrees of freedom
Multiple R-squared:  0.322, Adjusted R-squared:  0.3061
F-statistic: 20.27 on 6 and 256 DF,  p-value: < 2.2e-16

```

Now, let's use the `anova()` function to compare the models with **F-Test**. You can test these models in any order, but the convention is to go from smaller to larger model in the `anova()` function.

```

anova(lm.reduced, lm.large, lm.full)

```

Analysis of Variance Table

```

Model 1: Salary ~ AtBat + Hits + Walks
Model 2: Salary ~ AtBat + Hits + Walks + Division + PutOuts
Model 3: Salary ~ AtBat + Hits + Walks + Division + PutOuts + Errors
  Res.Df    RSS Df Sum of Sq    F    Pr(>F)
1     259 38613147
2     257 36385237  2    2227910  7.8888 0.0004735 ***
3     256 36148827  1     236409  1.6742 0.1968614
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

The ANOVA output above compares 3 models. But the comparisons are pairwise. That is, there are only 2 comparisons. The first line simply shows the degrees of freedom and residual sum of squares of the first model. Line 2 has the first comparison between **lm.reduced** and **lm.large**. The F-statistic in this comparison is 7.88, which translates to a significant p-value = 0.00047. This means that the large model has more explanatory power than the reduced model and this difference is significant. Line 3 has the second comparison between **lm.large** and **lm.full**. The F-statistic is quite small at 1.674 and the p-value = 0.196 is not significant. It is **very important** to note that the full model still has **more explanatory power** than the large model because it has more predictors, but the difference is **not significant**, so we retain the simpler large model. That is, the added size and complexity of the full model is not beneficial, statistically speaking.

One important thing to note is that if the `anova()` test is significant, the predictors we added will also be significant. Conversely, if the `anova()` test is not significant, the added predictors will not be significant either. This property is the foundation for the Step methods, which I discuss next.

Step Methods

Step methods are excellent for exploration when you don't have pre-selected subsets you would like to test. It is important to note that Step methods are no replacement for sound predictor selection from business domain familiarity, but they are very useful when the number of candidate predictors is quite large. For example, if you have 20 candidate predictors, there are $2^{20} = 1,048,576$ possible models, which is practically unfeasible to fully compare. For this purpose, we use the convenient `step()` function, which is included in the `{stats}` package that loads by default when you start R, which works with both `lm()` (OLS) and `glm()` (GLM) models. Let's illustrate its use with the **Hitters** baseball player data contained in the `{ISLR}` package.

There are three types of **Step** variable selection methods: **forward**, **backward** and **stepwise** (i.e., both). In all of three methods, there is a **lower bound** and an **upper bound** model. The Step method will add and remove predictors in between the lower and upper bound models. The lower bound model is the minimum and thus the mandatory set of predictors to include in the model. I often use the Null model (i.e., no predictors) for the lower bound, but if there are a few predictors that you must include in the model, you can set the lower bound to some Small model that includes those predictors only. For the upper bound, you can use the Full model that contains all the candidate predictors you identified. Let's start by specifying the lower and upper bound models

```
library(ISLR) # Contains the Hitters data set
options(scipen = 4) # To minimize the display of scientific notation
```

Lower bound model:

```
Hitters.null <- lm(Salary ~ 1, data = Hitters) # Null model with no predictors
summary(Hitters.null) # Take a look
```

Call:

```
lm(formula = Salary ~ 1, data = Hitters)
```

Residuals:

```
    Min      1Q  Median      3Q     Max
-468.4 -345.9 -110.9  214.1 1924.1
```

Coefficients:

```
              Estimate Std. Error t value Pr(>|t|)
(Intercept)   535.93      27.82   19.27  <2e-16 ***
---

```

```
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
Residual standard error: 451.1 on 262 degrees of freedom
```

Upper bound model:

```
Hitters.full <- lm(Salary ~., data = Hitters) # Full model with all predictors
summary(Hitters.full) # Take a look
```

Call:

```
lm(formula = Salary ~ ., data = Hitters)
```

Residuals:

	Min	1Q	Median	3Q	Max
	-907.62	-178.35	-31.11	139.09	1877.04

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)	
(Intercept)	163.10359	90.77854	1.797	0.073622	.
AtBat	-1.97987	0.63398	-3.123	0.002008	**
Hits	7.50077	2.37753	3.155	0.001808	**
HmRun	4.33088	6.20145	0.698	0.485616	
Runs	-2.37621	2.98076	-0.797	0.426122	
RBI	-1.04496	2.60088	-0.402	0.688204	
Walks	6.23129	1.82850	3.408	0.000766	***
Years	-3.48905	12.41219	-0.281	0.778874	
CAtBat	-0.17134	0.13524	-1.267	0.206380	
CHits	0.13399	0.67455	0.199	0.842713	
CHmRun	-0.17286	1.61724	-0.107	0.914967	
CRuns	1.45430	0.75046	1.938	0.053795	.
CRBI	0.80771	0.69262	1.166	0.244691	
CWalks	-0.81157	0.32808	-2.474	0.014057	*
LeagueN	62.59942	79.26140	0.790	0.430424	
DivisionW	-116.84925	40.36695	-2.895	0.004141	**
PutOuts	0.28189	0.07744	3.640	0.000333	***
Assists	0.37107	0.22120	1.678	0.094723	.
Errors	-3.36076	4.39163	-0.765	0.444857	
NewLeagueN	-24.76233	79.00263	-0.313	0.754218	

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 315.6 on 243 degrees of freedom

Multiple R-squared: 0.5461, Adjusted R-squared: 0.5106

F-statistic: 15.39 on 19 and 243 DF, p-value: < 2.2e-16

A solution with any of the Step methods will yield a model in between the lower and upper bound models. The `step()` function can be set to perform in a forward, backward and stepwise (both) directions for the variable selection between the two models.

The inclusion and exclusion p-value thresholds are $p < 0.15$ by default. This means that predictors will only be added to the model if they are significant at the $p < 0.15$ level and will only be removed if their p-values are greater than $p > 0.15$. This default can be changed as needed with the parameter `k`. The default is `k = 2`, which is approximately equivalent to $p < 0.15$. If you want more predictors in the final model, increase the p-value threshold by using higher values of `k`. For example, `k = 2.7` yields approximately $p < 0.10$. If you want fewer predictors in the final model, lower the p-value to a more restrictive inclusion level, by reducing `k`. To find exactly how `k` relates to p-values, you can use the chi-square distribution function `qchisq()`:

```
qchisq(0.01, 1, lower.tail = F) # the k value for p < 0.01 is 6.634
```

```
[1] 6.634897
```

```
qchisq(0.05, 1, lower.tail = F) # the k value for p < 0.05 is 3.841
```

```
[1] 3.841459
```

```
qchisq(0.10, 1, lower.tail = F) # the k value for p < 0.10 is 2.705
```

```
[1] 2.705543
```

```
qchisq(0.15, 1, lower.tail = F) # the k value for p < 0.15 is 2.072
```

```
[1] 2.072251
```

Because Step methods are exploratory in nature, there is no particular reason to change the default k value, as you will be able to observe the significance level of each predictor included. Nevertheless, you can use p-values smaller than 0.15 or k values higher than 2 to obtain smaller models, or use larger p-values or smaller k values to obtain larger models.

Forward Selection

In forward selection, the search starts with the lower bound model and the method adds predictors one at a time, starting with the most significant one and stopping when none of the predictors omitted from the model would have a $p < 0.15$ (or whatever threshold you used) if included in the model. The forward selection method **only adds variables**, one at a time, but does not remove any variables if they become non-significant.

To run a forward step variable selection use the lower and upper bound models in the `scope =` parameter using the `list()` function (i.e., the scope is passed to the `step()` function as a list object). The first model entered in the `step()` function is the starting point in the variable selection process. Since we are using the forward method, the starting point must be the **Null** model because we will only be adding predictors. We also need to use the `direction = "forward"` parameter, which will cause the `step()` function to only add predictors. Finally, we need to include the `test = F` parameter, which will cause the `step()` function to evaluate the inclusion of predictors based on the significance p-value of the added predictor, which is equivalent to an F-test. Otherwise, the default comparison criteria is the AIC (Akaike's Information Criterion), which is a generic statistic of predictive accuracy. You should get similar results, but the F-test is more robust.

```
Hitters.fwd <- step(Hitters.null,
  scope = list(lower = Hitters.null,
               upper = Hitters.full),
  direction = "forward",
  test = "F")
```

```
Start: AIC=3215.77
```

```
Salary ~ 1
```

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
+ CRBI	1	17139434	36179679	3115.8	123.6438	< 2.2e-16 ***
+ CRuns	1	16881162	36437951	3117.6	120.9174	< 2.2e-16 ***
+ CHits	1	16065140	37253973	3123.5	112.5518	< 2.2e-16 ***
+ CAtBat	1	14759710	38559403	3132.5	99.9052	< 2.2e-16 ***
+ CHmRun	1	14692193	38626920	3133.0	99.2744	< 2.2e-16 ***

+ CWalks	1	12792622	40526491	3145.6	82.3874	< 2.2e-16	***
+ RBI	1	10771083	42548030	3158.4	66.0725	1.757e-14	***
+ Walks	1	10504833	42814280	3160.1	64.0385	4.014e-14	***
+ Hits	1	10260491	43058621	3161.6	62.1940	8.531e-14	***
+ Runs	1	9399158	43919955	3166.8	55.8557	1.180e-12	***
+ Years	1	8559105	44760007	3171.7	49.9090	1.463e-11	***
+ AtBat	1	8309469	45009644	3173.2	48.1846	3.065e-11	***
+ HmRun	1	6273967	47045145	3184.8	34.8071	1.125e-08	***
+ PutOuts	1	4814100	48505013	3192.9	25.9041	6.871e-07	***
+ Division	1	1976102	51343011	3207.8	10.0454	0.001709	**
<none>			53319113	3215.8			
+ Assists	1	34497	53284615	3217.6	0.1690	0.681361	
+ League	1	10876	53308237	3217.7	0.0532	0.817687	
+ Errors	1	1555	53317558	3217.8	0.0076	0.930538	
+ NewLeague	1	428	53318684	3217.8	0.0021	0.963511	

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3115.78

Salary ~ CRBI

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)	
+ Hits	1	5533119	30646560	3074.1	46.9420	5.275e-11	***
+ Runs	1	5176532	31003147	3077.2	43.4117	2.450e-10	***
+ Walks	1	4199733	31979946	3085.3	34.1442	1.526e-08	***
+ AtBat	1	4064585	32115095	3086.4	32.9064	2.681e-08	***
+ RBI	1	3308272	32871407	3092.6	26.1671	6.085e-07	***
+ PutOuts	1	3267035	32912644	3092.9	25.8086	7.204e-07	***
+ Division	1	1733887	34445793	3104.9	13.0875	0.0003571	***
+ Years	1	1667339	34512340	3105.4	12.5610	0.0004669	***
+ HmRun	1	1271587	34908092	3108.4	9.4709	0.0023108	**
+ CRuns	1	354561	35825119	3115.2	2.5732	0.1099006	
+ Assists	1	346020	35833659	3115.2	2.5106	0.1142958	
<none>			36179679	3115.8			
+ Errors	1	194403	35985276	3116.4	1.4046	0.2370372	
+ CAtBat	1	92261	36087418	3117.1	0.6647	0.4156463	
+ CHits	1	75469	36104210	3117.2	0.5435	0.4616584	
+ CWalks	1	51974	36127705	3117.4	0.3740	0.5413451	
+ NewLeague	1	17778	36161901	3117.7	0.1278	0.7209896	
+ League	1	11825	36167855	3117.7	0.0850	0.7708606	
+ CHmRun	1	515	36179165	3117.8	0.0037	0.9515485	

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3074.13

Salary ~ CRBI + Hits

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)	
+ PutOuts	1	1397263	29249297	3063.8	12.3726	0.0005143	***
+ Division	1	1279275	29367285	3064.9	11.2824	0.0009002	***
+ AtBat	1	821767	29824793	3069.0	7.1363	0.0080327	**
+ Walks	1	781767	29864793	3069.3	6.7798	0.0097516	**
+ Years	1	254910	30391650	3073.9	2.1724	0.1417246	
<none>			30646560	3074.1			
+ League	1	208880	30437680	3074.3	1.7774	0.1836405	
+ CRuns	1	132614	30513946	3075.0	1.1256	0.2897011	

```

+ NewLeague 1 118474 30528086 3075.1 1.0051 0.3170083
+ Runs 1 114198 30532362 3075.1 0.9687 0.3259179
+ Errors 1 99776 30546784 3075.3 0.8460 0.3585477
+ CAtBat 1 83517 30563043 3075.4 0.7077 0.4009684
+ Assists 1 44781 30601779 3075.7 0.3790 0.5386742
+ CWalks 1 23668 30622892 3075.9 0.2002 0.6549532
+ CHmRun 1 4790 30641769 3076.1 0.0405 0.8406802
+ CHits 1 4358 30642202 3076.1 0.0368 0.8479531
+ HmRun 1 2173 30644387 3076.1 0.0184 0.8923043
+ RBI 1 1137 30645423 3076.1 0.0096 0.9219997
---
Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

Step: AIC=3063.85
Salary ~ CRBI + Hits + PutOuts

```

```

      Df Sum of Sq    RSS   AIC F value    Pr(>F)
+ Division 1 1278445 27970852 3054.1 11.7922 0.0006928 ***
+ AtBat 1 1009933 28239364 3056.6 9.2269 0.0026294 **
+ Walks 1 539490 28709807 3061.0 4.8481 0.0285617 *
+ CRuns 1 273649 28975648 3063.4 2.4366 0.1197606
<none>          29249297 3063.8
+ Years 1 136906 29112391 3064.6 1.2133 0.2717085
+ League 1 122841 29126456 3064.8 1.0881 0.2978655
+ Runs 1 117930 29131367 3064.8 1.0444 0.3077496
+ Errors 1 97244 29152053 3065.0 0.8606 0.3544307
+ NewLeague 1 57839 29191458 3065.3 0.5112 0.4752699
+ CHits 1 35096 29214201 3065.5 0.3099 0.5781973
+ RBI 1 33965 29215331 3065.6 0.2999 0.5843887
+ HmRun 1 31227 29218070 3065.6 0.2757 0.5999583
+ CWalks 1 28572 29220725 3065.6 0.2523 0.6159089
+ CAtBat 1 20518 29228779 3065.7 0.1811 0.6707739
+ Assists 1 1681 29247616 3065.8 0.0148 0.9031641
+ CHmRun 1 1419 29247878 3065.8 0.0125 0.9109989
---
Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

Step: AIC=3054.1
Salary ~ CRBI + Hits + PutOuts + Division

```

```

      Df Sum of Sq    RSS   AIC F value    Pr(>F)
+ AtBat 1 820952 27149899 3048.3 7.7711 0.005705 **
+ Walks 1 491584 27479268 3051.4 4.5975 0.032956 *
<none>          27970852 3054.1
+ CRuns 1 193604 27777248 3054.3 1.7913 0.181956
+ Years 1 166845 27804007 3054.5 1.5422 0.215424
+ League 1 110628 27860224 3055.1 1.0205 0.313351
+ Errors 1 81385 27889467 3055.3 0.7500 0.387296
+ Runs 1 65921 27904931 3055.5 0.6071 0.436592
+ RBI 1 53719 27917133 3055.6 0.4945 0.482553
+ NewLeague 1 52275 27918577 3055.6 0.4812 0.488502
+ CHits 1 33863 27936989 3055.8 0.3115 0.577240
+ HmRun 1 26390 27944462 3055.8 0.2427 0.622679
+ CAtBat 1 18751 27952101 3055.9 0.1724 0.678330
+ CWalks 1 5723 27965129 3056.0 0.0526 0.818791
+ Assists 1 1036 27969816 3056.1 0.0095 0.922368

```

```
+ CHmRun      1      165 27970687 3056.1  0.0015 0.968952
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Step: AIC=3048.26

Salary ~ CRBI + Hits + PutOuts + Division + AtBat

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
+ Walks	1	954996	26194904	3040.8	9.3331	0.002488 **
+ Years	1	253362	26896537	3047.8	2.4115	0.121683
+ Runs	1	208743	26941157	3048.2	1.9835	0.160234
<none>			27149899	3048.3		
+ CRuns	1	185825	26964075	3048.5	1.7642	0.185279
+ League	1	95986	27053913	3049.3	0.9083	0.341471
+ NewLeague	1	52693	27097206	3049.8	0.4978	0.481101
+ CHmRun	1	43173	27106726	3049.8	0.4077	0.523692
+ Assists	1	28898	27121001	3050.0	0.2728	0.601926
+ CAtBat	1	20989	27128910	3050.1	0.1981	0.656665
+ CWalks	1	15599	27134301	3050.1	0.1472	0.701576
+ Errors	1	6265	27143634	3050.2	0.0591	0.808137
+ CHits	1	5305	27144594	3050.2	0.0500	0.823180
+ RBI	1	1236	27148663	3050.2	0.0117	0.914099
+ HmRun	1	11	27149888	3050.3	0.0001	0.991729

```
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Step: AIC=3040.85

Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
+ CWalks	1	240687	25954217	3040.4	2.3647	0.1253
<none>			26194904	3040.8		
+ Years	1	184508	26010396	3041.0	1.8089	0.1798
+ CRuns	1	110695	26084209	3041.7	1.0822	0.2992
+ League	1	77974	26116930	3042.1	0.7613	0.3837
+ Assists	1	75782	26119122	3042.1	0.7399	0.3905
+ NewLeague	1	40909	26153995	3042.4	0.3989	0.5282
+ CHits	1	37304	26157599	3042.5	0.3637	0.5470
+ RBI	1	11728	26183176	3042.7	0.1142	0.7357
+ HmRun	1	4747	26190157	3042.8	0.0462	0.8299
+ Errors	1	2727	26192177	3042.8	0.0266	0.8707
+ CAtBat	1	2630	26192274	3042.8	0.0256	0.8730
+ CHmRun	1	943	26193961	3042.8	0.0092	0.9237
+ Runs	1	37	26194867	3042.8	0.0004	0.9849

Step: AIC=3040.42

Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks + CWalks

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
+ CRuns	1	794983	25159234	3034.2	8.0259	0.004981 **
+ CHits	1	273728	25680489	3039.6	2.7074	0.101122
<none>			25954217	3040.4		
+ Assists	1	138506	25815711	3041.0	1.3628	0.244155
+ CAtBat	1	89289	25864929	3041.5	0.8768	0.349959
+ RBI	1	86941	25867276	3041.5	0.8537	0.356382
+ League	1	77159	25877058	3041.6	0.7574	0.384977

+ Years	1	70126	25884091	3041.7	0.6881	0.407575
+ NewLeague	1	37807	25916410	3042.0	0.3705	0.543255
+ HmRun	1	33601	25920616	3042.1	0.3293	0.566603
+ CHmRun	1	9034	25945183	3042.3	0.0884	0.766406
+ Errors	1	6928	25947289	3042.3	0.0678	0.794746
+ Runs	1	82	25954135	3042.4	0.0008	0.977414

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3034.24

Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks + CWalks +
CRuns

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
+ CAtBat	1	345182	24814051	3032.6	3.5194	0.0618 .
+ Years	1	265068	24894165	3033.4	2.6939	0.1020
<none>			25159234	3034.2		
+ CHits	1	173215	24986019	3034.4	1.7539	0.1866
+ Assists	1	124676	25034558	3034.9	1.2600	0.2627
+ CHmRun	1	91728	25067505	3035.3	0.9258	0.3369
+ League	1	72985	25086248	3035.5	0.7361	0.3917
+ NewLeague	1	25244	25133990	3036.0	0.2541	0.6146
+ Runs	1	17700	25141534	3036.1	0.1781	0.6734
+ Errors	1	8531	25150703	3036.2	0.0858	0.7698
+ HmRun	1	2390	25156844	3036.2	0.0240	0.8769
+ RBI	1	0	25159234	3036.2	0.0000	0.9993

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3032.6

Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks + CWalks +
CRuns + CAtBat

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
+ Assists	1	313650	24500402	3031.3	3.2261	0.07367 .
<none>			24814051	3032.6		
+ Runs	1	153499	24660553	3033.0	1.5686	0.21158
+ League	1	146017	24668034	3033.1	1.4917	0.22310
+ NewLeague	1	77209	24736842	3033.8	0.7866	0.37599
+ Years	1	47431	24766620	3034.1	0.4826	0.48788
+ CHits	1	47127	24766925	3034.1	0.4795	0.48928
+ Errors	1	43926	24770126	3034.1	0.4469	0.50443
+ HmRun	1	23132	24790919	3034.4	0.2351	0.62816
+ CHmRun	1	19917	24794134	3034.4	0.2024	0.65315
+ RBI	1	19027	24795024	3034.4	0.1934	0.66050

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3031.26

Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks + CWalks +
CRuns + CAtBat + Assists

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
<none>			24500402	3031.3		
+ League	1	113056	24387345	3032.0	1.1636	0.2818
+ Runs	1	75900	24424501	3032.4	0.7800	0.3780

```
+ NewLeague 1      64712 24435690 3032.6 0.6647 0.4157
+ CHits      1      37564 24462838 3032.8 0.3854 0.5353
+ Errors     1      35264 24465138 3032.9 0.3618 0.5481
+ Years      1      19883 24480519 3033.0 0.2039 0.6520
+ CHmRun     1       4356 24496046 3033.2 0.0446 0.8328
+ HmRun      1       1189 24499212 3033.2 0.0122 0.9122
+ RBI        1        359 24500043 3033.2 0.0037 0.9517
```

```
summary(Hitters.fwd)
```

Call:

```
lm(formula = Salary ~ CRBI + Hits + PutOuts + Division + AtBat +
    Walks + CWalks + CRuns + CAtBat + Assists, data = Hitters)
```

Residuals:

```
      Min       1Q   Median       3Q      Max
-939.11 -176.87  -34.08   130.90 1910.55
```

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)	
(Intercept)	162.53544	66.90784	2.429	0.015830	*
CRBI	0.77431	0.20961	3.694	0.000271	***
Hits	6.91802	1.64665	4.201	0.0000369	***
PutOuts	0.29737	0.07444	3.995	0.0000850	***
DivisionW	-112.38006	39.21438	-2.866	0.004511	**
AtBat	-2.16865	0.53630	-4.044	0.0000700	***
Walks	5.77322	1.58483	3.643	0.000327	***
CWalks	-0.83083	0.26359	-3.152	0.001818	**
CRuns	1.40825	0.39040	3.607	0.000373	***
CAtBat	-0.13008	0.05550	-2.344	0.019858	*
Assists	0.28317	0.15766	1.796	0.073673	.

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 311.8 on 252 degrees of freedom

Multiple R-squared: 0.5405, Adjusted R-squared: 0.5223

F-statistic: 29.64 on 10 and 252 DF, p-value: < 2.2e-16

The `step()` outputs one model in each step, so that you can explore which variables entered the model when. In the first step of the output above you will notice two important things:

First, the predictors are ordered from smallest to largest p-value. These p-values are NOT the p-values in the model because initially there are no predictors in the Null model. Rather, these p-values indicate what the respective p-values would be if the predictor is added to the model.

Second, there is a + symbol next to each predictor. This is NOT a coefficient sign. Rather, it is a symbol that indicates that the predictor is a **candidate for inclusion** in the model, thus the +. Because the first step is the Null model, all predictors have a + symbol. Naturally, the first predictor in the output will be the first predictor to be added to the model, which in this case is **CRBI**, which will appear in the model output in the next step.

In the second step, you will notice that CRBI is no longer listed. This is so because it is already added to the model, so it is no longer a candidate for inclusion. You can also see that the model formula listed at the top of the step output includes **CRBI** in the model. Following the same logic, **Hits** will be the next predictor to be added to the model, and so on. You will notice in the very last step, that there are no more predictors with a p-value < 0.15, so no more predictors will be added to the model after this step and the process stops. The `summary()` function outputs the typical regression summary results.

Let's illustrate what happens when we increase k to 3.841. As you can see in the output below (cut to save paper), there are fewer predictors included because the p-value threshold is now 0.05. Notice that the all the final predictors included have a significance level of $p < 0.05$.

```
Hitters.fwd.3.8 <- step(Hitters.null,
  scope = list(lower = Hitters.null,
    upper = Hitters.full),
  direction = "forward",
  test = "F",
  k = 3.841)
```

Start: AIC=3217.61

Salary ~ 1

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)	
+ CRBI	1	17139434	36179679	3119.5	123.6438	< 2.2e-16	***
+ CRuns	1	16881162	36437951	3121.3	120.9174	< 2.2e-16	***
+ CHits	1	16065140	37253973	3127.2	112.5518	< 2.2e-16	***
+ CAtBat	1	14759710	38559403	3136.2	99.9052	< 2.2e-16	***
+ CHmRun	1	14692193	38626920	3136.7	99.2744	< 2.2e-16	***
+ CWalks	1	12792622	40526491	3149.3	82.3874	< 2.2e-16	***
+ RBI	1	10771083	42548030	3162.1	66.0725	1.757e-14	***
+ Walks	1	10504833	42814280	3163.7	64.0385	4.014e-14	***
+ Hits	1	10260491	43058621	3165.2	62.1940	8.531e-14	***
+ Runs	1	9399158	43919955	3170.4	55.8557	1.180e-12	***
+ Years	1	8559105	44760007	3175.4	49.9090	1.463e-11	***
+ AtBat	1	8309469	45009644	3176.9	48.1846	3.065e-11	***
+ HmRun	1	6273967	47045145	3188.5	34.8071	1.125e-08	***
+ PutOuts	1	4814100	48505013	3196.6	25.9041	6.871e-07	***
+ Division	1	1976102	51343011	3211.5	10.0454	0.001709	**
<none>			53319113	3217.6			
+ Assists	1	34497	53284615	3221.3	0.1690	0.681361	
+ League	1	10876	53308237	3221.4	0.0532	0.817687	
+ Errors	1	1555	53317558	3221.4	0.0076	0.930538	
+ NewLeague	1	428	53318684	3221.4	0.0021	0.963511	

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3119.46

Salary ~ CRBI

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)	
+ Hits	1	5533119	30646560	3079.7	46.9420	5.275e-11	***
+ Runs	1	5176532	31003147	3082.7	43.4117	2.450e-10	***
+ Walks	1	4199733	31979946	3090.8	34.1442	1.526e-08	***
+ AtBat	1	4064585	32115095	3092.0	32.9064	2.681e-08	***
+ RBI	1	3308272	32871407	3098.1	26.1671	6.085e-07	***
+ PutOuts	1	3267035	32912644	3098.4	25.8086	7.204e-07	***
+ Division	1	1733887	34445793	3110.4	13.0875	0.0003571	***
+ Years	1	1667339	34512340	3110.9	12.5610	0.0004669	***
+ HmRun	1	1271587	34908092	3113.9	9.4709	0.0023108	**
<none>			36179679	3119.5			
+ CRuns	1	354561	35825119	3120.7	2.5732	0.1099006	
+ Assists	1	346020	35833659	3120.8	2.5106	0.1142958	
+ Errors	1	194403	35985276	3121.9	1.4046	0.2370372	
+ CAtBat	1	92261	36087418	3122.6	0.6647	0.4156463	

```

+ CHits      1      75469 36104210 3122.8  0.5435 0.4616584
+ CWalks     1      51974 36127705 3122.9  0.3740 0.5413451
+ NewLeague  1      17778 36161901 3123.2  0.1278 0.7209896
+ League     1      11825 36167855 3123.2  0.0850 0.7708606
+ CHmRun     1         515 36179165 3123.3  0.0037 0.9515485

```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3079.65

Salary ~ CRBI + Hits

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)	
+ PutOuts	1	1397263	29249297	3071.2	12.3726	0.0005143	***
+ Division	1	1279275	29367285	3072.3	11.2824	0.0009002	***
+ AtBat	1	821767	29824793	3076.3	7.1363	0.0080327	**
+ Walks	1	781767	29864793	3076.7	6.7798	0.0097516	**
<none>			30646560	3079.7			
+ Years	1	254910	30391650	3081.3	2.1724	0.1417246	
+ League	1	208880	30437680	3081.7	1.7774	0.1836405	
+ CRuns	1	132614	30513946	3082.3	1.1256	0.2897011	
+ NewLeague	1	118474	30528086	3082.5	1.0051	0.3170083	
+ Runs	1	114198	30532362	3082.5	0.9687	0.3259179	
+ Errors	1	99776	30546784	3082.6	0.8460	0.3585477	
+ CAtBat	1	83517	30563043	3082.8	0.7077	0.4009684	
+ Assists	1	44781	30601779	3083.1	0.3790	0.5386742	
+ CWalks	1	23668	30622892	3083.3	0.2002	0.6549532	
+ CHmRun	1	4790	30641769	3083.4	0.0405	0.8406802	
+ CHits	1	4358	30642202	3083.4	0.0368	0.8479531	
+ HmRun	1	2173	30644387	3083.5	0.0184	0.8923043	
+ RBI	1	1137	30645423	3083.5	0.0096	0.9219997	

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3071.22

Salary ~ CRBI + Hits + PutOuts

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)	
+ Division	1	1278445	27970852	3063.3	11.7922	0.0006928	***
+ AtBat	1	1009933	28239364	3065.8	9.2269	0.0026294	**
+ Walks	1	539490	28709807	3070.2	4.8481	0.0285617	*
<none>			29249297	3071.2			
+ CRuns	1	273649	28975648	3072.6	2.4366	0.1197606	
+ Years	1	136906	29112391	3073.8	1.2133	0.2717085	
+ League	1	122841	29126456	3073.9	1.0881	0.2978655	
+ Runs	1	117930	29131367	3074.0	1.0444	0.3077496	
+ Errors	1	97244	29152053	3074.2	0.8606	0.3544307	
+ NewLeague	1	57839	29191458	3074.5	0.5112	0.4752699	
+ CHits	1	35096	29214201	3074.7	0.3099	0.5781973	
+ RBI	1	33965	29215331	3074.8	0.2999	0.5843887	
+ HmRun	1	31227	29218070	3074.8	0.2757	0.5999583	
+ CWalks	1	28572	29220725	3074.8	0.2523	0.6159089	
+ CAtBat	1	20518	29228779	3074.9	0.1811	0.6707739	
+ Assists	1	1681	29247616	3075.0	0.0148	0.9031641	
+ CHmRun	1	1419	29247878	3075.1	0.0125	0.9109989	

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3063.3

Salary ~ CRBI + Hits + PutOuts + Division

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
+ AtBat	1	820952	27149899	3059.3	7.7711	0.005705 **
+ Walks	1	491584	27479268	3062.5	4.5975	0.032956 *
<none>			27970852	3063.3		
+ CRuns	1	193604	27777248	3065.3	1.7913	0.181956
+ Years	1	166845	27804007	3065.6	1.5422	0.215424
+ League	1	110628	27860224	3066.1	1.0205	0.313351
+ Errors	1	81385	27889467	3066.4	0.7500	0.387296
+ Runs	1	65921	27904931	3066.5	0.6071	0.436592
+ RBI	1	53719	27917133	3066.6	0.4945	0.482553
+ NewLeague	1	52275	27918577	3066.7	0.4812	0.488502
+ CHits	1	33863	27936989	3066.8	0.3115	0.577240
+ HmRun	1	26390	27944462	3066.9	0.2427	0.622679
+ CAtBat	1	18751	27952101	3067.0	0.1724	0.678330
+ CWalks	1	5723	27965129	3067.1	0.0526	0.818791
+ Assists	1	1036	27969816	3067.1	0.0095	0.922368
+ CHmRun	1	165	27970687	3067.1	0.0015	0.968952

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3059.31

Salary ~ CRBI + Hits + PutOuts + Division + AtBat

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
+ Walks	1	954996	26194904	3053.7	9.3331	0.002488 **
<none>			27149899	3059.3		
+ Years	1	253362	26896537	3060.7	2.4115	0.121683
+ Runs	1	208743	26941157	3061.1	1.9835	0.160234
+ CRuns	1	185825	26964075	3061.3	1.7642	0.185279
+ League	1	95986	27053913	3062.2	0.9083	0.341471
+ NewLeague	1	52693	27097206	3062.6	0.4978	0.481101
+ CHmRun	1	43173	27106726	3062.7	0.4077	0.523692
+ Assists	1	28898	27121001	3062.9	0.2728	0.601926
+ CAtBat	1	20989	27128910	3062.9	0.1981	0.656665
+ CWalks	1	15599	27134301	3063.0	0.1472	0.701576
+ Errors	1	6265	27143634	3063.1	0.0591	0.808137
+ CHits	1	5305	27144594	3063.1	0.0500	0.823180
+ RBI	1	1236	27148663	3063.1	0.0117	0.914099
+ HmRun	1	11	27149888	3063.2	0.0001	0.991729

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3053.73

Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
<none>			26194904	3053.7		
+ CWalks	1	240687	25954217	3055.2	2.3647	0.1253
+ Years	1	184508	26010396	3055.7	1.8089	0.1798
+ CRuns	1	110695	26084209	3056.5	1.0822	0.2992
+ League	1	77974	26116930	3056.8	0.7613	0.3837
+ Assists	1	75782	26119122	3056.8	0.7399	0.3905

```

+ NewLeague 1      40909 26153995 3057.2  0.3989 0.5282
+ CHits      1      37304 26157599 3057.2  0.3637 0.5470
+ RBI        1      11728 26183176 3057.5  0.1142 0.7357
+ HmRun      1       4747 26190157 3057.5  0.0462 0.8299
+ Errors     1       2727 26192177 3057.6  0.0266 0.8707
+ CAtBat     1       2630 26192274 3057.6  0.0256 0.8730
+ CHmRun     1        943 26193961 3057.6  0.0092 0.9237
+ Runs       1         37 26194867 3057.6  0.0004 0.9849

```

```
summary(Hitters.fwd.3.8)
```

Call:

```
lm(formula = Salary ~ CRBI + Hits + PutOuts + Division + AtBat +
    Walks, data = Hitters)
```

Residuals:

```

      Min       1Q   Median       3Q      Max
-873.11 -181.72  -25.91   141.77 2040.47

```

Coefficients:

```

      Estimate Std. Error t value Pr(>|t|)
(Intercept)  91.51180    65.00006   1.408  0.160382
CRBI          0.64302     0.06443   9.979 < 2e-16 ***
Hits          7.60440     1.66254   4.574 0.00000746 ***
PutOuts       0.26431     0.07477   3.535  0.000484 ***
DivisionW    -122.95153    39.82029  -3.088  0.002239 **
AtBat        -1.86859     0.52742  -3.543  0.000470 ***
Walks         3.69765     1.21036   3.055  0.002488 **

```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 319.9 on 256 degrees of freedom

Multiple R-squared: 0.5087, Adjusted R-squared: 0.4972

F-statistic: 44.18 on 6 and 256 DF, p-value: < 2.2e-16

Backward Selection

In backward selection, the search starts with the upper bound model and the method removes predictors one at a time, starting with the least significant one and stopping when none of the predictors included in the model have $p > 0.15$ (or whatever threshold you used). The backward selection method **only removes variables**, one at a time, but does not remove any variables if they become non-significant.

Backward selection works just like forward selection, with the same lower and upper bound models, but this time the starting model must be the Full or upper bound model because we can only remove predictors. We also need to change the attribute to `direction = backward`. This will cause the process to proceed in a backward fashion. Just like in the forward process, the default k value is 2, which is approximately equivalent to $p < 0.15$. This means that any predictor that is not significant at the $p < 0.15$ level will be removed from the model. One more difference is that there is a - symbol next to each predictor, rather than +. This is so because predictors are **candidates for removal**, as there is no addition in backward step. The predictors are listed from least to most significance, so the first predictor to be removed is always the first one at the top.

```

Hitters.back <- step(Hitters.full,
                     scope = list(lower = Hitters.null,
                                   upper = Hitters.full),

```

```
direction = "backward",
test = "F")
```

Start: AIC=3046.02

```
Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + Years +
      CAtBat + CHits + CHmRun + CRuns + CRBI + CWalks + League +
      Division + PutOuts + Assists + Errors + NewLeague
```

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- CHmRun	1	1138	24201837	3044.0	0.0114	0.9149671
- CHits	1	3930	24204629	3044.1	0.0395	0.8427129
- Years	1	7869	24208569	3044.1	0.0790	0.7788736
- NewLeague	1	9784	24210484	3044.1	0.0982	0.7542178
- RBI	1	16076	24216776	3044.2	0.1614	0.6882042
- HmRun	1	48572	24249272	3044.6	0.4877	0.4856158
- Errors	1	58324	24259023	3044.7	0.5856	0.4448566
- League	1	62121	24262821	3044.7	0.6238	0.4304236
- Runs	1	63291	24263990	3044.7	0.6355	0.4261225
- CRBI	1	135439	24336138	3045.5	1.3599	0.2446905
- CAtBat	1	159864	24360564	3045.8	1.6052	0.2063804
<none>			24200700	3046.0		
- Assists	1	280263	24480963	3047.1	2.8141	0.0947232 .
- CRuns	1	374007	24574707	3048.1	3.7554	0.0537951 .
- CWalks	1	609408	24810108	3050.6	6.1191	0.0140574 *
- Division	1	834491	25035190	3052.9	8.3791	0.0041408 **
- AtBat	1	971288	25171987	3054.4	9.7527	0.0020077 **
- Hits	1	991242	25191941	3054.6	9.9531	0.0018082 **
- Walks	1	1156606	25357305	3056.3	11.6135	0.0007662 ***
- PutOuts	1	1319628	25520328	3058.0	13.2504	0.0003329 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3044.03

```
Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + Years +
      CAtBat + CHits + CRuns + CRBI + CWalks + League + Division +
      PutOuts + Assists + Errors + NewLeague
```

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- Years	1	7609	24209447	3042.1	0.0767	0.7820312
- NewLeague	1	10268	24212106	3042.2	0.1035	0.7479165
- CHits	1	14003	24215840	3042.2	0.1412	0.7074399
- RBI	1	14955	24216793	3042.2	0.1508	0.6981310
- HmRun	1	52777	24254614	3042.6	0.5321	0.4664293
- Errors	1	59530	24261367	3042.7	0.6002	0.4392618
- League	1	63407	24265244	3042.7	0.6393	0.4247563
- Runs	1	64860	24266698	3042.7	0.6539	0.4195043
- CAtBat	1	174992	24376830	3043.9	1.7643	0.1853360
<none>			24201837	3044.0		
- Assists	1	285766	24487603	3045.1	2.8811	0.0909022 .
- CRuns	1	611358	24813196	3048.6	6.1636	0.0137136 *
- CWalks	1	645627	24847464	3049.0	6.5091	0.0113434 *
- Division	1	834637	25036474	3050.9	8.4147	0.0040618 **
- CRBI	1	864220	25066057	3051.3	8.7130	0.0034675 **
- AtBat	1	970861	25172699	3052.4	9.7881	0.0019700 **
- Hits	1	1025981	25227819	3052.9	10.3438	0.0014747 **
- Walks	1	1167378	25369216	3054.4	11.7694	0.0007069 ***

- PutOuts 1 1325273 25527110 3056.1 13.3612 0.0003145 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3042.12

Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + CAtBat +
CHits + CRuns + CRBI + CWalks + League + Division + PutOuts +
Assists + Errors + NewLeague

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- NewLeague	1	9931	24219377	3040.2	0.1005	0.7515016
- RBI	1	15989	24225436	3040.3	0.1618	0.6878453
- CHits	1	18291	24227738	3040.3	0.1851	0.6673978
- HmRun	1	54144	24263591	3040.7	0.5479	0.4598692
- Errors	1	57312	24266759	3040.7	0.5800	0.4470438
- Runs	1	63172	24272619	3040.8	0.6393	0.4247368
- League	1	65732	24275178	3040.8	0.6652	0.4155208
<none>			24209447	3042.1		
- CAtBat	1	266205	24475652	3043.0	2.6940	0.1020097
- Assists	1	293479	24502926	3043.3	2.9700	0.0860827 .
- CRuns	1	646350	24855797	3047.1	6.5411	0.0111444 *
- CWalks	1	649269	24858716	3047.1	6.5706	0.0109657 *
- Division	1	827511	25036958	3049.0	8.3744	0.0041483 **
- CRBI	1	872121	25081568	3049.4	8.8259	0.0032652 **
- AtBat	1	968713	25178160	3050.4	9.8034	0.0019534 **
- Hits	1	1018379	25227825	3050.9	10.3060	0.0015033 **
- Walks	1	1164536	25373983	3052.5	11.7851	0.0007008 ***
- PutOuts	1	1334525	25543972	3054.2	13.5054	0.0002922 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3040.22

Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + CAtBat +
CHits + CRuns + CRBI + CWalks + League + Division + PutOuts +
Assists + Errors

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- RBI	1	15800	24235177	3038.4	0.1605	0.6890609
- CHits	1	15859	24235237	3038.4	0.1611	0.6885064
- Errors	1	54505	24273883	3038.8	0.5536	0.4575530
- HmRun	1	54938	24274316	3038.8	0.5580	0.4557745
- Runs	1	62294	24281671	3038.9	0.6327	0.4271242
- League	1	107479	24326856	3039.4	1.0917	0.2971253
<none>			24219377	3040.2		
- CAtBat	1	261336	24480713	3041.1	2.6544	0.1045418
- Assists	1	295536	24514914	3041.4	3.0018	0.0844249 .
- CWalks	1	648860	24868237	3045.2	6.5906	0.0108443 *
- CRuns	1	661449	24880826	3045.3	6.7184	0.0101129 *
- Division	1	824672	25044049	3047.0	8.3763	0.0041427 **
- CRBI	1	880429	25099806	3047.6	8.9427	0.0030687 **
- AtBat	1	999057	25218434	3048.9	10.1476	0.0016316 **
- Hits	1	1034463	25253840	3049.2	10.5072	0.0013534 **
- Walks	1	1157205	25376583	3050.5	11.7539	0.0007117 ***
- PutOuts	1	1335173	25554550	3052.3	13.5616	0.0002838 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3038.4

Salary ~ AtBat + Hits + HmRun + Runs + Walks + CAtBat + CHits +
CRuns + CRBI + CWalks + League + Division + PutOuts + Assists +
Errors

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- CHits	1	13483	24248660	3036.5	0.1374	0.7111808
- HmRun	1	44586	24279763	3036.9	0.4544	0.5008777
- Runs	1	54057	24289234	3037.0	0.5509	0.4586413
- Errors	1	57656	24292833	3037.0	0.5876	0.4440753
- League	1	108644	24343821	3037.6	1.1073	0.2937034
<none>			24235177	3038.4		
- CAtBat	1	252756	24487934	3039.1	2.5760	0.1097704
- Assists	1	294674	24529851	3039.6	3.0033	0.0843456 .
- CWalks	1	639690	24874868	3043.2	6.5196	0.0112712 *
- CRuns	1	693535	24928712	3043.8	7.0684	0.0083583 **
- Division	1	808984	25044161	3045.0	8.2450	0.0044412 **
- CRBI	1	893830	25129008	3045.9	9.1097	0.0028087 **
- Hits	1	1034884	25270061	3047.4	10.5473	0.0013249 **
- AtBat	1	1042798	25277975	3047.5	10.6280	0.0012706 **
- Walks	1	1145013	25380191	3048.5	11.6697	0.0007426 ***
- PutOuts	1	1340713	25575890	3050.6	13.6643	0.0002693 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3036.54

Salary ~ AtBat + Hits + HmRun + Runs + Walks + CAtBat + CRuns +
CRBI + CWalks + League + Division + PutOuts + Assists + Errors

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- HmRun	1	40487	24289148	3035.0	0.4141	0.5205005
- Errors	1	51930	24300590	3035.1	0.5311	0.4668297
- Runs	1	79343	24328003	3035.4	0.8115	0.3685611
- League	1	114742	24363402	3035.8	1.1735	0.2797336
<none>			24248660	3036.5		
- Assists	1	283442	24532103	3037.6	2.8989	0.0898946 .
- CAtBat	1	613356	24862016	3041.1	6.2730	0.0129017 *
- Division	1	801474	25050134	3043.1	8.1970	0.0045548 **
- CRBI	1	903248	25151908	3044.2	9.2379	0.0026244 **
- CWalks	1	1011953	25260613	3045.3	10.3496	0.0014674 **
- Walks	1	1246164	25494824	3047.7	12.7450	0.0004286 ***
- AtBat	1	1339620	25588280	3048.7	13.7008	0.0002641 ***
- CRuns	1	1390808	25639469	3049.2	14.2243	0.0002029 ***
- PutOuts	1	1406023	25654684	3049.4	14.3799	0.0001877 ***
- Hits	1	1607990	25856650	3051.4	16.4455	0.00006709 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3034.98

Salary ~ AtBat + Hits + Runs + Walks + CAtBat + CRuns + CRBI +
CWalks + League + Division + PutOuts + Assists + Errors

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- Errors	1	44085	24333232	3033.5	0.4519	0.5020421
- Runs	1	49068	24338215	3033.5	0.5030	0.4788415

```

- League      1      103837 24392985 3034.1  1.0645  0.3031961
<none>                24289148 3035.0
- Assists     1      247002 24536150 3035.6  2.5321  0.1128176
- CAtBat      1      652746 24941894 3040.0  6.6916  0.0102549 *
- Division    1      795643 25084791 3041.5  8.1565  0.0046527 **
- CWalks      1      982896 25272044 3043.4 10.0761  0.0016911 **
- Walks       1     1205823 25494971 3045.7 12.3615  0.0005206 ***
- AtBat       1     1300972 25590120 3046.7 13.3369  0.0003172 ***
- CRuns       1     1351200 25640348 3047.2 13.8518  0.0002446 ***
- CRBI        1     1353507 25642655 3047.2 13.8755  0.0002417 ***
- PutOuts     1     1429006 25718154 3048.0 14.6494  0.0001638 ***
- Hits        1     1574140 25863288 3049.5 16.1373  0.00007806 ***

```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3033.46

Salary ~ AtBat + Hits + Runs + Walks + CAtBat + CRuns + CRBI +
CWalks + League + Division + PutOuts + Assists

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- Runs	1	54113	24387345	3032.0	0.5560	0.4565953
- League	1	91269	24424501	3032.4	0.9377	0.3338061
<none>			24333232	3033.5		
- Assists	1	220010	24553242	3033.8	2.2604	0.1339832
- CAtBat	1	650513	24983746	3038.4	6.6834	0.0102988 *
- Division	1	799455	25132687	3040.0	8.2136	0.0045117 **
- CWalks	1	971260	25304493	3041.8	9.9787	0.0017784 **
- Walks	1	1239533	25572765	3044.5	12.7350	0.0004301 ***
- CRBI	1	1331672	25664904	3045.5	13.6816	0.0002663 ***
- CRuns	1	1361070	25694302	3045.8	13.9837	0.0002287 ***
- AtBat	1	1378592	25711824	3045.9	14.1637	0.0002089 ***
- PutOuts	1	1391660	25724892	3046.1	14.2979	0.0001952 ***
- Hits	1	1649291	25982523	3048.7	16.9448	0.0000523 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3032.04

Salary ~ AtBat + Hits + Walks + CAtBat + CRuns + CRBI + CWalks +
League + Division + PutOuts + Assists

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- League	1	113056	24500402	3031.3	1.1636	0.2817552
<none>			24387345	3032.0		
- Assists	1	280689	24668034	3033.1	2.8889	0.0904298 .
- CAtBat	1	596622	24983967	3036.4	6.1406	0.0138700 *
- Division	1	780369	25167714	3038.3	8.0317	0.0049703 **
- CWalks	1	946687	25334032	3040.1	9.7435	0.0020102 **
- Walks	1	1212997	25600342	3042.8	12.4844	0.0004883 ***
- CRuns	1	1334397	25721742	3044.1	13.7339	0.0002591 ***
- CRBI	1	1361339	25748684	3044.3	14.0112	0.0002253 ***
- PutOuts	1	1455210	25842555	3045.3	14.9774	0.0001388 ***
- AtBat	1	1522760	25910105	3046.0	15.6726	0.00009811 ***
- Hits	1	1718870	26106215	3047.9	17.6910	0.00003619 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3031.26

Salary ~ AtBat + Hits + Walks + CAtBat + CRuns + CRBI + CWalks +
Division + PutOuts + Assists

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
<none>			24500402	3031.3		
- Assists	1	313650	24814051	3032.6	3.2261	0.0736726 .
- CAtBat	1	534156	25034558	3034.9	5.4941	0.0198584 *
- Division	1	798473	25298875	3037.7	8.2127	0.0045109 **
- CWalks	1	965875	25466276	3039.4	9.9345	0.0018183 **
- CRuns	1	1265082	25765484	3042.5	13.0121	0.0003731 ***
- Walks	1	1290168	25790569	3042.8	13.2701	0.0003274 ***
- CRBI	1	1326770	25827172	3043.1	13.6466	0.0002706 ***
- PutOuts	1	1551523	26051925	3045.4	15.9583	0.00008504 ***
- AtBat	1	1589780	26090181	3045.8	16.3518	0.00006996 ***
- Hits	1	1716068	26216469	3047.1	17.6507	0.00003686 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```
summary(Hitters.back)
```

Call:

```
lm(formula = Salary ~ AtBat + Hits + Walks + CAtBat + CRuns +  
    CRBI + CWalks + Division + PutOuts + Assists, data = Hitters)
```

Residuals:

Min	1Q	Median	3Q	Max
-939.11	-176.87	-34.08	130.90	1910.55

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	162.53544	66.90784	2.429	0.015830 *
AtBat	-2.16865	0.53630	-4.044	0.0000700 ***
Hits	6.91802	1.64665	4.201	0.0000369 ***
Walks	5.77322	1.58483	3.643	0.000327 ***
CAtBat	-0.13008	0.05550	-2.344	0.019858 *
CRuns	1.40825	0.39040	3.607	0.000373 ***
CRBI	0.77431	0.20961	3.694	0.000271 ***
CWalks	-0.83083	0.26359	-3.152	0.001818 **
DivisionW	-112.38006	39.21438	-2.866	0.004511 **
PutOuts	0.29737	0.07444	3.995	0.0000850 ***
Assists	0.28317	0.15766	1.796	0.073673 .

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 311.8 on 252 degrees of freedom

Multiple R-squared: 0.5405, Adjusted R-squared: 0.5223

F-statistic: 29.64 on 10 and 252 DF, p-value: < 2.2e-16

Stepwise Selection

In stepwise selection, you can start with either the lower or upper bound model and go in either direction. Naturally, if you start with the lower bound model, your first step has to be forward. Similarly, if you start with the upper bound model, your first step has to be backwards. My recommendation is to start with the upper bound model

because it is the least biased of all possible models, so it provides a good starting base. In this case the process will evaluate which variable to remove from the upper bound model, starting with the least significant one and stopping when none of the predictors included in the model have $p > 0.15$ (or whatever threshold you selected). The difference with the forward and backward selection methods is that predictors can be either added or removed from the model. Unless you change the default value of k , any predictor that is significant at the $p < 0.15$ level will be added, and any that is not will be removed. Another difference in each step is that you may now see either a + or a -. As before, a + denotes that the predictor is not in the model and, therefore, it is a candidate for inclusion. Similarly, a - symbol denotes that the predictor is already in the model and, therefore, it is a candidate for removal.

Two other important differences are:

First, the **direction** attribute is set to `direction = "both"`, which will trigger the stepwise process of either adding or removing predictors; and

Second, the starting models can be either the Null or the Full model, your choice. If you choose the Null model, your first step will be to add predictors to the Null model in a forward fashion, which is the only direction you can go because there are no predictors in the Null model yet. If you choose the Full model, your first step will be to remove predictors from the Full model in a backward fashion. Again, that's the only direction possible. But after the first step, predictors may either be added or removed in every step. Let's illustrate this method. Notice that we start with the Full model, so our first step is backward. You can try starting with the Null model on your own, but my preference is to always start with the Full and least biased model. So, all predictors have a - symbol at the beginning, but notice that there is a predictor with a + in the second step, indicating that the predictor has already been removed, but it is now a candidate to be added back to the model.

```
Hitters.step <- step(Hitters.full,
  scope = list(lower = Hitters.null,
               upper = Hitters.full),
  direction = "both",
  test = "F")
```

Start: AIC=3046.02

```
Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + Years +
  CAtBat + CHits + CHmRun + CRuns + CRBI + CWalks + League +
  Division + PutOuts + Assists + Errors + NewLeague
```

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- CHmRun	1	1138	24201837	3044.0	0.0114	0.9149671
- CHits	1	3930	24204629	3044.1	0.0395	0.8427129
- Years	1	7869	24208569	3044.1	0.0790	0.7788736
- NewLeague	1	9784	24210484	3044.1	0.0982	0.7542178
- RBI	1	16076	24216776	3044.2	0.1614	0.6882042
- HmRun	1	48572	24249272	3044.6	0.4877	0.4856158
- Errors	1	58324	24259023	3044.7	0.5856	0.4448566
- League	1	62121	24262821	3044.7	0.6238	0.4304236
- Runs	1	63291	24263990	3044.7	0.6355	0.4261225
- CRBI	1	135439	24336138	3045.5	1.3599	0.2446905
- CAtBat	1	159864	24360564	3045.8	1.6052	0.2063804
<none>			24200700	3046.0		
- Assists	1	280263	24480963	3047.1	2.8141	0.0947232 .
- CRuns	1	374007	24574707	3048.1	3.7554	0.0537951 .
- CWalks	1	609408	24810108	3050.6	6.1191	0.0140574 *
- Division	1	834491	25035190	3052.9	8.3791	0.0041408 **
- AtBat	1	971288	25171987	3054.4	9.7527	0.0020077 **
- Hits	1	991242	25191941	3054.6	9.9531	0.0018082 **
- Walks	1	1156606	25357305	3056.3	11.6135	0.0007662 ***
- PutOuts	1	1319628	25520328	3058.0	13.2504	0.0003329 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3044.03

Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + Years +
 CAtBat + CHits + CRuns + CRBI + CWalks + League + Division +
 PutOuts + Assists + Errors + NewLeague

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- Years	1	7609	24209447	3042.1	0.0767	0.7820312
- NewLeague	1	10268	24212106	3042.2	0.1035	0.7479165
- CHits	1	14003	24215840	3042.2	0.1412	0.7074399
- RBI	1	14955	24216793	3042.2	0.1508	0.6981310
- HmRun	1	52777	24254614	3042.6	0.5321	0.4664293
- Errors	1	59530	24261367	3042.7	0.6002	0.4392618
- League	1	63407	24265244	3042.7	0.6393	0.4247563
- Runs	1	64860	24266698	3042.7	0.6539	0.4195043
- CAtBat	1	174992	24376830	3043.9	1.7643	0.1853360
<none>			24201837	3044.0		
- Assists	1	285766	24487603	3045.1	2.8811	0.0909022 .
+ CHmRun	1	1138	24200700	3046.0	0.0114	0.9149671
- CRuns	1	611358	24813196	3048.6	6.1636	0.0137136 *
- CWalks	1	645627	24847464	3049.0	6.5091	0.0113434 *
- Division	1	834637	25036474	3050.9	8.4147	0.0040618 **
- CRBI	1	864220	25066057	3051.3	8.7130	0.0034675 **
- AtBat	1	970861	25172699	3052.4	9.7881	0.0019700 **
- Hits	1	1025981	25227819	3052.9	10.3438	0.0014747 **
- Walks	1	1167378	25369216	3054.4	11.7694	0.0007069 ***
- PutOuts	1	1325273	25527110	3056.1	13.3612	0.0003145 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3042.12

Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + CAtBat +
 CHits + CRuns + CRBI + CWalks + League + Division + PutOuts +
 Assists + Errors + NewLeague

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- NewLeague	1	9931	24219377	3040.2	0.1005	0.7515016
- RBI	1	15989	24225436	3040.3	0.1618	0.6878453
- CHits	1	18291	24227738	3040.3	0.1851	0.6673978
- HmRun	1	54144	24263591	3040.7	0.5479	0.4598692
- Errors	1	57312	24266759	3040.7	0.5800	0.4470438
- Runs	1	63172	24272619	3040.8	0.6393	0.4247368
- League	1	65732	24275178	3040.8	0.6652	0.4155208
<none>			24209447	3042.1		
- CAtBat	1	266205	24475652	3043.0	2.6940	0.1020097
- Assists	1	293479	24502926	3043.3	2.9700	0.0860827 .
+ Years	1	7609	24201837	3044.0	0.0767	0.7820312
+ CHmRun	1	878	24208569	3044.1	0.0088	0.9251371
- CRuns	1	646350	24855797	3047.1	6.5411	0.0111444 *
- CWalks	1	649269	24858716	3047.1	6.5706	0.0109657 *
- Division	1	827511	25036958	3049.0	8.3744	0.0041483 **
- CRBI	1	872121	25081568	3049.4	8.8259	0.0032652 **
- AtBat	1	968713	25178160	3050.4	9.8034	0.0019534 **
- Hits	1	1018379	25227825	3050.9	10.3060	0.0015033 **

```

- Walks      1    1164536 25373983 3052.5 11.7851 0.0007008 ***
- PutOuts    1    1334525 25543972 3054.2 13.5054 0.0002922 ***
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

Step: AIC=3040.22

```

Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + CAtBat +
      CHits + CRuns + CRBI + CWalks + League + Division + PutOuts +
      Assists + Errors

```

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- RBI	1	15800	24235177	3038.4	0.1605	0.6890609
- CHits	1	15859	24235237	3038.4	0.1611	0.6885064
- Errors	1	54505	24273883	3038.8	0.5536	0.4575530
- HmRun	1	54938	24274316	3038.8	0.5580	0.4557745
- Runs	1	62294	24281671	3038.9	0.6327	0.4271242
- League	1	107479	24326856	3039.4	1.0917	0.2971253
<none>			24219377	3040.2		
- CAtBat	1	261336	24480713	3041.1	2.6544	0.1045418
- Assists	1	295536	24514914	3041.4	3.0018	0.0844249 .
+ NewLeague	1	9931	24209447	3042.1	0.1005	0.7515016
+ Years	1	7272	24212106	3042.2	0.0736	0.7864187
+ CHmRun	1	1307	24218070	3042.2	0.0132	0.9085489
- CWalks	1	648860	24868237	3045.2	6.5906	0.0108443 *
- CRuns	1	661449	24880826	3045.3	6.7184	0.0101129 *
- Division	1	824672	25044049	3047.0	8.3763	0.0041427 **
- CRBI	1	880429	25099806	3047.6	8.9427	0.0030687 **
- AtBat	1	999057	25218434	3048.9	10.1476	0.0016316 **
- Hits	1	1034463	25253840	3049.2	10.5072	0.0013534 **
- Walks	1	1157205	25376583	3050.5	11.7539	0.0007117 ***
- PutOuts	1	1335173	25554550	3052.3	13.5616	0.0002838 ***

```

---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

Step: AIC=3038.4

```

Salary ~ AtBat + Hits + HmRun + Runs + Walks + CAtBat + CHits +
      CRuns + CRBI + CWalks + League + Division + PutOuts + Assists +
      Errors

```

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- CHits	1	13483	24248660	3036.5	0.1374	0.7111808
- HmRun	1	44586	24279763	3036.9	0.4544	0.5008777
- Runs	1	54057	24289234	3037.0	0.5509	0.4586413
- Errors	1	57656	24292833	3037.0	0.5876	0.4440753
- League	1	108644	24343821	3037.6	1.1073	0.2937034
<none>			24235177	3038.4		
- CAtBat	1	252756	24487934	3039.1	2.5760	0.1097704
- Assists	1	294674	24529851	3039.6	3.0033	0.0843456 .
+ RBI	1	15800	24219377	3040.2	0.1605	0.6890609
+ NewLeague	1	9741	24225436	3040.3	0.0989	0.7533960
+ Years	1	8280	24226897	3040.3	0.0841	0.7720891
+ CHmRun	1	9	24235168	3040.4	0.0001	0.9922301
- CWalks	1	639690	24874868	3043.2	6.5196	0.0112712 *
- CRuns	1	693535	24928712	3043.8	7.0684	0.0083583 **
- Division	1	808984	25044161	3045.0	8.2450	0.0044412 **
- CRBI	1	893830	25129008	3045.9	9.1097	0.0028087 **

```

- Hits      1    1034884 25270061 3047.4 10.5473 0.0013249 **
- AtBat     1    1042798 25277975 3047.5 10.6280 0.0012706 **
- Walks     1    1145013 25380191 3048.5 11.6697 0.0007426 ***
- PutOuts   1    1340713 25575890 3050.6 13.6643 0.0002693 ***

```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3036.54

Salary ~ AtBat + Hits + HmRun + Runs + Walks + CAtBat + CRuns +
CRBI + CWalks + League + Division + PutOuts + Assists + Errors

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- HmRun	1	40487	24289148	3035.0	0.4141	0.5205005
- Errors	1	51930	24300590	3035.1	0.5311	0.4668297
- Runs	1	79343	24328003	3035.4	0.8115	0.3685611
- League	1	114742	24363402	3035.8	1.1735	0.2797336
<none>			24248660	3036.5		
- Assists	1	283442	24532103	3037.6	2.8989	0.0898946 .
+ CHits	1	13483	24235177	3038.4	0.1374	0.7111808
+ RBI	1	13423	24235237	3038.4	0.1368	0.7117909
+ Years	1	11981	24236679	3038.4	0.1221	0.7270650
+ NewLeague	1	7510	24241150	3038.5	0.0765	0.7822973
+ CHmRun	1	5924	24242737	3038.5	0.0604	0.8061379
- CAtBat	1	613356	24862016	3041.1	6.2730	0.0129017 *
- Division	1	801474	25050134	3043.1	8.1970	0.0045548 **
- CRBI	1	903248	25151908	3044.2	9.2379	0.0026244 **
- CWalks	1	1011953	25260613	3045.3	10.3496	0.0014674 **
- Walks	1	1246164	25494824	3047.7	12.7450	0.0004286 ***
- AtBat	1	1339620	25588280	3048.7	13.7008	0.0002641 ***
- CRuns	1	1390808	25639469	3049.2	14.2243	0.0002029 ***
- PutOuts	1	1406023	25654684	3049.4	14.3799	0.0001877 ***
- Hits	1	1607990	25856650	3051.4	16.4455	0.00006709 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3034.98

Salary ~ AtBat + Hits + Runs + Walks + CAtBat + CRuns + CRBI +
CWalks + League + Division + PutOuts + Assists + Errors

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- Errors	1	44085	24333232	3033.5	0.4519	0.5020421
- Runs	1	49068	24338215	3033.5	0.5030	0.4788415
- League	1	103837	24392985	3034.1	1.0645	0.3031961
<none>			24289148	3035.0		
- Assists	1	247002	24536150	3035.6	2.5321	0.1128176
+ HmRun	1	40487	24248660	3036.5	0.4141	0.5205005
+ Years	1	11136	24278012	3036.9	0.1138	0.7361964
+ CHits	1	9384	24279763	3036.9	0.0959	0.7571211
+ NewLeague	1	9063	24280084	3036.9	0.0926	0.7611839
+ RBI	1	5230	24283918	3036.9	0.0534	0.8174246
+ CHmRun	1	47	24289101	3037.0	0.0005	0.9824929
- CAtBat	1	652746	24941894	3040.0	6.6916	0.0102549 *
- Division	1	795643	25084791	3041.5	8.1565	0.0046527 **
- CWalks	1	982896	25272044	3043.4	10.0761	0.0016911 **
- Walks	1	1205823	25494971	3045.7	12.3615	0.0005206 ***
- AtBat	1	1300972	25590120	3046.7	13.3369	0.0003172 ***

```

- CRuns      1    1351200 25640348 3047.2 13.8518  0.0002446 ***
- CRBI       1    1353507 25642655 3047.2 13.8755  0.0002417 ***
- PutOuts    1    1429006 25718154 3048.0 14.6494  0.0001638 ***
- Hits       1    1574140 25863288 3049.5 16.1373  0.00007806 ***

```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3033.46

Salary ~ AtBat + Hits + Runs + Walks + CAtBat + CRuns + CRBI +
 CWalks + League + Division + PutOuts + Assists

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- Runs	1	54113	24387345	3032.0	0.5560	0.4565953
- League	1	91269	24424501	3032.4	0.9377	0.3338061
<none>			24333232	3033.5		
- Assists	1	220010	24553242	3033.8	2.2604	0.1339832
+ Errors	1	44085	24289148	3035.0	0.4519	0.5020421
+ HmRun	1	32642	24300590	3035.1	0.3345	0.5635601
+ Years	1	8122	24325111	3035.4	0.0831	0.7733321
+ NewLeague	1	6890	24326342	3035.4	0.0705	0.7907946
+ CHits	1	5330	24327902	3035.4	0.0546	0.8155110
+ RBI	1	2382	24330851	3035.4	0.0244	0.8760656
+ CHmRun	1	9	24333223	3035.5	0.0001	0.9922430
- CAtBat	1	650513	24983746	3038.4	6.6834	0.0102988 *
- Division	1	799455	25132687	3040.0	8.2136	0.0045117 **
- CWalks	1	971260	25304493	3041.8	9.9787	0.0017784 **
- Walks	1	1239533	25572765	3044.5	12.7350	0.0004301 ***
- CRBI	1	1331672	25664904	3045.5	13.6816	0.0002663 ***
- CRuns	1	1361070	25694302	3045.8	13.9837	0.0002287 ***
- AtBat	1	1378592	25711824	3045.9	14.1637	0.0002089 ***
- PutOuts	1	1391660	25724892	3046.1	14.2979	0.0001952 ***
- Hits	1	1649291	25982523	3048.7	16.9448	0.0000523 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3032.04

Salary ~ AtBat + Hits + Walks + CAtBat + CRuns + CRBI + CWalks +
 League + Division + PutOuts + Assists

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
- League	1	113056	24500402	3031.3	1.1636	0.2817552
<none>			24387345	3032.0		
- Assists	1	280689	24668034	3033.1	2.8889	0.0904298 .
+ Runs	1	54113	24333232	3033.5	0.5560	0.4565953
+ Errors	1	49130	24338215	3033.5	0.5047	0.4781239
+ CHits	1	22676	24364669	3033.8	0.2327	0.6299694
+ Years	1	8532	24378813	3033.9	0.0875	0.7676295
+ HmRun	1	5924	24381421	3034.0	0.0607	0.8055343
+ NewLeague	1	4287	24383058	3034.0	0.0440	0.8341147
+ CHmRun	1	1146	24386199	3034.0	0.0118	0.9137590
+ RBI	1	75	24387270	3034.0	0.0008	0.9778452
- CAtBat	1	596622	24983967	3036.4	6.1406	0.0138700 *
- Division	1	780369	25167714	3038.3	8.0317	0.0049703 **
- CWalks	1	946687	25334032	3040.1	9.7435	0.0020102 **
- Walks	1	1212997	25600342	3042.8	12.4844	0.0004883 ***
- CRuns	1	1334397	25721742	3044.1	13.7339	0.0002591 ***

```

- CRBI      1    1361339 25748684 3044.3 14.0112 0.0002253 ***
- PutOuts   1    1455210 25842555 3045.3 14.9774 0.0001388 ***
- AtBat     1    1522760 25910105 3046.0 15.6726 0.00009811 ***
- Hits      1    1718870 26106215 3047.9 17.6910 0.00003619 ***

```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: AIC=3031.26

Salary ~ AtBat + Hits + Walks + CAtBat + CRuns + CRBI + CWalks +
Division + PutOuts + Assists

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
<none>			24500402	3031.3		
+ League	1	113056	24387345	3032.0	1.1636	0.2817552
+ Runs	1	75900	24424501	3032.4	0.7800	0.3779884
+ NewLeague	1	64712	24435690	3032.6	0.6647	0.4156749
- Assists	1	313650	24814051	3032.6	3.2261	0.0736726 .
+ CHits	1	37564	24462838	3032.8	0.3854	0.5352800
+ Errors	1	35264	24465138	3032.9	0.3618	0.5480572
+ Years	1	19883	24480519	3033.0	0.2039	0.6520127
+ CHmRun	1	4356	24496046	3033.2	0.0446	0.8328494
+ HmRun	1	1189	24499212	3033.2	0.0122	0.9121905
+ RBI	1	359	24500043	3033.2	0.0037	0.9517012
- CAtBat	1	534156	25034558	3034.9	5.4941	0.0198584 *
- Division	1	798473	25298875	3037.7	8.2127	0.0045109 **
- CWalks	1	965875	25466276	3039.4	9.9345	0.0018183 **
- CRuns	1	1265082	25765484	3042.5	13.0121	0.0003731 ***
- Walks	1	1290168	25790569	3042.8	13.2701	0.0003274 ***
- CRBI	1	1326770	25827172	3043.1	13.6466	0.0002706 ***
- PutOuts	1	1551523	26051925	3045.4	15.9583	0.00008504 ***
- AtBat	1	1589780	26090181	3045.8	16.3518	0.00006996 ***
- Hits	1	1716068	26216469	3047.1	17.6507	0.00003686 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```
summary(Hitters.step)
```

Call:

```
lm(formula = Salary ~ AtBat + Hits + Walks + CAtBat + CRuns +  
CRBI + CWalks + Division + PutOuts + Assists, data = Hitters)
```

Residuals:

Min	1Q	Median	3Q	Max
-939.11	-176.87	-34.08	130.90	1910.55

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	162.53544	66.90784	2.429	0.015830 *
AtBat	-2.16865	0.53630	-4.044	0.0000700 ***
Hits	6.91802	1.64665	4.201	0.0000369 ***
Walks	5.77322	1.58483	3.643	0.000327 ***
CAtBat	-0.13008	0.05550	-2.344	0.019858 *
CRuns	1.40825	0.39040	3.607	0.000373 ***
CRBI	0.77431	0.20961	3.694	0.000271 ***
CWalks	-0.83083	0.26359	-3.152	0.001818 **

```

DivisionW    -112.38006   39.21438  -2.866   0.004511 **
PutOuts       0.29737    0.07444   3.995  0.0000850 ***
Assists       0.28317    0.15766   1.796   0.073673 .
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

Residual standard error: 311.8 on 252 degrees of freedom
Multiple R-squared:  0.5405,    Adjusted R-squared:  0.5223
F-statistic: 29.64 on 10 and 252 DF,  p-value: < 2.2e-16

```

I'm not running the code below, but I show the commands to run the stepwise method using $p < 0.05$ as the inclusion/removal threshold

```

Hitters.step <- step(Hitters.full,
                     scope = list(lower = Hitters.null,
                                   upper = Hitters.full),
                     direction = "both",
                     test = "F",
                     k = qchisq(0.05, 1, lower.tail = F)) # or just k = 3.841)
summary(Hitters.step)

```

Best Subset Selection

I only discuss this method briefly, because the Step methods accomplish the same purpose and they are superior in my opinion. But it is a useful method to know. Best subset selection works similarly to the Step method, but there are no additions or removals in steps. Rather, the first step will try all possible 1-predictor models and select the best of all in terms of explanatory power. It will then fit all possible 2-predictor models, and so on. We use the `regsubsets()` function from the `{leaps}` package for this purpose. By default, `regsubsets()` stops when the model has 8 predictors, but you can change this with the `nvmax =` parameter. Let's illustrate this:

```

library(leaps) # Contains the regsubsets() function
regfit.full <- regsubsets(Salary ~ ., Hitters)
summary(regfit.full)

```

```

Subset selection object
Call: regsubsets.formula(Salary ~ ., Hitters)
19 Variables (and intercept)
      Forced in Forced out
AtBat      FALSE      FALSE
Hits       FALSE      FALSE
HmRun      FALSE      FALSE
Runs       FALSE      FALSE
RBI        FALSE      FALSE
Walks      FALSE      FALSE
Years      FALSE      FALSE
CAtBat     FALSE      FALSE
CHits      FALSE      FALSE
CHmRun     FALSE      FALSE
CRuns      FALSE      FALSE
CRBI       FALSE      FALSE
CWalks     FALSE      FALSE
LeagueN    FALSE      FALSE
DivisionW  FALSE      FALSE
PutOuts    FALSE      FALSE

```

```

Assists      FALSE      FALSE
Errors       FALSE      FALSE
NewLeagueN   FALSE      FALSE
1 subsets of each size up to 8
Selection Algorithm: exhaustive
      AtBat Hits HmRun Runs RBI Walks Years CatBat CHits CHmRun CRuns CRBI
1 ( 1 ) " " " " " " " " " " " " " " " " " " " " " "
2 ( 1 ) " " "*" " " " " " " " " " " " " " " " " " "
3 ( 1 ) " " "*" " " " " " " " " " " " " " " " " "
4 ( 1 ) " " "*" " " " " " " " " " " " " " " " " "
5 ( 1 ) "*" "*" " " " " " " " " " " " " " " " " "
6 ( 1 ) "*" "*" " " " " " " "*" " " " " " " " " " "
7 ( 1 ) " " "*" " " " " " "*" " " "*" "*" "*" " " "
8 ( 1 ) "*" "*" " " " " " " "*" " " " " "*" "*" " "

      CWalks LeagueN DivisionW PutOuts Assists Errors NewLeagueN
1 ( 1 ) " " " " " " " " " " " "
2 ( 1 ) " " " " " " " " " " " "
3 ( 1 ) " " " " " " "*" " " " " "
4 ( 1 ) " " " " "*" "*" " " " " " "
5 ( 1 ) " " " " "*" "*" " " " " " "
6 ( 1 ) " " " " "*" "*" " " " " " "
7 ( 1 ) " " " " "*" "*" " " " " " "
8 ( 1 ) "*" " " "*" "*" " " " " " "

```

The *** in the output shows the predictors selected in each model. You can also view the R-Squared of each model with the `$rsq` attribute:

```
summary(regfit.full)$rsq # View the R-square of each model
```

```

[1] 0.3214501 0.4252237 0.4514294 0.4754067 0.4908036 0.5087146 0.5141227
[8] 0.5285569

```

Let's change the number of predictors in the model up to 10

```

regfit.full <- regsubsets(Salary ~ .,
                          data = Hitters,
                          nvmax = 10)
summary(regfit.full)

```

Subset selection object

Call: `regsubsets.formula(Salary ~ ., data = Hitters, nvmax = 10)`

19 Variables (and intercept)

	Forced in	Forced out
AtBat	FALSE	FALSE
Hits	FALSE	FALSE
HmRun	FALSE	FALSE
Runs	FALSE	FALSE
RBI	FALSE	FALSE
Walks	FALSE	FALSE
Years	FALSE	FALSE
CatBat	FALSE	FALSE
CHits	FALSE	FALSE
CHmRun	FALSE	FALSE
CRuns	FALSE	FALSE

CRBI	FALSE	FALSE
CWalks	FALSE	FALSE
LeagueN	FALSE	FALSE
DivisionW	FALSE	FALSE
PutOuts	FALSE	FALSE
Assists	FALSE	FALSE
Errors	FALSE	FALSE
NewLeagueN	FALSE	FALSE

1 subsets of each size up to 10

Selection Algorithm: exhaustive

		AtBat	Hits	HmRun	Runs	RBI	Walks	Years	CAtBat	CHits	CHmRun	CRuns	CRBI
1	(1)	" "	" "	" "	" "	" "	" "	" "	" "	" "	" "	" "	"*
2	(1)	" "	"*	" "	" "	" "	" "	" "	" "	" "	" "	" "	"*
3	(1)	" "	"*	" "	" "	" "	" "	" "	" "	" "	" "	" "	"*
4	(1)	" "	"*	" "	" "	" "	" "	" "	" "	" "	" "	" "	"*
5	(1)	"*	"*	" "	" "	" "	" "	" "	" "	" "	" "	" "	"*
6	(1)	"*	"*	" "	" "	" "	"*	" "	" "	" "	" "	" "	"*
7	(1)	" "	"*	" "	" "	" "	"*	" "	"*	"*	"*	" "	" "
8	(1)	"*	"*	" "	" "	" "	"*	" "	" "	" "	"*	"*	" "
9	(1)	"*	"*	" "	" "	" "	"*	" "	"*	" "	" "	"*	"*
10	(1)	"*	"*	" "	" "	" "	"*	" "	"*	" "	" "	"*	"*

		CWalks	LeagueN	DivisionW	PutOuts	Assists	Errors	NewLeagueN
1	(1)	" "	" "	" "	" "	" "	" "	" "
2	(1)	" "	" "	" "	" "	" "	" "	" "
3	(1)	" "	" "	" "	"*	" "	" "	" "
4	(1)	" "	" "	"*	"*	" "	" "	" "
5	(1)	" "	" "	"*	"*	" "	" "	" "
6	(1)	" "	" "	"*	"*	" "	" "	" "
7	(1)	" "	" "	"*	"*	" "	" "	" "
8	(1)	"*	" "	"*	"*	" "	" "	" "
9	(1)	"*	" "	"*	"*	" "	" "	" "
10	(1)	"*	" "	"*	"*	"*	" "	" "