



# Live There with Airbnb - Sign up now

From bedrooms to apartments to villas - Airbnb has it all. Go to [airbnb.com](http://airbnb.com)



≡ Menu

- [Home](#)
- [Free eBook](#)
- [Start Here](#)
- [Contact](#)
- [About](#)

## 8 Linux TR Command Examples

by Lakshmanan Ganapathy on December 19, 2012



Tweet

tr is an UNIX utility for translating, or deleting, or squeezing repeated characters. It will read from STDIN and write to STDOUT.

tr stands for translate.

### Syntax

The syntax of tr command is:

```
$ tr [OPTION] SET1 [SET2]
```

### Translation

If both the SET1 and SET2 are specified and '-d' OPTION is not specified, then tr command will replace each characters in SET1 with each character in same position in SET2.

#### 1. Convert lower case to upper case

The following tr command is used to convert the lower case to upper case

```
$ tr abcdefghijklmnopqrstuvwxyz ABCDEFGHIJKLMNOPQRSTUVWXYZ  
thegeekstuff  
THEGEEKSTUFF
```

The following command will also convert lower case to upper case

```
$ tr [:lower:] [:upper:]
thegeekstuff
THEGEEKSTUFF
```

You can also use ranges in tr. The following command uses ranges to convert lower to upper case.



## Live There with Airbnb - Sign up now

From bedrooms to apartments  
to villas - Airbnb has it all.

airbnb.com



```
$ tr a-z A-Z
thegeekstuff
THEGEEKSTUFF
```

## 2. Translate braces into parenthesis

You can also translate from and to a file. In this example we will translate braces in a file with parenthesis.

```
$ tr '{}' '()' < inputfile > outputfile
```

The above command will read each character from “inputfile”, translate if it is a brace, and write the output in “outputfile”.

## 3. Translate white-space to tabs

The following command will translate all the white-space to tabs

```
$ echo "This is for testing" | tr [:space:] '\t'
This      is      for      testing
```

## 4. Squeeze repetition of characters using -s

In Example 3, we see how to translate space with tabs. But if there are two or more spaces present continuously, then the previous command will translate each space to a tab as follows.

```
$ echo "This  is  for testing" | tr [:space:] '\t'
This      is      for      testing
```

We can use -s option to squeeze the repetition of characters.

```
$ echo "This  is  for testing" | tr -s [:space:] '\t'
This      is      for      testing
```

Similarly you can convert multiple continuous spaces with a single space

```
$ echo "This is for testing" | tr -s [:space:] ' '  
This is for testing
```

## 5. Delete specified characters using -d option

tr can also be used to remove particular characters using -d option.

```
$ echo "the geek stuff" | tr -d 't'  
he geek suff
```

To remove all the digits from the string, use

```
$ echo "my username is 432234" | tr -d [:digit:]  
my username is
```

Also, if you like to delete lines from file, you can use [sed d command](#).

## 6. Complement the sets using -c option

You can complement the SET1 using -c option. For example, to remove all characters except digits, you can use the following.

```
$ echo "my username is 432234" | tr -cd [:digit:]  
432234
```

## 7. Remove all non-printable character from a file

The following command can be used to remove all non-printable characters from a file.

```
$ tr -cd [:print:] < file.txt
```

## 8. Join all the lines in a file into a single line

The below command will translate all newlines into spaces and make the result as a single line.

```
$ tr -s '\n' ' ' < file.txt
```



31

Tweet


Like 58

> [Add your comment](#)

If you enjoyed this article, you might also like..

1. [50 Linux Sysadmin Tutorials](#)
2. [50 Most Frequently Used Linux Commands \(With Examples\)](#)
3. [Top 25 Best Linux Performance Monitoring and Debugging Tools](#)
4. [Mommy, I found it! – 15 Practical Linux Find Command Examples](#)
5. [Linux 101 Hacks 2nd Edition eBook](#) **Free**

- [Awk Introduction – 7 Awk Print Examples](#)
- [Advanced Sed Substitution Examples](#)
- [8 Essential Vim Editor Navigation Fundamentals](#)
- [25 Most Frequently Used Linux IPTables Rules Examples](#)
- [Turbocharge PuTTY with 12 Powerful Add-Ons](#)



Tagged as: [UNIX TR Command](#)

{ 22 comments... [add one](#) }

- mre December 19, 2012, 10:42 am

Hello

How can I order in script lower words to upper the first letter of word only ?

ex: ramesh natarajan > Ramesh Natarajan

Thank you!

[Link](#)

- Jalal Hajigholamali December 19, 2012, 8:45 pm

Hi,  
Thanks for nice article.

Hi “mre”

tr can not solve your problem...

[Link](#)

- Goxxi December 20, 2012, 2:18 am

Hi,

I think, that [:lower:], [:digit:], .... must be quoted  
to protect this symbolic names against filename expansion!

Command line example:

```
$ touch d i g t
$ tr [:digit:] '*'
tr: extra operand `i'
Try `tr --help' for more information.
$
```

With regards,  
Goxxi

[Link](#)

- Kamal Kishore December 24, 2012, 6:37 am

8) Join all the lines in a file into a single line

The below command will translate all newlines into spaces and make the result as a single line.

```
$ tr -s '\n' ' ' < file.txt
```

also can use `tr '\n' <file.txt` # here we get the same result without using -s (switch)

[Link](#)

- Saravanan February 6, 2013, 12:55 pm

Nice article.

[Link](#)

- VIVEK August 1, 2013, 8:19 pm

```
echo "This is for testing" | tr [:space:] '\t' ...
```

This command works only when I enclose single quotes in between `[:space:]`..

i.e `echo "This is for testing" | tr '[:space:]' '\t'`

[Link](#)

- surendra December 23, 2013, 5:09 am

```
echo "welcome"|tee word|cut -c1|tr [a-z] [A-Z]|tee word1|echo "`cat` `cat word`"|cut -c1,4-10.
```

this will work to make the first letter of word to be capital

[Link](#)

- linux torvalds February 16, 2014, 11:37 am

how to replace multiple characters with only one given characters ?

[Link](#)

- Bhupender Singh March 31, 2014, 7:15 pm

This is how you can change multiple characters to only one character

```
echo `tr wabd A filename to save the output
```

[Link](#)

- linux torvalds April 9, 2014, 7:13 am

@bhupender singh

hey,

I don't think 'wabd' are options for tr; check by ``man tr`` command...

[Link](#)

- linux torvalds April 9, 2014, 7:19 am

@bhupender singh

hey,

I don't think 'wabd' are options for tr; check by ``man tr`` command...

[Link](#)

- maria May 14, 2014, 7:18 am

how to delete all control symbols from a line except NULL and new line?

I try

```
tr -d [[:cntrl:]]
```

but i need to save \n

[Link](#)

- Anonymous November 9, 2014, 1:48 pm

fast commend is not working

fast commmend ANS -tr -s " [a-z]" "[A-Z" < file name

[Link](#)

- Vijay January 8, 2015, 5:49 pm

Dear Lakshmanan,

Your tr of lower to upper is incorrect. You need to surround the brackets in single quotes.

Sincerely,

Vijay

[Link](#)

- Bensen June 5, 2015, 2:25 am

Hi! Thanks for the article.

I am trying to to use your command from nr 2 to change all text within a file from lower to upper.  
however bash just deletes everything!

```
tr [[:lower:]] [[:upper:]] text.txt
```

any advice on how i could avoid this? i want to overwrite the same file basically input and output at the same location. thx!

[Link](#)

- Pratyush July 20, 2015, 5:49 am

@Bensen

If this is your exact command

```
tr [[:lower:]] [[:upper:]] text.txt
```

Then it needs to be changed to

```
tr [[:lower:]] [[:upper:]] < text.txt
```

You need to redirect the file content, using '<' , to the 'tr' command

[Link](#)

- Maswood Alam November 13, 2015, 2:23 am

```
[root@abc alam]# cat kbc |tr [[:lower:]] [[:upper:]]
```

```
HI ALAM HOW ARE YOU []
```

```
I [AM FINE] BRO
```

```
[root@nldtlx07 alam]#
```

How can I also translate the braces in same command

```
cat kbc |tr [[:lower:]] [[:upper:]] && [] {}====> Its not working
```

[Link](#)

- Dinis November 24, 2015, 5:46 am

How can I change a text file with only NL line separators to a DOS one?

[Link](#)

- Ivan February 11, 2016, 10:39 am

Hi, i working on an assignment where i have to encrypt a text file.  
I finish most of the sub part but i could not solve the main part.

Im suppose to add a “key” into a-z. for example, the key is ZEROZEBRA->ZEROBA  
( i also have to remove the alphabet if they are the same)

plaintext alphabet ->abcdefghijklmnopqrstuvwxyz  
ciphertext alphabet->zerobacdfghijklmnpqstuvwxyz

notice that key is place to the left and the order of the alphabet is changed

After that, i use the ciphertext to encrypt a text file( i done this part).

[Link](#)

- JP March 19, 2016, 11:14 am

How do you combine many [SET1](s) and [SET2](s) into one tr -d command? I want to see an example of this. For example, I want to remove both the '00' and 'E-' in one tr -d command from a file1.

[Link](#)

- HTechnology March 26, 2016, 4:32 am

Thanks, it helped me, I like the organisation of this tuto, it really saves a time then reading the documentation topic of command 😊

[Link](#)

- arun April 8, 2016, 3:09 am

how to replace a character with multiple table. For example I need to replace a by 4 tabs

[Link](#)

Leave a Comment

Name

Email

Website

Comment

☐ Notify me of followup comments via e-mail

Next post: [Happy New Year 2013 – From Geek and the Dolls](#)

Previous post: [C Loops Explained with Examples \(For Loop, Do While and While\)](#)

[RSS](#) | [Email](#) | [Twitter](#) | [Facebook](#) | [Google+](#)




### Free Wallpaper For PC's

Download Any Wallpaper And Make Your Desktop Background Look Amazing. 100% Free Download!

Wallpapers.fm



## EBOOKS

- **Free** [Linux 101 Hacks 2nd Edition eBook](#) - Practical Examples to Build a Strong Foundation in Linux
- [Bash 101 Hacks eBook](#) - Take Control of Your Bash Command Line and Shell Scripting
- [Sed and Awk 101 Hacks eBook](#) - Enhance Your UNIX / Linux Life with Sed and Awk
- [Vim 101 Hacks eBook](#) - Practical Examples for Becoming Fast and Productive in Vim Editor
- [Nagios Core 3 eBook](#) - Monitor Everything, Be Proactive, and Sleep Well



The Geek Stuff

16,682 likes



Be the first of your friends to like this



## POPULAR POSTS

- [12 Amazing and Essential Linux Books To Enrich Your Brain and Library](#)
- [50 UNIX / Linux Sysadmin Tutorials](#)
- [50 Most Frequently Used UNIX / Linux Commands \(With Examples\)](#)
- [How To Be Productive and Get Things Done Using GTD](#)



- [30 Things To Do When you are Bored and have a Computer](#)
- [Linux Directory Structure \(File System Structure\) Explained with Examples](#)
- [Linux Crontab: 15 Awesome Cron Job Examples](#)
- [Get a Grip on the Grep! – 15 Practical Grep Command Examples](#)
- [Unix LS Command: 15 Practical Examples](#)
- [15 Examples To Master Linux Command Line History](#)
- [Top 10 Open Source Bug Tracking System](#)
- [Vi and Vim Macro Tutorial: How To Record and Play](#)
- [Mommy, I found it! -- 15 Practical Linux Find Command Examples](#)
- [15 Awesome Gmail Tips and Tricks](#)
- [15 Awesome Google Search Tips and Tricks](#)
- [RAID 0, RAID 1, RAID 5, RAID 10 Explained with Diagrams](#)
- [Can You Top This? 15 Practical Linux Top Command Examples](#)
- [Top 5 Best System Monitoring Tools](#)
- [Top 5 Best Linux OS Distributions](#)
- [How To Monitor Remote Linux Host using Nagios 3.0](#)
- [Awk Introduction Tutorial – 7 Awk Print Examples](#)
- [How to Backup Linux? 15 rsync Command Examples](#)
- [The Ultimate Wget Download Guide With 15 Awesome Examples](#)
- [Top 5 Best Linux Text Editors](#)
- [Packet Analyzer: 15 TCPDUMP Command Examples](#)
- [The Ultimate Bash Array Tutorial with 15 Examples](#)
- [3 Steps to Perform SSH Login Without Password Using ssh-keygen & ssh-copy-id](#)
- [Unix Sed Tutorial: Advanced Sed Substitution Examples](#)
- [UNIX / Linux: 10 Netstat Command Examples](#)
- [The Ultimate Guide for Creating Strong Passwords](#)
- [6 Steps to Secure Your Home Wireless Network](#)
- [Turbocharge PuTTY with 12 Powerful Add-Ons](#)

## CATEGORIES

- [Linux Tutorials](#)
- [Vim Editor](#)
- [Sed Scripting](#)
- [Awk Scripting](#)
- [Bash Shell Scripting](#)
- [Nagios Monitoring](#)
- [OpenSSH](#)
- [IPTables Firewall](#)
- [Apache Web Server](#)
- [MySQL Database](#)
- [Perl Programming](#)
- [Google Tutorials](#)
- [Ubuntu Tutorials](#)
- [PostgreSQL DB](#)
- [Hello World Examples](#)
- [C Programming](#)
- [C++ Programming](#)
- [DELL Server Tutorials](#)
- [Oracle Database](#)
- [VMware Tutorials](#)

Ramesh Natarajan

 Follow

## About The Geek Stuff



My name is **Ramesh Natarajan**. I will be posting instruction guides, how-to, troubleshooting tips and tricks on Linux, database, hardware, security and web. My focus is to write articles that will either teach you or help you resolve a problem. Read more about [Ramesh Natarajan](#) and the blog.

## Contact Us

**Email Me :** Use this [Contact Form](#) to get in touch me with your comments, questions or suggestions about this site. You can also simply drop me a line to say hello!.

[Follow us on Google+](#)

[Follow us on Twitter](#)

[Become a fan on Facebook](#)

## Support Us

Support this blog by purchasing one of my ebooks.

[Bash 101 Hacks eBook](#)

[Sed and Awk 101 Hacks eBook](#)

[Vim 101 Hacks eBook](#)

[Nagios Core 3 eBook](#)

Copyright © 2008–2017 Ramesh Natarajan. All rights reserved | [Terms of Service](#)