



技术规格 Technical Specifications		Unit:mm		未注线性与角度尺寸公差		Tolerances for linear and angular dimensions without individual tolerance indications		未注形状与位置尺寸公差		Geometrical tolerance for features without individual tolerance indications		规格书 Specification	
1、步距角 Step Angle	1.8° ±5%											AD28HY32-4030A	杭州安久传动有限公司 Hangzhou ANG Drive CO., Ltd
2、相数 Number of Phase	2												
3、绝缘电阻 Insulation Resistance	100MΩ min. (500VDC)			GB/T 1804-Ⅶ eqv IOS 2768-1:Ⅲ									
4、绝缘等级 Insulation Class	Class B(F级可用)											11HY型混合式步进电机 Hybrid stepping motor	
5、额定电压 Rated Voltage	6.6 V DC			GB/T 1184-X eqv IOS 2768-2:K									
6、额定电流 Rated Current	0.3 Amp												
7、相电阻 Phase Resistance	22±10% Ω (20℃)												
8、相电感 Phase Inductance	12.5±20% mH												
9、保持转矩 Holding Torque	0.06Nm	标记	处数	更改文件名	签字	日期							
10、转动惯量 Rotor Inertia	9g.cm²	设	计										
11、定位转矩 Detent Torque	50g.cm												
12、电机重量 Motor Weight	0.11Kg												
												1:1.5	
												第 1 张	

励磁顺序 vs. 旋转方向		Exciting Sequence vs. Direction of Rotation			
STEP	A	B	A-B-	-B	CW
1	+	+	-	-	
2	-	+	+ -		
3	-	-	+ +		
4	+	-	- -		
			CW		
			以安装面看为顺时针方向		
			Clockwise view from mounting side		

