Internet Sharing

From ArchWiki

This article explains how to share the internet connection from one machine to other(s).

Contents

- 1 Requirements
- 2 Configuration
 - 2.1 Static IP address
 - 2.2 Enable packet forwarding
 - 2.3 Enable NAT
 - 2.4 Assigning ip addresses to the client pc(s)
 - 2.4.1 Manually adding an ip
- 3 Troubleshooting
- 4 See also

Requirements

- The machine acting as server should have an additional network device.
- That network device should be connected to the machines that are going to receive internet access. They can be one or more machines. To be able to share internet to several machines a switch is required. If you are sharing to only one machine, a crossover cable is sufficient.

Note: If one of the two computers has a gigabit ethernet card, a crossover cable is not necessary and a regular ethernet cable should be enough

Configuration

This section assumes, that the network device connected to the client computer(s) is named *net0* and the network device connected to the internet as *internet0*.

Tip: You can rename your devices to this scheme using Udev#Setting static device names.

Static IP address

Assign an static IPv4 address to the interface connected to the other machines. The first 3 bytes of this address cannot be exactly the same as those of another interface.

ip link set up dev net0

```
ip addr add 139.96.30.100/24 dev net0 # arbitrary address
```

To have your static ip assigned at boot, you can use netctl.

Enable packet forwarding

Check the current packet forwarding settings;

```
# sysctl -a | grep forward
```

Enter this command to temporarily enable packet forwarding:

```
# sysctl net.ipv4.ip_forward=1
```

Edit /etc/sysctl.d/30-ipforward.conf to make the previous change persistent after a reboot.

```
/etc/sysctl.d/30-ipforward.conf

net.ipv4.ip_forward=1

net.ipv6.conf.default.forwarding=1

net.ipv6.conf.all.forwarding=1
```

Enable NAT

Install the package iptables (https://www.archlinux.org/packages/?name=iptables) from the official repositories. Use iptables to enable NAT:

```
# iptables -t nat -A POSTROUTING -o internet0 -j MASQUERADE
```

Replace internet 0 with the device name of your network device that receives internet access, e.g. eth0, tun0 etc.

Note: Of course, this also works with a mobile broadband connection (usually called ppp0 on PC1).

Read the iptables article for more information (especially saving the rule and applying it automatically on boot). There is also an excellent guide on iptables Simple stateful firewall.

Assigning ip addresses to the client pc(s)

If you are planning to regularly have several machines using the internet shared by this machine, then is a good idea to install a dhcp server.

You can read the dhcpd wiki article, to add a dhcp server. Then, install the dhcpcd client on every client pc.

If you are not planing to use this setup regularly, you can manually add an ip to each client instead.

Manually adding an ip

Instead of using dhcp, on each client pc, add an ip address and the default route:

```
# ip addr add 139.96.30.120/24 dev eth0
# ip link set up dev eth0
# ip route add default via 139.96.30.100 dev eth0
```

Add a nameserver:

```
# echo "nameserver <nameserver ip>" >> /etc/resolv.conf
```

You can figure out the address of the nameserver by looking into the /etc/resolv.conf of the server, if its Internet connection is already established.

If you don't have a nameserver, you can use any of the free public DNS servers, which are relatively fast:

- Google Public DNS (https://code.google.com/speed/public-dns/)
 - **8.8.8.8**
 - **8.8.4.4**
 - **[**2001:4860:4860::8888]
 - **[**2001:4860:4860::8844]
- OpenDNS (https://opendns.com):
 - **208.67.222.222**
 - **2**08.67.220.220
 - [2620:0:ccc::2]
 - [2620:0:ccd::2]

Note: Bracket notation must be used for IPv6 addresses in resolv.conf.

That's it. The client PC should now have Internet.

Troubleshooting

If you are able to connect the two PCs but cannot send data (for example, if the client PC makes a DHCP request to the server PC, the server PC receives the request and offers an IP to the client, but the client does not accept it, timing out instead), check that you don't have other Iptables rules interfering (https://bbs.archlinux.org/viewtopic.php?pid=1093208).

See also

- Ad-hoc networking
- Sharing PPP Connection
- Simple stateful firewall
- Router
- USB 3G Modem

Retrieved from "https://wiki.archlinux.org/index.php?title=Internet_Sharing&oldid=291477" Category: Networking

- This page was last modified on 3 January 2014, at 13:08.
- Content is available under GNU Free Documentation License 1.3 or later unless otherwise noted.