https://ko.aliexpress.com/item/1005007522334852.html?spm=a2g0o.tesla.0.0.591926ta26taOx&afTraceInfo=1005007522334852__pc__c_ppc_item_bridge_pc_jfy_wf__WpW5sqz__1774336521418&gatewayAdapt=glo2kor

2.0 inch touch display module

Specification:

- Model Name : D200C2409V0
- Screen size : 2.0 inch
- Resolution : 480*640
- Outline Size (mm): 37.5(W)*54.5(H)*2.95(T)
- Active area(mm) : 30.6 (W)*40.8 (H)
- LCD Interface Type : MIPI and RGB565
- LCD Driver : ST7701S
- Touch : apacitive touch screen
- Touch Interface Type : I2C
- Touch Driver : FT6336
- Brightness : 400 Cd/m²
- Display type : IPS
- Operation temperature:-20℃ ~ +70℃

Product Image:

IPS
Resolution: 480*640
LCD Interface: MIPI and RGB 565 interface
Touch Interface: I2C

D200FPC2409-A
2405

front

back

Pin No.	Symbol	Description	When not in use
1	LEDA	B/L positive pin	--
2	LEDK	B/L negative pin	--
3	VDD	Power supply,2.8-3.3V type.	--
4	GND	Power Ground	--
5	D0N	MIPI DSI differential data pair.	--
6	D0P		--
7	GND	Power Ground	--
8	CLKN	MIPI DSI differential clock pair.	--
9	CLKP		--
10	GND	Power Ground	--
11	D1N	MIPI DSI differential data pair.	--
12	D1P		--
13-33	GND	Power Ground	--
34	RESET	Reset the LCM	--
35-37	GND	Power Ground	
38	VDD	Power supply,2.8-3.3V type.	
39	GND	Power Ground	--
40	NC	dummy	--

Pin No.	Symbol	Description	When not in use
1	GND	Ground	--
2	REST	RESET	--
3	SDA	3.3V I2C data input and output	--
4	SCL	3.3V I2C clock input	--
5	EINT	Interrupt to the host	--
6	VDD	power supply 2.8V-3.3V	--