



MICROSOFT WINDOWS SERVER 2022

不同的系统版本，有着不同的封装方式，封装过程中包含：“语言包：添加、关联、删除”、“驱动：添加、删除”、“累积更新：添加、删除”等。

在这背后藏着很多的隐藏故事，想解开这些，你准备好开始尝试封装了吗？

摘要

章节 1 封装

章节 1	封装	第 4 页
A.	先决条件	第 4 页
II	正在运行的操作系统	第 4 页
III	ISO 工具	第 4 页
IV	要求	第 4 页
1.	系统安装包	第 4 页
2.	语言包	第 4 页
2.1.	学习	第 4 页
2.2.	语言包：下载	第 5 页
V	Windows 安全中心	第 5 页
VI	命令行	第 5 页
B.	语言包：提取	第 5 页
II	语言包：准备	第 6 页
III	语言包：提取方案	第 6 页
IV	执行提取命令	第 6 页
C.	自定义封装	第 12 页
II	自定义封装：Install.wim	第 12 页
1.	查看 Install.wim 详细信息	第 12 页
2.	指定挂载 Install.wim 路径	第 12 页
3.	开始挂载 Install.wim	第 12 页
3.1.	自定义封装：WinRE.wim	第 12 页
3.1.1.	查看 WinRE.wim 详细信息	第 12 页
3.1.2.	指定挂载 WinRE.wim 路径	第 12 页
3.1.3.	开始挂载 WinRE.wim	第 12 页
3.1.4.	语言包	第 13 页

3.1.4.1.	语言包：添加	第 13 页
3.1.4.2.	组件：映像中已安装的所有包	第 14 页
3.1.5.	保存映像	第 15 页
3.1.6.	卸载映像	第 15 页
3.1.7.	重建 WinRE.wim 后，可缩小文件大小	第 15 页
3.1.8.	备份 WinRE.wim	第 16 页
3.1.9.	替换 Install.wim 映像内的 WinRE.wim	第 16 页
4.	语言包	第 16 页
4.1.	语言包：添加	第 16 页
4.2.	组件：映像中已安装的所有包	第 18 页
5.	累积更新	第 18 页
5.1.	下载	第 18 页
5.2.	添加	第 18 页
5.3.	固化更新	第 19 页
5.3.1.	固化更新后清理组件	第 19 页
6.	部署引擎：添加	第 19 页
7.	健康	第 19 页
8.	替换 WinRE.wim	第 19 页
9.	保存映像	第 19 页
10.	卸载映像	第 20 页
11.	如何批量替换 Install.wim 里的所有索引号里的 WinRE.wim	第 20 页
11.1.	获取 WimLib	第 20 页
11.2.	如何在 Install.wim 里提取和更新 WinRE.wim	第 20 页
12.	重建 Install.wim 后可缩小文件大小	第 21 页

III	自定义封装：boot.wim	第 22 页
1.	查看 Boot.wim 文件信息	第 22 页
2.	指定挂载 Boot.wim 路径	第 22 页
3.	开始挂载 Boot.wim	第 22 页
4.	语言包	第 22 页
4.1.	语言包：添加	第 22 页
4.2.	组件：映像中已安装的所有包	第 24 页
4.3.	语言包：同步到 ISO 安装程序	第 24 页
4.4.	重新生成 Lang.ini	第 24 页
4.4.1.	重新生成已挂载目录 lang.ini	第 24 页
4.4.2.	重新生成 lang.ini 后，同步到安装程序	第 24 页
5.	保存映像	第 24 页
6.	卸载映像	第 24 页
IV	部署引擎	第 25 页
1.	添加方式	第 25 页
2.	部署引擎：进阶	第 28 页
D.	生成 ISO	第 30 页

章节 1 封装

A. 先决条件

II 正在运行的操作系统

正在运行的操作系统是 Windows 10 或者低于 Windows 11 24H2 时，在某些情况下使用 DISM 命令在制作高版本镜像时，会引发一些未知的问题，例如：在 Windows 10 操作系统里运行 DISM 命令来处理 Windows Server 2025 脱机映像时，在封装过程中也许会收到报错信息：“此应用无法在你的电脑运行”，解决方法：

1. 升级正在运行的操作系统或重新安装到更高的版本（建议）；
2. 升级或安装新版 ADK 或 PowerShell 版本（不建议）
 - 2.1. 可尝试升级到最新 PowerShell 7 以上的版本；
 - 2.2. 安装最新版 ADK 后并替换 DISM 命令后能解决 DISM 版本低的问题，但是：封装脚本主要使用的命令行是 PowerShell 命令行，所以不建议你使用以上方法，最佳的方法是：升级正在运行的操作系统或重新安装到更高的版本。

II ISO 工具

使用一款可编辑 ISO 文件的软件，例如：[PowerISO](#)、[DAEMON Tools](#)、[ISO Workshop](#)；

III 要求

1. 系统安装包

- 1.1. 准备：[en-us_windows_server_2022_x64_dvd_620d7eac.iso](#)
- 1.2. 解压到：[D:\en-us_windows_server_2022_x64_dvd_620d7eac](#)
- 1.3. 解压完成后，将目录 [en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08c](#) 更改为 [D:\OS_2022](#)

注意：解压到 D 盘前，你应该检查是否 ReFS 分区格式，如果是 ReFS 分区格式时：执行部分命令将出现异常。解决方法：请使用 NTFS 格式的磁盘分区。

- 1.4. 所有脚本、所有路径，已默认设置为 [D:\OS_2022](#) 为映像来源。

2. 语言包

2.1. 学习

阅读时，请了解“蓝色”重要突出部分。

- 2.1.1. [将语言添加到 Windows 11 映像](#)
- 2.1.2. [语言和区域按需功能 \(FOD\)](#)

2.2. 语言包：下载

[20348.1.210507-1500.fe_release_amd64fre_SERVER_LOF_PACKAGES_OEM.iso](#)

IV Windows 安全中心

- 在处理封装任务时，将产生大量的临时文件，安装 InBox Apps 里的应用时会释放大量的安装文件；
- 开启 Windows 安全中心会扫描文件、会占用大量的 CPU。
- 测试中：未关闭前耗时 1 小时 22 分，关闭后耗时 20 分钟。

如何关闭：

绿色为命令行，按住 Windows 键并按 R 键启动“运行”。

1. 打开“Windows 安全中心”或运行：`windowsdefender:`
2. 选择“病毒和威胁防护”或运行：`windowsdefender://threat`
3. 找到“病毒和威胁防护设置”，点击“管理设置”或运行：`windowsdefender://threatsettings`，建议您关闭部分功能：
 - 3.1. 实时保护
 - 3.2. 云提供的保护
 - 3.3. 自动提交样本
 - 3.4. 篡改防护
4. 未处于封装时，建议您开启 Windows 安全中心。

V 命令行

1. 可选“Terminal”或“PowerShell ISE”，未安装“Terminal”，请前往 <https://github.com/microsoft/terminal/releases> 后下载；
2. 以管理员身份打开“Terminal”或“PowerShell ISE”，建议设置 PowerShell 执行策略：绕过，PS 命令行：
`Set-ExecutionPolicy -ExecutionPolicy Bypass -Force`
3. 在本文中，PS 命令行，绿色部分，请复制后，粘贴到“Terminal”对话框，按回车键（Enter）后开始运行；
4. 有 .ps1 时，点击文件右键，选择以 PowerShell 运行，或复制路径，粘贴到 Terminal 里运行，带冒号的路径，在命令行添加 & 字符，示例：
`& "D:\YiSolutions_Encapsulation_SIP.ps1"`

B. 语言包：提取

II 语言包：准备

挂载 20348.1.210507-1500.fe_release_amd64fre_SERVER_LOF_PACKAGES_OEM.iso 或解压到任意位置；

III 语言包：提取方案

1. 添加

1.1. 语言名称：简体中文 - 中国，区域：zh-CN，适用范围：Install.Wim，Boot.Wim，WinRE.Wim

2. 删除

2.1. 语言名称：英语 - 美国，区域：en-US，适用范围：Install.Wim，Boot.Wim，WinRE.Wim

IV 执行提取命令

- Auto = 自动搜索本地所有磁盘，默认；
- 自定义路径，例如指定为 E 盘：\$ISO = "E:\"
- Extract.ps1
 - \Expand\Extract.ps1
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/Extract.ps1

• 复制代码

```
$ISO = "Auto"

$SaveTo = "D:\OS_2022_Custom"

$Extract_language_Pack = @(

    @{ Tag = "zh-CN"; Act = "Add"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }

    @{ Tag = "en-US"; Act = "Del"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }

)

Function Extract_Language

{

    param( $Act, $NewLang, $Expand )

    Function Match_Required_Fonts

    {

        param( $Lang )

        $Fonts = @(

            @{ Match = @( "as", "ar-SA", "ar", "ar-AE", "ar-BH", "ar-DJ", "ar-DZ", "ar-EG", "ar-ER", "ar-IL", "ar-IQ", "ar-JO", "ar-KM", "ar-KW", "ar-LB", "ar-LY", "ar-MA", "ar-MR", "ar-OM", "ar-PS", "ar-QA", "ar-SD", "ar-SO", "ar-SS", "ar-SY", "ar-TD", "ar-TN", "ar-YE", "arz-Arab", "ckb-Arab", "fa", "fa-AF", "fa-IR", "glk-Arab", "ha-
```

```
Arab", "ks-Arab", "ks-Arab-IN", "ku-Arab", "ku-Arab-IQ", "mzn-Arab", "pa-Arab", "pa-Arab-PK", "pnb-Arab", "prs", "prs-AF", "prs-Arab", "ps", "ps-AF", "sd-Arab", "sd-Arab-PK", "tk-Arab", "ug", "ug-Arab", "ug-CN", "ur", "ur-IN", "ur-PK", "uz-Arab", "uz-Arab-AF"); Name = "Arab"; }

    @ { Match = @ ("bn-IN", "as-IN", "bn", "bn-BD", "bpy-Beng"); Name = "Beng"; }

    @ { Match = @ ("da-dk", "iu-Cans", "iu-Cans-CA"); Name = "Cans"; }

    @ { Match = @ ("chr-Cher-US", "chr-Cher"); Name = "Cher"; }

    @ { Match = @ ("hi-IN", "bh-Deva", "brx", "brx-Deva", "brx-IN", "hi", "ks-Deva", "mai", "mr", "mr-IN", "ne", "ne-IN", "ne-NP", "new-Deva", "pi-Deva", "sa", "sa-Deva", "sa-IN"); Name = "Deva"; }

    @ { Match = @ ("am", "am-ET", "byn", "byn-ER", "byn-Ethi", "ti", "ti-ER", "ti-ET", "tig", "tig-ER", "tig-Ethi", "ve-Ethi", "wal", "wal-ET", "wal-Ethi"); Name = "Ethi"; }

    @ { Match = @ ("gu", "gu-IN"); Name = "Gujr"; }

    @ { Match = @ ("pa", "pa-IN", "pa-Guru"); Name = "Guru"; }

    @ { Match = @ ("zh-CN", "cmn-Hans", "gan-Hans", "hak-Hans", "wuu-Hans", "yue-Hans", "zh-gan-Hans", "zh-hak-Hans", "zh-Hans", "zh-SG", "zh-wuu-Hans", "zh-yue-Hans"); Name = "Hans"; }

    @ { Match = @ ("zh-TW", "cmn-Hant", "hak-Hant", "lzh-Hant", "zh-hak-Hant", "zh-Hant", "zh-HK", "zh-lzh-Hant", "zh-MO", "zh-yue-Hant"); Name = "Hant"; }

    @ { Match = @ ("he", "he-IL", "yi"); Name = "Hebr"; }

    @ { Match = @ ("ja", "ja-JP"); Name = "Jpan"; }

    @ { Match = @ ("km", "km-KH"); Name = "Khmr"; }

    @ { Match = @ ("kn", "kn-IN"); Name = "Knda"; }

    @ { Match = @ ("ko", "ko-KR"); Name = "Kore"; }

    @ { Match = @ ("de-de", "lo", "lo-LA"); Name = "Lao"; }

    @ { Match = @ ("ml", "ml-IN"); Name = "Mlym"; }

    @ { Match = @ ("or", "or-IN"); Name = "Orya"; }

    @ { Match = @ ("si", "si-LK"); Name = "Sinh"; }

    @ { Match = @ ("tr-tr", "arc-Syrc", "syr", "syr-SY", "syr-Syrc"); Name = "Syrc"; }

    @ { Match = @ ("ta", "ta-IN", "ta-LK", "ta-MY", "ta-SG"); Name = "Taml"; }

    @ { Match = @ ("te", "te-IN"); Name = "Telu"; }

    @ { Match = @ ("th", "th-TH"); Name = "Thai"; }

)

ForEach ($item in $Fonts) {

    if (($item.Match) -Contains $Lang) {

        return $item.Name

    }

}

return "Not_matched"

}
```



```
Function Match_Other_Region_Specific_Requirements

{

    param( $Lang )

    $RegionSpecific = @(

        @{ Match = @"(zh-TW)"; Name = "Taiwan"; }

    )

    ForEach ($item in $RegionSpecific) {

        if (($item.Match) -Contains $Lang) {

            return $item.Name

        }

    }

    return "Skip_specific_packages"

}

Function Extract_Process

{

    param( $Package, $Name, $NewSaveTo )

    $NewSaveTo = "$($SaveTo)\$($NewSaveTo)\Language\$($Act)\$($NewLang)"

    New-Item -Path $NewSaveTo -ItemType Directory -ErrorAction SilentlyContinue | Out-Null

    if ($ISO -eq "Auto") {

        Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

            ForEach ($item in $Package) {

                $TempFilePath = Join-Path -Path $_.Root -ChildPath $item -ErrorAction SilentlyContinue

                if (Test-Path $TempFilePath -PathType Leaf) {

                    Write-host "`n Find: " -NoNewLine; Write-host $TempFilePath -ForegroundColor Green

                    Write-host " Copy to: " -NoNewLine; Write-host $NewSaveTo

                    Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

                }

            }

        }

    } else {

        ForEach ($item in $Package) {

            $TempFilePath = Join-Path -Path $ISO -ChildPath $item -ErrorAction SilentlyContinue

            Write-host "`n Find: " -NoNewline; Write-host $TempFilePath -ForegroundColor Green

            if (Test-Path $TempFilePath -PathType Leaf) {
```

```

        Write-host "  Copy to: " -NoNewLine; Write-host $NewSaveTo

        Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

    } else {

        Write-host "  Not found"

    }

}

}

}

Write-host "`n  Verify the language pack file"

ForEach ($item in $Package) {

    $Path = "$($NewSaveTo)\${[IO.Path]::GetFileName($item)}"

    if (Test-Path $Path -PathType Leaf) {

        Write-host "  Discover: " -NoNewLine; Write-host $Path -ForegroundColor Green

    } else {

        Write-host "  Not found: " -NoNewLine; Write-host $Path -ForegroundColor Red

    }

}

}

}

$AdvLanguage = @(

    @(

        Path = "Install\Install"

        Rule = @(

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Fonts-{DiyLang}-Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Server-Language-Pack_x64_{Lang}.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Basic-{Lang}-Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Handwriting-{Lang}-Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-OCR-{Lang}-Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Speech-{Lang}-Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-TextToSpeech-{Lang}-Package~31bf3856ad364e35~amd64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

```

```
"LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

)

}

@{

    Path = "Install\WinRE"

    Rule = @(

        "Windows Preinstallation Environment\x64\WinPE_OC\WinPE-FontSupport-{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\lp.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-securestartup_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-atbroker_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiocore_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiodrivers_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-enhancedstorage_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-narrator_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-scripting_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-speech-tts_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srh_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srt_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wds-tools_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wmi_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-appxpackaging_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-storagewmi_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wifi_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-rejuv_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-opcservices_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-hta_{Lang}.cab"

    )

}

@{

    Path = "Boot\Boot"

    Rule = @(
```

```

"Windows Preinstallation Environment\x64\WinPE_OC\WinPE-FontSupport-{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\lp.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\WinPE-Setup_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\WINPE-SETUP-Server_{Lang}.CAB"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-securestartup_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-atbroker_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiocore_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-audiodrivers_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-enhancedstorage_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-narrator_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-scripting_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-speech-tts_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srh_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-srt_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wds-tools_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\{Lang}\winpe-wmi_{Lang}.cab"

)

}

)

$NewFonts = Match_Required_Fonts -Lang $NewLang

$SpecificPackage = Match_Other_Region_Specific_Requirements -Lang $NewLang

Foreach ($item in $Expand) {

    $Language = @()

    Foreach ($itemList in $AdvLanguage) {

        if ($itemList.Path -eq $item) {

            Foreach ($PrintLang in $itemList.Rule) {

                $Language += "$($PrintLang)".Replace("{Lang}", $NewLang).Replace("{DiyLang}", $NewFonts).Replace("{Specific}", $SpecificPackage)

            }

            Extract_Process -NewSaveTo $itemList.Path -Package $Language -Name $item

        }

    }

}

}

}

Foreach ($item in $Extract_language_Pack) { Extract_Language -Act $item.Act -NewLang $item.Tag -Expand $item.Scope }

```

C. 自定义封装

II 自定义封装：Install.wim

1. 查看 Install.wim 详细信息

映像名称、映像描述、映像大小、架构、版本、索引号等；

```
$ViewFile = "D:\OS_2022\Sources\Install.wim"

Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

循环操作区域，开始，

2. 指定挂载 Install.wim 路径

```
New-Item -Path "D:\OS_2022_Custom\Install\Install\Mount" -ItemType directory -ea SilentlyContinue
```

3. 开始挂载 Install.wim

默认索引号：1

```
Mount-WindowsImage -ImagePath "D:\OS_2022\sources\install.wim" -Index "1" -Path "D:\OS_2022_Custom\Install\Install\Mount"
```

处理 Install.wim 映像内的文件，可选项，开始，

3.1. 自定义封装：WinRE.wim

注意：

- WinRE.wim 属于 Install.wim 映像内的文件；
- Install.wim 有多个索引号时，仅处理任意一个 WinRE.wim 即可；
- 同步至所有索引号即可减少 Install.wim 体积；学习“[如何批量替换 Install.wim 里的所有索引号里的 WinRE.wim](#)”。

3.1.1. 查看 WinRE.wim 详细信息

映像名称、映像描述、映像大小、架构、版本、索引号等；

```
$ViewFile = "D:\OS_2022_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

3.1.2. 指定挂载 WinRE.wim 路径

```
New-Item -Path "D:\OS_2022_Custom\Install\WinRE\Mount" -ItemType directory -ea SilentlyContinue
```

3.1.3. 开始挂载 WinRE.wim

默认索引号：1

```
Mount-WindowsImage -ImagePath $FileName -Index "1" -Path "D:\OS_2022_Custom\Install\WinRE\Mount"
```

3.1.4. 语言包

- 自动安装语言包：获取“组件：映像中已安装的所有包”后进行匹配，匹配到对应的名称后，再安装本地对应的语言包文件，查看报告“语言安装包适用于 WinRE.wim”。
- 添加语言时，须对应不同的架构版本，未对应时，添加过程中报错等提示。

3.1.4.1. 语言包：添加

- WinRE.Instl.lang.ps1
 - [\Expand\Install\WinRE\WinRE.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/Install/WinRE/WinRE.Instl.lang.ps1

- 复制代码

```
$Mount = "D:\OS_2022_Custom\Install\WinRE\Mount"

$Sources = "D:\OS_2022_Custom\Install\WinRE\Language\Add\zh-CN"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language_List = @(

    @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

    @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

    @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

    @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

    @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

    @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

    @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }
```

```
@{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

@{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

@{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_zh-CN.cab"; }

@{ Match = "*StorageWMI*"; File = "winpe-storagewmi_zh-CN.cab"; }

@{ Match = "*WiFi*"; File = "winpe-wifi_zh-CN.cab"; }

@{ Match = "*rejuv*"; File = "winpe-rejuv_zh-CN.cab"; }

@{ Match = "*opcservices*"; File = "winpe-opcservices_zh-CN.cab"; }

@{ Match = "*hta*"; File = "winpe-hta_zh-CN.cab"; }

)

ForEach ($Rule in $Language_List) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Installing ".PadRight(22) -NoNewline

            try{

                Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

            }

            break

        }

    }

}
```

3.1.4.2. 组件：映像中已安装的所有包

3.1.4.2.1. 查看

```
Get-WindowsPackage -Path "D:\OS_2022_Custom\Install\WinRE\Mount" | Out-GridView
```

3.1.4.2.2. 导出到 Csv

	<pre>\$SaveTo = "D:\OS_2022_Custom\Install\WinRE\Report.\${Get-Date -Format "yyyyMMddHHmmss").csv" Get-WindowsPackage -Path "D:\OS_2022_Custom\Install\WinRE\Mount" Export-CSV - NoType -Path \$SaveTo Write-host \$SaveTo -ForegroundColor Green</pre>
--	---

3.1.5. 保存映像

```
Save-WindowsImage -Path "D:\OS_2022_Custom\Install\WinRE\Mount"
```

3.1.6. 卸载映像

关闭所有可能正在访问映像中文件的应用程序，包括文件资源管理器。

```
Dismount-WindowsImage -Path "D:\OS_2022_Custom\Install\WinRE\Mount" -Discard
```

3.1.7. 重建 WinRE.wim 后，可缩小文件大小

- WinRE.Rebuild.ps1
 - [\Expand\Install\WinRE\WinRE.Rebuild.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/Install/WinRE/WinRE.Rebuild.ps1

- 复制代码

```
$FileName = "D:\OS_2022_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

Get-WindowsImage -ImagePath $Filename -ErrorAction SilentlyContinue | ForEach-Object {

    Write-Host " Image name: " -NoNewline

    Write-Host $_.ImageName -ForegroundColor Yellow

    Write-Host " The index number: " -NoNewline

    Write-Host $_.ImageIndex -ForegroundColor Yellow

    Write-Host "`n Rebuild".PadRight(28) -NoNewline

    Export-WindowsImage -SourceImagePath $Filename -SourceIndex $_.ImageIndex -DestinationImagePath
"$($FileName).New" -CompressionType max

    Write-Host "Finish`n" -ForegroundColor Green

}

if (Test-Path "$($FileName).New" -PathType Leaf) {

    Remove-Item -Path $Filename

    Move-Item -Path "$($FileName).New" -Destination $Filename

    Write-Host "Finish" -ForegroundColor Green

} else {
```



```
Write-host "Failed" -ForegroundColor Red  
  
}
```

3.1.8. 备份 WinRE.wim

- WinRE.Backup.ps1
 - [\Expand\Install\WinRE\WinRE.Backup.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/Install/WinRE/WinRE.Backup.ps1

- 复制代码

```
$WimLibPath = "D:\OS_2022_Custom\Install\Install\Update\Winlib"  
  
$FileName = "D:\OS_2022_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"  
  
New-Item -Path $WimLibPath -ItemType Directory -ea SilentlyContinue  
  
Copy-Item -Path $FileName -Destination $WimLibPath -Force
```

3.1.9. 替换 Install.wim 映像内的 WinRE.wim

- 每次挂载 Install.wim 后“[替换 WinRE.wim](#)”；
- 学习“[获取 Install.wim 所有索引号后并替换旧的 WinRE.wim](#)”。

[处理 Install.wim 映像内的文件，结束。](#)

4. 语言包

- 自动安装语言包：获取“组件：映像中已安装的所有包”后进行匹配，匹配到对应的名称后，再安装本地对应的语言包文件，查看报告“[语言安装包适用于 Install.wim](#)”。
- 添加语言时，须对应不同的架构版本，未对应时，添加过程中报错等提示。

4.1. 语言包：添加

- Install.Instl.lang.ps1
 - [\Expand\Install\Install.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/Install/Install.Instl.lang.ps1

- 复制代码

```
$Mount = "D:\OS_2022_Custom\Install\Install\Mount"  
  
$Sources = "D:\OS_2022_Custom\Install\Install\Language\Add\zh-CN"
```

```
$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\Microsoft-Windows-LanguageFeatures-Fonts-Hans-
Package~31bf3856ad364e35~amd64~~.cab"

$Language_List = @(

    @{ Match = "*Server-LanguagePack-Package*"; File = "Microsoft-Windows-Server-Language-Pack_x64_zh-CN.cab"; }

    @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-zh-CN-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-zh-CN-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-zh-CN-Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-zh-CN-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-CN-
Package~31bf3856ad364e35~amd64~~.cab"; }

    @{ Match = "*MSPaint*amd64*"; File = "Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~amd64~zh-CN~.cab"; }

    @{ Match = "*MSPaint*wow64*"; File = "Microsoft-Windows-MSPaint-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab"; }

    @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~.cab"; }

    @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab"; }

    @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-
CN~.cab"; }

    @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-
CN~.cab"; }

    @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~zh-
CN~.cab"; }

    @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-
CN~.cab"; }

    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~.cab"; }

    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab"; }

    @{ Match = "*Client*LanguagePack*zh-TW*"; File = "Microsoft-Windows-InternationalFeatures-Taiwan-
Package~31bf3856ad364e35~amd64~~.cab"; }

)

ForEach ($Rule in $Language_List) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "$($Rule.Match)*") {
```

```
Write-host " Component name: " -NoNewline

Write-host $Component -ForegroundColor Green

Write-host " Language pack file: " -NoNewline

Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

Write-Host " Installing ".PadRight(22) -NoNewline

try{

    Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

    Write-host "Finish" -ForegroundColor Green

    break

} catch {

    Write-host "Failed" -ForegroundColor Red

}

}

}

}
```

4.2. 组件：映像中已安装的所有包

4.2.1. 查看

```
Get-WindowsPackage -Path "D:\OS_2022_Custom\Install\Install\Mount" | Out-GridView
```

4.2.2. 导出到 Csv

```
$SaveTo = "D:\OS_2022_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"

Get-WindowsPackage -Path "D:\OS_2022_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

5. 累积更新

5.1. 下载

查阅“[Windows Server 2022 更新历史](#)”，例如安装累积更新：[KB5030216](#)

前往下载页面：<https://www.catalog.update.microsoft.com/Search.aspx?q=Kb5030216> 或 “[直连下载](#)”（无法下载时请进入下载页面），保存到：

[D:\OS_2022_Custom\Install\Install\Update\windows10.0-kb5030216-x64_cbe587155f9818548b75f65d5cd41d341ed2fc61.msu](#)

5.2. 添加

```
$KBPath = "D:\OS_2022_Custom\Install\Install\Update\windows10.0-kb5030216-  
x64_cbe587155f9818548b75f65d5cd41d341ed2fc61.msu"  
  
Add-WindowsPackage -Path "D:\OS_2022_Custom\Install\Install\Mount" -PackagePath $KBPath
```

5.3. 固化更新

固化后不可卸载，固化时将清理恢复映像并重置任何被取代的组件的基础。

```
Dism /Image:"D:\OS_2022_Custom\Install\Install\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

5.3.1. 固化更新后清理组件

```
$Mount = "D:\OS_2022_Custom\Install\Install\Mount"  
  
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {  
  
    if ($_.PackageState -eq "Superseded") {  
  
        Write-Host " $(($_.PackageName)) -ForegroundColor Green  
  
        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null  
  
    }  
  
}
```

6. 部署引擎：添加

- 了解“[部署引擎](#)”，如果添加到 ISO 安装介质，可跳过添加到已挂载。
- 如果添加部署引擎到已挂载里，请继续在当前位置执行下一步。

7. 健康

保存前应检查是否损坏，健康状态异常时，中止保存

```
Repair-WindowsImage -Path "D:\OS_2022_Custom\Install\Install\Mount" -ScanHealth
```

8. 替换 WinRE.wim

已批量替换 Install.wim 里的所有索引号里的 WinRE.wim 请跳过该步骤。

```
$WinRE = "D:\OS_2022_Custom\Install\Install\Update\Winlib\WinRE.wim"  
  
$CopyTo = "D:\OS_2022_Custom\Install\Install\Mount\Windows\System32\Recovery"  
  
Copy-Item -Path $WinRE -Destination $CopyTo -Force
```

9. 保存映像

```
Save-WindowsImage -Path "D:\OS_2022_Custom\Install\Install\Mount"
```

10. 卸载映像

关闭所有可能正在访问映像中文件的应用程序，包括文件资源管理器。

```
Dismount-WindowsImage -Path "D:\OS_2022_Custom\Install\Install\Mount" -Discard
```

循环操作区域，结束。

11. 如何批量替换 Install.wim 里的所有索引号里的 WinRE.wim

11.1. 获取 WimLib

前往 <https://wimlib.net> 官方网站后，选择不同的版本：arm64, x64, x86，下载完成后解压到：D:\Wimlib

11.2. 如何在 Install.wim 里提取和更新 WinRE.wim

11.2.1. 从 Install.wim 里提取 WinRE.wim 文件 Install.wim

- Install.WinRE.Extract.ps1
 - [\Expand\Install\Install.WinRE.Extract.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/Install/Install.WinRE.Extract.ps1

- 复制代码

```
$Arguments = @(
    "extract",
    "D:\OS_2022\sources\install.wim", "1",
    "\Windows\System32\Recovery\Winre.wim",
    "--dest-dir=""D:\OS_2022_Custom\Install\Install\Update\Winlib""
)

New-Item -Path "D:\OS_2022_Custom\Install\Install\Update\Winlib" -ItemType Directory -ea SilentlyContinue

Start-Process -FilePath "d:\wimlib\wimlib-imagex.exe" -ArgumentList $Arguments -wait -nonewwindow
```

11.2.2. 获取 Install.wim 所有索引号后并替换旧的 WinRE.wim

- Install.WinRE.Replace.wim.ps1
 - [\Expand\Install\Install.WinRE.Replace.wim.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/Install/Install.WinRE.Replace.wim.ps1

- 复制代码

```
Get-WindowsImage -ImagePath "D:\OS_2022\sources\install.wim" -ErrorAction SilentlyContinue | ForEach-Object {  
  
    Write-Host "  Image name: " -NoNewline; Write-Host $_.ImageName -ForegroundColor Yellow  
  
    Write-Host "  The index number: " -NoNewline; Write-Host $_.ImageIndex -ForegroundColor Yellow  
  
    Write-Host "`n  Replacement "  
  
    $Arguments = @(  
  
        "update",  
  
        "D:\OS_2022\sources\install.wim", $_.ImageIndex,  
  
        "--command="""add 'D:\OS_2022_Custom\Install\Install\Update\Winlib\WinRE.wim'  
        '\Windows\System32\Recovery\WinRe.wim'""""  
  
    )  
  
    Start-Process -FilePath "d:\wimlib\wimlib-imageex.exe" -ArgumentList $Arguments -wait -nonewwindow  
  
    Write-Host "  Finish`n" -ForegroundColor Green  
  
}
```

12. 重建 Install.wim 后可缩小文件大小

12.1. Install.Rebuild.wim.ps1

- o [\Expand\Install\Install.Rebuild.wim.ps1](#)
- o https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/Install/Install.Rebuild.wim.ps1

• 复制代码

```
$InstallWim = "D:\OS_2022\sources\install.wim"  
  
Get-WindowsImage -ImagePath $InstallWim -ErrorAction SilentlyContinue | ForEach-Object {  
  
    Write-Host "  Image name: " -NoNewline  
  
    Write-Host $_.ImageName -ForegroundColor Yellow  
  
    Write-Host "  The index number: " -NoNewline  
  
    Write-Host $_.ImageIndex -ForegroundColor Yellow  
  
    Write-Host "`n  Rebuild".PadRight(28) -NoNewline  
  
    Export-WindowsImage -SourceImagePath $InstallWim -SourceIndex $_.ImageIndex -DestinationImagePath "$($InstallWim).New" -  
    CompressionType max | Out-Null  
  
    Write-Host "Finish`n" -ForegroundColor Green  
  
}  
  
if (Test-Path "$($InstallWim).New" -PathType Leaf) {  
  
    Remove-Item -Path $InstallWim  
  
    Move-Item -Path "$($InstallWim).New" -Destination $InstallWim  
  
    Write-Host "Finish" -ForegroundColor Green  
  
}
```

```
} else {  
  
    Write-host "Failed" -ForegroundColor Red  
  
}
```

III 自定义封装：boot.wim

1. 查看 Boot.wim 文件信息

映像名称、映像描述、映像大小、架构、版本、索引号等；

```
$ViewFile = "D:\OS_2022\Sources\Boot.wim"  
  
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

2. 指定挂载 Boot.wim 路径

```
New-Item -Path "D:\OS_2022_Custom\Boot\Boot\Mount" -ItemType directory -ea SilentlyContinue
```

3. 开始挂载 Boot.wim

默认索引号：2

```
Mount-WindowsImage -ImagePath "D:\OS_2022\sources\boot.wim" -Index "2" -Path "D:\OS_2022_Custom\Boot\Boot\Mount"
```

4. 语言包

- 自动安装语言包：获取“组件：映像中已安装的所有包”后进行匹配，匹配到对应的名称后，再安装本地对应的语言包文件，查看报告“[语言安装包适用于 Boot.wim](#)”。
- 添加语言时，须对应不同的架构版本，未对应时，添加过程中报错等提示。

4.1. 语言包：添加

- Boot.Instl.lang.ps1
 - [\Expand\Boot\Boot.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/Boot/Boot.Instl.lang.ps1

- 复制代码

```
$Mount = "D:\OS_2022_Custom\Boot\Boot\Mount"  
  
$Sources = "D:\OS_2022_Custom\Boot\Boot\Language\Add\zh-CN"  
  
$Initl_install_Language_Component = @()  
  
Get-WindowsPackage -Path $Mount | ForEach-Object {  
  
    $Initl_install_Language_Component += $_.PackageName
```

```

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language = @(

    @{ Match = "*WinPE*Setup*Server_zh*Package*"; File = "WINPE-SETUP-Server_zh-CN.CAB"; }

    @{ Match = "*WinPE*Setup*Package*"; File = "WinPE-Setup_zh-CN.cab"; }

    @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

    @{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

    @{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

    @{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

    @{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

    @{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

    @{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

    @{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

    @{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

    @{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }

    @{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

    @{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host " $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*") {

            Write-host " Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host " Language file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host " Installing ".PadRight(22) -NoNewline

            try{

                Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

            }

        }

    }

}

```



```
        break
    }
}
}
```

4.2. 组件：映像中已安装的所有包

4.2.1. 查看

```
Get-WindowsPackage -Path "D:\OS_2022_Custom\Boot\Boot\Mount" | Out-GridView
```

4.2.2. 导出到 Csv

```
$SaveTo = "D:\OS_2022_Custom\Boot\Boot\Report.${Get-Date -Format "yyyyMMddHHmmss"}.csv"

Get-WindowsPackage -Path "D:\OS_2022_Custom\Boot\Boot\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

4.3. 语言包：同步到 ISO 安装程序

```
Copy-Item -Path "D:\OS_2022_Custom\Boot\Boot\Mount\sources\zh-CN" -Destination "D:\OS_2022\sources\zh-CN" -Recurse -Force
```

4.4. 重新生成 Lang.ini

重新生成后，可调整“安装界面”，选择“语言”时的顺序，打开 lang.ini，默认首选值 = 3，非默认值 = 2。

4.4.1. 重新生成已挂载目录 lang.ini

重新生成的 Lang.ini 文件位置：[D:\OS_2022_Custom\Boot\Boot\Mount\Sources\lang.ini](#)

```
Dism /image:"D:\OS_2022_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_2022_Custom\Boot\Boot\Mount"
```

4.4.2. 重新生成 lang.ini 后，同步到安装程序

重新生成的 Lang.ini 文件位置：[D:\OS_2022\Sources\lang.ini](#)

```
Dism /image:"D:\OS_2022_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_2022"
```

5. 保存映像

```
Save-WindowsImage -Path "D:\OS_2022_Custom\Boot\Boot\Mount"
```

6. 卸载映像

关闭所有可能正在访问映像中文件的应用程序，包括文件资源管理器。

Dismount-WindowsImage -Path "D:\OS_2022_Custom\Boot\Boot\Mount" -Discard

IV 部署引擎

- 了解“自动添加 Windows 系统已安装的语言”，学习：<https://github.com/ilikeyi/Multilingual>，如何下载：
 - 进入网站后，点击“代码”，“下载压缩包”，下载完成后得到 main.zip 压缩包文件。
 - 前往 <https://github.com/ilikeyi/Multilingual/releases> 下载页面，选择可用版本：1.1.1.1，选择下载源代码格式：zip，下载完成后得到 Multilingual-1.1.1.1.zip 压缩包文件；
- 将已下载的 main.zip 或 Multilingual-1.1.1.1.zip，解压到：D:\Multilingual-1.1.1.1，重命名：D:\Multilingual
- 学习“无人值守 Windows 安装参考”，通过无人值守来干预安装过程。

1. 添加方式

1.1. 添加到 ISO 安装介质

1.1.1. 无人值守

1.1.1.1. 添加到：[ISO]:\Autounattend.xml

引导 ISO 安装时，Autounattend.xml 干预 WinPE 安装程序。

复制 D:\Multilingual_Learn\Unattend\Mul.Unattend.xml 到 D:\OS_2022\Autounattend.xml

Copy-Item "D:\Multilingual_Learn\Unattend\Mul.Unattend.xml" -Destination "D:\OS_2022\Autounattend.xml" -Force

1.1.1.2. 添加到：[ISO]:\Sources\Unattend.xml

挂载或解压 ISO 时，运行 [ISO]:\Setup.exe 安装程序后，[ISO]:\Sources\Unattend.xml 将干预安装过程。

复制 D:\Multilingual_Learn\Unattend\Mul.Unattend.xml 到 D:\OS_2022\Sources\Unattend.xml

Copy-Item "D:\Multilingual_Learn\Unattend\Mul.Unattend.xml" -Destination "D:\OS_2022\Sources\Unattend.xml" -Force

1.1.1.3. 添加到：[ISO]:\sources\\$\OEM\$\\$\$\Panther\unattend.xml

安装过程中复制到系统盘里，复制到：{系统盘}:\Windows\Panther\unattend.xml

1.1.1.3.1. 创建 \$OEM\$ 路径

New-Item -Path "D:\OS_2022\sources\`\$OEM\$\`\$\$\Panther" -ItemType Directory

1.1.1.3.2. 复制

复制 D:\Multilingual\Learn\Unattend\Mul.Unattend.xml 到
D:\OS_2022\Sources\OEM\$\Panther\Unattend.xml

```
Copy-Item "D:\Multilingual\Learn\Unattend\Mul.Unattend.xml" -Destination  
"D:\OS_2022\sources\`$OEM$\`$$\Panther\Unattend.xml" -Force
```

1.1.2. 部署引擎：添加

添加“自动添加 Windows 系统已安装的语言”到 D:\OS_2022\sources\OEM\$\1\Yi\Engine 目录里。

1.1.2.1. 部署引擎：复制

复制 D:\Multilingual\Engine 到 D:\OS_2022\Sources\OEM\$\1\Yi\Engine

```
Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_2022\sources\`$OEM$\`$1\Yi\Engine" -Recurse -Force
```

1.1.2.2. 部署引擎：自定义部署标记

```
$Flag = @(

    "Is_Mark_Sync" # 允许全盘搜索并同步部署标记

    # 先决部署

    # "Auto_Update" # 允许自动更新

    # "Use_UTF8" # Beta 版： 使用 Unicode UTF-8 提供全球语言支持

    "Disable_Network_Location_Wizard" # 网络位置向导

    "Disable_Cleanup_Appx_Tasks" # Appx 清理维护任务

    "Disable_Cleanup_On_Demand_Language" # 阻止清理未使用的按需功能语言包

    "Disable_Cleanup_Unsed_Language" # 阻止清理未使用的语言包

    "Prerequisites_Reboot" # 重新启动计算机

    # 完成首次部署

    # "Popup_Engine" # 允许首次弹出部署引擎主界面

    # "Allow_First_Pre_Experience" # 允许首次预体验，按计划

    "Reset_Execution_Policy" # 恢复 PowerShell 执行策略：受限

    "Clear_Solutions" # 删除整个解决方案

    "Clear_Engine" # 删除部署引擎，保留其它

    # "First_Experience_Reboot" # 重新启动计算机
```

```
)

ForEach ($item in $Flag) {

    Write-host "  $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS_2022\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS_2022\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\$( $item )" -Encoding utf8 -ErrorAction SilentlyContinue

}

}
```

1.2. 添加到已挂载

通过“自定义封装：Install.wim”，执行“开始挂载 Install.wim”，挂载到：D:\OS_2022_Custom\Install\Install\Mount

1.2.1. 无人值守

复制 D:\Multilingual\Learn\Unattend\Mul.Unattend.xml 到 D:\OS_2022_Custom\Install\Install\Mount\Panther\Unattend.xml

```
Copy-Item "D:\Multilingual\Learn\Unattend\Mul.Unattend.xml" -Destination
"D:\OS_2022_Custom\Install\Install\Mount\Panther" -Force
```

1.2.2. 部署引擎

添加“自动添加 Windows 系统已安装的语言”到 D:\OS_2022_Custom\Install\Install\Mount\Yi\Engine 目录里。

1.2.2.1. 部署引擎：复制

复制 D:\Multilingual\Engine 到 D:\OS_2022_Custom\Install\Install\Mount\Yi\Engine

```
Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_2022_Custom\Install\Install\Mount\Yi\Engine" -Recurse -
Force
```

1.2.2.2. 部署引擎：自定义部署标记

```
$Flag = @(

    "Is_Mark_Sync" # 允许全盘搜索并同步部署标记

    # 先决部署

    # "Auto_Update" # 允许自动更新

    # "Use_UTF8" # Beta 版：使用 Unicode UTF-8 提供全球语言支持

    "Disable_Network_Location_Wizard" # 网络位置向导

    "Disable_Cleanup_Appx_Tasks" # Appx 清理维护任务
```

```
"Disable_Cleanup_On_Demand_Language" # 阻止清理未使用的按需功能语言包

"Disable_Cleanup_Unsed_Language" # 阻止清理未使用的语言包

"Prerequisites_Reboot" # 重新启动计算机

# 完成首次部署

# "Popup_Engine" # 允许首次弹出部署引擎主界面

# "Allow_First_Pre_Experience" # 允许首次预体验，按计划

"Reset_Execution_Policy" # 恢复 PowerShell 执行策略：受限

"Clear_Solutions" # 删除整个解决方案

"Clear_Engine" # 删除部署引擎，保留其它

# "First_Experience_Reboot" # 重新启动计算机

)

ForEach ($item in $Flag) {

    Write-host " $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS_2022_Custom\Install\Install\Mount\Yi\Engine\Deploy\Allow" -ItemType Directory -
    ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS_2022_Custom\Install\Install\Mount\Yi\Engine\Deploy\Allow\${$item}" -Encoding utf8 -
    ErrorAction SilentlyContinue

}
```

2. 部署引擎：进阶

2.1. 部署引擎：添加过程中

在复制部署引擎后，可添加部署标记来干预安装过程。

2.2. 无人值守方案

自定义无人值守时，以下文件存在时请同步修改：

- [D:\OS_2022\Autounattend.xml](#)
- [D:\OS_2022\Sources\Unattend.xml](#)
- [D:\OS_2022\sources\\\${OEM\\$\}\\\$\Panther\unattend.xml](#)
- [D:\OS_2022_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

2.2.1. 多语言或单语

多语言时，单语时，可互相切换，替换时，请替换文件里所有相同的。

2.2.1.1. 多语言

```
<UILanguage>%OSDUILanguage%</UILanguage>

<InputLocale>%OSDInputLocale%</InputLocale>

<SystemLocale>%OSDSystemLocale%</SystemLocale>

<UILanguage>%OSDUILanguage%</UILanguage>

<UILanguageFallback>%OSDUILanguageFallback%</UILanguageFallback>

<UserLocale>%OSDUserLocale%</UserLocale>
```

2.2.1.2. 单语

单语需指定区域，例如指定区域：zh-CN

```
<UILanguage>zh-CN</UILanguage>

<InputLocale>zh-CN</InputLocale>

<SystemLocale>zh-CN</SystemLocale>

<UILanguage>zh-CN</UILanguage>

<UILanguageFallback>zh-CN</UILanguageFallback>

<UserLocale>zh-CN</UserLocale>
```

2.2.2. 用户方案

默认使用自建用户 Administrator 并自动登录，可通过修改以下配置切换：自建、自定义用户。

2.2.2.1. 自建用户 Administrator

默认使用自建用户：Administrator 并自动登录，插入到 <OOBE> 和 </OOBE> 之间。

```
<UserAccounts>

  <LocalAccounts>

    <LocalAccount wcm:action="add">

      <Password>

        <Value></Value>

        <PlainText>true</PlainText>

      </Password>

      <Description>Administrator</Description>

      <DisplayName>Administrator</DisplayName>

      <Group>Administrators</Group>

      <Name>Administrator</Name>
```

```
</LocalAccount>

</LocalAccounts>

</UserAccounts>

<AutoLogon>

  <Password>

    <Value></Value>

    <PlainText>true</PlainText>

  </Password>

  <Enabled>true</Enabled>

  <Username>Administrator</Username>

</AutoLogon>
```

2.2.2.2. 自定义用户

设置自定义用户后，安装系统完成后，在 OOB 里，可选择本地、在线用户等设置。

2.2.2.2.1. 删除

用户名：从开始处删除 <UserAccounts> 到 </UserAccounts>

自动登录：从开始处删除 <AutoLogon> 到 </AutoLogon>

2.2.2.2.2. 替换

从开始处 <OOBE> 到 </OOBE>

```
<OOBE>

  <ProtectYourPC>3</ProtectYourPC>

  <HideEULAPage>true</HideEULAPage>

  <HideWirelessSetupInOOBE>true</HideWirelessSetupInOOBE>

</OOBE>
```

D. 生成 ISO

1. 下载 OScdimg

根据架构选择 Oscding 版本，下载后保存到：D:\，保存在其它路径请输入 OScding.exe 绝对路径；

1.1. x64

https://github.com/ilikeyi/solutions/raw/main/_Software/Oscding/amd64/oscdimg.exe

1.2. x86

https://github.com/ilikeyi/solutions/raw/main/_Software/Oscding/x86/oscdimg.exe

1.3. arm64

https://github.com/ilikeyi/solutions/raw/main/_Software/Oscding/arm64/oscdimg.exe

2. 使用 oscding 命令行生成一个 ISO 文件，保存到：D:\WS2022.iso

- ISO.ps1
 - \Expand\ISO.ps1
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.2022/Expand/ISO.ps1

- 复制代码

```
$Oscding = "D:\Oscding.exe"
```

```
$ISO = "D:\Win2022"
```

```
$Volume = "Win2022"
```

```
$SaveTo = "D:\Win2022.iso"
```

```
$Arguments = @("-m", "-o", "-u2", "-udfver102", "-l"("$Volume)""", "-bootdata:2#p0,e,b"("$ISO)\boot\etfsboot.com""#pEF,e,b"("$ISO)\efi\microsoft\boot\efisys.bin""", $ISO, $FileName)
```

```
Start-Process -FilePath $Oscding -ArgumentList $Arguments -wait -nonewwindow
```




此副本封装教程隶属于 Yi's Solutions 内容，学习更多：

- Yi 的官方网站 | <https://fengyi.tel/solutions>
- Github | <https://github.com/ilikeyi/solutions>

作者：Yi

邮箱：775159955@qq.com, ilikeyi@outlook.com

文档版本：1.2

文档模型：精简版

更新日期：2024 - 8

建议或反馈：<https://github.com/ilikeyi/solutions/issues>