



MICROSOFT WINDOWS 11 22H2

PACKAGING TUTORIAL: Different system versions have different packaging methods. The packaging process includes: "Language pack: add, associate, delete", "Drive: add, delete", "Cumulative update: add, delete", "InBox Apps: add, Update, mark" etc.

There are many hidden stories hidden behind this. If you want to unlock these, are you ready to start trying to encapsulate them?

Summary

| | |
|-----------|----------------|
| Chapter 1 | Encapsulation |
| Chapter 2 | Report |
| Chapter 3 | Common problem |
| Chapter 4 | Known issues |

Table of contents

| | | |
|------------|--|---------|
| Chapter 1 | Encapsulation | Page 6 |
| A. | Prerequisites | Page 6 |
| II | Running operating system | Page 6 |
| III | ISO tools | Page 6 |
| IV | Requirements | Page 6 |
| 1. | System installation package | Page 6 |
| 2. | Language pack | Page 8 |
| 2.1. | Learn | Page 8 |
| 2.2. | Language pack: Download | Page 10 |
| 2.3. | Language pack: Fixed | Page10 |
| 3. | InBox Apps | Page 11 |
| V | Windows Security | Page 11 |
| VI | Command line | Page 12 |
| B. | Language Pack: Extract | Page 12 |
| II | Language pack: Ready | Page 12 |
| III | Language pack: Scheme | Page 12 |
| IV | Execute the extract command | Page 12 |
| C. | Custom encapsulation | Page 18 |
| II | Custom encapsulation Install.wim | Page 18 |
| 1. | View Install.wim details | Page 18 |
| 2. | Specify the path to mount Install.wim | Page 18 |
| 3. | Start mounting Install.wim | Page 18 |
| 3.1. | Custom encapsulation WinRE.wim | Page 18 |
| 3.1.1. | View WinRE.wim details | Page 19 |
| 3.1.2. | Specify the path to mount WinRE.wim | Page 19 |
| 3.1.3. | Start mounting WinRE.wim | Page 19 |
| 3.1.4. | Language pack: WinRE | Page 19 |
| 3.1.4.1. | Language pack: add | Page 19 |
| 3.1.4.2. | Offline image language: change | Page 21 |
| 3.1.4.2.1. | Change default language, regional settings, and other international settings | Page 21 |

| | | |
|------------|--|---------|
| 3.1.4.2.2. | View available language settings | Page 21 |
| 3.1.4.3. | Language packs: Removed | Page 21 |
| 3.1.4.4. | Components: All packages installed in the image | Page 23 |
| 3.1.5. | Cumulative updates | Page 23 |
| 3.1.5.1. | Add | Page 24 |
| 3.1.5.2. | Delete | Page 24 |
| 3.1.5.3. | Solid update | Page 24 |
| 3.1.5.3.1. | Clean components after curing and updating | Page 24 |
| 3.1.6. | Drive | Page 24 |
| 3.1.7. | Save image: WinRE.wim | Page 24 |
| 3.1.8. | Unmount image: WinRE.wim | Page 24 |
| 3.1.9. | After rebuilding WinRE.wim, the file size can be reduced | Page 24 |
| 3.1.10. | Backup WinRE.wim | Page 25 |
| 3.1.11. | Replace WinRE.wim within the Install.wim image | Page 25 |
| 4. | Language pack | Page 26 |
| 4.1. | Language pack: add | Page 26 |
| 4.2. | Offline image language: change | Page 31 |
| 4.2.1. | Change default language, regional settings, and other international settings | Page 32 |
| 4.2.2. | View available language settings | Page 32 |
| 4.3. | Language packs: Removed | Page 32 |
| 4.4. | Components: All packages installed in the image | Page 34 |
| 5. | InBox Apps | Page 35 |
| 5.1. | Learn | Page 35 |
| 5.2. | InBox Apps: Pre-install the application | Page 35 |
| 5.3. | InBox Apps: Installed | Page 37 |
| 5.4. | Remove all installed pre-applications | Page 37 |
| 5.5. | Region tag: Understanding | Page 37 |
| 5.6. | Region tag: | Page 38 |
| 5.7. | InBox Apps: Install | Page 41 |
| 5.8. | Region tag: delete | Page 50 |

| | | |
|--------|--|---------|
| 5.9. | InBox Apps: optimization | Page 51 |
| 6. | Cumulative updates | Page 51 |
| 6.1. | Initial version | Page 51 |
| 6.2. | Other Version | Page 52 |
| 6.3. | Solidify Updated | Page 53 |
| 6.3.1. | Clean components after curing and updating | Page 53 |
| 7. | Drive | Page 53 |
| 8. | Deployment engine: Add | Page 53 |
| 9. | Health | Page 53 |
| 10. | Replace WinRE.wim | Page 53 |
| 11. | Save image: Install.wim | Page 53 |
| 12. | Unmount image: Install.wim | Page 54 |
| 13. | How to batch replace WinRE.wim in all index numbers in Install.wim | Page 54 |
| 13.1. | Obtain WimLib | Page 54 |
| 13.2. | How to extract and update WinRE.wim in Install.wim | Page 54 |
| 14. | Rebuilding Install.wim reduces file size | Page 55 |
| III | Custom encapsulation boot.wim | Page 56 |
| 1. | View Boot.wim details | Page 56 |
| 2. | Specify the path to mount Boot.wim | Page 56 |
| 3. | Start mounting Boot.wim | Page 56 |
| 4. | Language pack: Boot | Page 56 |
| 4.1. | Language pack: Add | Page 56 |
| 4.2. | Offline image language: change | Page 57 |
| 4.2.1. | Change default language, regional settings, and other international settings | Page 57 |
| 4.2.2. | View available language settings | Page 58 |
| 4.3. | Language pack: Removed | Page 58 |
| 4.4. | Components: All packages installed in the image | Page 60 |
| 4.5. | Language: Repair | Page 60 |
| 4.6. | Language packs: sync to ISO installer | Page 61 |
| 4.7. | Regenerate Lang.ini | Page 61 |

| | | |
|-----------|---|---------|
| | 4.7.1. Regenerate the mounted directory lang.ini | Page 61 |
| | 4.7.2. After regenerating lang.ini, sync to the installer | Page 61 |
| | 5. Cumulative updates | Page 61 |
| | 5.1. Add | Page 61 |
| | 5.2. Delete | Page 61 |
| | 5.3. Solid update | Page 61 |
| | 5.3.1. Clean components after curing and updating | Page 62 |
| | 6. Drive | Page 62 |
| | 7. Other | Page 62 |
| | 7.1. Bypass TPM check during installation | Page 62 |
| | 8. Save image: Boot.wim | Page 63 |
| | 9. Unmount image: Boot.wim | Page 63 |
| IV | Deployment engine | Page 63 |
| | 1. Add method | Page 63 |
| | 2. Deployment Engine: Advanced | Page 66 |
| D. | ISO | Page 68 |
| II | Generate ISO | Page 68 |
| III | Bypass TPM installation check | Page 69 |
| Chapter 2 | Report | Page 69 |
| | II Reports: Different versions | Page 69 |
| | III Report: Language installation packages apply to Install.wim | Page 71 |
| | IV Report: Language installation packages apply to WinRE.wim | Page 73 |
| | V Report: Language installation packages apply to Boot.wim | Page 74 |
| Chapter 3 | Common problem | Page 75 |
| | II Clean all mounts to | Page 75 |
| | III Fix the problem of abnormal mounting | Page 75 |
| | IV Clean directories | Page 75 |
| Chapter 4 | Known issues | Page 76 |

A. Prerequisites

II Running operating system

When the operating system you are running is Windows 10 or lower than Windows 11 24H2, in some cases, using the DISM command to create a higher version image will cause some unknown problems. For example, when running the DISM command in the Windows 10 operating system to process the Windows Server 2025 offline image, you may receive an error message during the packaging process: "This application cannot run on your computer." Solution:

1. Upgrade the running operating system or reinstall to a higher version (recommended);
2. Upgrade or install a new version of ADK or PowerShell (not recommended)
 - 2.1. You can try to upgrade to the latest PowerShell 7 or higher version;
 - 2.2. After installing the latest version of ADK and replacing the DISM command, the problem of low DISM version can be solved. However, the command line mainly used by the packaging script is the PowerShell command line, so it is not recommended that you use the above method. The best method is to upgrade the running operating system or reinstall to a higher version.

II ISO tools

Use a software that can edit ISO files, such as: [PowerISO](#), [DAEMON Tools](#), [ISO Workshop](#);

III Requirements

1. System installation package

Keywords: [iteration](#), [cross-version](#), [major version](#), [cumulative update](#), [initial release](#)

1.1. illustrate

- 1.1.1. Please remake the image when each version is updated, for example, when crossing from 21H1 to 22H2, avoid other compatibility problems, and do not make the image based on the old image;
- 1.1.2. The regulation has been clearly communicated to packagers in various forms by some OEMs, and direct upgrades from iterative versions are not allowed;
- 1.1.3. Please use "Initial Version" and "Developer Edition" for production. There was a brief appearance in the official Microsoft documentation that the initial version must be used in production, but this sentence was later deleted in the official documentation;
- 1.1.4. After installing the language pack, you must re-add the cumulative update (the same version number), and if you do not add the cumulative update, problems such as "garbled characters" and "interface flashback" will occur.
- 1.1.5. Evolutionary process: Windows 11 22H2, Build 22621.382 + KB5027303 = OS Build 22621.1928

1.2. Prepare to download the initial or developer version

1.2.1. x64

- 1.2.1.1. [en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08ce3.iso](#)
- 1.2.1.2. [en-us_windows_11_consumer_editions_version_22h2_x64_dvd_e630fafd.iso](#)
- 1.2.1.3. [en-us_windows_11_iot_enterprise_version_22h2_x64_dvd_eb39bf70.iso](#)

- 1.2.2. arm64
 - 1.2.2.1. [en-us_windows_11_iot_enterprise_version_22h2_arm64_dvd_f09f5d29.iso](#)

1.3. After the sample download [en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08ce3.iso](#), Unzip to: [D:\en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08c](#)

Note: Before decompressing to disk D, you should check whether it is a ReFS partition. If it is a ReFS partition, some commands will fail. Solution: Please use a disk partition in NTFS format.

1.4. After decompression is complete, change the directory [en-us_windows_11_business_editions_version_22h2_x64_dvd_17a08c](#) change to [D:\OS_11](#)

1.5. All scripts and all paths are set to [D:\OS_11](#) as the image source.

1.6. Installation configuration

1.6.1. Learn: [Windows Setup Edition Configuration and Product ID Files \(Ei.cfg and PID.txt \)](#)

1.6.2. Known issues

1.6.2.1. When there is no Ei.cfg, ISO boot installation will report an error when selecting certain versions, prompting:
Windows cannot find the Microsoft Software License terms. Make sure the installation sources are valid and restart the installation.

1.6.2.2. How to solve it? Add ei.cfg to D:\OS_11\Sources and create ei.cfg:

```
@"  
[Channel]  
volume  
  
[VL]  
1  
  
"@ | Out-File -FilePath "D:\OS_11\sources\EI.CFG" -Encoding Ascii
```

1.7. Report

Check the installed image package: language packs, associated language pack components, pre-installed InBox Apps applications and other detailed information. After downloading the report, use Excel software to open the .xlsx.

1.7.1. Report: Overview

Contains: ISO system installation package, image version, region, region association, associated language pack components, etc.

[Report.Overview.xlsx](#)

1.7.2. Report: Complete

Inclusion: ISO system installation package, image version, region, region association, associated language pack components, installed InBox Apps pre-installed applications, etc.

[en-us](#), [ar-sa](#), [bg-bg](#), [cs-cz](#), [da-dk](#), [de-de](#), [el-gr](#), [en-gb](#), [es-es](#), [es-mx](#), [et-ee](#), [fi-fi](#), [fr-ca](#), [fr-fr](#), [he-il](#), [hr-hr](#), [hu-hu](#), [it-it](#), [ja-jp](#), [ko-kr](#), [lt-lt](#), [lv-lv](#), [nb-no](#), [nl-nl](#), [pl-pl](#), [pt-br](#), [pt-pt](#), [ro-ro](#), [ru-ru](#), [sk-sk](#), [sl-si](#), [sr-latn-rs](#), [sv-se](#), [th-th](#), [tr-tr](#), [uk-ua](#), [zh-cn](#), [zh-tw](#)

2. Language pack

2.1. Learn

As you read, please understand the important highlights of "Blue".

2.1.1. [Languages overview](#)

2.1.2. [Add languages to a Windows 11 image](#)

2.1.3. [Language and region Features on Demand \(FOD\)](#)

2.1.3.1. Fonts

- When adding a language pack, when the corresponding region is triggered, the required font functions need to be added, download "[List of all available language FODs](#)" learn more.
- In "Language Pack: Extract", the automatic recognition function has been added, and you can understand the functions: [Function Match_Required_Fonts](#)

2.1.3.2. Regional association

What are regional connections?

- When the image language is only in English, after adding the [zh-HK](#) language pack, the image language will not be added. You should install [zh-TW](#) first, and then install [zh-HK](#) to obtain the corresponding association.

Known regional associations:

2.1.3.2.1. Region: [ar-sa](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.1.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.1.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.2. Region: [bg-bg](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.2.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.2.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.3. Region: [da-dk](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.3.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.3.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.4. Region: [el-gr](#), Optional associated areas: [en-US](#), associated installation package:

2.1.3.2.4.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab

- 2.1.3.2.4.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.5. Region: **fr-ca**, Optional associated areas: **en-US**, **fr-fr**, associated installation package:
 - 2.1.3.2.5.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab
 - 2.1.3.2.5.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab
 - 2.1.3.2.5.3. Microsoft-Windows-LanguageFeatures-Basic-fr-fr-
Package~31bf3856ad364e35~amd64~~.cab
 - 2.1.3.2.5.4. Microsoft-Windows-LanguageFeatures-Handwriting-fi-fi-
Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.6. Region: **he-il**, Optional associated areas: **en-US**, associated installation package:
 - 2.1.3.2.6.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab
 - 2.1.3.2.6.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.7. Region: **ru-ru**, Optional associated areas: **en-US**, associated installation package:
 - 2.1.3.2.7.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab
 - 2.1.3.2.7.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.8. Region: **th-th**, Optional associated areas: **en-US**, associated installation package:
 - 2.1.3.2.8.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab
 - 2.1.3.2.8.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.9. Region: **uk-ua**, Optional associated areas: **en-US**, associated installation package:
 - 2.1.3.2.9.1. Microsoft-Windows-LanguageFeatures-Basic-es-us-
Package~31bf3856ad364e35~amd64~~.cab
 - 2.1.3.2.9.2. Microsoft-Windows-LanguageFeatures-OCR-en-us-
Package~31bf3856ad364e35~amd64~~.cab
- 2.1.3.2.10. Region: **zh-TW** , Optional associated areas: **zh-HK**, associated installation package:
 - 2.1.3.2.10.1. Microsoft-Windows-LanguageFeatures-Basic-zh-hk-
Package~31bf3856ad364e35~amd64~~.cab
 - 2.1.3.2.10.2. Microsoft-Windows-LanguageFeatures-Speech-zh-hk-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.2.10.3. Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-hk-
Package~31bf3856ad364e35~amd64~~.cab

2.1.3.3. Other region-specific requirements

When triggering a known area, a specific "package" needs to be added.

2.1.3.3.1. Region: zh-TW

Package: Microsoft-Windows-InternationalFeatures-Taiwan-
Package~31bf3856ad364e35~amd64~~.cab

Description: Supplemental support for Taiwan date formatting requirements. Package will be
provided to customers located in Taiwan.

Recommendation: Preinstall only on devices shipping to the Taiwan market. Not installing this
capability on devices causes any API calls to that use the Taiwan calendar to fail.

THERE IS CONTROVERSY:

- During the test, it was found that this package was not installed in the original image of Microsoft's
official original Windows 11. However, there are known issues in the recommended items. In the end, it is
consistent with the official Microsoft original version, and the packager can freely choose to install it. or
not.

2.2. Language pack: Download

https://software-static.download.prss.microsoft.com/dbazure/988969d5-f34g-4e03-ac9d-1f9786c66749/22621.1.220506-1250.ni_release_amd64fre_CLIENT_LOF_PACKAGES_OEM.iso

2.3. Language pack: Fixed

2.3.1. Select any website and open:

2.3.1.1. <https://uupdump.net>

2.3.1.2. <https://uup.ee>

2.3.1.3. <https://osdump.com>

2.3.2. After opening, search for keywords: 22621.382, select from the search results: Windows 11, version 22H2 (22621.382)
amd64

2.3.3. After opening, select "All files";

2.3.4. Search the green part in the "All Files" page and download

2.3.4.1. Applies to: Install.wim:

2.3.4.1.1. MediaPlayer

2.3.4.2. Applies to: WinRE.wim, none yet

2.3.4.3. Applies to: Boot.wim, none yet

- 2.3.5. After downloading all the files, scroll to the bottom of the page, download and run "[Generate Rename Script \(Windows\)](#)"
- 2.3.6. Use ISO editing software, edit [22621.1.220506-1250.ni_release_amd64fre_CLIENT_LOF_PACKAGES_OEM.iso](#), and add the downloaded file to the [\[ISO\]:\LanguagesAndOptionalFeatures](#) directory;

3. InBox Apps

- 3.1. Download: https://software-static.download.prss.microsoft.com/dbazure/888969d5-f34g-4e03-ac9d-1f9786c66749/22621.1778.230511-2102.ni_release_svc_prod3_amd64fre_InboxApps.iso
- 3.2. Download: https://software-static.download.prss.microsoft.com/dbazure/988969d5-f34g-4e03-ac9d-1f9786c66749/22621.1.220506-1250.ni_release_amd64fre_InboxApps.iso finally, Extract:
 - 3.2.1. Microsoft.HEVCVideoExtension
 - 3.2.1.1. [Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.arm64.appx](#)
 - 3.2.1.2. [Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.arm64.xml](#)
 - 3.2.1.3. [Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.appx](#)
 - 3.2.1.4. [Microsoft.HEVCVideoExtension_8wekyb3d8bbwe.x64.xml](#)
- 3.3. Use the ISO editing tool to edit [22621.1778.230511-2102.ni_release_svc_prod3_amd64fre_InboxApps.iso](#) and add the extracted files to the [\[ISO\]:\packages](#) directory;

IV Windows Security

- When processing the encapsulation task, a large number of temporary files will be generated, and a large number of installation files will be released when installing the application in InBox Apps;
- Turning on Windows Security scans files and takes up a lot of CPU.
- In test: 1 hour and 22 minutes before shutdown, 20 minutes after shutdown.

How to close:

With the command line in green, hold down the Windows key and press R to launch Run.

1. Open Windows Security or run: [windowsdefender:](#)
2. Select "Virus & Threat Protection" or Run: [windowsdefender://threat](#)
3. Find "Virus & Threat Protection Settings", click "Manage Settings" or Run: [windowsdefender://threatsettings](#), we recommend that you turn off some features:
 - 3.1. Real-time protection
 - 3.2. Cloud=delivered protection
 - 3.3. Automatic sample submission
 - 3.4. Tamper Protection
4. When you're not encapsulated, we recommend that you turn on Windows Security.

V Command line

1. Optional "Terminal" or "PowerShell ISE", if "Terminal" is not installed, please go to: <https://github.com/microsoft/terminal/releases> After downloading;
2. Open "Terminal" or "PowerShell ISE" as administrator, it is recommended to set the PowerShell execution policy: bypass, PS command line:

`Set-ExecutionPolicy -ExecutionPolicy Bypass -Force`
3. In this article, PS command line, green part, please copy it, paste it into the "Terminal" dialog box, press Enter and start running;
4. When there is `.ps1`, right-click the file and select Run with PowerShell, or copy the path and paste it into Terminal to run, the path with a colon, add the & character in the command line, example: `& "D:\YiSolutions_Encapsulation_SIP.ps1"`

B. Language Pack: Extract

II Language pack: Ready

Mount [22621.1.220506-1250.ni_release_amd64fre_CLIENT_LOF_PACKAGES_OEM.iso](#) or unzipped to any location;

III Language pack: Scheme

1. Add
 - 1.1. Language name: [Simplified Chinese - China](#), Region: [zh-CN](#), Scope of application: [Install.Wim](#), [Boot.Wim](#), [WinRE.Wim](#)
2. Delete
 - 2.1. Language name: [English - United States](#), Region: [en-US](#), Scope of application: [Install.Wim](#), [Boot.Wim](#), [WinRE.Wim](#)

IV Execute the extract command

- [Auto](#) = automatically search all local disks, default;
- Customize the path, for example, specify the E drive: `$ISO = "E:\\"`
- Extract.ps1
 - [\Expand\Extract.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.11/22H2/Expand/Extract.ps1

- Copy the code

```
$ISO = "Auto"
```

```
$SaveTo = "D:\OS_11_Custom"
```

```
$Extract_Language_Pack = @(
```

```
    @{ Tag = "zh-CN"; Act = "Add"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }
```

```
    @{ Tag = "en-US"; Act = "Del"; Scope = @( "Install\Install"; "Install\WinRE"; "Boot\Boot" ) }
```

```
)
```

```
Function Extract_Language
```

```

{

    param( $Act, $NewLang, $Expand )

    Function Match_Required_Fonts

    {

        param( $Lang )

        $Fonts = @(

            @{ Match = @("as", "ar-SA", "ar", "ar-AE", "ar-BH", "ar-DJ", "ar-DZ", "ar-EG", "ar-ER", "ar-IL", "ar-IQ", "ar-JO", "ar-KM", "ar-KW", "ar-LB", "ar-LY",
            "ar-MA", "ar-MR", "ar-OM", "ar-PS", "ar-QA", "ar-SD", "ar-SO", "ar-SS", "ar-SY", "ar-TD", "ar-TN", "ar-YE", "arz-Arab", "ckb-Arab", "fa", "fa-AF", "fa-IR",
            "glk-Arab", "ha-Arab", "ks-Arab", "ks-Arab-IN", "ku-Arab", "ku-Arab-IQ", "mzn-Arab", "pa-Arab", "pa-Arab-PK", "pnb-Arab", "prs", "prs-AF", "prs-Arab",
            "ps", "ps-AF", "sd-Arab", "sd-Arab-PK", "tk-Arab", "ug", "ug-Arab", "ug-CN", "ur", "ur-IN", "ur-PK", "uz-Arab", "uz-Arab-AF"); Name = "Arab"; }

            @{ Match = @("bn-IN", "as-IN", "bn", "bn-BD", "bpy-Beng"); Name = "Beng"; }

            @{ Match = @("da-dk", "iu-Cans", "iu-Cans-CA"); Name = "Cans"; }

            @{ Match = @("chr-Cher-US", "chr-Cher"); Name = "Cher"; }

            @{ Match = @("hi-IN", "bh-Deva", "brx", "brx-Deva", "brx-IN", "hi", "ks-Deva", "mai", "mr", "mr-IN", "ne", "ne-IN", "ne-NP", "new-Deva", "pi-Deva",
            "sa", "sa-Deva", "sa-IN"); Name = "Deva"; }

            @{ Match = @("am", "am-ET", "byn", "byn-ER", "byn-Ethi", "ti", "ti-ER", "ti-ET", "tig", "tig-ER", "tig-Ethi", "ve-Ethi", "wal", "wal-ET", "wal-Ethi");
            Name = "Ethi"; }

            @{ Match = @("gu", "gu-IN"); Name = "Gujr"; }

            @{ Match = @("pa", "pa-IN", "pa-Guru"); Name = "Guru"; }

            @{ Match = @("zh-CN", "cmn-Hans", "gan-Hans", "hak-Hans", "wuu-Hans", "yue-Hans", "zh-gan-Hans", "zh-hak-Hans", "zh-Hans", "zh-SG", "zh-
            wuu-Hans", "zh-yue-Hans"); Name = "Hans"; }

            @{ Match = @("zh-TW", "cmn-Hant", "hak-Hant", "lzh-Hant", "zh-hak-Hant", "zh-Hant", "zh-HK", "zh-lzh-Hant", "zh-MO", "zh-yue-Hant"); Name =
            "Hant"; }

            @{ Match = @("he", "he-IL", "yi"); Name = "Hebr"; }

            @{ Match = @("ja", "ja-JP"); Name = "Jpan"; }

            @{ Match = @("km", "km-KH"); Name = "Khmr"; }

            @{ Match = @("kn", "kn-IN"); Name = "Knda"; }

            @{ Match = @("ko", "ko-KR"); Name = "Kore"; }

            @{ Match = @("de-de", "lo", "lo-LA"); Name = "Lao"; }

            @{ Match = @("ml", "ml-IN"); Name = "Mlym"; }

            @{ Match = @("or", "or-IN"); Name = "Orya"; }

            @{ Match = @("si", "si-LK"); Name = "Sinh"; }

            @{ Match = @("tr-tr", "arc-Syrc", "syr", "syr-SY", "syr-Syrc"); Name = "Syrc"; }

            @{ Match = @("ta", "ta-IN", "ta-LK", "ta-MY", "ta-SG"); Name = "Taml"; }

            @{ Match = @("te", "te-IN"); Name = "Telu"; }

            @{ Match = @("th", "th-TH"); Name = "Thai"; }

        )
    }
}

```

```

ForEach ($item in $Fonts) {

    if (($item.Match) -Contains $Lang) {

        return $item.Name

    }

}

return "Not_matched"

}

Function Match_Other_Region_Specific_Requirements

{

    param( $Lang )

    $RegionSpecific = @(

        @{ Match = @"(zh-TW)"; Name = "Taiwan"; }

    )

    ForEach ($item in $RegionSpecific) {

        if (($item.Match) -Contains $Lang) {

            return $item.Name

        }

    }

    return "Skip_specific_packages"

}

Function Extract_Process

{

    param( $Package, $Name, $NewSaveTo )

    $NewSaveTo = "$($SaveTo)\$($NewSaveTo)\Language\$($Act)\$($NewLang)"

    New-Item -Path $NewSaveTo -ItemType Directory -ErrorAction SilentlyContinue | Out-Null

    if ($ISO -eq "Auto") {

        Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

            ForEach ($item in $Package) {

                $TempFilePath = Join-Path -Path $_.Root -ChildPath $item -ErrorAction SilentlyContinue

                if (Test-Path $TempFilePath -PathType Leaf) {

                    Write-host "`n Find: " -NoNewLine; Write-host $TempFilePath -ForegroundColor Green

                    Write-host " Copy to: " -NoNewLine; Write-host $NewSaveTo

                    Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

                }

            }

        }

    }

}

```

```

    }

}

} else {

    ForEach ($item in $Package) {

        $TempFilePath = Join-Path -Path $ISO -ChildPath $item -ErrorAction SilentlyContinue

        Write-host "`n  Find: " -NoNewline; Write-host $TempFilePath -ForegroundColor Green

        if (Test-Path $TempFilePath -PathType Leaf) {

            Write-host "    Copy to: " -NoNewLine; Write-host $NewSaveTo

            Copy-Item -Path $TempFilePath -Destination $NewSaveTo -Force

        } else {

            Write-host "    Not found"

        }

    }

}

Write-host "`n  Verify the language pack file"

ForEach ($item in $Package) {

    $Path = "$($NewSaveTo)\${[IO.Path]::GetFileName($item)}"

    if (Test-Path $Path -PathType Leaf) {

        Write-host "    Discover: " -NoNewLine; Write-host $Path -ForegroundColor Green

    } else {

        Write-host "    Not found: " -NoNewLine; Write-host $Path -ForegroundColor Red

    }

}

}

$AdvLanguage = @(

    @{

        Path = "Install\Install"

        Rule = @(

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Fonts-{DiyLang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-Client-Language-Pack_x64_{Lang}.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Basic-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Handwriting-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-OCR-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

            "LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-Speech-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

```



```

"LanguagesAndOptionalFeatures\Microsoft-Windows-LanguageFeatures-TextToSpeech-{Lang}-Package~31bf3856ad364e35~AMD64~~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-MediaPlayer-Package-AMD64-{Lang}.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-MediaPlayer-Package-wow64-{Lang}.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~AMD64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~{Lang}~.cab"

"LanguagesAndOptionalFeatures\Microsoft-Windows-InternationalFeatures-{Specific}-Package~31bf3856ad364e35~amd64~~.cab"

)

}

@{

    Path = "Install\WinRE"

    Rule = @(

        "Windows Preinstallation Environment\x64\WinPE_OCs\WinPE-FontSupport-{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\lp.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-securestartup_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-atbroker_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-audiocore_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-audiodrivers_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-enhancedstorage_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-narrator_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-scripting_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-speech-tts_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-srh_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-srt_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OCs\{Lang}\winpe-wds-tools_{Lang}.cab"

```

```

"Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-wmi_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-appxdeployment_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-appxpackaging_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-storagewmi_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-wifi_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-windowsupdate_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-rejuv_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-opcservices_{Lang}.cab"

"Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-hta_{Lang}.cab"

)

}

@{

    Path = "Boot\Boot"

    Rule = @(

        "Windows Preinstallation Environment\x64\WinPE_OC\WinPE-FontSupport-{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\lp.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\WinPE-Setup_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\WINPE-SETUP-CLIENT_{Lang}.CAB"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-securestartup_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-atbroker_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-audiocore_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-audiodrivers_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-enhancedstorage_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-narrator_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-scripting_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-speech-tts_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-srh_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-srt_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-wds-tools_{Lang}.cab"

        "Windows Preinstallation Environment\x64\WinPE_OC\s\{Lang}\winpe-wmi_{Lang}.cab"

    )

}

)

$NewFonts = Match_Required_Fonts -Lang $NewLang

```

```

$SpecificPackage = Match_Other_Region_Specific_Requirements -Lang $NewLang

Foreach ($item in $Expand) {

    $Language = @()

    Foreach ($itemList in $AdvLanguage) {

        if ($itemList.Path -eq $item) {

            Foreach ($PrintLang in $itemList.Rule) {

                $Language += "$($PrintLang)".Replace("{Lang}", $NewLang).Replace("{DiyLang}", $NewFonts).Replace("{Specific}", $SpecificPackage)

            }

            Extract_Process -NewSaveTo $itemList.Path -Package $Language -Name $item

        }

    }

}

Foreach ($item in $Extract_language_Pack) { Extract_Language -Act $item.Act -NewLang $item.Tag -Expand $item.Scope }

```

C. Custom encapsulation

II Custom encapsulation Install.wim

1. View Install.wim details

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS_11\Sources\Install.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

LOOP OPERATING AREA, START,

2. Specify the path to mount Install.wim

```
New-Item -Path "D:\OS_11_Custom\Install\Install\Mount" -ItemType directory -ea SilentlyContinue
```

3. Start mounting Install.wim

Default index number: 1

```
Mount-WindowsImage -ImagePath "D:\OS_11\sources\install.wim" -Index "1" -Path "D:\OS_11_Custom\Install\Install\Mount"
```

PROCESS FILES WITHIN THE INSTALL.WIM IMAGE, OPTIONALLY, START,

3.1. Custom encapsulation WinRE.wim

WARNING:

- WinRE.wim is a file within the Install.wim image;
- When Install.wim has multiple index numbers, only process any WinRE.wim;

- Synchronize to all index numbers to reduce the size of Install.wim, learn "[How to batch replace WinRE.wim in all index numbers in Install.wim](#)".

3.1.1. View WinRE.wim details

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index
$_.ImageIndex }
```

3.1.2. Specify the path to mount WinRE.wim

```
New-Item -Path "D:\OS_11_Custom\Install\WinRE\Mount" -ItemType directory -ea SilentlyContinue
```

3.1.3. Start mounting WinRE.wim

Default index number: 1

```
Mount-WindowsImage -ImagePath "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim" -
Index "1" -Path "D:\OS_11_Custom\Install\WinRE\Mount"
```

3.1.4. Language pack: WinRE

- Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for WinRE.wim](#)".
- When adding languages, different schema versions must be corresponded, and if not, errors are reported during the addition process.

3.1.4.1. Language pack: add

- WinRE.Instl.lang.ps1
 - [\Expand\Install\WinRE\WinRE.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/WinRE/WinRE.Instl.lang.ps1

- Copy the code

```
$Mount = "D:\OS_11_Custom\Install\WinRE\Mount"
```

```
$Sources = "D:\OS_11_Custom\Install\WinRE\Language\Add\zh-CN"
```

```
$Initl_install_Language_Component = @()
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component +=
$_.PackageName }
```

```
Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"
```

```
$Language_List = @(
```

```
@{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }
```

```

@{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }

@{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

@{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

@{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

@{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

@{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

@{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

@{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

@{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

@{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }

@{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

@{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

@{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_zh-CN.cab"; }

@{ Match = "*StorageWMI*"; File = "winpe-storagewmi_zh-CN.cab"; }

@{ Match = "*WiFi*"; File = "winpe-wifi_zh-CN.cab"; }

@{ Match = "*rejuv*"; File = "winpe-rejuv_zh-CN.cab"; }

@{ Match = "*opcservices*"; File = "winpe-opcservices_zh-CN.cab"; }

@{ Match = "*hta*"; File = "winpe-hta_zh-CN.cab"; }

@{ Match = "*windowsupdate*"; File = "winpe-windowsupdate_zh-CN.cab"; }

@{ Match = "*appxdeployment*"; File = "winpe-appxdeployment_zh-CN.cab"; }

)

ForEach ($Rule in $Language_List) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component){

        if ($Component -like "$($Rule.Match)*") {

            Write-host "  Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline; Write-host "$($Sources)\$($Rule.File)" -
ForegroundColor Green

            Write-Host "  Installing ".PadRight(22) -NoNewline

            try{

                Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

            }

```

```

        break
    }
}
}
}

```

3.1.4.2. Offline image language: change

3.1.4.2.1. Change default language, regional settings, and other international settings

Region: zh-CN

```
Dism /Image:"D:\OS_11_Custom\Install\WinRE\Mount" /Set-AllIntl:"zh-CN"
```

3.1.4.2.2. View available language settings

```
Dism /Image:"D:\OS_11_Custom\Install\WinRE\Mount" /Get-Intl
```

3.1.4.3. Language packs: Removed

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "English - United States" in reverse, the Region tag: en-US, you need to extract the language pack in advance
- WinRE.Del.Specified.lang.Tag.ps1
 - \Expand\Install\WinRE\WinRE.Del.Specified.lang.Tag.ps1
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.11/22H2/Expand/Install/WinRE/WinRE.Del.Specified.lang.Tag.ps1

- Copy the code

```
$Lang = "en-US"
```

```
$Mount = "D:\OS_11_Custom\Install\WinRE\Mount"
```

```
$Sources = "D:\OS_11_Custom\Install\WinRE\Language\Del\en-US"
```

```
$Initl_install_Language_Component = @()
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component +=
$_.PackageName }
```

```
$Language = @(
```

```
@{ Match = "*windowsupdate*"; File = "winpe-windowsupdate_$( $Lang).cab"; }
```

```
@{ Match = "*appxdeployment*"; File = "winpe-appxdeployment_$( $Lang).cab"; }
```

```
@{ Match = "*hta*"; File = "winpe-hta_$( $Lang).cab"; }
```

```
@{ Match = "*opcservices*"; File = "winpe-opcservices_$( $Lang).cab"; }
```

```
@{ Match = "*rejuv*"; File = "winpe-rejuv_$( $Lang).cab"; }
```

```

@{ Match = "*WiFi*"; File = "winpe-wifi_$(Lang).cab"; }

@{ Match = "*StorageWMI*"; File = "winpe-storagewmi_$(Lang).cab"; }

@{ Match = "*WinPE-AppxPackaging*"; File = "winpe-appxpackaging_$(Lang).cab"; }

@{ Match = "*-WMI-Package*"; File = "winpe-wmi_$(Lang).cab"; }

@{ Match = "*wds-tools*"; File = "winpe-wds-tools_$(Lang).cab"; }

@{ Match = "*srt*"; File = "winpe-srt_$(Lang).cab"; }

@{ Match = "*srh*"; File = "winpe-srh_$(Lang).cab"; }

@{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_$(Lang).cab"; }

@{ Match = "*scripting*"; File = "winpe-scripting_$(Lang).cab"; }

@{ Match = "*Narrator*"; File = "winpe-narrator_$(Lang).cab"; }

@{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_$(Lang).cab"; }

@{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_$(Lang).cab"; }

@{ Match = "*AudioCore*"; File = "winpe-audiocore_$(Lang).cab"; }

@{ Match = "*ATBroker*"; File = "winpe-atbroker_$(Lang).cab"; }

@{ Match = "*SecureStartup*"; File = "winpe-securestartup_$(Lang).cab"; }

@{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*$(Lang)*") {

            Write-host "  Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline; Write-host "$($Sources)\$($Rule.File)" -
ForegroundColor Green

            Write-Host "  Deleting ".PadRight(22) -NoNewline

            try {

                Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" -ErrorAction
SilentlyContinue | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

                Write-host "  $_" -ForegroundColor Red

            }

            break

        }

    }

}

```

```

    }

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*${Lang}*") {

        $InitlClearLanguagePackage += $_.PackageName

    }

}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n $($item)" -ForegroundColor Green

        Write-Host "  Deleting ".PadRight(22) -NoNewline

        try{

            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue |
Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

            Write-host "  $($_) " -ForegroundColor Red

        }

    }

}

}

```

3.1.4.4. Components: All packages installed in the image

3.1.4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_11_Custom\Install\WinRE\Mount" | Out-GridView
```

3.1.4.4.2. Export to csv

```
$SaveTo = "D:\OS_11_Custom\Install\WinRE\Report.${(Get-Date -Format
"yyyyMMddHHmmss")}.csv"
```

```
Get-WindowsPackage -Path "D:\OS_11_Custom\Install\WinRE\Mount" | Export-CSV -
NoType -Path $SaveTo
```

```
Write-host $SaveTo -ForegroundColor Green
```

3.1.5. Cumulative updates

To prepare the cumulative updates file available, change the example file name: **KB_WinRE.cab**

3.1.5.1. Add

```
$KBPath = "D:\OS_11_Custom\Install\WinRE\Update\KB_WinRE.cab"
```

```
Add-WindowsPackage -Path "D:\OS_11_Custom\Install\WinRE\Mount" -PackagePath $KBPath
```

3.1.5.2. Delete

```
$KBPath = "D:\OS_11_Custom\Install\WinRE\Update\KB_WinRE.cab"
```

```
Remove-WindowsPackage -Path "D:\OS_11_Custom\Install\WinRE\Mount" -PackagePath $KBPath
```

3.1.5.3. Solid update

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /image:"D:\OS_11_Custom\Install\WinRE\Mount" /cleanup-image /StartComponentCleanup  
/ResetBase
```

3.1.5.3.1. Clean components after curing and updating

```
$Mount = "D:\OS_11_Custom\Install\WinRE\Mount"
```

```
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {
```

```
    if ($_.PackageState -eq "Superseded") {
```

```
        Write-Host "  $($_.PackageName)" -ForegroundColor Green
```

```
        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null
```

```
    }
```

```
}
```

3.1.6. Drive

3.1.7. Save image: WinRE.wim

```
Save-WindowsImage -Path "D:\OS_11_Custom\Install\WinRE\Mount"
```

3.1.8. Unmount image: WinRE.wim

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowsImage -Path "D:\OS_11_Custom\Install\WinRE\Mount" -Discard
```

3.1.9. After rebuilding WinRE.wim, the file size can be reduced

- WinRE.Rebuild.ps1
 - [\Install\WinRE\WinRE.Rebuild.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/WinRE/WinRE.Rebuild.ps1

- Copy the code

```
$FileName = "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

Get-WindowsImage -ImagePath $Filename -ErrorAction SilentlyContinue | ForEach-Object {

    Write-Host "` Image name: " -NoNewLine

    Write-Host $_.ImageName -ForegroundColor Yellow

    Write-Host "` The index number: " -NoNewLine

    Write-Host $_.ImageIndex -ForegroundColor Yellow

    Write-Host "` n Rebuild".PadRight(28) -NoNewLine

    Export-WindowsImage -SourceImagePath $Filename -SourceIndex $_.ImageIndex -DestinationImagePath
"$($FileName).New" -CompressionType max

    Write-Host "Finish`n" -ForegroundColor Green

}

if (Test-Path "$($FileName).New" -PathType Leaf) {

    Remove-Item -Path $Filename

    Move-Item -Path "$($FileName).New" -Destination $Filename

    Write-Host "Finish" -ForegroundColor Green

} else {

    Write-host "Failed" -ForegroundColor Red

}

}
```

3.1.10. Backup WinRE.wim

- WinRE.Backup.ps1
 - [\Expand\Install\WinRE\WinRE.Backup.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/WinRE/WinRE.Backup.ps1

- Copy the code

```
$WimLibPath = "D:\OS_11_Custom\Install\Install\Update\Winlib"

$FileName = "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery\WinRE.wim"

New-Item -Path $WimLibPath -ItemType Directory -ea SilentlyContinue

Copy-Item -Path $FileName -Destination $WimLibPath -Force
```

3.1.11. Replace WinRE.wim within the Install.wim image

- After each mount Install.wim "[Replace WinRE.wim](#)";
- Learn "[Get all index numbers of Install.wim and replace the old WinRE.wim](#)".

Process the files in the Install.wim image and end.

4. Language pack

- Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for Install.wim](#)".
- When adding languages, different schema versions must be corresponded, and if not, errors are reported during the addition process.

4.1. Language pack: add

- Install.Instl.lang.ps1
 - [\Expand\Install\Install.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/Install.Instl.lang.ps1

- Copy the code

```
Function Language_Install
{
    param($Mount, $Sources, $Lang)

    $InitL_install_Language_Component = @()

    if (Test-Path $Mount -PathType Container) {

        Get-WindowsPackage -Path $Mount | ForEach-Object { $InitL_install_Language_Component += $_.PackageName }

    } else {

        Write-Host "Not mounted: $($Mount)"

        return

    }

    $Script:Init_Folder_All_File = @()

    if (Test-Path "$($Sources)\$($Lang)" -PathType Container) {

        Get-ChildItem -Path $Sources -Recurse -Include "*.cab" -ErrorAction SilentlyContinue | ForEach-Object {

            $Script:Init_Folder_All_File += $_.FullName

        }

        Write-host "`n Available language pack installation files"

        if ($Script:Init_Folder_All_File.Count -gt 0) {

            ForEach ($item in $Script:Init_Folder_All_File) {

                Write-host "  $($item)"

            }

        } else {
```

```

        Write-host "There are no language pack files locally"

    }

    return
}

} else {

    Write-Host "Path does not exist: $($Sources)\$($Lang)"

    return

}

$Script:Init_Folder_All_File_Match_Done = @()

$Script:Init_Folder_All_File_Exclude = @()

$Script:Search_File_Order = @(

    @{

        Name = "Fonts"

        Description = "Fonts"

        Rule = @(

            @{ Match_Name = "*Fonts*"; IsMatch = "No"; Capability = ""; }

        )

    }

    @{

        Name = "Basic"

        Description = "Basic"

        Rule = @(

            @{ Match_Name = "*LanguageFeatures-Basic*"; IsMatch = "Yes"; Capability = "Language.Basic~~~lb-LU~0.0.1.0"; }

            @{ Match_Name = "*Client*Language*Pack*"; IsMatch = "Yes"; Capability = "Language.Basic~~~lb-LU~0.0.1.0"; }

        )

    }

    @{

        Name = "OCR"

        Description = "Optical character recognition"

        Rule = @(

            @{ Match_Name = "*LanguageFeatures-OCR*"; IsMatch = "Yes"; Capability = "Language.OCR~~~fr-FR~0.0.1.0"; }

        )

    }

    @{

        Name = "Handwriting"

```

```

        Description = "Handwriting recognition"

        Rule = @(

            @{ Match_Name = "*LanguageFeatures-Handwriting*"; IsMatch = "Yes"; Capability = "Language.Handwriting~~~fr-FR~0.0.1.0"; }

        )

    }

    @{

        Name = "TextToSpeech"

        Description = "Text-to-speech"

        Rule = @(

            @{ Match_Name = "*LanguageFeatures-TextToSpeech*"; IsMatch = "Yes"; Capability = "Language.TextToSpeech~~~fr-FR~0.0.1.0"; }

        )

    }

    @{

        Name = "Speech"

        Description = "Speech recognition"

        Rule = @(

            @{ Match_Name = "*LanguageFeatures-Speech*"; IsMatch = "Yes"; Capability = "Language.Speech~~~fr-FR~0.0.1.0"; }

        )

    }

    @{

        Name = "RegionSpecific"

        Description = "Other region-specific requirements"

        Rule = @(

            @{ Match_Name = "*InternationalFeatures*"; IsMatch = "No"; Capability = ""; }

        )

    }

    @{

        Name = "Retail"

        Description = "Retail demo experience"

        Rule = @(

            @{ Match_Name = "*RetailDemo*"; IsMatch = "Yes"; Capability = ""; }

        )

    }

```

```

@{

    Name = "Features_On_Demand"

    Description = "Features on demand"

    Rule = @(

        @{ Match_Name = "*InternetExplorer*"; IsMatch = "Yes"; Capability = ""; }

        @{ Match_Name = "*MSPaint*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

        @{ Match_Name = "*MSPaint*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.MSPaint~~~~0.0.1.0"; }

        @{ Match_Name = "*Notepad*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.Notepad~~~~0.0.1.0"; }

        @{ Match_Name = "*Notepad*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.Notepad~~~~0.0.1.0"; }

        @{ Match_Name = "*MediaPlayer*amd64*"; IsMatch = "Yes"; Capability = "Media.WindowsMediaPlayer~~~~0.0.12.0"; }

        @{ Match_Name = "*MediaPlayer*wow64*"; IsMatch = "Yes"; Capability = "Media.WindowsMediaPlayer~~~~0.0.12.0"; }

        @{ Match_Name = "*PowerShell-ISE-FOD-Package*amd64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

        @{ Match_Name = "*PowerShell-ISE-FOD-Package*wow64*"; IsMatch = "Yes"; Capability =
"Microsoft.Windows.PowerShell.ISE~~~~0.0.1.0"; }

        @{ Match_Name = "*Printing*PMCPPC*amd64*"; IsMatch = "Yes"; Capability = "Print.Management.Console~~~~0.0.1.0"; }

        @{ Match_Name = "*StepsRecorder*amd64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

        @{ Match_Name = "*StepsRecorder*wow64*"; IsMatch = "Yes"; Capability = "App.StepsRecorder~~~~0.0.1.0"; }

        @{ Match_Name = "*WordPad*amd64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.WordPad~~~~0.0.1.0"; }

        @{ Match_Name = "*WordPad*wow64*"; IsMatch = "Yes"; Capability = "Microsoft.Windows.WordPad~~~~0.0.1.0"; }

        @{ Match_Name = "*WMIC*FoD*Package*amd64*"; IsMatch = "Yes"; Capability = "WMIC~~~~"; }

        @{ Match_Name = "*WMIC*FoD*Package*wow64*"; IsMatch = "Yes"; Capability = "WMIC~~~~"; }

    )

}

)

ForEach ($item in $Script:Search_File_Order) { New-Variable -Name "Init_File_Type_$( $item.Name )" -Value @() -Force }

ForEach ($Wildcard in $Script:Init_Folder_All_File) {

    ForEach ($item in $Script:Search_File_Order) {

        ForEach ($NewRule in $item.Rule) {

            if ($Wildcard -like "*$( $NewRule.Match_Name )*") {

                Write-host "`n  Fuzzy matching: " -NoNewline; Write-host $NewRule.Match_Name -ForegroundColor Green

                Write-host "  Language pack file: " -NoNewline; Write-host $Wildcard -ForegroundColor Green

                $OSDefaultUser = (Get-Variable -Name "Init_File_Type_$( $item.Name )" -ErrorAction SilentlyContinue).Value

                $TempSave = @{ Match_Name = $NewRule.Match_Name; Capability = $NewRule.Capability; FileName = $Wildcard }

                $new = $OSDefaultUser + $TempSave
            }
        }
    }
}

```

```

        if ($NewRule.IsMatch -eq "Yes") {

            ForEach ($Component in $Initl_install_Language_Component) {

                if ($Component -like "*${$NewRule.Match_Name}*") {

                    Write-host "  Component name: " -NoNewline; Write-host $Component -ForegroundColor Green

                    New-Variable -Name "Init_File_Type_${$item.Name}" -Value $new -Force

                    $Script:Init_Folder_All_File_Match_Done += $Wildcard

                    break

                }

            }

        } else {

            Write-host "  Do not match, install directly" -ForegroundColor Yellow

            New-Variable -Name "Init_File_Type_${$item.Name}" -Value $new -Force

            $Script:Init_Folder_All_File_Match_Done += $Wildcard

        }

    }

}

Write-host "`n  Grouping is complete, pending installation" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($Wildcard in $Script:Search_File_Order) {

    $OSDefaultUser = (Get-Variable -Name "Init_File_Type_${$Wildcard.Name}" -ErrorAction SilentlyContinue).Value

    Write-host "`n  ${$Wildcard.Description} ( ${$OSDefaultUser.Count} item )"

    if ($OSDefaultUser.Count -gt 0) {

        ForEach ($item in $OSDefaultUser) {

            Write-host "  ${$item.FileName}" -ForegroundColor Green

        }

    } else {

        Write-host "  Not available" -ForegroundColor Red

    }

}

Write-host "`n  Not matched, no longer installed" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

ForEach ($item in $Script:Init_Folder_All_File) {

    if ($Script:Init_Folder_All_File_Match_Done -notcontains $item) {

```

```

$Script:Init_Folder_All_File_Exclude += $item

Write-host " $($item)" -ForegroundColor Red

}

}

Write-host "`n  Install" -ForegroundColor Yellow; Write-host " $('-' * 80)"

ForEach ($WildCard in $Script:Search_File_Order){

    $OSDefaultUser = (Get-Variable -Name "Init_File_Type_{$WildCard.Name}" -ErrorAction SilentlyContinue).Value

    Write-host "`n  $($WildCard.Description) ( $($OSDefaultUser.Count) item ); Write-host " $('-' * 80)"

    if ($OSDefaultUser.Count -gt 0){

        ForEach ($item in $OSDefaultUser){

            Write-host "  Language pack file: " -NoNewline; Write-host $item.FileName -ForegroundColor Green

            Write-Host "  Installing ".PadRight(22) -NoNewline

            if (Test-Path $item.FileName -PathType Leaf){

                try{

                    Add-WindowsPackage -Path $Mount -PackagePath $item.FileName | Out-Null

                    Write-host "Finish`n" -ForegroundColor Green

                } catch {

                    Write-host "Failed" -ForegroundColor Red

                    Write-host "  $($_) " -ForegroundColor Red

                }

            } else {

                Write-host "Does not exist`n"

            }

        }

    } else {

        Write-host "  Not available`n" -ForegroundColor Red

    }

}

}

Language_Install -Mount "D:\OS_11_Custom\Install\Install\Mount" -Sources "D:\OS_11_Custom\Install\Install\Language\Add" -
Lang "zh-CN"

```

4.2. Offline image language: change

- Starting Windows 11, the [default System UI Language](#) set by DISM is left unaltered on all editions except for Home edition. For [all commercial editions](#) the language chosen during the Out-of-Box Experience (OOBE) is set as the [System Preferred UI language](#) and Windows will be displayed in this language and for Home edition the language chosen at OOBE will continue to

be the default System UI Language.

- As of Windows 10, version 2004, if an .appx-based Language Experience Pack (LXP) backed language is passed as an argument then the language will be set as the System Preferred UI language and its parent language will be set as the Default System UI language. In prior versions only .cab based language packs were supported.

4.2.1. Change default language, regional settings, and other international settings

Region: zh-CN

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /Set-AllIntl:zh-CN
```

4.2.2. View available language settings

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /Get-Intl
```

4.3. Language packs: Removed

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "English - United States" in reverse, the Region tag: en-US, you need to extract the language pack in advance

- Install.Del.Specified.lang.Tag.ps1

- \Expand\Install\Install.Del.Specified.lang.Tag.ps1

- https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.11/22H2/Expand/Install/Install.Del.Specified.lang.Tag.ps1

- Copy the code

```
$Lang = "en-US"
```

```
$Mount = "D:\OS_11_Custom\Install\Install\Mount"
```

```
$Sources = "D:\OS_11_Custom\Install\Install\Language\Del\en-US"
```

```
$Initl_install_Language_Component = @()
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object {
```

```
    $Initl_install_Language_Component += $_.PackageName
```

```
}
```

```
$Language = @(
```

```
    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-  
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-  
Package~31bf3856ad364e35~AMD64~$( $Lang)~.cab"; }
```

```

        @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-
Package~31bf3856ad364e35~amd64~$(Lang)~.cab"; }

        @{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(Lang).cab"; }

        @{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(Lang).cab"; }

        @{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

        @{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

        @{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

        @{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }

    )

    ForEach ($Rule in $Language) {

        Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

        ForEach ($Component in $InitL_install_Language_Component) {

            if ($Component -like "*$($Rule.Match)*$(Lang)*") {

                Write-host "  Component name: " -NoNewline

                Write-host $Component -ForegroundColor Green

                Write-host "  Language pack file: " -NoNewline

                Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

                Write-Host "  Deleting ".PadRight(22) -NoNewline

            }

            try {

```

```

Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\ $($Rule.File)" -ErrorAction SilentlyContinue | Out-Null

Write-host "Finish" -ForegroundColor Green

} catch {

Write-host "Failed" -ForegroundColor Red

Write-host "  $($_) " -ForegroundColor Red

}

break

}

}

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

if ($_.PackageName -like "* $($Lang)*") {

$InitlClearLanguagePackage += $_.PackageName

}

}

if ($InitlClearLanguagePackage.count -gt 0) {

ForEach ($item in $InitlClearLanguagePackage) {

Write-Host "`n $($item)" -ForegroundColor Green

Write-Host "  Deleting ".PadRight(22) -NoNewline

try {

Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null

Write-host "Finish" -ForegroundColor Green

} catch {

Write-host "Failed" -ForegroundColor Red

Write-host "  $($_) " -ForegroundColor Red

}

}

}

}

```

4.4. Components: All packages installed in the image

4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Out-GridView
```

4.4.2. Export to csv

```
$SaveTo = "D:\OS_11_Custom\Install\Install\Report.$(Get-Date -Format "yyyyMMddHHmmss").csv"

Get-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green
```

5. InBox Apps

5.1. Learn

5.1.1. DISM App Package (.appx or .appxbundle) Servicing Command-Line Options

5.2. InBox Apps: Pre-install the application

- Group abbreviations
 - Group A: Education, Professional, ProfessionalEducation, ProfessionalWorkstation, Enterprise, IoTEnterprise, ServerRdsh
 - Group B: EnterpriseN, EnterpriseGN, EnterpriseSN, ProfessionalN, EducationN, ProfessionalWorkstationN, ProfessionalEducationN
 - Group C: Core, CoreN, CoreSingleLanguage

| | Name | Products ID | Grouping |
|-----|--|--------------|----------|
| 1. | Microsoft.HEIFImageExtension | 9PMMSR1CGPWG | A, C |
| 2. | Microsoft.HEVCVideoExtension | 9NMZLZ57R3T7 | A, C |
| 3. | Microsoft.VP9VideoExtensions | 9N4D0MSMP0PT | A, C |
| 4. | Microsoft.WebpImageExtension | 9PG2DK419DRG | A, C |
| 5. | Microsoft.GamingApp | 9MV0B5HZVK9Z | A, C |
| 6. | Microsoft.ZuneMusic | 9WZDNCRFJ3PT | A, C |
| 7. | MicrosoftCorporationII.MicrosoftFamily | 9PDJDS743XF | C |
| 8. | Microsoft.WebMediaExtensions | 9N5TDP8VCMHS | A, C |
| 9. | Microsoft.WindowsSoundRecorder | 9WZDNCRFHWKN | A, C |
| 10. | Microsoft.Xbox.TCUI | 9NKNC0LD5NN6 | A, C |
| 11. | Microsoft.XboxGamingOverlay | 9NZKPSTSNW4P | A, C |
| 12. | Microsoft.ZuneVideo | 9WZDNCRFJ3P2 | A, C |
| 13. | Microsoft.RawImageExtension | 9NCTDW2W1BH8 | A, C |
| 14. | Microsoft.UI.Xaml.2.3 | | A, B, C |
| 15. | Microsoft.UI.Xaml.2.4 | | A, B, C |
| 16. | Microsoft.UI.Xaml.2.7 | | A, B, C |
| 17. | Microsoft.NET.Native.Framework.2.2 | | A, B, C |
| 18. | Microsoft.NET.Native.Runtime.2.2 | | A, B, C |
| 19. | Microsoft.VCLibs.140.00 | | A, B, C |

| | | | |
|-----|---------------------------------------|--------------|---------|
| 20. | Microsoft.VCLibs.140.00.UWPDesktop | | A, B, C |
| 21. | Microsoft.SecHealthUI | 9NK0JLZT7JD0 | A, B, C |
| 22. | Microsoft.WindowsStore | 9WZDNCRFJBMP | A, B, C |
| 23. | Microsoft.Sticky.Notes | 9NBLGGH4QGHW | A, B, C |
| 24. | Microsoft.Paint | 9PCFS5B6T72H | A, B, C |
| 25. | Microsoft.PowerAutomateDesktop | 9NFTCH6J7FHV | A, B, C |
| 26. | Microsoft.ScreenSketch | 9MZ95KL8MR0L | A, B, C |
| 27. | Microsoft.WindowsNotepad | 9MSMLRH6LZF3 | A, B, C |
| 28. | Microsoft.WindowsTerminal | 9N0DX20HK701 | A, B, C |
| 29. | Clipchamp.Clipchamp | 9P1J8S7CCWWT | A, B, C |
| 30. | Microsoft.Solitaire.Collection | 9WZDNCRFHWD2 | A, B, C |
| 31. | Microsoft.WindowsAlarms | 9WZDNCRFJ3PR | A, B, C |
| 32. | Microsoft.WindowsFeedbackHub | 9NBLGGH4R32N | A, B, C |
| 33. | Microsoft.WindowsMaps | 9WZDNCRDTBVB | A, B, C |
| 34. | Microsoft.BingNews | 9WZDNCRFHVFW | A, B, C |
| 35. | Microsoft.DesktopAppInstaller | 9NBLGGH4NNS1 | A, B, C |
| 36. | Microsoft.WindowsCamera | 9WZDNCRFJBBG | A, B, C |
| 37. | Microsoft.Getstarted | 9WZDNCRDTBJJ | A, B, C |
| 38. | Microsoft.Cortana | 9NFFX4SZZ23L | A, B, C |
| 39. | Microsoft.BingWeather | 9WZDNCRFJ3Q2 | A, B, C |
| 40. | Microsoft.GetHelp | 9PKDZBMV1H3T | A, B, C |
| 41. | Microsoft.MicrosoftOfficeHub | 9WZDNCRD29V9 | A, B, C |
| 42. | Microsoft.People | 9NBLGGH10PG8 | A, B, C |
| 43. | Microsoft.StorePurchaseApp | 9NBLGGH4LS1F | A, B, C |
| 44. | Microsoft.Todos | 9NBLGGH5R558 | A, B, C |
| 45. | Microsoft.Windows.Photos | 9WZDNCRFJBH4 | A, B, C |
| 46. | Microsoft.WindowsCalculator | 9WZDNCRFHVN5 | A, B, C |
| 47. | Microsoft.Windows.CommunicationsApps | 9WZDNCRFHVQM | A, B, C |
| 48. | Microsoft.XboxGameOverlay | 9NBLGGH537C2 | A, B, C |
| 49. | Microsoft.XboxIdentityProvider | 9WZDNCRD1HKW | A, B, C |
| 50. | Microsoft.XboxSpeechToTextOverlay | 9P086NHDNB9W | A, B, C |
| 51. | Microsoft.YourPhone | 9NMPJ99VJBWV | A, B, C |
| 52. | MicrosoftCorporationII.QuickAssist | 9P7BP5VNWKX5 | A, B, C |
| 53. | MicrosoftWindows.Client.WebExperience | 9MSSGKG348SP | A, B, C |

5.3. InBox Apps: Installed

5.3.1. View

```
Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Out-GridView
```

5.3.2. Export to Csv

```
$SaveTo = "D:\OS_11_Custom\Install\Install\Report.${(Get-Date -Format "yyyyMMddHHmmss")}.csv"
```

```
Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Export-CSV -NoType -Path $SaveTo
```

```
Write-host $SaveTo -ForegroundColor Green
```

5.4. Remove all installed pre-applications

- Install.InBox.Appx.Clear.all.ps1
 - [\Expand\Install\Install.InBox.Appx.Clear.all.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/Install.InBox.Appx.Clear.all.ps1

- Copy the code

```
Get-AppXProvisionedPackage -path "D:\OS_11_Custom\Install\Install\Mount" -ErrorAction SilentlyContinue | ForEach-Object {
```

```
    Write-host "`n ${($_.DisplayName)}"; Write-Host "    Deleting ".PadRight(22) -NoNewline
```

```
    try {
```

```
        Remove-AppxProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackageName $_.PackageName -ErrorAction SilentlyContinue | Out-Null
```

```
        Write-host "Finish" -ForegroundColor Green
```

```
    } catch {
```

```
        Write-host "Failed" -ForegroundColor Red
```

```
    }
```

```
}
```

5.5. Region tag: Understanding

Before understanding zone tags, first understand the list of languages available in the ZuneMusic app: **en-us**, en-gb, as-in, az-latn-az, bs-latn-ba, bn-in, cs-cz, cy-gb, ar-sa, de-de, af-za, am-et, da-dk, el-gr, es-es, es-mx, ca-es, ca-es-valencia, eu-es, fi-fi, bg-bg, ga-ie, et-ee, gl-es, gu-in, gd-gb, fil-ph, fr-ca, fr-fr, hy-am, fa-ir, hu-hu, id-id, it-it, ja-jp, hr-hr, ka-ge, is-is, he-il, hi-in, kk-kz, lo-la, km-kh, lt-lt, kn-in, kok-in, ko-kr, mk-mk, lv-lv, ms-my, mi-nz, mr-in, mt-mt, ne-np, nl-nl, nb-no, ml-in, nn-no, lb-lu, or-in, ro-ro, sk-sk, ru-ru, pl-pl, quz-pe, pt-br, pt-pt, sq-al, ta-in, th-th, sv-se, pa-in, sr-cyrl-ba, sr-cyrl-rs, sr-latn-rs, ur-pk, ug-cn, tr-tr, uk-ua, tt-ru, **zh-cn**, vi-vn, uz-latn-uz, sl-si, zh-tw, te-in

View installed languages for offline images

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /Get-Intl
```

View results for installed languages: [en-US](#), [zh-CN](#), When installing the ZuneMusic app, the installer will match "Installed Languages" and automatically filter the list of uninstalled languages, This is the area tag.

5.6. Region tag: Add

Microsoft officially provides the Local Language Experience Package (LXPS) installation file for Windows 10. It will no longer be provided for Windows 11. Want to get:

5.6.1. Download using the Windows Local Language Experience Packs (LXPs) Downloader

learn: <https://github.com/ilikeyi/LXPs>

After downloading, save to: [D:\OS_11_Custom\Install\Install\InBox.Appx](#)

File format: [LanguageExperiencePack.zh-CN.Neutral.Appx](#)

5.6.2. Manual download

5.6.2.1. Region

| Region | Products ID | Region | Products ID |
|--------------------------------|---------------|-----------------------------|--------------|
| en-US | C9PDSCC711RVF | af-za | 9PDW16B5HMXR |
| am-et | 9NGL4R61W3PL | ar-sa | 9N4S78P86PKX |
| as-in | 9NTJLXMX35J | az-latn-az | 9P5TFKZHQ5K8 |
| be-by | 9MXPBGNNNDW3L | bg-bg | 9MX54588434F |
| bn-bd | 9PH7TKVXGGM8 | bn-in | 9P1M44L7W84T |
| bs-latn-ba | 9MVFKLJ10MFL | ca-es | 9P6JMKJQZ9S7 |
| ca-es-valencia | 9P9K3WMFSW90 | chr-cher-us | 9MX15485N3RK |
| cs-cz | 9P3WXZ1KTM7C | cy-gb | 9NKJ9TBML4HB |
| da-dk | 9NDMT2VKSNNL1 | de-de | 9P6CT0SLW589 |
| el-gr | 9N586B13PBLD | en-gb | 9NT52VQ39BVN |
| es-es | 9NWWGWLHPB1Z | es-mx | 9N8MCM1X3928 |
| et-ee | 9NFBHFMCR30L | eu-es | 9NMCHQHZ37HZ |
| fa-ir | 9NGS7DD4QS21 | fi-fi | 9MW3PQ7SD3QK |
| fil-ph | 9NWM2KGTDSSS | fr-ca | 9MTP2VP0VL92 |
| fr-fr | 9NHMG4BJKMDG | ga-ie | 9P0L5Q848KXT |
| gd-gb | 9P1DBPF36BF3 | gl-es | 9NXRNBRNJN9B |
| gu-in | 9P2HMSWDJDQ1 | ha-latn-ng | 9N1L95DBGRG3 |
| he-il | 9NB6ZFND5HCQ | hi-in | 9NZC3GRX8LD3 |
| hr-hr | 9NW01VND4LTW | hu-hu | 9MWN3C58HL87 |
| hy-am | 9NKM28TM6P67 | id-id | 9P4X3N4SDK8P |

| | | | |
|------------|--------------|-------------|--------------|
| ig-ng | 9PG4ZFJ48JSX | is-is | 9NTHJR7TQXX1 |
| it-it | 9P8PQWNS6VJX | ja-jp | 9N1W692FV4S1 |
| ka-ge | 9P60JZL05WGH | kk-kz | 9PHV179R97LV |
| km-kh | 9PGKTS4JS531 | kn-in | 9NC6DB7N95F9 |
| kok-in | 9MV3P55CMZ6P | ko-kr | 9N4TXPCVRNGF |
| ku-arab-iq | 9P1C18QL3D7H | ky-kg | 9P7D3JJGZM48 |
| lb-lu | 9N0ST1WBZ9D9 | lo-la | 9N8X352G5NZV |
| lt-lt | 9NWW891H6HN | lv-lv | 9N5CQDPH6SQT |
| mi-nz | 9P2GDFB3JPSX | mk-mk | 9P1X6XB1K3RN |
| ml-in | 9NWDTV8FFV7L | mn-mn | 9PG1DHC4VTZW |
| mr-in | 9MWXCKHJVR1J | ms-my | 9NPXL8ZSDDQ7 |
| mt-mt | 9PDG96SQ6BN8 | nb-no | 9N6J0M5DHCK0 |
| ne-np | 9P7CHPLWDQVN | nl-nl | 9PF1C9NB5PRV |
| nn-no | 9PK7KM3Z06KH | nso-za | 9NS49QLX5CDV |
| or-in | 9NTHCXCXSJDH | pa-arab-pk | 9NJRL03WH6FM |
| pa-in | 9NSNC0ZX69B | pl-pl | 9NC5HW94R0LD |
| prs-af | 9P3NGC6X5ZQC | pt-br | 9P8LBDM4FW35 |
| pt-pt | 9P7X8QJ7FL0X | quc-latn-gt | 9P2V6MNNQZ0B |
| quz-pe | 9NHTX8NVQ04K | ro-ro | 9MWXGPJ5PJ3H |
| ru-ru | 9NMJCX77QKPX | rw-rw | 9NFW0M20H9WG |
| sd-arab-pk | 9NB9JSCXW9X5 | si-lk | 9NVF9QSLGTL0 |
| sk-sk | 9N7LSNN099WB | sl-si | 9NV27L34J4ST |
| sq-al | 9MWLRGNMDGK7 | sr-cyrl-ba | 9MXGN7V65C7B |
| sr-cyrl-rs | 9PPD6CCK9K5H | sr-latn-rs | 9NBZ0SJDPPVT |
| sv-se | 9P0HSNX08177 | sw-ke | 9NFF2M19DQ55 |
| ta-in | 9PDZB1WT1B34 | te-in | 9PMQJJGF63FW |
| tg-cyrl-tj | 9MZHLBPPT2HC | th-th | 9MSTWFRL0LR4 |
| ti-et | 9NC8C9RDNK2S | tk-tm | 9NKHQ4GL6VLT |
| tn-za | 9NFSXM123DHT | tr-tr | 9NL1D3T5HG9R |
| tt-ru | 9NV90Q1X1ZR2 | ug-cn | 9P52C5D7VL5S |
| uk-ua | 9PPPMZRSGHR8 | ur-pk | 9NDWFTFW12BQ |
| uz-latn-uz | 9P5P2T5P5L9S | vi-vn | 9P0W68X0XZPT |
| wo-sn | 9NH3SW1CR90F | xh-za | 9NW3QWSLQD17 |
| yo-ng | 9NGM3VPPZS5V | zh-cn | 9NRMNT6GMZ7 |

Download Region: zh-CN, application ID: 9NRMNT6GMZ70, Store link:
<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.6.2.2. Open the website: <https://store.rg-adguard.net>

5.6.2.2.1. Search keywords:

<https://www.microsoft.com/store/productId/9NRMNT6GMZ70>

5.6.2.2.2. Search 22621 content in the web page, search results:
[Microsoft.LanguageExperiencePackzh-CN_22621.*.neutral__8wekyb3d8bbwe.appx](#)

5.6.2.2.3. After downloading, save it to the

[D:\OS_11_Custom\Install\Install\InBox.Appx](#) directory and rename it:
[LanguageExperiencePack.zh-cn.Neutral.Appx](#)

5.6.3. Execute the installation command to install the local language experience package (LXPs)

After understanding how to add zone tags, obtain [LanguageExperiencePack.zh-cn.Neutral](#), execute the installation command:

```
Add-AppxProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackagePath  
"D:\OS_11_Custom\Install\Install\InBox.appx\LanguageExperiencePack.zh-cn.Neutral.appx" -SkipLicense
```

5.6.4. Regional tag: New changes

The installed language of the offline image will become the default. For example, if the installed languages are en-US and zh-CN, when you reinstall or update the InBox Apps application, the installed language will be referenced for matching and the corresponding language pack will be automatically added. You can view the changes in the following ways.

5.6.4.1. InBox Apps: An installed application package

5.6.4.1.1. View

[Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Out-GridView](#)

5.6.4.1.2. Export to Csv

[\\$SaveTo = "D:\OS_11_Custom\Install\Install\Report.\\${\(Get-Date -Format "yyyyMMddHHmmss"\)}.csv"](#)

[Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Export-CSV -NoType -Path \\$SaveTo](#)

[Write-host \\$SaveTo -ForegroundColor Green](#)

5.6.4.2. View available language settings

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /Get-Intl
```

5.7. InBox Apps: Install

5.7.1. Mount or decompress the InBox Apps installation file

Mount [22621.1.220506-1250.ni_release_amd64fre_InboxApps.iso](#) or extract to any location;

5.7.2. After executing the installation command, install InBox Apps to: Install.wim

- [Auto](#) = Automatically search all local disks, default;
- Custom path, e.g. specify F drive: `$ISO = "F:\packages"`
- Architecture: [x64](#)
- `Install.Inst.InBox.Appx.ps1`
 - [\Expand\Install\Install.Inst.InBox.Appx.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/Install.Inst.InBox.Appx.ps1

- Copy the code

```
$ISO = "Auto"
```

```
$Mount = "D:\OS_11_Custom\Install\Install\Mount"
```

```
$Arch = "x64"
```

```
try{
```

```
Write-host "`n Offline image version: " -NoNewline
```

```
$Current_Edition_Version = (Get-WindowsEdition -Path $Mount).Edition
```

```
Write-Host $Current_Edition_Version -ForegroundColor Green
```

```
} catch {
```

```
Write-Host "Error" -ForegroundColor Red
```

```
Write-Host " $($_) " -ForegroundColor Yellow
```

```
return
```

```
}
```

```
$Pre_Config_Rules = @{
```

```
Edition = @(
```

```
@{
```

```
Name = @( "CloudEdition"; )
```

```
Apps = @(
```

```
"Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
```

```
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
```

```
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.Services.Store.Engagement"; "Microsoft.VP9VideoExtensions";
```

```

"Clipchamp.Clipchamp"; "Microsoft.BingNews"; "Microsoft.BingWeather"; "Microsoft.DesktopAppInstaller";
"Microsoft.GetHelp"; "Microsoft.Getstarted"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.MicrosoftOfficeHub"; "Microsoft.MicrosoftStickyNotes"; "Microsoft.MinecraftEducationEdition";
"Microsoft.Paint"; "Microsoft.RawImageExtension"; "Microsoft.ScreenSketch"; "Microsoft.SecHealthUI";
"Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions";
"Microsoft.WebpImageExtension"; "Microsoft.Whiteboard"; "Microsoft.Windows.Photos"; "Microsoft.WindowsAlarms";
"Microsoft.WindowsCalculator"; "Microsoft.WindowsCamera"; "Microsoft.WindowsFeedbackHub";
"Microsoft.WindowsMaps"; "Microsoft.WindowsNotepad"; "Microsoft.WindowsSoundRecorder";
"Microsoft.Xbox.TCUI"; "Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay";
"Microsoft.ZuneMusic"; "Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist";

    )

}

@{

    Name = @( "CloudEditionN"; )

    Apps = @(

        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.Services.Store.Engagement";
"Microsoft.XboxSpeechToTextOverlay"; "Clipchamp.Clipchamp"; "Microsoft.BingNews"; "Microsoft.BingWeather";
"Microsoft.DesktopAppInstaller"; "Microsoft.GetHelp"; "Microsoft.Getstarted"; "Microsoft.MicrosoftOfficeHub";
"Microsoft.MicrosoftStickyNotes"; "Microsoft.MinecraftEducationEdition"; "Microsoft.Paint"; "Microsoft.ScreenSketch";
"Microsoft.SecHealthUI"; "Microsoft.StorePurchaseApp"; "Microsoft.Whiteboard"; "Microsoft.Windows.Photos";
"Microsoft.WindowsAlarms"; "Microsoft.WindowsCalculator"; "Microsoft.WindowsCamera";
"Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.WindowsNotepad";
"Microsoft.XboxIdentityProvider"; "MicrosoftCorporationII.QuickAssist";

    )

}

@{

    Name = @(

        "Core"; "CoreN"; "CoreSingleLanguage";

    )

    Apps = @(

        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
"Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.MicrosoftStickyNotes"; "Microsoft.Paint";
"Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
"Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.MicrosoftSolitaireCollection";
"Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.ZuneMusic";
"Microsoft.BingNews"; "Microsoft.BingWeather"; "Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera";
"Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.GetHelp"; "Microsoft.MicrosoftOfficeHub"; "Microsoft.People";
"Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos";
"Microsoft.WindowsCalculator"; "Microsoft.windowscommunicationsapps"; "Microsoft.WindowsSoundRecorder";
"Microsoft.Xbox.TCUI"; "Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay";
"Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone";
"Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";

```

```

"Microsoft.RawImageExtension"; "MicrosoftCorporationII.MicrosoftFamily";

    )

}

@{

    Name = @(

        "Education"; "Professional"; "ProfessionalEducation"; "ProfessionalWorkstation"; "Enterprise"; "IoTEnterprise";
"ServerRdsh";

    )

    Apps = @(

        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.HEIFImageExtension"; "Microsoft.HEVCVideoExtension";
"Microsoft.SecHealthUI"; "Microsoft.VP9VideoExtensions"; "Microsoft.WebpImageExtension";
"Microsoft.WindowsStore"; "Microsoft.GamingApp"; "Microsoft.MicrosoftStickyNotes"; "Microsoft.Paint";
"Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch"; "Microsoft.WindowsNotepad";
"Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp"; "Microsoft.MicrosoftSolitaireCollection";
"Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub"; "Microsoft.WindowsMaps"; "Microsoft.ZuneMusic";
"Microsoft.BingNews"; "Microsoft.BingWeather"; "Microsoft.DesktopAppInstaller"; "Microsoft.WindowsCamera";
"Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.GetHelp"; "Microsoft.MicrosoftOfficeHub"; "Microsoft.People";
"Microsoft.StorePurchaseApp"; "Microsoft.Todos"; "Microsoft.WebMediaExtensions"; "Microsoft.Windows.Photos";
"Microsoft.WindowsCalculator"; "Microsoft.windowscommunicationsapps"; "Microsoft.WindowsSoundRecorder";
"Microsoft.Xbox.TCUI"; "Microsoft.XboxGameOverlay"; "Microsoft.XboxGamingOverlay";
"Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay"; "Microsoft.YourPhone";
"Microsoft.ZuneVideo"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";
"Microsoft.RawImageExtension";

    )

}

@{

    Name = @(

        "EnterpriseN"; "EnterpriseGN"; "EnterpriseSN"; "ProfessionalN"; "EducationN"; "ProfessionalWorkstationN";
"ProfessionalEducationN"; "CloudN"; "CloudEN"; "CloudEditionLN"; "StarterN";

    )

    Apps = @(

        "Microsoft.UI.Xaml.2.3"; "Microsoft.UI.Xaml.2.4"; "Microsoft.UI.Xaml.2.7";
"Microsoft.NET.Native.Framework.2.2"; "Microsoft.NET.Native.Runtime.2.2"; "Microsoft.VCLibs.140.00";
"Microsoft.VCLibs.140.00.UWPDesktop"; "Microsoft.SecHealthUI"; "Microsoft.WindowsStore";
"Microsoft.MicrosoftStickyNotes"; "Microsoft.Paint"; "Microsoft.PowerAutomateDesktop"; "Microsoft.ScreenSketch";
"Microsoft.WindowsNotepad"; "Microsoft.WindowsTerminal"; "Clipchamp.Clipchamp";
"Microsoft.MicrosoftSolitaireCollection"; "Microsoft.WindowsAlarms"; "Microsoft.WindowsFeedbackHub";
"Microsoft.WindowsMaps"; "Microsoft.BingNews"; "Microsoft.BingWeather"; "Microsoft.DesktopAppInstaller";
"Microsoft.WindowsCamera"; "Microsoft.Getstarted"; "Microsoft.Cortana"; "Microsoft.GetHelp";
"Microsoft.MicrosoftOfficeHub"; "Microsoft.People"; "Microsoft.StorePurchaseApp"; "Microsoft.Todos";
"Microsoft.Windows.Photos"; "Microsoft.WindowsCalculator"; "Microsoft.windowscommunicationsapps";
"Microsoft.XboxGameOverlay"; "Microsoft.XboxIdentityProvider"; "Microsoft.XboxSpeechToTextOverlay";
"Microsoft.YourPhone"; "MicrosoftCorporationII.QuickAssist"; "MicrosoftWindows.Client.WebExperience";

```

```

    )

}

)

Rule = @(

    @{ Name="Microsoft.UI.Xaml.2.3"; Match="UI.Xaml*{ARCHTag}*2.3";License="UI.Xaml*{ARCHTag}*2.3";
Dependencies=@(); }

    @{ Name="Microsoft.UI.Xaml.2.4"; Match="UI.Xaml*{ARCHTag}*2.4";License="UI.Xaml*{ARCHTag}*2.4";
Dependencies=@(); }

    @{ Name="Microsoft.UI.Xaml.2.7"; Match="UI.Xaml*{ARCHTag}*2.7";License="UI.Xaml*{ARCHTag}*2.7";
Dependencies=@(); }

    @{ Name="Microsoft.NET.Native.Framework.2.2";
Match="Native.Framework*{ARCHTag}*2.2";License="Native.Framework*{ARCHTag}*2.2"; Dependencies=@(); }

    @{ Name="Microsoft.NET.Native.Runtime.2.2";
Match="Native.Runtime*{ARCHTag}*2.2";License="Native.Runtime*{ARCHTag}*2.2"; Dependencies=@(); }

    @{ Name="Microsoft.VCLibs.140.00"; Match="VCLibs*{ARCHTag}";License="VCLibs*{ARCHTag}";
Dependencies=@(); }

    @{ Name="Microsoft.VCLibs.140.00.UWPDesktop";
Match="VCLibs*{ARCHTag}*Desktop";License="VCLibs*{ARCHTag}*Desktop"; Dependencies=@(); }

    @{ Name="Microsoft.HEIFImageExtension"; Match="HEIFImageExtension";License="HEIFImageExtension*";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.HEVCVideoExtension";
Match="HEVCVideoExtension*{ARCHC}";License="HEVCVideoExtension*{ARCHC}*xml";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.SecHealthUI"; Match="SecHealthUI*{ARCHC}";License="SecHealthUI*{ARCHC}";
Dependencies=@("Microsoft.UI.Xaml.2.4","Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.VP9VideoExtensions";
Match="VP9VideoExtensions*{ARCHC}";License="VP9VideoExtensions*{ARCHC}";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WebpImageExtension";
Match="WebpImageExtension*{ARCHC}";License="WebpImageExtension*{ARCHC}";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WindowsStore"; Match="WindowsStore";License="WindowsStore";
Dependencies=@("Microsoft.UI.Xaml.2.3","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"
,"Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.GamingApp"; Match="GamingApp";License="GamingApp";
Dependencies=@("Microsoft.UI.Xaml.2.3","Microsoft.VCLibs.140.00","Microsoft.VCLibs.140.00.UWPDesktop"); }

    @{ Name="Microsoft.MicrosoftStickyNotes"; Match="Microsoft.Sticky.Notes";License="MicrosoftStickyNotes";
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.
00"); }

    @{ Name="Microsoft.Paint"; Match="Paint";License="Paint";
Dependencies=@("Microsoft.VCLibs.140.00","Microsoft.VCLibs.140.00.UWPDesktop","Microsoft.UI.Xaml.2.7"); }

    @{ Name="Microsoft.PowerAutomateDesktop";
Match="PowerAutomateDesktop";License="PowerAutomateDesktop";

```

```
Dependencies=@("Microsoft.VCLibs.140.00.UWPDesktop"); }
```

```
    @{ Name="Microsoft.ScreenSketch"; Match="ScreenSketch";License="ScreenSketch";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00"); }
```

```
    @{ Name="Microsoft.WindowsNotepad"; Match="WindowsNotepad";License="WindowsNotepad";  
Dependencies=@("Microsoft.VCLibs.140.00","Microsoft.VCLibs.140.00.UWPDesktop","Microsoft.UI.Xaml.2.7"); }
```

```
    @{ Name="Microsoft.WindowsTerminal"; Match="WindowsTerminal";License="WindowsTerminal";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00.UWPDesktop"); }
```

```
    @{ Name="Clipchamp.Clipchamp"; Match="Clipchamp.Clipchamp";License="Clipchamp.Clipchamp";  
Dependencies=@(); }
```

```
    @{ Name="Microsoft.MicrosoftSolitaireCollection";  
Match="MicrosoftSolitaireCollection";License="MicrosoftSolitaireCollection";  
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.  
00"); }
```

```
    @{ Name="Microsoft.WindowsAlarms"; Match="WindowsAlarms";License="WindowsAlarms";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"  
,"Microsoft.VCLibs.140.00"); }
```

```
    @{ Name="Microsoft.WindowsFeedbackHub"; Match="WindowsFeedbackHub";License="WindowsFeedbackHub";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"  
,"Microsoft.VCLibs.140.00"); }
```

```
    @{ Name="Microsoft.WindowsMaps"; Match="WindowsMaps";License="WindowsMaps";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"  
,"Microsoft.VCLibs.140.00"); }
```

```
    @{ Name="Microsoft.ZuneMusic"; Match="ZuneMusic";License="ZuneMusic";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00"); }
```

```
    @{ Name="MicrosoftCorporationII.MicrosoftFamily"; Match="MicrosoftFamily";License="MicrosoftFamily";  
Dependencies=@(); }
```

```
    @{ Name="Microsoft.BingNews"; Match="BingNews";License="BingNews";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"  
,"Microsoft.VCLibs.140.00"); }
```

```
    @{ Name="Microsoft.BingWeather"; Match="BingWeather";License="BingWeather";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"  
,"Microsoft.VCLibs.140.00"); }
```

```
    @{ Name="Microsoft.DesktopAppInstaller"; Match="DesktopAppInstaller";License="DesktopAppInstaller";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.VCLibs.140.00.UWPDesktop"); }
```

```
    @{ Name="Microsoft.WindowsCamera"; Match="WindowsCamera";License="WindowsCamera";  
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.  
00"); }
```

```
    @{ Name="Microsoft.Getstarted"; Match="Getstarted";License="Getstarted";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"  
,"Microsoft.VCLibs.140.00"); }
```

```
    @{ Name="Microsoft.Cortana"; Match="Cortana";License="Cortana";  
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.  
00","Microsoft.VCLibs.140.00.UWPDesktop"); }
```

```
    @{ Name="Microsoft.GetHelp"; Match="GetHelp";License="GetHelp";  
Dependencies=@("Microsoft.UI.Xaml.2.7","Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2"
```

```

, "Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.MicrosoftOfficeHub"; Match="MicrosoftOfficeHub"; License="MicrosoftOfficeHub";
Dependencies=@("Microsoft.VCLibs.140.00", "Microsoft.VCLibs.140.00.UWPDesktop"); }

    @{ Name="Microsoft.People"; Match="People"; License="People";
Dependencies=@("Microsoft.NET.Native.Framework.2.2", "Microsoft.NET.Native.Runtime.2.2", "Microsoft.VCLibs.140.
00"); }

    @{ Name="Microsoft.StorePurchaseApp"; Match="StorePurchaseApp"; License="StorePurchaseApp";
Dependencies=@("Microsoft.NET.Native.Framework.2.2", "Microsoft.NET.Native.Runtime.2.2", "Microsoft.VCLibs.140.
00"); }

    @{ Name="Microsoft.Todos"; Match="Todos"; License="Todos";
Dependencies=@("Microsoft.UI.Xaml.2.4", "Microsoft.NET.Native.Framework.2.2", "Microsoft.NET.Native.Runtime.2.2"
, "Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WebMediaExtensions"; Match="WebMediaExtensions"; License="WebMediaExtensions";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.Windows.Photos"; Match="Windows.Photos"; License="Windows.Photos";
Dependencies=@("Microsoft.UI.Xaml.2.4", "Microsoft.NET.Native.Framework.2.2", "Microsoft.NET.Native.Runtime.2.2"
, "Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WindowsCalculator"; Match="WindowsCalculator"; License="WindowsCalculator";
Dependencies=@("Microsoft.UI.Xaml.2.4", "Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.windowscommunicationsapps";
Match="WindowsCommunicationsApps"; License="WindowsCommunicationsApps";
Dependencies=@("Microsoft.UI.Xaml.2.7", "Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.WindowsSoundRecorder";
Match="WindowsSoundRecorder"; License="WindowsSoundRecorder";
Dependencies=@("Microsoft.UI.Xaml.2.3", "Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.Xbox.TCUI"; Match="Xbox.TCUI"; License="Xbox.TCUI";
Dependencies=@("Microsoft.NET.Native.Framework.2.2", "Microsoft.NET.Native.Runtime.2.2", "Microsoft.VCLibs.140.
00"); }

    @{ Name="Microsoft.XboxGameOverlay"; Match="XboxGameOverlay"; License="XboxGameOverlay";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.XboxGamingOverlay"; Match="XboxGamingOverlay"; License="XboxGamingOverlay";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.XboxIdentityProvider"; Match="XboxIdentityProvider"; License="XboxIdentityProvider";
Dependencies=@("Microsoft.NET.Native.Framework.2.2", "Microsoft.NET.Native.Runtime.2.2", "Microsoft.VCLibs.140.
00"); }

    @{ Name="Microsoft.XboxSpeechToTextOverlay";
Match="XboxSpeechToTextOverlay"; License="XboxSpeechToTextOverlay";
Dependencies=@("Microsoft.VCLibs.140.00"); }

    @{ Name="Microsoft.YourPhone"; Match="YourPhone"; License="YourPhone";
Dependencies=@("Microsoft.NET.Native.Framework.2.2", "Microsoft.NET.Native.Runtime.2.2", "Microsoft.VCLibs.140.
00", "Microsoft.VCLibs.140.00.UWPDesktop"); }

    @{ Name="Microsoft.ZuneVideo"; Match="ZuneVideo"; License="ZuneVideo";
Dependencies=@("Microsoft.UI.Xaml.2.7", "Microsoft.VCLibs.140.00"); }

    @{ Name="MicrosoftCorporationII.QuickAssist"; Match="QuickAssist"; License="QuickAssist";
Dependencies=@(); }

```



```

        @{ Name="MicrosoftWindows.Client.WebExperience"; Match="WebExperience";License="WebExperience";
Dependencies=@("Microsoft.VCLibs.140.00"); }

        @{ Name="Microsoft.MinecraftEducationEdition";
Match="MinecraftEducationEdition";License="MinecraftEducationEdition";
Dependencies=@("Microsoft.VCLibs.140.00.UWPDesktop"); }

        @{ Name="Microsoft.Whiteboard"; Match="Whiteboard";License="Whiteboard";
Dependencies=@("Microsoft.NET.Native.Framework.2.2","Microsoft.NET.Native.Runtime.2.2","Microsoft.VCLibs.140.
00"); }

        @{ Name="Microsoft.RawImageExtension"; Match="RawImageExtension"; License="RawImageExtension";
Dependencies=@(); }

    )

}

$Allow_Install_App = @()

ForEach ($item in $Pre_Config_Rules.Edition) {

    if ($item.Name -contains $Current_Edition_Version) {

        Write-host "`n  Match to: "-NoNewline; Write-host $Current_Edition_Version -ForegroundColor Green

        $Allow_Install_App = $item.Apps

        break

    }

}

Write-host "`n  The app to install ( $($Allow_Install_App.Count) item )" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($item in $Allow_Install_App) {

    Write-host "  $($item)" -ForegroundColor Green

}

Function Match_InBox_Apps_Install_Pack

{

    param ( $NewPath )

    $NewArch = $Arch

    $NewArchC = $Arch.Replace("AMD64", "x64")

    $NewArchCTag = $Arch.Replace("AMD64", "x64")

    if ($Arch -eq "arm64") { $NewArchCTag = "arm" }

    if ($Pre_Config_Rules.Rule.Count -gt 0) {

        ForEach ($itemInBoxApps in $Pre_Config_Rules.Rule){

            $InstallPacker = ""

            $InstallPackerCert = ""

            $SearchNewStructure = $itemInBoxApps.Match.Replace("{ARCH}", $NewArch).Replace("{ARCHC}",

```



```

$NewArchC).Replace("{ARCHTag}", $NewArchCTag)

        $SearchNewLicense = $itemInBoxApps.License.Replace("{ARCH}", $NewArch).Replace("{ARCHC}",
$NewArchC).Replace("{ARCHTag}", $NewArchCTag)

        Get-ChildItem -Path $NewPath -Filter "*$($SearchNewStructure)*" -Include "*.appx", "*.appxbundle",
"**.msixbundle" -Recurse -Force -ErrorAction SilentlyContinue | ForEach-Object {

            if (Test-Path -Path $_.FullName -PathType Leaf) {

                $InstallPacker = $_.FullName

                Get-ChildItem -Path $NewPath -Filter "*$($SearchNewLicense)*" -Include *.xml -Recurse -Force -ErrorAction
SilentlyContinue | ForEach-Object {

                    $InstallPackerCert = $_.FullName

                }

                $Script:InBoxAppx += @{

                    Name      = $itemInBoxApps.Name;

                    Depend    = $itemInBoxApps.Dependencies;

                    Search     = $SearchNewStructure;

                    InstallPacker = $InstallPacker;

                    Certificate = $InstallPackerCert

                    CertificateRule = $SearchNewLicense

                }

                return

            }

        }

    }

}

Write-host "`n  InBox Apps: Installation packages, automatic search for full disk or specified paths" -ForegroundColor
Yellow

Write-host "  $('-' * 80)"

$Script:InBoxAppx = @()

if ($ISO -eq "Auto") {

    Get-PSDrive -PSProvider FileSystem -ErrorAction SilentlyContinue | ForEach-Object {

        $AppPath = Join-Path -Path $_.Root -ChildPath "packages" -ErrorAction SilentlyContinue

        Match_InBox_Apps_Install_Pack -NewPath $AppPath

    }

} else {

    Match_InBox_Apps_Install_Pack -NewPath $ISO

```

```

}

Write-host "  Search Complete" -ForegroundColor Green

Write-host "`n  Inbox Apps: Installer Match Results" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

if ($Script:InBoxAppx.Count -gt 0) {

    Write-host "    Match successful" -ForegroundColor Green

} else {

    Write-host "    Failed match" -ForegroundColor Red

    return

}

Write-host "`n  Inbox Apps: Details of the application to be installed ( $($Script:InBoxAppx.Count) item )" -
ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($Rule in $Script:InBoxAppx) {

    Write-host "    Apps name: " -NoNewline; Write-host $Rule.Name -ForegroundColor Yellow

    Write-host "    Apps installer: " -NoNewline; Write-host $Rule.InstallPacker -ForegroundColor Yellow

    Write-host "    License: " -NoNewline; Write-host $Rule.Certificate -ForegroundColor Yellow

    Write-host ""

}

Write-host "`n  Inbox Apps: Installation" -ForegroundColor Yellow

Write-host "  $('-' * 80)"

ForEach ($Rule in $Script:InBoxAppx) {

    Write-host "    Name: " -NoNewline; Write-host $Rule.Name -ForegroundColor Yellow

    Write-host "    $('-' * 80)"

    if($Allow_Install_App -contains $Rule.Name) {

        Write-host "      Search for apps: " -NoNewline; Write-host $Rule.InstallPacker -ForegroundColor Yellow

        Write-host "      Search for License: " -NoNewline; Write-host $Rule.Certificate -ForegroundColor Yellow

        if (Test-Path -Path $Rule.InstallPacker -PathType Leaf) {

            if (Test-Path -Path $Rule.Certificate -PathType Leaf) {

                Write-host "        License: " -NoNewline

                Write-host $Rule.Certificate -ForegroundColor Yellow

                Write-host "        With License".PadRight(22) -NoNewline -ForegroundColor Green

                Write-host "        Installing".PadRight(22) -NoNewline

                try {

                    Add-AppxProvisionedPackage -Path $Mount -PackagePath $Rule.InstallPacker -LicensePath $Rule.Certificate

```

```

-ErrorAction SilentlyContinue | Out-Null

        Write-Host "Done`n" -ForegroundColor Green

    } catch {

        Write-Host "Failed" -ForegroundColor Red

        Write-Host "  $($_)`n" -ForegroundColor Red

    }

} else {

    Write-host "  No License".PadRight(22) -NoNewline -ForegroundColor Red

    Write-host "  Installing".PadRight(22) -NoNewline

    try {

        Add-AppxProvisionedPackage -Path $Mount -PackagePath $Rule.InstallPacker -SkipLicense -ErrorAction
        SilentlyContinue | Out-Null

        Write-Host "Done`n" -ForegroundColor Green

    } catch {

        Write-Host "Failed" -ForegroundColor Red

        Write-Host "  $($_)`n" -ForegroundColor Red

    }

}

} else {

    Write-host "  The installation package does not exist" -ForegroundColor Red

}

} else {

    Write-host "  Skip the installation`n" -ForegroundColor Red

}

}

```

5.8. Region tag: delete

- After completing the installation of the InBox Apps application, the Region tag is no longer important and can be deleted or not deleted. Delete "Local Language Experience Package (LXPs), Simplified Chinese - China)" and uniquely identify the Region tag: **zh-CN**, can be changed to other Region tag.
- Install.Clear.Flag.ps1
 - [\Expand\Install\Install.Clear.Flag.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/Install.Clear.Flag.ps1
- Copy the code

```

$Lang = "zh-CN"

Get-AppXProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" | Foreach-object {

    if ($_.DisplayName -Like "*LanguageExperiencePack*${$Lang}*") {

        Write-host " ${_.DisplayName}"; Write-Host "  Deleting ".PadRight(22) -NoNewline

        try {

            Remove-AppxProvisionedPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackageName $_.PackageName -
ErrorAction SilentlyContinue | Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

        }

    }

}

}

```

5.9. InBox Apps: optimization

After the app is installed, provisioning the Appx package should be optimized to reduce the app's disk usage by replacing identical files with hard links, only for offline images.

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /Optimize-ProvisionedAppxPackages
```

6. Cumulative updates

- When upgrading different versions or old versions to the latest version, you need to add the "Function Enablement Package" first before adding the latest cumulative update;
- After adding a language pack, you can install the same cumulative update as the initial version to resolve a known issue where the "Components: All packages installed in the image" status is not refreshed after installation;
- To stay up to date, it is recommended that you download the latest version.

6.1. Initial version

6.1.1. How to download

Cumulative update [KB5016632](#) is no longer searchable from <https://www.catalog.update.microsoft.com/Search.aspx?q=KB5016632>

6.1.1.1. Select any website and open:

6.1.1.1.1. <https://uupdump.net>

6.1.1.1.2. <https://uup.ee>

6.1.1.1.3. <https://osdump.com>

6.1.1.2. After opening, search for keywords: [22621.382](#), select from the search results: [Windows 11, version 22H2 \(22621.382\) amd64](#) and [Windows 11, version 22H2 \(22621.382\) arm64](#)

- 6.1.1.3. After opening, select "All files";
- 6.1.1.4. Search for: [KB5016632](#) in the "All Files" page, download:
- [Windows11.0-KB5016632-x64.cab](#)
 - [Windows11.0-KB5016632-x64.psf](#)
- 6.1.1.5. Cumulative updates: Merging
- 6.1.1.5.1. Go to <https://github.com/abbodi1406/WHd/tree/master/scripts> After downloading [PSFX_Repack_6.zip](#)
- 6.1.1.5.2. After downloading, unzip it to: [D:\PSFX_Repack_6](#)
- 6.1.1.5.3. Copy [Windows11.0-KB5016632-x64.cab](#), [Windows11.0-KB5016632-x64.psf](#) to: [D:\PSFX_Repack_6](#)
- 6.1.1.5.4. After running: [psfx2cab_GUI.cmd](#), you will get a new file:
- [Windows11.0-KB5016632-x64-full_psf.cab](#)
- 6.1.1.5.5. Save [Windows11.0-KB5016632-x64-full_psf.cab](#) to:
- [D:\OS_11_Custom\Install\Install\Update\Windows11.0-KB5016632-x64-full_psf.cab](#)

6.1.2. Add

```
$KBPath = "D:\OS_11_Custom\Install\Install\Update\Windows11.0-KB5016632-x64-full_psf.cab"
```

```
Add-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.2. Other Version

Check "[Windows 11 version information](#)", for example, download cumulative update: [KB5035853](#), Version: [22H2.3296](#), go to the download page: <https://www.catalog.update.microsoft.com/Search.aspx?q=KB5035853>, download and save to: [D:\OS_11_Custom\Install\Install\Update](#), or download through direct connection, select download according to the architecture:

6.2.1. x64, default

- Direct download

https://catalog.sf.dl.delivery.mp.microsoft.com/filestreamingservice/files/594b22d5-84c3-4665-bdc7-3167c91759b9/public/windows11.0-kb5035853-x64_8ca1a9a646dbe25c071a8057f249633a61929efa.msu

- Add to

```
$KBPath = "D:\OS_11_Custom\Install\Install\Update\windows11.0-kb5035853-x64_8ca1a9a646dbe25c071a8057f249633a61929efa.msu"
```

```
Add-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.2.2. Arm64

- Direct download

<https://catalog.sf.dl.delivery.mp.microsoft.com/filestreamingservice/files/72ba502a-7982-471c-aad2->

[355efddbff61/public/windows11.0-kb5035853-arm64_076c009bca80cfa85272bd50d65951c2f663fcc5.msu](https://www.microsoft.com/softwareupdates/details/355efddbff61/public/windows11.0-kb5035853-arm64_076c009bca80cfa85272bd50d65951c2f663fcc5.msu)

- Add to

```
$KBPath = "D:\OS_11_Custom\Install\Install\Update\windows11.0-kb5035853-arm64_076c009bca80cfa85272bd50d65951c2f663fcc5.msu"
```

```
Add-WindowsPackage -Path "D:\OS_11_Custom\Install\Install\Mount" -PackagePath $KBPath
```

6.3. Solidify Updated

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /Image:"D:\OS_11_Custom\Install\Install\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

6.3.1. Clean components after curing and updating

```
$Mount = "D:\OS_11_Custom\Install\Install\Mount"
```

```
Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {
```

```
    if ($_.PackageState -eq "Superseded") {
```

```
        Write-Host "  $($_.PackageName)" -ForegroundColor Green
```

```
        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null
```

```
    }
```

```
}
```

7. Drive

8. Deployment engine: Add

- Learn "Deployment Engine", if added to ISO installation media, can skip adding to mounted.
- After adding the deployment engine, continue at the current location.

9. Health

Before saving, check whether it is damaged. If the health status is abnormal, stop saving.

```
Repair-WindowsImage -Path "D:\OS_11_Custom\Install\Install\Mount" -ScanHealth
```

10. Replace WinRE.wim

WinRE.wim in all index numbers in Install.wim has been replaced in batches. Please skip this step.

```
$WinRE = "D:\OS_11_Custom\Install\Install\Update\Winlib\WinRE.wim"
```

```
$CopyTo = "D:\OS_11_Custom\Install\Install\Mount\Windows\System32\Recovery"
```

```
Copy-Item -Path $WinRE -Destination $CopyTo -Force
```

11. Save image: Install.wim

```
Save-WindowImage -Path "D:\OS_11_Custom\Install\Install\Mount"
```

12. Unmount image: Install.wim

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowImage -Path "D:\OS_11_Custom\Install\Install\Mount" -Discard
```

LOOP OPERATING AREA, END.

13. How to batch replace WinRE.wim in all index numbers in Install.wim

13.1. Obtain WimLib

After going to the official website of <https://wimlib.net>, select a different version: [arm64](#), [x64](#), [x86](#), and extract it to: [D:Wimlib](#) after downloading

13.2. How to extract and update WinRE.wim in Install.wim

13.2.1. Extract the WinRE.wim file Install.wim from Install.wim

- Install.WinRE.Extract.ps1
 - [\Expand\Install\Install.WinRE.Extract.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/Install.WinRE.Extract.ps1

- Copy the code

```
$Arguments = @(
    "extract",
    "D:\OS_11\sources\install.wim", "1",
    "\"Windows\System32\Recovery\Winre.wim",
    "--dest-dir=\""D:\OS_11_Custom\Install\Install\Update\Winlib\""
)

New-Item -Path "D:\OS_11_Custom\Install\Install\Update\Winlib" -ItemType Directory -ea SilentlyContinue

Start-Process -FilePath "d:\wimlib\wimlib-imagex.exe" -ArgumentList $Arguments -wait -nonewwindow
```

13.2.2. Get all index numbers of Install.wim and replace the old WinRE.wim

- Install.WinRE.Replace.wim.ps1
 - [\Expand\Install\Install.WinRE.Replace.wim.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/Install.WinRE.Replace.wim.ps1

- Copy the code

```

Get-WindowsImage -ImagePath "D:\OS_11\sources\install.wim" -ErrorAction SilentlyContinue | ForEach-Object {

    Write-Host "  Image name: " -NoNewline; Write-Host $_.ImageName -ForegroundColor Yellow

    Write-Host "  The index number: " -NoNewline; Write-Host $_.ImageIndex -ForegroundColor Yellow

    Write-Host "`n  Replacement "

    $Arguments = @(

        "update",

        "D:\OS_11\sources\install.wim", $_.ImageIndex,

        "--command=""add 'D:\OS_11_Custom\Install\Install\Update\Winlib\WinRE.wim'
'\Windows\System32\Recovery\WinRe.wim'""""

    )

    Start-Process -FilePath "d:\wimlib\wimlib-imagex.exe" -ArgumentList $Arguments -wait -nonewwindow

    Write-Host "  Finish`n" -ForegroundColor Green

}

```

14. Rebuilding Install.wim reduces file size

- Install.Rebuild.wim.ps1
 - [\Expand\Install\Install.Rebuild.wim.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/Install/Install.Rebuild.wim.ps1

- Copy the code

```

$InstallWim = "D:\OS_11\sources\install.wim"

Get-WindowsImage -ImagePath $InstallWim -ErrorAction SilentlyContinue | ForEach-Object {

    Write-Host "  Image name: " -NoNewline; Write-Host $_.ImageName -ForegroundColor Yellow

    Write-Host "  The index number: " -NoNewline; Write-Host $_.ImageIndex -ForegroundColor Yellow

    Write-Host "`n  Under reconstruction".PadRight(28) -NoNewline

    Export-WindowsImage -SourceImagePath $InstallWim -SourceIndex $_.ImageIndex -DestinationImagePath "$($InstallWim).New" -
    CompressionType max | Out-Null

    Write-Host "Finish`n" -ForegroundColor Green

}

if (Test-Path "$($InstallWim).New" -PathType Leaf) {

    Remove-Item -Path $InstallWim

    Move-Item -Path "$($InstallWim).New" -Destination $InstallWim

    Write-Host "Finish" -ForegroundColor Green

} else {

    Write-host "Failed" -ForegroundColor Red

}

```


III Custom encapsulation boot.wim

1. View Boot.wim details

Image name, image description, image size, architecture, version, index number, etc.

```
$ViewFile = "D:\OS_11\Sources\Boot.wim"
```

```
Get-WindowsImage -ImagePath $ViewFile | Foreach-Object { Get-WindowsImage -ImagePath $ViewFile -index $_.ImageIndex }
```

2. Specify the path to mount Boot.wim

```
New-Item -Path "D:\OS_11_Custom\Boot\Boot\Mount" -ItemType directory -ea SilentlyContinue
```

3. Start mounting Boot.wim

Default index number: 2

```
Mount-WindowsImage -ImagePath "D:\OS_11\sources\boot.wim" -Index "2" -Path "D:\OS_11_Custom\Boot\Boot\Mount"
```

4. Language pack: Boot

- Automatically install language packs: Get "Component: All installed packages in the image" and match them. After matching the corresponding names, install the local corresponding language pack files, View the report "[Language installation package for Boot.wim](#)".
- When adding languages, different schema versions must be corresponded, and if not, errors are reported during the addition process.

4.1. Language pack: Add

- Boot.Instl.lang.ps1
 - [\Expand\Boot\Boot.Instl.lang.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.11/22H2/Expand/Boot/Boot.Instl.lang.ps1

- Copy the code

```
$Mount = "D:\OS_11_Custom\Boot\Boot\Mount"

$Sources = "D:\OS_11_Custom\Boot\Boot\Language\Add\zh-CN"

$Initl_install_Language_Component = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    $Initl_install_Language_Component += $_.PackageName

}

Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\WinPE-FontSupport-zh-CN.cab"

$Language_List = @(

    @{ Match = "*WinPE*Setup*Client*Package*"; File = "WINPE-SETUP-CLIENT_zh-CN.CAB"; }

    @{ Match = "*WinPE*Setup*Package*"; File = "WinPE-Setup_zh-CN.cab"; }

    @{ Match = "*WinPE-LanguagePack-Package*"; File = "lp.cab"; }

    @{ Match = "*SecureStartup*"; File = "winpe-securestartup_zh-CN.cab"; }
```

```

@{ Match = "*ATBroker*"; File = "winpe-atbroker_zh-CN.cab"; }

@{ Match = "*AudioCore*"; File = "winpe-audiocore_zh-CN.cab"; }

@{ Match = "*AudioDrivers*"; File = "winpe-audiodrivers_zh-CN.cab"; }

@{ Match = "*EnhancedStorage*"; File = "winpe-enhancedstorage_zh-CN.cab"; }

@{ Match = "*Narrator*"; File = "winpe-narrator_zh-CN.cab"; }

@{ Match = "*scripting*"; File = "winpe-scripting_zh-CN.cab"; }

@{ Match = "*Speech-TTS*"; File = "winpe-speech-tts_zh-CN.cab"; }

@{ Match = "*srh*"; File = "winpe-srh_zh-CN.cab"; }

@{ Match = "*srt*"; File = "winpe-srt_zh-CN.cab"; }

@{ Match = "*wds-tools*"; File = "winpe-wds-tools_zh-CN.cab"; }

@{ Match = "*-WMI-Package*"; File = "winpe-wmi_zh-CN.cab"; }

)

ForEach ($Rule in $Language_List) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $Initl_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline

            Write-host "$($Sources)\$($Rule.File)" -ForegroundColor Green

            Write-Host "  Installing ".PadRight(22) -NoNewline

            try {

                Add-WindowsPackage -Path $Mount -PackagePath "$($Sources)\$($Rule.File)" | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

            }

            break

        }

    }

}

```

4.2. Offline image language: change

4.2.1. Change default language, regional settings, and other international settings

Region: **zh-CN**

```
Dism /Image:"D:\OS_11_Custom\Boot\Boot\Mount" /Set-AllIntl:"zh-CN"
```

4.2.2. View available language settings

```
Dism /Image:"D:\OS_11_Custom\Boot\Boot\Mount" /Get-Intl
```

4.3. Language pack: Removed

- After you add languages, if you want to deploy to a non-English locale, you can save space by removing the English language component. When you remove a language, uninstall the language components in the reverse order in which you added them.
- After adding the Chinese, delete "English - United States" in reverse, the Region tag: **en-US**, you need to extract the language pack in advance
- `Boot.Del.Specified.lang.Tag.ps1`
 - [\Expand\Boot\Boot.Del.Specified.lang.Tag.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.11/22H2/Expand/Boot/Boot.Del.Specified.lang.Tag.ps1

- Copy the code

```
$Lang = "en-US"
```

```
$Mount = "D:\OS_11_Custom\Boot\Boot\Mount"
```

```
$Sources = "D:\OS_11_Custom\Boot\Boot\Language\Del\en-US"
```

```
$Initl_install_Language_Component = @()
```

```
Get-WindowsPackage -Path $Mount | ForEach-Object { $Initl_install_Language_Component += $_.PackageName }
```

```
$Language = @(
```

```
    @{ Match = "*WordPad*wow64*"; File = "Microsoft-Windows-WordPad-FoD-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*WordPad*amd64*"; File = "Microsoft-Windows-WordPad-FoD-  
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*WMIC*FoD*Package*wow64*"; File = "Microsoft-Windows-WMIC-FoD-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*WMIC*FoD*Package*amd64*"; File = "Microsoft-Windows-WMIC-FoD-  
Package~31bf3856ad364e35~AMD64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*StepsRecorder*wow64*"; File = "Microsoft-Windows-StepsRecorder-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*StepsRecorder*amd64*"; File = "Microsoft-Windows-StepsRecorder-  
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*Printing*PMCPPC*amd64*"; File = "Microsoft-Windows-Printing-PMCPPC-FoD-  
Package~31bf3856ad364e35~AMD64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*PowerShell*wow64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-  
Package~31bf3856ad364e35~wow64~$( $Lang)~.cab"; }
```

```
    @{ Match = "*PowerShell*amd64*"; File = "Microsoft-Windows-PowerShell-ISE-FOD-  
Package~31bf3856ad364e35~amd64~$( $Lang)~.cab"; }
```

```

@{ Match = "*MediaPlayer*wow64*"; File = "Microsoft-Windows-MediaPlayer-Package-wow64-$(Lang).cab"; }

@{ Match = "*MediaPlayer*amd64*"; File = "Microsoft-Windows-MediaPlayer-Package-AMD64-$(Lang).cab"; }

@{ Match = "*Notepad*wow64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~wow64~$(Lang)~.cab"; }

@{ Match = "*Notepad*amd64*"; File = "Microsoft-Windows-Notepad-System-FoD-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

@{ Match = "*InternetExplorer*"; File = "Microsoft-Windows-InternetExplorer-Optional-
Package~31bf3856ad364e35~AMD64~$(Lang)~.cab"; }

@{ Match = "*TextToSpeech*"; File = "Microsoft-Windows-LanguageFeatures-TextToSpeech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

@{ Match = "*LanguageFeatures-Speech*"; File = "Microsoft-Windows-LanguageFeatures-Speech-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

@{ Match = "*OCR*"; File = "Microsoft-Windows-LanguageFeatures-OCR-$(Lang)-Package~31bf3856ad364e35~amd64~~.cab"; }

@{ Match = "*Handwriting*"; File = "Microsoft-Windows-LanguageFeatures-Handwriting-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

@{ Match = "*LanguageFeatures-Basic*"; File = "Microsoft-Windows-LanguageFeatures-Basic-$(Lang)-
Package~31bf3856ad364e35~amd64~~.cab"; }

@{ Match = "*Client-LanguagePack-Package*"; File = "Microsoft-Windows-Client-Language-Pack_x64_$(Lang).cab"; }

)

ForEach ($Rule in $Language) {

    Write-host "`n Rule name: $($Rule.Match)" -ForegroundColor Yellow; Write-host "  $('-' * 80)"

    ForEach ($Component in $InitL_install_Language_Component) {

        if ($Component -like "*$($Rule.Match)*$(Lang)*") {

            Write-host "  Component name: " -NoNewline

            Write-host $Component -ForegroundColor Green

            Write-host "  Language pack file: " -NoNewline

            Write-host "$($Sources)\ $($Rule.File)" -ForegroundColor Green

            Write-Host "  Deleting ".PadRight(22) -NoNewline

            try {

                Remove-WindowsPackage -Path $Mount -PackagePath "$($Sources)\ $($Rule.File)" -ErrorAction SilentlyContinue | Out-Null

                Write-host "Finish" -ForegroundColor Green

            } catch {

                Write-host "Failed" -ForegroundColor Red

                Write-host "  $('_)" -ForegroundColor Red

            }

            break

        }

    }

}

```

```

    }

}

$InitlClearLanguagePackage = @()

Get-WindowsPackage -Path $Mount | ForEach-Object {

    if ($_.PackageName -like "*${$Lang}*") {

        $InitlClearLanguagePackage += $_.PackageName

    }

}

if ($InitlClearLanguagePackage.count -gt 0) {

    ForEach ($item in $InitlClearLanguagePackage) {

        Write-Host "`n $($item)" -ForegroundColor Green

        Write-Host "  Deleting ".PadRight(22) -NoNewline

        try {

            Remove-AppxProvisionedPackage -Path $Mount -PackageName $item -ErrorAction SilentlyContinue | Out-Null

            Write-host "Finish" -ForegroundColor Green

        } catch {

            Write-host "Failed" -ForegroundColor Red

            Write-host "  ${$_}" -ForegroundColor Red

        }

    }

}

```

4.4. Components: All packages installed in the image

4.4.1. View

```
Get-WindowsPackage -Path "D:\OS_11_Custom\Boot\Boot\Mount" | Out-GridView
```

4.4.2. Export to csv

```

$SaveTo = "D:\OS_11_Custom\Boot\Boot\Report.${(Get-Date -Format "yyyyMMddHHmmss")}.csv"

Get-WindowsPackage -Path "D:\OS_11_Custom\Boot\Boot\Mount" | Export-CSV -NoType -Path $SaveTo

Write-host $SaveTo -ForegroundColor Green

```

4.5. Language: Repair

4.5.1. Extract

Open: [D:\OS_11_Custom\Install\Install\Language\Add\zh-CN\Microsoft-Windows-Client-Language-Pack_x64_zh-CN.cab](#), enter the directory: [Setup\sources\zh-cn\cli](#), and copy the following files to the deskto:

4.5.1.1. arunres.dll.mui

4.5.1.2. spwizres.dll.mui

4.5.1.3. w32uires.dll.mui

4.5.2. Copy

Copy the extracted files to: D:\OS_11_Custom\Boot\Boot\Mount\sources\zh-CN

4.6. Language packs: sync to ISO installer

```
Copy-Item -Path "D:\OS_11_Custom\Boot\Boot\Mount\sources\zh-CN" -Destination "D:\OS_11\sources\zh-CN" -Recurse -Force
```

4.7. Regenerate Lang.ini

After regeneration, you can adjust the "Installation Interface", the order when selecting "Language", open lang.ini, the default preferred value = 3, non-default value = 2.

4.7.1. Regenerate the mounted directory lang.ini

Regenerated Lang.ini file location: D:\OS_11_Custom\Boot\Boot\Mount\Sources\lang.ini

```
Dism /image:"D:\OS_11_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_11_Custom\Boot\Boot\Mount"
```

4.7.2. After regenerating lang.ini, sync to the installer

Regenerated Lang.ini file location: D:\OS_11\Sources\lang.ini

```
Dism /image:"D:\OS_11_Custom\Boot\Boot\Mount" /gen-langini /distribution:"D:\OS_11"
```

5. Cumulative updates

To prepare the cumulative updates file available, change the example file name: KB_Boot.cab

5.1. Add

```
$KBPath = "D:\OS_11_Custom\Boot\Boot\Update\KB_Boot.cab"
```

```
Add-WindowsPackage -Path "D:\OS_11_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.2. Delete

```
$KBPath = "D:\OS_11_Custom\Boot\Boot\Update\KB_Boot.cab"
```

```
Remove-WindowsPackage -Path "D:\OS_11_Custom\Boot\Boot\Mount" -PackagePath $KBPath
```

5.3. Solid update

It cannot be uninstalled after curing, which cleans the recovery image and resets the basis of any superseded components.

```
Dism /image:"D:\OS_11_Custom\Boot\Boot\Mount" /cleanup-image /StartComponentCleanup /ResetBase
```

5.3.1. Clean components after curing and updating

```
$Mount = "D:\OS_11_Custom\Boot\Boot\Mount"

Get-WindowsPackage -Path $Mount -ErrorAction SilentlyContinue | ForEach-Object {

    if ($_.PackageState -eq "Superseded") {

        Write-Host " $_.PackageName" -ForegroundColor Green

        Remove-WindowsPackage -Path $Mount -PackageName $_.PackageName | Out-Null

    }

}
```

6. Drive

7. Other

7.1. Bypass TPM check during installation

- Boot.Bypass.TPM.ps1
 - [\Expand\Boot\Boot.Bypass.TPM.ps1](#)
 - https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging/tutorial/OS.11/22H2/Expand/Boot/Boot.Bypass.TPM.ps1

- Copy the code

```
$RegSystem = "D:\OS_11_Custom\Boot\Boot\Mount\Windows\System32\Config\SYSTEM"

$RandomGuid = [guid]::NewGuid()

Write-Host " HKLM:\$($RandomGuid)"

New-PSDrive -PSProvider Registry -Name OtherTasksTPM -Root HKLM -ErrorAction SilentlyContinue | Out-Null

Start-Process reg -ArgumentList "Load ""HKLM\$($RandomGuid)"" ""$($RegSystem)"" -Wait -WindowStyle Hidden -ErrorAction SilentlyContinue

New-Item "HKLM:\$($RandomGuid)\Setup\LabConfig" -force -ea SilentlyContinue | Out-Null

New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassCPUCheck" -Value 1 -PropertyType DWord -Force -ea SilentlyContinue | Out-Null

New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassStorageCheck" -Value 1 -PropertyType DWord -Force -ea SilentlyContinue | Out-Null

New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassRAMCheck" -Value 1 -PropertyType DWord -Force -ea SilentlyContinue | Out-Null

New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassTPMCheck" -Value 1 -PropertyType DWord -Force -ea SilentlyContinue | Out-Null

New-ItemProperty -LiteralPath "HKLM:\$($RandomGuid)\Setup\LabConfig" -Name "BypassSecureBootCheck" -Value 1 -PropertyType DWord -Force -ea SilentlyContinue | Out-Null

[gc]::collect()

Start-Process reg -ArgumentList "unload ""HKLM\$($RandomGuid)"" -Wait -WindowStyle Hidden -ErrorAction SilentlyContinue

Remove-PSDrive -Name OtherTasksTPM
```

8. Save image: Boot.wim

```
Save-WindowImage -Path "D:\OS_11_Custom\Boot\Boot\Mount"
```

9. Unmount image: Boot.wim

Close any applications that may be accessing files in the image, including File Explorer.

```
Dismount-WindowImage -Path "D:\OS_11_Custom\Boot\Boot\Mount" -Discard
```

IV Deployment engine

- Learn about "Automatically Adding Languages Installed in Windows Systems", learn: <https://github.com/ilikeyi/Multilingual>, how to download:
 - After entering the website, click "Code", "Download Compressed Package", and after the download is completed, you will get the [main.zip](#) compressed package file.
 - Go to the <https://github.com/ilikeyi/Multilingual/releases> download page, select the available version: [1.1.1.1](#), select the download source code format: zip, and get the [Multilingual-1.1.1.1.zip](#) compressed package file after the download is completed;
- Unzip the downloaded [main.zip](#) or [Multilingual-1.1.1.1.zip](#) to: [D:\Multilingual-1.1.1.1](#), and rename: [D:\Multilingual](#)
- Learn "[Unattended Windows Setup Reference](#)", Intervene in the installation process by leaving it unattended.

1. Add method

1.1. Add to ISO installation media

1.1.1. Unattended

1.1.1.1. Add to: [\[ISO\]:\Autounattend.xml](#)

Autounattend.xml interferes with the WinPE installer when booting an ISO installation.

Copy [D:\Multilingual_Learn\Unattend\Mul.Unattend.xml](#) to [D:\OS_11\Autounattend.xml](#)

```
Copy-Item "D:\Multilingual\_Learn\Unattend\Mul.Unattend.xml" -Destination "D:\OS_11\Autounattend.xml" -Force
```

1.1.1.2. Add to: [\[ISO\]:\Sources\Unattend.xml](#)

When mounting or unpacking an ISO, after running the [\[ISO\]:\Setup.exe](#) installer, [\[ISO\]:\Sources\Unattend.xml](#) will intervene in the installation process.

Copy [D:\Multilingual_Learn\Unattend\Mul.Unattend.xml](#) to [D:\OS_11\Sources\Unattend.xml](#)

```
Copy-Item "D:\Multilingual\_Learn\Unattend\Mul.Unattend.xml" -Destination "D:\OS_11\Sources\Unattend.xml" -Force
```

1.1.1.3. Add to: [\[ISO\]:\sources\\\$\OEM\\$\\\$\\$\Panther\unattend.xml](#)

Copy it to the system disk during the installation process, copy to: {system disk}\Windows\Panther\unattend.xml

1.1.1.3.1. Create \$OEM\$ path

```
New-Item -Path "D:\OS_11\sources\`$OEM$\`$$\Panther" -ItemType Directory
```


1.1.1.3.2. Copy

Copy D:\Multilingual\Learn\Unattend\Mul.Unattend.xml to
D:\OS_11\Sources\OEM\$\Panther\Unattend.xml

```
Copy-Item "D:\Multilingual\Learn\Unattend\Mul.Unattend.xml" -Destination  
"D:\OS_11\sources\`$OEM$\`$$\Panther\Unattend.xml" -Force
```

1.1.2. Deployment engine: add

Add "Automatically add installed languages for Windows systems" to D:\OS_11\sources\OEM\$\\$1\Yi\Engine in the directory.

1.1.2.1. Deployment Engine: Copy

Copy D:\Multilingual\Engine to D:\OS_11\Sources\OEM\$\\$1\Yi\Engine

```
Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_11\sources\`$OEM$\`$1\Yi\Engine" -Recurse -  
Force
```

1.1.2.2. Deployment engine: custom deployment tags

```
$Flag = @(

    "Is_Mark_Sync" # Allow global search and synchronization of deployment tags

    # Prerequisite deployment

    # "Auto_Update" # Allow automatic updates

    # "Use_UTF8" # Beta: Global language support using Unicode UTF-8

    "Disable_Network_Location_Wizard" # Network Location Wizard

    "Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks

    "Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature language  
packs

    "Disable_Cleanup_Unsed_Language" # Prevent cleaning of unused language packs

    "Prerequisites_Reboot" # Restart your computer

    # Complete first deployment

    # "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time

    # "Allow_First_Pre_Experience" # Allow first preview, as planned

    "Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted

    "Clear_Solutions" # Delete the entire solution

    "Clear_Engine" # Delete the deployment engine and keep the others

    # "First_Experience_Reboot" # Restart your computer

)

ForEach ($item in $Flag) {

    Write-host " $($item)" -ForegroundColor Green
```

```

New-Item -Path "D:\OS_11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -
ErrorAction SilentlyContinue | Out-Null

Out-File -FilePath "D:\OS_11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\$(Item)" -Encoding utf8 -
ErrorAction SilentlyContinue

}

```

1.2. Add to mounted

Through "[Custom encapsulation: Install.wim](#)", execute "[Start mounting Install.wim](#)" and mount to:

[D:\OS_11_Custom\Install\Install\Mount](#)

1.2.1. Unattended

Copy [D:\Multilingual\Learn\Unattend\Mul.Unattend.xml](#) to
[D:\OS_11_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

```

Copy-Item "D:\Multilingual\Learn\Unattend\Mul.Unattend.xml" -Destination
"D:\OS_11_Custom\Install\Install\Mount\Panther" -Force

```

1.2.2. Deployment engine: add

Add "[Automatically add languages installed on Windows systems](#)" to the
[D:\OS_11_Custom\Install\Install\Mount\Yi\Engine](#) directory.

1.2.2.1. Deployment Engine: Copy

Copy [D:\Multilingual\Engine](#) to [D:\OS_11_Custom\Install\Install\Mount\Yi\Engine](#)

```

Copy-Item "D:\Multilingual\Engine" -Destination "D:\OS_11_Custom\Install\Install\Mount\Yi\Engine" -
Recurse -Force

```

1.2.2.2. Deployment engine: custom deployment tags

```
$Flag = @(
```

```
"Is_Mark_Sync" # Allow global search and synchronization of deployment tags
```

```
# Prerequisite deployment
```

```
# "Auto_Update" # Allow automatic updates
```

```
# "Use_UTF8" # Beta: Global language support using Unicode UTF-8
```

```
"Disable_Network_Location_Wizard" # Network Location Wizard
```

```
"Disable_Cleanup_Appx_Tasks" # Appx Cleanup and maintenance tasks
```

```
"Disable_Cleanup_On_Demand_Language" # Prevent cleanup of unused on-demand feature language
packs
```

```
"Disable_Cleanup_Unsed_Language" # Prevent cleaning of unused language packs
```

```
"Prerequisites_Reboot" # Restart your computer
```

```
# Complete first deployment
```

```
# "Popup_Engine" # Allow the deployment engine main interface to pop up for the first time
```

```
# "Allow_First_Pre_Experience" # Allow first preview, as planned

"Reset_Execution_Policy" # Restore PowerShell execution policy: Restricted

"Clear_Solutions" # Delete the entire solution

"Clear_Engine" # Delete the deployment engine and keep the others

# "First_Experience_Reboot" # Restart your computer

)

ForEach ($item in $Flag) {

    Write-host "  $($item)" -ForegroundColor Green

    New-Item -Path "D:\OS_11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow" -ItemType Directory -
    ErrorAction SilentlyContinue | Out-Null

    Out-File -FilePath "D:\OS_11\sources\`$OEM$\`$1\Yi\Engine\Deploy\Allow\$( $item )" -Encoding utf8 -
    ErrorAction SilentlyContinue

}
```

2. Deployment Engine: Advanced

2.1. Deployment engine: adding process

After copying the deployment engine, you can add deployment tags to intervene in the installation process.

2.2. Unattended solution

When the customization is unattended, please modify it simultaneously if the following files exist:

- [D:\OS_11\Autounattend.xml](#)
- [D:\OS_11\Sources\Unattend.xml](#)
- [D:\OS_11\sources\\\$OEM\\$\\\$\\$\Panther\unattend.xml](#)
- [D:\OS_11_Custom\Install\Install\Mount\Panther\Unattend.xml](#)

2.2.1. Multilingual or monolingual

In multi-language and monolingual, you can switch between each other. When replacing, please replace all the same ones in the file.

2.2.1.1. Multi-language

```
<UILanguage>%OSDUILanguage%</UILanguage>

<InputLocale>%OSDInputLocale%</InputLocale>

<SystemLocale>%OSDSysLocale%</SystemLocale>

<UILanguage>%OSDUILanguage%</UILanguage>

<UILanguageFallback>%OSDUILanguageFallback%</UILanguageFallback>

<UserLocale>%OSDUserLocale%</UserLocale>
```

2.2.1.2. Monolingual

A single language needs to specify a Region tag, for example, specify a Region tag: **zh-CN**

```
<UILanguage>zh-CN</UILanguage>

<InputLocale>zh-CN</InputLocale>

<SystemLocale>zh-CN</SystemLocale>

<UILanguage>zh-CN</UILanguage>

<UILanguageFallback>zh-CN</UILanguageFallback>

<UserLocale>zh-CN</UserLocale>
```

2.2.2. User plan

By default, the self-created user **Administrator** is used and logged in automatically. It can be switched by modifying the following configuration: self-created or customized user.

2.2.2.1. Self-created user Administrator

By default, the self-created user: **Administrator** is used and logged in automatically, inserted between **<OOBE>** and **</OOBE>**.

```
<UserAccounts>

  <LocalAccounts>

    <LocalAccount wcm:action="add">

      <Password>

        <Value></Value>

        <PlainText>true</PlainText>

      </Password>

      <Description>Administrator</Description>

      <DisplayName>Administrator</DisplayName>

      <Group>Administrators</Group>

      <Name>Administrator</Name>

    </LocalAccount>

  </LocalAccounts>

</UserAccounts>

<AutoLogon>

  <Password>

    <Value></Value>

    <PlainText>true</PlainText>

  </Password>

  <Enabled>true</Enabled>
```

<Username>Administrator</Username>

</AutoLogon>

2.2.2.2. Custom user

After setting up a custom user and installing the system, in OOBE, you can choose settings such as local and online users.

2.2.2.2.1. Delete

Username: Removed from start <UserAccounts> to </UserAccounts>

Autologin: Remove from start <AutoLogon> to </AutoLogon>

2.2.2.2.2. Replace

From the beginning <OOBE> to </OOBE>

<OOBE>

<ProtectYourPC>3</ProtectYourPC>

<HideEULAPage>true</HideEULAPage>

<HideWirelessSetupInOOBE>true</HideWirelessSetupInOOBE>

</OOBE>

D. ISO

II Generate ISO

1. Download OScdimg

Select the Oscdimg version according to the architecture, and save it to: D:\ after downloading. To save in other paths, please enter the absolute path of OScdimg.exe;

1.1. x64

https://github.com/ilikeyi/solutions/raw/main/_Software/Oscdimg/amd64/oscdimg.exe

1.2. x86

https://github.com/ilikeyi/solutions/raw/main/_Software/Oscdimg/x86/oscdimg.exe

1.3. arm64

https://github.com/ilikeyi/solutions/raw/main/_Software/Oscdimg/arm64/oscdimg.exe

2. Use the oscdimg command line to generate an ISO file and save it to: D:\OS_11.iso

- ISO.ps1
 - \Expand\ISO.ps1

o https://github.com/ilikeyi/solutions/blob/main/_Learn/Packaging.tutorial/OS.11/22H2/Expand/ISO.ps1

- Copy the code

```
$Oscding = "D:\Oscding.exe"

$ISO = "D:\OS_11"

$Volume = "OS_11"

$SaveTo = "D:\OS_11.iso"

$Arguments = @("-m", "-o", "-u2", "-udfver102", "-l" "$($Volume)\"", "-bootdata:2#p0,e,b" "$($ISO)\boot\etfsboot.com" "#pEF,e,b" "$($ISO)\efi\microsoft\boot\efisys.bin\"", $ISO, $SaveTo)

Start-Process -FilePath $Oscding -ArgumentList $Arguments -wait -nonewwindow
```

III Bypass TPM installation check

1. Learn about: <https://github.com/AveYo/MediaCreationTool.bat/tree/main/bypass11> and download: [Quick_11_iso_esd_wim_TPM_toggle.bat](#)
2. Drag the [D:\OS_11.iso](#) file to [Quick_11_iso_esd_wim_TPM_toggle.bat](#), and "add" or "delete" the TPM installation check function in reverse order.

Chapter 2 Report

- Group abbreviations:
 - Group A: [Windows 11 Education](#), [Windows 11 Enterprise](#), [Windows 11 Pro](#), [Windows 11 Pro Education](#), [Windows 11 Pro for Workstations](#), [Windows 11 IoT Enterprise](#)
 - Group B: [Windows 11 Education N](#), [Windows 11 Enterprise N](#), [Windows 11 Pro N](#), [Windows 11 Pro Education N](#), [Windows 11 Pro N for Workstations](#)
 - Group C: [Windows 11 Home](#), [Windows 11 Home Single Language](#)
 - Group D: [Windows 11 Home N](#)

II Reports: Different versions

| | | |
|----|--|------------|
| 1. | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~~10.0.22621.382 | A, C |
| | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.317 | |
| 2. | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | A, C |
| | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | |
| 3. | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B |
| 4. | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | |
| 5. | Microsoft-OneCore-ApplicationModel-Sync-Desktop-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.317 | A, B, C, D |
| 6. | Microsoft-OneCore-DirectX-Database-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 7. | Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.382 | A, B, C, D |
| 8. | Microsoft-Windows-Ethernet-Client-Intel-E1i68x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 9. | Microsoft-Windows-Ethernet-Client-Intel-E2f68-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |

| | | |
|-----|---|------------|
| 10. | Microsoft-Windows-Ethernet-Client-Realtek-Rtcx21x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 11. | Microsoft-Windows-Ethernet-Client-Vmware-Vmxnet3-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 12. | Microsoft-Windows-FodMetadata-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 13. | Microsoft-Windows-Foundation-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 14. | Microsoft-Windows-Hello-Face-Package~31bf3856ad364e35~amd64~~10.0.22621.317 | A, B, C, D |
| 15. | Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~~11.0.22621.1 | A, B, C, D |
| | Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~en-US~11.0.22621.1 | A, B, C, D |
| 16. | Microsoft-Windows-Kernel-LA57-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.382 | A, B, C, D |
| 17. | Microsoft-Windows-LanguageFeatures-Basic-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 18. | Microsoft-Windows-LanguageFeatures-Handwriting-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 19. | Microsoft-Windows-LanguageFeatures-OCR-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 20. | Microsoft-Windows-LanguageFeatures-Speech-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 21. | Microsoft-Windows-LanguageFeatures-TextToSpeech-en-us-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 22. | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | A, B, C, D |
| 23. | Microsoft-Windows -Notepad-System-FoD-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | A, B, C, D |
| | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | A, B, C, D |
| 24. | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | A, B, C, D |
| 25. | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | A, B, C, D |
| | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | A, B, C, D |
| 26. | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | A, B, C, D |
| 27. | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | A, B, C, D |
| | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | A, B, C, D |
| 28. | Microsoft-Windows-TabletPCMath-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 29. | Microsoft-Windows-Wallpaper-Content-Extended-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 30. | Microsoft-Windows-Wifi-Client-Broadcom-Bcmpciedhd63-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 31. | Microsoft-Windows-Wifi-Client-Broadcom-Bcmwl63a-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 32. | Microsoft-Windows-Wifi-Client-Broadcom-Bcmwl63al-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 33. | Microsoft-Windows-Wifi-Client-Intel-Netwbw02-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 34. | Microsoft-Windows-Wifi-Client-Intel-Netwew00-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 35. | Microsoft-Windows-Wifi-Client-Intel-Netwew01-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 36. | Microsoft-Windows-Wifi-Client-Intel-Netwlv64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |

| | | |
|-----|--|------------|
| 37. | Microsoft-Windows-Wifi-Client-Intel-Netwns64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 38. | Microsoft-Windows-Wifi-Client-Intel-Netwsw00-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 39. | Microsoft-Windows-Wifi-Client-Intel-Netwtw02-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 40. | Microsoft-Windows-Wifi-Client-Intel-Netwtw04-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 41. | Microsoft-Windows-Wifi-Client-Intel-Netwtw06-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 42. | Microsoft-Windows-Wifi-Client-Intel-Netwtw08-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 43. | Microsoft-Windows-Wifi-Client-Intel-Netwtw10-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 44. | Microsoft-Windows-Wifi-Client-Marvel-Mrvlpcie8897-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 45. | Microsoft-Windows-Wifi-Client-Qualcomm-Athw8x-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 46. | Microsoft-Windows-Wifi-Client-Qualcomm-Athwnx-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 47. | Microsoft-Windows-Wifi-Client-Qualcomm-Qcamain10x64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 48. | Microsoft-Windows-Wifi-Client-Ralink-Netr28x-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 49. | Microsoft-Windows-Wifi-Client-Realtek-Rtl8187se-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 50. | Microsoft-Windows-Wifi-Client-Realtek-Rtl8192se-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 51. | Microsoft-Windows-Wifi-Client-Realtek-Rtl819xp-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 52. | Microsoft-Windows-Wifi-Client-Realtek-Rtl85n64-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 53. | Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 54. | Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan01-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 55. | Microsoft-Windows-Wifi-Client-Realtek-Rtlwlan13-FOD-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 56. | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.382 | A, B, C, D |
| | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621 | A, B, C, D |
| 57. | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | A, B, C, D |
| | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | A, B, C, D |
| 58. | Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~~10.0.22621.317 | A, B, C, D |
| | Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~en-US~10.0.22621.1 | A, B, C, D |
| 59. | Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~~10.0.22621.1 | A, B, C, D |
| | Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~en-US~10.0.22621.1 | A, B, C, D |
| 60. | OpenSSH-Client-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | A, B, C, D |
| 61. | Package_for_DotNetRollup_481~31bf3856ad364e35~amd64~~10.0.9065.6 | A, B, C, D |
| 62. | Package_for_RollupFix~31bf3856ad364e35~amd64~~22621.382.1.13 | A, B, C, D |
| 63. | Package_for_ServicingStack_378~31bf3856ad364e35~amd64~~22621.378.1.0 | A, B, C, D |

III Report: Language installation packages apply to Install.wim

| | | |
|----|---|------|
| 1. | Microsoft-Windows-MediaPlayer-Package-AMD64-zh-CN.cab | A, C |
| | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 | |

| | | |
|-----|--|------------|
| 2. | Microsoft-Windows-MediaPlayer-Package-wow64-zh-CN.cab | A, C |
| | Microsoft-Windows-MediaPlayer-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 | |
| 3. | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab | A, B |
| | Microsoft-Windows-Printing-PMCPPC-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 | |
| 4. | Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~AMD64~~.cab | A, B, C, D |
| | Microsoft-Windows-LanguageFeatures-Fonts-Hans-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | |
| 5. | Microsoft-Windows-Client-Language-Pack_x64_zh-CN.cab | A, B, C, D |
| | Microsoft-Windows-Client-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 | |
| 6. | Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~AMD64~zh-CN~.cab | A, B, C, D |
| | Microsoft-Windows-InternetExplorer-Optional-Package~31bf3856ad364e35~amd64~zh-CN~11.0.22621.1 | |
| 7. | Microsoft-Windows-LanguageFeatures-Basic-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab | A, B, C, D |
| | Microsoft-Windows-LanguageFeatures-Basic-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | |
| 8. | Microsoft-Windows-LanguageFeatures-Handwriting-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab | A, B, C, D |
| | Microsoft-Windows-LanguageFeatures-Handwriting-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | |
| 9. | Microsoft-Windows-LanguageFeatures-OCR-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab | A, B, C, D |
| | Microsoft-Windows-LanguageFeatures-OCR-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | |
| 10. | Microsoft-Windows-LanguageFeatures-Speech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab | A, B, C, D |
| | Microsoft-Windows-LanguageFeatures-Speech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | |
| 11. | Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-CN-Package~31bf3856ad364e35~AMD64~~.cab | A, B, C, D |
| | Microsoft-Windows-LanguageFeatures-TextToSpeech-zh-cn-Package~31bf3856ad364e35~amd64~~10.0.22621.1 | |
| 12. | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab | A, B, C, D |
| | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 | |
| 13. | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab | A, B, C, D |
| | Microsoft-Windows-Notepad-System-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 | |
| 14. | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab | A, B, C, D |
| | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 | |
| 15. | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~.cab | |
| | Microsoft-Windows-PowerShell-ISE-FOD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 | |
| 16. | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~AMD64~zh-CN~.cab | A, B, C, D |
| | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 | |
| 17. | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~.cab | A, B, C, D |
| | Microsoft-Windows-StepsRecorder-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 | |
| 18. | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab | A, B, C, D |
| | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1 | |
| 19. | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab | A, B, C, D |
| | Microsoft-Windows-WMIC-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1 | |

20.

Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~AMD64~zh-CN~.cab

A, B, C, D
- Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
21.

Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~.cab

A, B, C, D
- Microsoft-Windows-WordPad-FoD-Package~31bf3856ad364e35~wow64~zh-CN~10.0.22621.1

IV Report: Language installation packages apply to WinRE.wim

1.

WinPE-FontSupport-zh-CN.cab

Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.22621.1
2.

lp.cab

Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
3.

winpe-appxdeployment_zh-CN.cab

WinPE-AppxDeployment-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
4.

winpe-appxpackaging_zh-CN.cab

WinPE-AppxPackaging-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
5.

winpe-atbroker_zh-CN.cab

WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
6.

winpe-audiocore_zh-CN.cab

WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
7.

winpe-audiodrivers_zh-CN.cab

WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
8.

winpe-enhancedstorage_zh-CN.cab

WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
9.

winpe-hta_zh-CN.cab

WinPE-HTA-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
10.

winpe-narrator_zh-CN.cab

WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
11.

winpe-opcservices_zh-CN.cab

WinPE-OpcServices-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
12.

winpe-rejuv_zh-CN.cab

WinPE-Rejuv-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
13.

winpe-scripting_zh-CN.cab

WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
14.

winpe-securestartup_zh-CN.cab

WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
15.

winpe-speech-tts_zh-CN.cab

- WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
16. winpe-srh_zh-CN.cab
- WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
17. winpe-srt_zh-CN.cab
- WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
18. winpe-storagewmi_zh-CN.cab
- WinPE-StorageWMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
19. winpe-wds-tools_zh-CN.cab
- WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
20. winpe-wifi_zh-CN.cab
- WinPE-WiFi-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
21. winpe-windowsupdate_zh-CN.cab
- WinPE-WindowsUpdate-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
22. winpe-wmi_zh-CN.cab
- WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1

V Report: Language installation packages apply to Boot.wim

1. WinPE-FontSupport-zh-CN.cab
- Microsoft-Windows-WinPE-FontSupport-ZH-CN-Package~31bf3856ad364e35~amd64~~10.0.22621.1
2. lp.cab
- Microsoft-Windows-WinPE-LanguagePack-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
3. winpe-atbroker_zh-CN.cab
- WinPE-ATBroker-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
4. winpe-audiocore_zh-CN.cab
- WinPE-AudioCore-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
5. winpe-audiodrivers_zh-CN.cab
- WinPE-AudioDrivers-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
6. winpe-enhancedstorage_zh-CN.cab
- WinPE-EnhancedStorage-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
7. winpe-narrator_zh-CN.cab
- WinPE-Narrator-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
8. winpe-scripting_zh-CN.cab
- WinPE-Scripting-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
9. winpe-securestartup_zh-CN.cab
- WinPE-SecureStartup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1

10.

WINPE-SETUP-CLIENT_zh-CN.CAB

WinPE-Setup-Client-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
11.

WinPE-Setup_zh-CN.cab

WinPE-Setup-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
12.

winpe-speech-tts_zh-CN.cab

WinPE-Speech-TTS-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
13.

winpe-srh_zh-CN.cab

WinPE-SRH-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
14.

winpe-srt_zh-CN.cab

WinPE-SRT-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
15.

winpe-wds-tools_zh-CN.cab

WinPE-WDS-Tools-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1
16.

winpe-wmi_zh-CN.cab

WinPE-WMI-Package~31bf3856ad364e35~amd64~zh-CN~10.0.22621.1

Chapter 3

Common problem

- II

Clean all mounts to

Close any applications that may be accessing files in the image, including File Explorer.

Dismount-WindowsImage -Path "D:\OS_11_Custom\Install\Install\Mount" -Discard

Dismount-WindowsImage -Path "D:\OS_11_Custom\Install\WinRE\Mount" -Discard

Dismount-WindowsImage -Path "D:\OS_11_Custom\Boot\Boot\Mount" -Discard

- III

Fix the problem of abnormal mounting

1.

View mounted

Get-WindowsImage -Mounted

2.

Delete the DISM mount record saved in the registry

Remove-Item -Path "HKLM:\SOFTWARE\Microsoft\WIMMount\Mounted Images*" -Force -Recurse -ErrorAction SilentlyContinue

3.

Delete all resources associated with the corrupted mounted image

Clear-WindowsCorruptMountPoint

Dism /cleanup-wim

- IV

Clean directories

Remove-Item "D:\OS_11_Custom" -Force -Recurse

Remove-Item "D:\OS_11\Sources\`\$OEM\$" -Force -Recurse

Remove-Item -Path "D:\OS_11\Autounattend.xml" -Force

Remove-Item -Path "D:\OS_11\Sources\Unattend.xml" -Force

| | |
|-----------|--------------|
| Chapter 4 | Known issues |
| | None yet |



This copy packaging tutorial is part of Yi's Solutions content, learn more:

- Yi's official website | <https://fengyi.tel/solutions>
- Github | <https://github.com/ilikeyi/solutions>

Author: Yi

Email: 775159955@qq.com, ilikeyi@outlook.com

Document version: 1.2

Documentation model: Full version

Translation: Chinese to English version

Updated: 2024 - 8

Suggestions or feedback: <https://github.com/ilikeyi/solutions/issues>