



The SAGE Handbook of Social Network Analysis

The Development of Social Network Analysis – with an Emphasis on Recent Events

Contributors: Linton C. Freeman

Edited by: John Scott & Peter J. Carrington

Book Title: The SAGE Handbook of Social Network Analysis

Chapter Title: "The Development of Social Network Analysis – with an Emphasis on Recent Events"

Pub. Date: 2014

Access Date: January 2, 2019

Publishing Company: SAGE Publications Ltd

City: London

Print ISBN: 9781847873958


Online ISBN: 9781446294413

DOI: <http://dx.doi.org/10.4135/9781446294413.n3>

Print pages: 26-39

© 2014 SAGE Publications Ltd All Rights Reserved.

This PDF has been generated from SAGE Knowledge. Please note that the pagination of the online version will vary from the pagination of the print book.



Moreover, [Figure 3.3](#) also shows that, at that point, 98 percent of the citations were made within either the physics community or the social network community. For the most part, physicists ignored the earlier work by social network analysts. And social network analysts responded in kind.

Physicists were also quick to follow up on Barabási and Albert's work on degree distributions. According to Google Scholar, their first paper had received over 4,000 citations as of mid-November 2008. But practically none of those citations were produced by social network analysts.

It soon became evident that the physicists' interest in social networks was not going to be confined to small-world phenomena and degree distributions. Members of the physics community quickly began to explore other problems that had traditionally belonged to social network analysts. Nor was that interest restricted to physicists. At the same time, physicists succeeded in getting biologists and computer scientists involved in their efforts. Two main foci of this new thrust involved the study of cohesive groups, or what physicists call *communities*, and the study of the positions that nodes occupy in a network—particularly their centrality. I will review these foci in the next two sections.

Cohesive Groups or Communities

The notion of cohesive groups is foundational in sociology. Early sociologists (Tönnies, 1855/1936; Maine, 1861/1931; Durkheim, 1893/1964; Spencer, 1897; Cooley, 1909/1962) talked about little else. Their work provided an intuitive “feel” for groups, but it did not define groups in any systematic way.

When the social network perspective emerged, however, network analysts set out to specify groups in struc-

tural terms. Freeman and Webster (1994) described the observation behind this structural perspective on groups:

Whenever human association is examined, we see what can be described as thick spots—relatively unchanging clusters or collections of individuals who are linked by frequent interaction and often by sentimental ties. These are surrounded by thin areas where interaction does occur, but tends to be less frequent and to involve very little if any sentiment.

Thus, the social ties within a cohesive group will tend to be dense; most individuals in the group will be linked to a great many other group members. Moreover, those in-group ties will tend to display clustering—where, as described above, friends of friends are friends. In contrast, relatively few social ties will link members of different groups, and clustering will be relatively rare.

An early social network analyst, George Homans (1950: 84), spelled out the intuitive basis for the social network conception of cohesive groups:

A group is defined by the interactions of its members. If we say that individuals A, B, C, D, E, ... form a group, this will mean that at least the following circumstances hold. Within a given period of time, A interacts more often with B, C, D, E, ... than he does with M, N, L, O, P, ... whom we choose to consider outsiders or members of other groups. B also interacts more often with A, C, D, E, ... than he does with outsiders, and so on for the other members of the group. It is possible just by counting interactions to map out a group quantitatively distinct from others.

Over the years, network analysts have proposed dozens of models of cohesive groups. These models serve to define groups in structural terms and provide procedures to find groups in network data. They all try to capture something close to Homans's intuition in one way or another. Some of them represent groups in terms of on/off or binary links among actors (e.g., Luce and Perry, 1949; Mokken, 1979). Others represent them in terms of quantitative links that index the strength of ties linking pairs of actors (e.g., Sailer and Gaulin, 1984; Freeman, 1992).

Currently, then, we have a huge number of models of cohesive groups. Most of them were reviewed by Wasserman and Faust (1994). Some were algebraic (e.g., Breiger, 1974; Freeman and White, 1993), some were graph theoretic (e.g., Alba, 1973; Moody and White, 2003), some were built on probability theory (e.g., Frank, 1995; Skvortz and Faust, 1999), and some were based on matrix permutation (e.g., Beum and Brundage, 1950; Seary and Richards, 2003). All, however, were designed to specify the properties of groups in exact terms, to uncover group structure in network data, or both.

Over the years social network analysts have also drawn on various computational algorithms in an attempt to uncover groups. These include multidimensional scaling (Freeman et al., 1987; Arabie and Carroll, 1989); various versions of singular value decomposition, including principal components analysis and correspondence analysis (Levine, 1972; Roberts, 2000); hierarchical clustering (Breiger et al., 1975; Wasserman and Faust, 1994: 382–83); the max-cut min-flow algorithm (Zachary, 1977, Blythe, 2006); simulated annealing (Boyd, 1991: 223; Dekker, 2001); and the genetic algorithm (Freeman, 1993; Borgatti and Everett, 1997).

In social network research, the general tendency over the years has been to move from binary representations to representations in which the links between nodes take numeric values that represent the strengths of connections. At the same time social network analysts have gradually shifted from building algebraic and graph theoretic models to developing models grounded in probability theory. And, as time has passed, they have relied more often on the use of computational procedures to uncover groups.

A notable exception to this trend can be found in an article by Moody and White (2003). They used graph theory to define *structural cohesion*. They defined structural cohesion "... as the minimum number of actors who, if removed from a group, would disconnect the group." Then they went on to define *embeddedness* in terms

of a hierarchical nesting of cohesive structures. This approach represents a new and sophisticated version of the traditional social network model building.

Since the early 1970s, mathematicians and computer scientists had also been interested in groups or communities. They defined that interest in terms of *graph partitioning* (Fiedler, 1973, 1975; Parlett, 1980; Fiducia and Mattheyses, 1982; Glover, 1989, 1990; Pothén et al., 1990). Social network analysts recognized this tradition when the work by Glover was cited and integrated into the program UCInet (Borgatti et al., 1992). And in 1993 the link in the other direction was made when a team composed of an electrical engineer and a computer engineer, Wu and Leahy (1993), cited the work of a statistician and social network analyst, Hubert (1974). And in 2000 three computer scientists, Flake, Lawrence, and Giles (2000), cited the social network text by Scott (1992).

Until quite recently, however, these efforts did not stir up much interest in the physics community. Instead, the physicists turned to the procedures developed in social network analysis. Girvan and Newman (2002) adapted the social network model of betweenness centrality (Freeman, 1977) to the task of uncovering groups. Their adaptation was based on the betweenness of graph edges, rather than nodes, and the result was a new algorithm for partitioning graphs.

Edge betweenness refers to the degree to which an edge in the graph falls along a shortest path linking every pair of nodes. A path in a graph is a sequence of nodes and edges beginning and ending with nodes. Girvan and Newman reasoned that since there should be relatively few edges linking individuals in different groups, those linking edges should display a high degree of betweenness. So they began by removing the edge with the highest betweenness, and they continued that process until the graph was partitioned.

Two years later Newman and Girvan (2004) published a follow-up article. Their second paper again focused on edge removal, but this time they introduced an alternative model that had two intuitive foundations. In one, they showed that random walks between all pairs of nodes would determine the betweenness of edges—not just along shortest paths, but along all the paths linking pairs of nodes. The other intuition was motivated by a physical model where edges were defined as resistors that impeded the flow of current between nodes. The edge with the lowest current flow was removed. If that did not yield a partition the process was continued until partitioning did take place. These two models produced the same partitions.

Newman and Girvan went on to show that all of their algorithms always partitioned the data even though some of the partitions might not reflect the presence of actual communities. So they introduced a measure called *modularity*. Modularity is based on the ratio of within-partition ties to those that cross partition boundaries and compares that ratio to its expected value when ties are produced at random. Thus, it provides an index of the degree to which each partition embodies a group- or community-like form.

The result of the two papers by Girvan and Newman was dramatic. Both physicists and computer scientists quickly developed an interest in groups or communities. Radicchi and colleagues (2004) specified two kinds of communities. One was characterized as “strong;” it defined a partition as a community if it met the condition that every node had more within-group ties than cross-cutting ones.⁴ The other they characterized as “weak.” It proposed that a partition was a community if the total number of ties within each partition was greater than the total number of ties linking nodes in the partition to nodes outside the partition.

Radicchi et al. also pointed out that the Girvan and Newman betweenness-based algorithm was computationally slow. So they introduced a new, more efficient measure. They reasoned that edges that bridge between communities are likely to be involved in very few 3-cycles (where friends of friends are friends). So they based their measure on the number of 3-cycles in which each edge is involved, and they showed that their measure had moderate negative correlation with the Girvan-Newman measure. The number of 3-cycles in which an edge is involved, then, turns out to be inversely related to the betweenness of that edge.

Newman (2004) quickly jumped back in. He, too, was troubled by the slowness of the Girvan-Newman algorithm for finding communities. So he proposed a fast “greedy” algorithm. A greedy algorithm makes the optimal choice at each step in a process, without regard to the long-term consequences of that choice.⁵ In this case, Newman proposed starting a process by having each cluster contain a single node. Then, at each stage in the process, the pair of clusters that yields the highest modularity is merged.

The concern with computing speed seems to have started a race to see who could develop the fastest algorithm to cluster nodes in terms of their modularity. A computer scientist, Clauset, working with two physicists, Clauset et al. (2004), was able to speed up Newman's “greedy” algorithm. Two more computer scientists, Duch and Arenas (2005), devised an algorithm to speed it up even more. And in 2006 Newman showed how to gain still more speed by applying singular value decomposition to the modularity matrix. Then, in 2007, a computer scientist, Djidjev, developed a still faster algorithm for constructing partitions based on modularities.

Continuing the search for speed, two other computer scientists, Pons and Latapy (2006), took an entirely different approach. They reasoned that since communities are clusters of densely linked nodes that are only sparsely linked together, a short (two- or three-step) random walk should typically stay within the community in which it is started. They proposed an algorithm that begins with a series of randomly selected starter nodes. Each starter is used to generate a random walk. Then the starters, along with the nodes that are reached, are tallied as linked. The likelihood is that once these results are cumulated, they will display the clustered communities. Finally, two industrial engineers and a physicist, Raghavan, Albert, and Kumara (2007), produced a very fast algorithm based on graph coloring. Nodes begin with unique colors, then, iteratively, each acquires the color of the majority of their immediate neighbors.

Other quite different procedures were also introduced. A physicist and a computer scientist, Wu and Huberman (2004), developed a model based on assuming that edges are resistors, as was the case in the earlier model introduced by Newman and Girvan. But Wu and Huberman's model turns out to be much more complicated and ad hoc. Four physicists, Capocci, Servedio, Caldarelli, and Colaioni (2004), suggested using singular value decomposition to uncover communities. And three others, Fortunato, Latora, and Marchiori (2004), proposed a variation of edge centrality called “information centrality.” Their centrality is based on the inverse of the shortest path length connecting each pair of nodes. The physicists Palla et al. (2005) defined communities as cliques and focused on patterning of clique overlap. Reichardt and Bornholdt (2006) used simulated annealing to search for partitions that yield communities that have a large number of ties within groups and a small number of ties that cut across groups.

Some of these ideas, like overlapping cliques and simulated annealing, will be familiar to seasoned social network analysts. Many others, however, are new and several are quite creative. In particular, edge betweenness, modularity, the use of 3-cycles, short random walks, and graph coloring appear to have promise.

Almost all of these contributions focused on building new tools to uncover groups or communities. They all reported applications to data, but for the most part their applications were merely illustrative. The main thrust of this research has been to build better and faster group-finding algorithms. That preoccupation with developing ever-faster algorithms may not seem too important to most social network analysts, but many applications — particularly those in biology — involve data sets that involve connections linking hundreds of thousands or millions of nodes. For those applications, speed is essential.

Positions

Concern with the positions occupied by individual actors has been the second main theme in social network analysis. Four kinds of positions have been defined. First, positions in groups — *core* and *periphery* — have been specified. Second, a good deal of attention has been focused on *social roles*. Third, some attention has

(Freeman, 2008). In addition, a few physicists have attended the annual Sun Belt social network meetings,⁶ and a few social network analysts have been invited to the meetings of the physicists.⁷ Representatives of each discipline are beginning to publish in journals usually associated with the other.⁸ There are even some joint publications (e.g., Reichardt and White, 2007; Salganik et al., 2006).

My earlier hope for rapprochement between physics and social network analysis, it seems, is beginning to take place. All that is required now is that the social network analysts relax their claim to ownership of the field. The physicists are making important contributions to what could easily end up as a collective effort.⁹

Notes

1 Important publications from each of these centers are listed in Freeman (2004).

2 Scott, in the current volume, also describes the entry of physicists into social network analysis. His description centers on their theoretical perspective.

3 The Barabási and Albert model, however, turns out to be essentially the same as that proposed by a social network analyst, Derek de Solla Price, in 1976.

4 They did not cite the similar social network models introduced by Sailer and Gaulin (1984).

5 Hierarchical clustering is an example of a greedy algorithm.

6 Freeman (2004: 166) mentions the attendance of the physicists Watts, Newman, and Hoser at social network meetings.

7 The social network analysts Vladimir Batagelj and Linton Freeman were invited to the Summer Workshop in Complex Systems and Networks, put on by physicists in Transylvania in 2007.

8 See, for example, the physicists Watts (1999), Holme, Edling, Liljeros (2004), and Newman (2005) publishing in Social Networks or network analysts Borgatti et al. (2009) appearing in Science.

9 A hopeful sign is that Jeroen Bruggeman (2008) cites 77 reports by physicists in a book about social network analysis.

References

- Alba, R.D. (1973) 'A graph theoretic definition of a sociometric clique', *Journal of Mathematical Sociology* 3: 113–26. <http://dx.doi.org/10.1080/0022250X.1973.9989826>
- Arabie, P. and Carroll, J.D. (1989) 'Conceptions of overlap in social structure'. In Freeman, L.C., White, D.R. and Romney, A.K. (eds.), *Research Methods in Social Network Analysis*. George Mason University Press, pp. 367–92.
- Barabási, A-L. and Albert, R. (1999) 'Emergence of scaling in random networks', *Science* 286: 509–12.
- Batchelder, W.H. and Simpson, R.S. (1988) 'Rating system for human abilities: the case of rating chess skill', *Modules in Undergraduate Mathematics and Its Applications*. Arlington, MA: Consortium for Mathematics and its Applications, Inc. pp. 289–314.
- Bavelas, A. (1948) 'A mathematical model for small group structures', *Human Organization* 7: 16–30.
- Beum, C.O. and Brundage, E.G. (1950) 'A method for analyzing the sociomatrix', *Sociometry* 13: 141–45. <http://dx.doi.org/10.2307/2784940>

- Blythe, J. (2006) KP 4.3. from <http://www.isi.edu/~blythe/KP4>.
- Bonacich, P. (1972) 'Factoring and weighting approaches to status scores and clique identification', *Journal of Mathematical Sociology*2: 113–20. <http://dx.doi.org/10.1080/0022250X.1972.9989806>
- Bonacich, P. (1978) 'Using boolean algebra to analyze the overlapping Memberships', *Sociological Methodology*15: 101–15. <http://dx.doi.org/10.2307/270805>
- Bonacich, P. (1987) 'Power and centrality-a family of measures', *American Journal of Sociology*92(5): 1170–82. <http://dx.doi.org/10.1086/228631>
- Bonacich, P. (2004) 'The invasion of the physicists', *Social Networks*26(3): 285–88. <http://dx.doi.org/10.1016/j.socnet.2004.06.002>
- Borgatti, S.P. and Everett, M.G. (1997) 'Network analysis of 2-mode data', *Social Networks*19(3): 243–69. <http://dx.doi.org/10.1016/S0378-8733%2896%2900301-2>
- Borgatti, S.P. and Everett, M.G. (1999) 'Models of core/periphery structures', *Social Networks*21(4): 375–95. <http://dx.doi.org/10.1016/S0378-8733%2899%2900019-2>
- Borgatti, S.P., Everett, M.G. and Freeman, L.C. (1992) 'Ucinet, version iv', *Analytic Technology*, Columbia, SC.
- Borgatti, S.P., Mehra, A., Brass, D.J. and Labianca, G. (2009) 'Network analysis in the social sciences', *Science*323: 892–5. <http://dx.doi.org/10.1126/science.1165821>
- Boyd, J.P. (1991) *Social Semigroups*. Fairfax, VA: George Mason University Press.
- Breiger, R.L. (1974) 'The duality of persons and groups', *Social Forces*53: 181–90. <http://dx.doi.org/10.1093/sf/53.2.181>
- Bruggeman, J. (2008) *Social Networks*, London: Routledge.
- Breiger, R.L., Boorman, S.A. and Arabie, P. (1975) 'An algorithm for clustering relational data, with applications to social network analysis and comparison to multidimensional scaling', *Journal of Mathematical Psychology*12: 328–83. <http://dx.doi.org/10.1016/0022-2496%2875%2990028-0>
- Capocci, A., Servedio, V.D.P. and Caldarelli, G. and Colaioni, F. (2004) 'Detecting communities in large networks', *Physica: Statistical Mechanics and Its Applications*352: 669–76. <http://dx.doi.org/10.1016/j.physa.2004.12.050>
- Cartwright, D. and Harary, F. (1956) 'Structural balance: a generalization of heider's theory', *Psychological Review*63: 277–92. <http://dx.doi.org/10.1037/h0046049>
- Clauset, A., Newman, M.E.J. and Moore, C. (2004) 'Finding communities in very large networks', *Physical Review E*70(6): 066111. <http://dx.doi.org/10.1103/PhysRevE.70.066111>
- Coleman, J.S. (1964) *Introduction to Mathematical Sociology*. New York: Free Press.
- Cooley, C.H. (1909/1962) *Social Organization*. New York: Schocken Books.
- Davis, A., Gardner, B.B. and Gardner, M.R. (1941) *Deep South*. Chicago: The University of Chicago Press.
- Dekker, A. (2001) 'Visualization of social networks using Cavalier', *Proceedings of the 2001 Asia-Pacific Symposium on Information Visualization*9: 49–55.
- Djidjev, H. (2007) 'A fast multilevel algorithm for graph clustering and community detection'. Arxiv preprint arXiv:0707.2387, 2007 - <http://arxiv.org>.
- Doreian, P. (1979) 'On the deliniation of small group structures', *Classifying Social Data*. Hudson, M. (ed.), San Francisco: Jossey-Bass pp. 215–30.
- Duch, J. and Arenas, A. (2005) 'Community detection in complex networks using external optimization', *Physical Review*72: 2027104.
- Durkheim, E. (1893/1964) *The Division of Labor in Society*. New York: Free Press.
- Evans, T.S. (2004) 'Complex networks', *Contemporary Physics*. 45(6): 455–74. <http://dx.doi.org/10.1080/00107510412331283531>
- Everett, M. and Borgatti, S.R. (2000) 'Peripheries of cohesive subsets', *Social Networks*21(4): 397–407. <http://dx.doi.org/10.1016/S0378-8733%2899%2900020-9>
- Festinger, L., Schachter, S. and Back, K.W. (1950) *Social Pressures in Informal Groups*. New York: Harper & Bros.
- Fiduccia, C.M. and Mattheyses, R.M. (1982) 'A linear time heuristic for improving network partitions', *Design Automation Conference* pp. 175–81.
- Fiedler, M. (1973) 'Algebraic connectivity of graphs', *Czechoslovak Mathematics Journal*23: 298–305.
- Fiedler, M. (1975) 'A property of eigenvectors of non-negative symmetric matrices and its application to graph

- theory', *Czechoslovak Mathematics Journal*25: 619–33. <http://dx.doi.org/10.1007/BF01591018>
- Flake, G.W., Lawrence, S. and Giles, C.L. (2000) 'Efficient identification of web communities', *Proceedings of the Sixth International Conference on Knowledge Discovery and Data Mining*New York, NY: ACM Press, pp. 150–60. <http://dx.doi.org/10.1145/347090.347121>
- Fortunato, S., Latora, V. and Marchiori, M. (2004) 'Method to find community structures based on information centrality', *Physical Review*70(5): 056104.
- Frank, K.A. (1995) 'Identifying cohesive subgroups', *Social Networks*17(1): 27–56. <http://dx.doi.org/10.1016/0378-8733%2894%2900247-8>
- Freeman, L.C. (1977) 'A set of measures of centrality based on betweenness', *Sociometry*40: 35–41. <http://dx.doi.org/10.2307/3033543>
- Freeman, L.C. (1979) 'Centrality in social networks: conceptual Clarification', *Social Networks*1: 215–39. <http://dx.doi.org/10.1016/0378-8733%2878%2990021-7>
- Freeman, L.C. (1992) 'On the sociological concept of "group": a empirical test of two models', *American Journal of Sociology*98: 152–66. <http://dx.doi.org/10.1086/229972>
- Freeman, L.C. (1993) 'Finding groups with a simple genetic algorithm', *Journal of Mathematical Sociology*17: 227–41. <http://dx.doi.org/10.1080/0022250X.1993.9990109>
- Freeman, L.C. (1997) 'Uncovering organizational hierarchies', *Computational and Mathematical Organization Theory*3: 5–18. <http://dx.doi.org/10.1023/A:1009690520577>
- Freeman, L.C. (2004) 'The development of social network analysis: a study in the sociology of science', Vancouver, B.C.: Empirical Press.
- Freeman, L.C. (2008) 'Going the wrong way on a one-way street: centrality in physics and biology', *Journal of Social Structure*9(2).
- Freeman, L.C., Romney, A.K. and Freeman, S.C. (1987) 'Cognitive structure and informant accuracy', *American Anthropologist*89: 311–25.
- Freeman, L.C. and Webster, C.M. (1994) 'Interpersonal proximity in social and cognitive space', *Social Cognition*12: 223–47. <http://dx.doi.org/10.1521/soco.1994.12.3.223>
- Freeman, L.C. and White, D.R. (1993) 'Using galois lattices to represent network data', Marsden, P. (ed.), *Sociological Methodology 1993*. Cambridge, MA: Blackwell pp. 127–46.
- Girvan, M. and Newman, M.E.J. (2002) 'Community structure in social and biological networks', *PNAS*99(12): 7821–26. <http://dx.doi.org/10.1073/pnas.122653799>
- Glover, F. (1989) 'Tabu search-part I', *ORSA Journal on Computing*1: 190–206. <http://dx.doi.org/10.1287/ijoc.1.3.190>
- Glover, F. (1990) 'Tabu search-part II', *ORSA Journal on Computing*2: 4–32. <http://dx.doi.org/10.1287/ijoc.2.1.4>
- Gower, J.C. (1977) 'The analysis of asymmetry and orthogonality', *Recent Developments in Statistics*. Barra, J., Brodeau, F., and Romier, G. (eds.), Amsterdam: North Holland, pp. 109–23.
- Holme, P. (2005) 'Core-periphery organization of complex networks', *Physical Review*72(4).
- Holme, P. and Huss, M. (2005) 'Role-similarity based functional prediction in networked systems: application to the yeast proteome', *Journal of the Royal Society Interface*. 2(4): 327–33. <http://dx.doi.org/10.1098/rsif.2005.0046>
- Holme, P., Edling, C.R. and Liljeros, F. (2004) 'Structure and time evolution of an Internet dating community', *Social Networks*26: 155–74. <http://dx.doi.org/10.1016/j.socnet.2004.01.007>
- Holme, P., Huss, M. and Jeong, H.W. (2003) 'Subnetwork hierarchies of biochemical pathways', *Bioinformatics*19(4): 532–38. <http://dx.doi.org/10.1093/bioinformatics/btg033>
- Homans, G.C. (1950) *The Human Group*. New York: Harcourt, Brace and Company.
- Huber, P. (1802) 'Observations on several species of the genus apis, known by the name of humble bees, and called bombinatrices by linnaeus', *Transactions of the Linnean Society of London*6: 214–98. <http://dx.doi.org/10.1111/j.1096-3642.1802.tb00484.x>
- Hubert, L. (1974) 'Approximate evaluation techniques for the single-link and complete-link hierarchical clustering procedures', *Journal of the American Statistical Association*69: 698–704. <http://dx.doi.org/10.1080/01621459.1974.10480191>
- Jameson, K.A., Appleby, M.C. and Freeman, L.C. (1999) 'Finding an appropriate order for a hierarchy based on probabilistic dominance', *Animal Behaviour*57: 991–98. <http://dx.doi.org/10.1006/anbe.1998.1077>

- Jeong, H., Mason, S.P., Barabási, A.L. and Oltvai, Z.N. (2001) 'Lethality and centrality in protein networks', *Nature*411(6833): 41–42. <http://dx.doi.org/10.1038/35075138>
- Killworth, P.D., McCarty, C., Bernard, H.R. and House, M. (2006) 'The accuracy of small world chains in social networks', *Social Networks*28: 85–96. <http://dx.doi.org/10.1016/j.socnet.2005.06.001>
- Killworth, P.D., McCarty, C., Bernard, H.R., Johnsen, E.C., Domini, J. and Shelley, G.A., (2003) 'Two interpretations of reports of knowledge of subpopulation sizes', *Social Networks*25: 141–69. <http://dx.doi.org/10.1016/S0378-8733%2802%2900040-0>
- Kochen, M. (1989) *The Small World*. Northwood, NJ: Ablex Publishing Co.
- Kolaczyk, E.D., Chua, D.B. and Barthelemy, M. (2007) 'Co-betweenness: a pairwise notion of centrality', Arxiv preprint arXiv:0709.3420, 2007 – <http://arxiv.org>.
- Landau, H.G. (1951) 'On dominance relations and the structure of animal societies: some effects of possible social factors', *Bulletin of Mathematical Biophysics*13: 245–62. <http://dx.doi.org/10.1007/BF02477920>
- Leavitt, H.J. (1951) 'Some effects of communication patterns on group performance', *Journal of Abnormal and Social Psychology*46: 38–50. <http://dx.doi.org/10.1037/h0057189>
- Levine, J.H. (1972) 'The sphere of influence', *American Sociological Review*37: 14–27. <http://dx.doi.org/10.2307/2093490>
- Lewin, K. and Lippitt, R. (1938) 'An experimental approach to the study of autocracy and democracy: a preliminary note', *Sociometry*1(3/4): 292–300. <http://dx.doi.org/10.2307/2785585>
- Linton, R. (1936) *The Study of Man*. New York: D. Appleton-Century Company.
- Lorrain, F.P. and White, H.C. (1971) 'Structural equivalence of individuals in social networks', *Journal of Mathematical Sociology*1: 49–80. <http://dx.doi.org/10.1080/0022250X.1971.9989788>
- Luce, R.D. and Perry, A. (1949) 'A method of matrix analysis of group structure', *Psychometrika*14: 95–116. <http://dx.doi.org/10.1007/BF02289146>
- Maine, H. (1861/1931) *Ancient Law*. London: Oxford University Press.
- Milgram, S. (1967) 'The small world problem', *Psychology Today*22: 61–67.
- Mokken, R.J. (1979) 'Cliques, clubs and clans', *Quantity and Quality*13: 161–73. <http://dx.doi.org/10.1007/BF00139635>
- Moody, J. and White, D.R. (2003) 'Structural cohesion and embeddedness: a hierarchical concept of social groups', *American Sociological Review*68(1): 103–27. <http://dx.doi.org/10.2307/3088904>
- Moreno, J.L. (1932) *Application of the Group Method to Classification*. New York: National Committee on Prisons and Prison Labor.
- Moreno, J.L. (1934) *Who Shall Survive?* Washington, DC: Nervous and Mental Disease Publishing Company.
- Moreno, J.L. and Jennings, H.H. (1938) 'Statistics of social configurations', *Sociometry*1: 342–74. <http://dx.doi.org/10.2307/2785588>
- Nadel, S.F. (1957) *The Theory of Social Structure*. London: Cohen and West.
- Newcomb, T.M. (1961) *The Acquaintance Process*. New York: Holt, Rhinehart, and Winston. <http://dx.doi.org/10.1037/13156-000>
- Newman, M.E.J. (2003) 'The structure and function of complex networks', *Siam Review*45(2): 167–256. <http://dx.doi.org/10.1137/S003614450342480>
- Newman, M.E.J. (2004) 'Detecting community structure in networks', *European Physical Journal*38(2): 321–30. <http://dx.doi.org/10.1140/epjb/e2004-00124-y>
- Newman, M.E.J. (2006) 'Finding community structure in networks using the eigenvectors of matrices', *Physical Review*74(3): 19.
- Newman, M.E.J. and Girvan, M. (2004) 'Finding and evaluating community structure in networks', *Physical Review*69: 026113.
- Nieminen, J. (1974) 'On centrality in a graph', *Scandinavian Journal of Psychology*15(4): 332–36. <http://dx.doi.org/10.1111/j.1467-9450.1974.tb00598.x>
- Palla, G., Derényi, I., Farkas, I. and Vicsek, T. (2005) 'Uncovering the overlapping community structure of complex networks in nature and society', *Nature*435: 814–18. <http://dx.doi.org/10.1038/nature03607>
- Park, J. and Newman, M.E.J. (2005) 'A network-based ranking system for U.S. college football', *Journal of Statistical Mechanics: P Theory and Experiment* Vol. P10014.
- Parlett, B.N. (1980) 'A new look at the {L}anczos method for solving symmetric systems of linear equations', *Linear Algebra Applied*29: 323–46. <http://dx.doi.org/10.1016/0024-3795%2880%2990248-7>

- Pons, P. and Latapy, M. (2006) 'Computing communities in large networks using random walks', *Journal of Graph Algorithms and Applications*10(2): 191–218. <http://dx.doi.org/10.7155/jgaa.00124>
- Pool, I.D. and Kochen, M. (1978) 'Contacts and influence', *Social Networks*1(1): 5–51. <http://dx.doi.org/10.1016/0378-8733%2878%2990011-4>
- Pothen, A., Simon, H. and Liou, K-P. (1990) 'Partitioning sparse matrices with eigenvalues of graphs', *Journal of Matrix Analysis Applied*11(3): 430–52. <http://dx.doi.org/10.1137/0611030>
- Price, D.J. (1965) 'Networks of scientific papers', *Science*149: 510–15. <http://dx.doi.org/10.1126/science.149.3683.510>
- Price, D.J. (1976) 'A general theory of bibliometric and other cumulative advantage processes', *Journal of the American Society for Information Science*27: 292–306. <http://dx.doi.org/10.1002/asi.4630270505>
- Radicchi, F., Castellano, C., Cecconi, F., Loretto, V. and Parisi, D. (2004) 'Defining and identifying communities in networks', *Proceedings of the National Academy of Sciences*101: 2658–63. <http://dx.doi.org/10.1073/pnas.0400054101>
- Raghavan, U.N., Albert, R. and Kumara, S. (2007) 'Near linear time algorithm to detect community structures in large-scale networks', *Physical Review*76: 036106.
- Reichardt, J. and Bornholdt, S. (2006) 'Statistical mechanics of community detection', *Physical Review*74: 016110.
- Reichardt, J. and White, D.R. (2007) 'Role models for complex networks', *The European Physical Journal*60: 217–24. <http://dx.doi.org/10.1140/epjb/e2007-00340-y>
- Roberts, J.M. (2000) 'Correspondence analysis of two-mode network data', *Social Networks*22: 65–72. <http://dx.doi.org/10.1016/S0378-8733%2800%2900017-4>
- Roethlisberger, F.J. and Dickson, W.J. (1939) *Management and the worker*, Cambridge, MA: Harvard University Press.
- Sabidussi, G. (1966) 'The centrality index of a graph', *Psychometrika*31(4): 581–603. <http://dx.doi.org/10.1007/BF02289527>
- Sailer, L.D. (1978) 'Structural equivalence: meaning and definition, computation and application', *Social Networks*1: 73–90. <http://dx.doi.org/10.1016/0378-8733%2878%2990014-X>
- Sailer, L.D. and Gaulin, S.J.C. (1984) 'Proximity, sociality and observation: the definition of social groups', *American Anthropologist*86: 91–98. <http://dx.doi.org/10.1525/aa.1984.86.1.02a00080>
- Salganik, M.J., Dodds, P.S. and Watts, D.J. (2006) 'Experimental study of inequality and unpredictability in an artificial cultural market', *Science*311: 854–56. <http://dx.doi.org/10.1126/science.1121066>
- Scott, J. (1992) *Social Network Analysis*. Newbury Park, CA: Sage.
- Seary, A.J. and Richards, W.D. (2003) 'Spectral methods for analyzing and visualizing networks: an introduction', *Dynamic Social Network Modeling and Analysis*. Breiger, R.L., Carley, K.M., and Pattison, P. (eds.), Washington: The National Academies Press, pp. 209–28.
- Skvoretz, J. and Faust, K. (1999) 'Logit models for affiliation networks', *Sociological Methodology*29: 253–80. <http://dx.doi.org/10.1111/0081-1750.00066>
- Spencer, H. (1897) *The Principles of Sociology*. New York: Appleton-Century-Crofts Vol I.
- Tönnies, F. (1855/1936) *Fundamental Concepts of Sociology*. New York: American Book Company.
- Vendruscolo, M., Dokholyan, N.V., Paci, E. and Karplus, M. (2002) 'Small-world view of the amino acids that play a key role in protein folding', *Physical Review*65(6): 061910–061913.
- Wagner, A. and Fell, D.A. (2001) 'The small world inside large metabolic networks', *Proceedings of the Royal Society of London Series B-Biological Sciences*268(1478): 1803–10. <http://dx.doi.org/10.1098/rspb.2001.1711>
- Warner, W.L. and Lunt, P.S. (1941) *The Social Life of a Modern Community*. New Haven, CT: Yale University Press.
- Wasserman, S. and Faust, K. (1994) *Social Network Analysis: Methods and Applications*. Cambridge: Cambridge University Press. <http://dx.doi.org/10.1017/CBO9780511815478>
- Watts, D.J. (1999) 'Networks, dynamics, and the small-world phenomenon', *American Journal of Sociology*105: 493–527. <http://dx.doi.org/10.1086/210318>
- Watts, D.J. and Strogatz, S.H. (1998) 'Collective dynamics of "small-world" networks', *Nature*393(6684): 440–42. <http://dx.doi.org/10.1038/30918>
- White, H.C., Boorman, S.A. and Breiger, R.L. (1976) 'Social structure from multiple networks i: blockmodels

of roles and positions', *American Journal of Sociology* 81: 730–81. <http://dx.doi.org/10.1086/226141>

Wu, F. and Huberman, B.A. (2004) 'Finding communities in linear time: a physics approach', *European Physical Journal* 38(2): 331–38. <http://dx.doi.org/10.1140/epjb/e2004-00125-x>

Wu, Z. and Leahy, R. (1993) 'An optimal graph theoretic approach to data clustering: theory and its application to image segmentation', *IEEE Transactions on Pattern Analysis and Machine Intelligence* 15: 1101–13. <http://dx.doi.org/10.1109/34.244673>

Zachary, W. (1977) 'An information flow model for conflict and fission in small groups', *Journal of Anthropological Research* 33: 452–73.

- physicists
- nodes
- social networks
- social network analysis
- network analysis
- algorithms
- modularity

<http://dx.doi.org/10.4135/9781446294413.n3>